Contract No.: EP-W-09-002

Region 2 RAC2 Remedial Action Contract

Final Human Health Risk Assessment

Maunabo Groundwater Contamination Site

Remedial Investigation/Feasibility Study

Maunabo, Puerto Rico

WA No.: 014-RICO-02XF

July 3, 2012



Table of Contents

Executive SummaryES		
Section 1	Introduction	1-1
	1.1 Overview	1-1
	1.2 Report Organization	1-2
Section 2	Site Background and Setting	2-1
	2.1 Site Location and Description	2-1
	2.2 Site History	2-1
	2.3 Site Geology and Hydrogeology	2-2
	2.3.1 Site Geology	2-2
	2.3.2 Site Hydrogeology	2-2
	2.4 Demography and Land Use	2-2
Section 3	Data Evaluation	3-1
	3.1 Sample Collection and Analysis	3-1
	3.1.1 Soil Sampling	3-1
	3.1.2 Groundwater Sampling	3-1
	3.1.3 Surface Water and Sediment Sampling	3-2
	3.2 Data Usability	3-2
	3.3 Summary of Analytical Results	3-2
	3.3.1 Soil	3-2
	3.3.1.1 Former Sugar Mill	3-2
	3.3.1.2 Puerto Rico Beverage	3-3
	3.3.2 Groundwater	3-4
	3.3.3 Surface Water	3-4
	3.3.4 Sediment	3-4
	3.4 Identification of Chemicals of Potential Concern	3-4
Section 4	Exposure Assessment	4-1
	4.1 Exposure Pathways	4-1
	4.1.1 Conceptual Site Model	4-1
	4.1.2 Identification of Exposure Pathways	4-1
	4.1.2.1 Soil Exposure Pathways	4-2
	4.1.2.2 Groundwater Exposure Pathways	4-2
	4.1.2.3 Surface Water and Sediment Exposure Pathways	4-2
	4.2 Characterization of Potentially Exposed Populations	4-2
	4.2.1 Current Receptors	4-3
	4.2.1.1 Commercial/Industrial Workers	4-3
	4.2.1.2 Trespassers	4-3
	4.2.1.3 Residents	4-3
	4.2.1.4 Recreational Users	4-3
	4.2.2 Future Receptors	4-3
	4.2.2.1 Commercial/Industrial Workers	4-3



		4.2.2.2 Trespassers	4-4
		4.2.2.3 Residents	4-4
		4.2.2.4 Recreational Users	4-4
		4.2.2.5 Construction Workers	4-4
	4.3 Summ	nary of Exposure Pathways and Receptors	4-4
		ation of Exposure Point Concentrations	
		Exposure Point Concentrations of Samples Collected	
		Ambient Air Exposure Point Concentrations	
		Indoor Air Exposure Point Concentrations Using the Shower Model	
		ure Parameter Assumptions	
		Commercial/Industrial Workers	
		4.5.1.1 Soil	4-9
		4.5.1.2 Groundwater	
		Trespassers	
		Residents	
		4.5.3.1 Soil	
		4.5.3.2 Groundwater	
		4.5.3.3 Surface Water	
		Construction Workers	
		Recreational Users	
		4.5.5.1 Surface Water	
		4.5.5.2 Sediment	
Section 5		city Assessment	
	5.1 Health	n Effects Criteria for Noncarcinogens	5-1
		n Effects Criteria for Carcinogens	
	5.3 Toxicit	ty Values	5-4
Section 6	Risk	Characterization	6-1
	6.1 Result	ts of Risk Calculations	6-1
		Current Land-Use Scenario	
		6.1.1.1 Commercial/Industrial Worker	
		6.1.1.2 Trespasser	
		6.1.1.3 Resident at Former Sugar Mill	
		6.1.1.4 Recreational User at Maunabo River	
		Future Land-Use Scenario	
		6.1.2.1 Commercial/Industrial Worker	
		6.1.2.2 Trespasser	
		6.1.2.3 Resident	
		6.1.2.4 Future Construction Worker	
		6.1.2.5 Future Recreational User at Maunabo River	
	6.2	Risk Associated with Exposure to Lead	
	6.3	Uncertainty in Risk Assessment	
	6.3.1		
	6.2.2		
	-	· · · · · · · · · · · · · · · · · · ·	
		·	
		·	
	6.2.3		
	6.2.4	Risk Characterization	ხ-გ

Section 7	Summary of Risk Assessment	
7	7.1 Approach	7-1
	7.2 Site Risks	
	7.2.1 Current Land-Use Scenario	7-2
	7.2.1.1 Cancer Risk	7-2
	7.2.1.2 Noncancer Health Hazard	7-2
	7.2.2 Future Land-Use Scenario	7-3
	7.2.2.1 Cancer Risk	7-3
	7.2.2.2 Noncancer Health Hazard	7-4
7	7.3 Summary and Conclusions	
Section 8	References	8-1

List of Tables

Table 3-1	Lead Worksheet
Table 3-2	List of Chemicals of Potential Concern
Table 4-1	Selection of Exposure Pathways
Table 5-1	Noncancer Toxicity Data – Oral/Dermal
Table 5-2	Noncancer Toxicity Data – Inhalation (Chronic)
Table 5-3	Noncancer Toxicity Data – Inhalation (Acute)
Table 5-4	Cancer Toxicity Data – Oral/Dermal
Table 5-5	Cancer Toxicity Data – Inhalation

List of Figures

Figure 2-1	Site Location Map
Figure 2-2	Site Map
Figure 3-1	Soil Sampling Location
Figure 3-2	Monitoring Well Location
Figure 3-3	Surface Water and Sediment Sampling Location
Figure 4-1	Conceptual Site Model for Current Land-Use Scenario
Figure 4-2	Conceptual Site Model for Future Land-Use Scenario

Appendices

Appendix A	List of Samples Used in the Risk Assessment
Appendix B	RAGS D Tables – RME Scenario
Appendix C	ProUCL Output for Chemicals of Potential Concern
Appendix D	Shower Model – Input Assumptions and Estimated Air Concentrations
Appendix E	Vapor Intrusion Screening
Appendix F	RAGS D Tables – CTE Scenario



Table of Contents
This page intentionally left blank.

Acronyms

ATSDR Agency for Toxic Substances and Disease Registry

bgs below ground surface

Cal/EPA California Environmental Protection Agency

CDM Smith CDM Federal Programs Corporation COPC chemicals of potential concern

CSM conceptual site model
CTE central tendency exposure

DCE dichloroethene

4,4'-DDE p,p'-dichlorodiphenyldichloroethylene 4,4'-DDT p,p'-dichlorodiphenyltrichloroethane

EPA United States Environmental Protection Agency

EPC exposure point concentration

FS Feasibility Study

HHRA human health risk assessment

HQ hazard quotient

IRIS Integrated Risk Information System

IUR inhalation unit risk

MCL Maximum Contaminant Level

MTBE methyltertbutylether

NCEA National Center for Environmental Assessment

NOAEL no-observed-adverse-effect level

NPL National Priority List

PAH polycyclic aromatic hydrocarbon

PCB polychlorinated biphenyl

PCE tetrachloroethene

PEF particulate emission factor

PPRTV Provisional Peer Reviewed Toxicity Values
PRASA Puerto Rico Aqueduct and Sewer Authority

PRDOH Puerto Rico Department of Health

PRIDCO Puerto Rico Industrial Development Corporation

RAC Remedial Action Contract

RAGS Risk Assessment Guidance for Superfund

RfC reference concentration

RfD reference dose

RI Remedial Investigation

RME reasonable maximum exposure

RPF relative potency factor
RSL Regional Screening Level
SAT2 Site Assessment Team 2

SF slope factor

the site Maunabo Groundwater Contamination Site

SVOC semi-volatile organic compound

TAL target analyte list TCE trichloroethene



• Acronyms

TCL target compound list
TDS total dissolved solid
TKN total Kjehldahl nitrogen
TOC total organic carbon
TSS total suspended solid
UCL upper confidence limit
VOC volatile organic compound

cm centimeter

cm² square centimeter

hr hour kilogram kg L liter meter m $\,m^3\,$ cubic meter mg milligram ml milliliter μg microgram

Executive Summary

CDM Federal Programs Corporation (CDM Smith) received Work Assignment No. 014-RICO-02XF under the Remedial Action Contract (RAC) II to perform a Remedial Investigation/Feasibility Study (RI/FS) for the United States Environmental Protection Agency (EPA), Region 2 at the Maunabo Groundwater Contamination site (the site) located in Maunabo, Puerto Rico.

This human health risk assessment (HHRA), as part of the RI/FS, is developed to characterize potential human health risks associated with groundwater in the absence of any remedial action. The HHRA is conducted in accordance with current EPA guidance outlined in *Risk Assessment Guidance for Superfund* (RAGS), Parts A, D, E, and F and other EPA guidance pertinent to human health risk assessments. The HHRA consists of sections describing site background and setting, data evaluation, exposure assessment, toxicity assessment, risk characterization, and summary of risk assessment.

Site Background and Setting

The Maunabo Groundwater Contamination site is located in the municipality of Maunabo, in the southeastern coastal area of Puerto Rico. The site is located within an isolated alluvial river valley, and is surrounded by mountains to the north, east, and west, and the Caribbean Sea to the southeast. The Maunabo River and several intermittent streams are located within the vicinity and flow southeast toward the Caribbean Sea. Groundwater discharge forms the baseflow of the river and also discharges to smaller tributaries and streams (quebradas) such as Quebrada Arenas. Puerto Rico Beverage and the Former Sugar Mill are located to the north and south of the Maunabo #1 supply well and have been investigated as possible sources of contamination.

Maunabo's public water system, known as Maunabo Urbano, consists of four groundwater wells: Maunabo #1, Maunabo #2 (Bordaleza), Maunabo #3 (Calzada), and Maunabo #4 (San Pedro). In March 2002, the Puerto Rico Department of Health (PRDOH) ordered the Puerto Rico Aqueduct and Sewer Authority (PRASA) to close Maunabo #1 due to concentrations of tetrachloroethene (PCE) above the maximum contaminant level (MCL). Rather than close the well, PRASA opted to treat the groundwater with activated carbon treatment tanks due to water supply needs. Detections of PCE in pre-treatment samples from Maunabo #1 exceeded the MCL, but post-treatment samples exhibited PCE at concentrations below the MCL. PRASA has since replaced the tanks with three new tanks. The 2011 monthly data supplied by PRASA show that PCE has been detected in some post-treatment samples, but at levels below the MCL.

In October 2005, EPA's Region 2 Site Assessment Team 2 (SAT 2) collected water samples from each well, and from the distribution water line. In December 2005, SAT 2 conducted an investigation of possible sources of groundwater contamination at five industrial sites around the Maunabo area. Results of the October and December 2005 investigations indicated there was insufficient information to conclusively determine the source(s) of contamination of the drinking water supply well. Subsequently, the Agency for Toxic Substances and Disease Registry (ATSDR) evaluated available data, and conducted a site visit to complete a Public Health Assessment. Results of the Public Health Assessment concluded that the wells exceeded EPA's MCLs for PCE and *cis*-1,2-DCE in the past. However, exceedances were intermittent and did not exceed ATSDR's health based comparison values, and that current and future conditions at the site present no apparent public health hazard. The Maunabo groundwater contamination site was proposed for the National Priority List (NPL) on April 19, 2006 and was listed on September 27, 2006.



Data Evaluation

Previous investigations were conducted by SAT 2 in October and December 2005 to identify possible sources of contamination in Maunabo public water supply wells. CDM Smith, on behalf of EPA, conducted an RI field investigation in January through June 2011. Soil, groundwater, surface water, and sediment samples were collected as part of this investigation. These data are used to adequately characterize contamination at the site to support the RI and the HHRA.

Chemicals of potential concern (COPCs) are identified based on criteria outlined in RAGS, primarily through comparison to risk-based screening levels. Two semi-volatile organic compounds (SVOC) and eight inorganics are identified as COPCs in the surface and subsurface soil at the Former Sugar Mill area. Seven inorganics are identified as COPCs in the surface and subsurface soil at the Puerto Rico Beverage area. Five volatile organic compounds (VOC) and nine inorganics are identified as COPCs in the groundwater. Two VOCs and six inorganics are identified as COPCs in surface water and sediment, respectively, from the Maunabo River.

Exposure Assessment

Potential exposure pathways at the site are defined based on potential source areas, release mechanisms, and current and potential future uses of the site. Potential receptors evaluated in the risk assessment include:

- Current Land-Use Scenario
 - Commercial Industrial Workers at Former Sugar Mill and Puerto Rico Beverage
 - Trespassers at Former Sugar Mill and Puerto Rico Beverage
 - Residents at Former Sugar Mill
 - Recreational Users at Maunabo River
- Future Land-Use Scenario
 - Commercial Industrial Workers at Former Sugar Mill and Puerto Rico Beverage
 - Trespassers at Former Sugar Mill and Puerto Rico Beverage
 - Residents at Former Sugar Mill, Puerto Rico Beverage, and Maunabo River
 - Recreational Users at Maunabo River
 - Construction Workers at Former Sugar Mill and Puerto Rico Beverage

Exposure pathways evaluated for soil include ingestion of and dermal contact with soil, inhalation of particulates from soil by commercial/industrial workers, trespassers, residents, and construction workers. Exposure pathways evaluated for groundwater include ingestion of and dermal contact with groundwater, inhalation of vapor released during showering and bathing, and inhalation of vapor through vapor intrusion by commercial/industrial workers and residents. Exposure pathways evaluated for surface water and sediment include ingestion of and dermal contact by recreational users.

Exposure point concentrations (EPCs) for the COPCs are used in the exposure assessment calculations to estimate potential chemical intake. The EPC is the lower of the upper confidence limit (UCL) on the mean or the maximum detected concentration.

Quantification of exposure includes evaluation of exposure parameters that describe the exposed population (e.g., contact rate, exposure frequency and duration, and body weight). Each exposure parameter in the equation has a range of values. Daily intakes are calculated based on the reasonable maximum exposure (RME) scenario (the highest exposure reasonably expected to occur at a site). The intent is to estimate a conservative exposure case that is still within the range of possible exposures. Central tendency exposure (CTE) assumptions are also developed, when the estimated risks under RME scenario exceed EPA's threshold risk range. CTE scenarios reflect more typical exposures.



Toxicity Assessment

COPCs are quantitatively evaluated on the basis of their noncancer and/or cancer potential. The reference dose (RfD) and reference concentration (RfC) are the toxicity values used to evaluate noncancer health hazards in humans. Inhalation unit risk and slope factor are the toxicity values used to evaluate cancer health effects in humans. These toxicity values are obtained from various sources following the hierarchy order specified by EPA.

Risk Characterization

Risk characterization integrates the exposure and toxicity assessments into quantitative expressions of risks/health effects. To characterize potential noncancer health effects, comparisons are made between estimated intakes of substances and toxicity thresholds. Potential cancer effects are evaluated by calculating probabilities that an individual will develop cancer over a lifetime exposure based on projected intakes and chemical specific dose-response information. In general, EPA recommends target risk values, i.e., cancer risk of 10^{-6} (1 in a million) to 10^{-4} (1 in a 10,000) or noncancer health HI of unity, as threshold values for potential human health impacts (EPA 1989). These target values aid in determining whether additional remedial action is necessary at the site.

Risks for all receptors are estimated using RME assumptions. Risks are also estimated using CTE assumptions when the RME assumptions resulted in risk estimates above EPA's thresholds.

For the current and future land-use scenarios, total estimated cancer risks are within EPA's target range (cancer risk of 1×10^{-6} to 1×10^{-6} to 1×10^{-4}) for all receptors under the RME scenario, except residents at both the Former Sugar Mill and Puerto Rico Beverage areas. However, under the CTE scenario, the total cancer risks are within EPA's target range of 1×10^{-6} to 1×10^{-4} .

For the current and future land-use scenarios, total noncancer health hazards are below EPA's target threshold (HI of 1) for all receptors under the RME scenario, except commercial and industrial workers, construction workers, and residents at both the Former Sugar Mill and Puerto Rico Beverage areas. The current and future commercial/industrial workers, construction workers, and residents have noncancer HIs exceeding EPA's threshold of unity under the RME scenario for the kidney, respiratory system, lung, and GI tract. Noncancer health hazards for current and future commercial/industrial workers and construction workers are almost entirely due to the hypothetical use of contaminated groundwater as a potable water supply.

For current and future residents, the potential health hazards to the kidney are results of exposure of *cis*-1,2-DCE and vanadium in groundwater, while the potential adverse health effects to the respiratory system are results of exposure to vanadium in soil and groundwater. The potential adverse health effects to the lung and GI tract are mainly results of exposure to arsenic and iron, respectively, in both soil and groundwater. Under the CTE scenario, the HIs still exceed EPA's threshold of unity for the same target organs/effects, except lung and GI tract, affected under the RME.

Current and future commercial/industrial workers and residents may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. However, vapor intrusion is currently not a concern because the existing structures are not near the COPC concentrations which exceed the screening levels and no detections of COPCs were above the screening levels at the top of the water table.



Executive Summary
This page intentionally left blank.

Section 1

Introduction

CDM Federal Programs Corporation (CDM Smith) received Work Assignment No. 014-RICO-02XF under the Remedial Action Contract (RAC) II to perform a Remedial Investigation/Feasibility Study (RI/FS) for the United States Environmental Protection Agency (EPA), Region 2 at the Maunabo Groundwater Contamination site (the site) located in Maunabo, Puerto Rico.

This human health risk assessment (HHRA), as part of the RI/FS, is developed to characterize potential human health risks associated with the site in the absence of any remedial action. This HHRA identifies the potential exposure pathways by which populations may be exposed. Exposure pathways are identified based on considerations of the sources and locations of contaminants related to the site, the likely environmental fate of the contaminants, and the location and activities of the potentially exposed populations. The HHRA describes exposure points and routes of exposure for each exposure pathway, as well as underlying assumptions regarding receptor characteristics and behavior (e.g., body weight, ingestion rate, exposure frequency). The HHRA also identifies chemicals of potential concern (COPCs) for each environmental medium, exposure point concentrations (EPCs) and toxicity values of COPCs. Finally, the HHRA characterizes potential cancer risks and noncancer health hazards associated with each complete exposure pathway.

1.1 Overview

To prepare this HHRA, CDM Smith reviewed the available information pertaining to the site. Potential exposure pathways, exposure routes, and potentially exposed populations under current and future land-use scenarios are identified. Exposure parameters and daily intakes for exposure scenarios that are quantified and toxicity values for COPCs are presented. The exposure pathways and receptors, exposure parameters, daily intakes, and toxicity values are presented in tabular form in accordance with the standard tables in *Risk Assessment Guidance for Superfund (RAGS) Part D* (EPA 2001).

This HHRA is developed in accordance with the following EPA guidance documents:

- Risk Assessment Guidance for Superfund: Human Health Evaluation Manual, Part A (EPA 1989)
- Human Health Evaluation Manual, Supplemental Guidance: Standard Default Exposure Factors (EPA 1991)
- Risk Assessment Guidance for Superfund: Human Health Evaluation Manual, Part D (EPA 2001)
- Risk Assessment Guidance for Superfund: Human Health Evaluation Manual, Part E, Supplemental Guidance for Dermal Risk Assessment (EPA 2004)
- Risk Assessment Guidance for Superfund: Human Health Evaluation Manual, Part F, Supplemental Guidance for Inhalation Risk Assessment (EPA 2009)
- EPA Regional Screening Levels for Chemical Contaminants at Superfund Sites (EPA 2011a)
- OSWER Draft Guidance for Evaluating the Vapor Intrusion to Indoor Air Pathway from Groundwater and Soils (Subsurface Vapor Intrusion Guidance) (EPA 2002)



- ProUCL Version 4.1 User Guide (Draft) and ProUCL Version 4.1.00 Technical Guide (Draft) (EPA 2010a and 2010b)
- Integrated Risk Information System (IRIS) (on-line database of toxicity information) (EPA 2011b)
- Provisional Peer Reviewed Toxicity Values (PPRTV) (on-line database of toxicity values derived for use in the Superfund program when such values are not available from IRIS)

1.2 Report Organization

This HHRA is composed of six sections, with tables and figures presented at the end of the text. The organization of the report and the contents of each section are described below.

Section 1	Introduction – provides an overview of the objectives and organization of the HHRA
Section 2	Site Background and Setting – briefly describes the site location and description, site history, site geology and hydrogeology, demography, and land use
Section 3	Data Evaluation – presents sample collection and analysis at various media, analytical data summary, data usability, and identification of COPCs
Section 4	Exposure Assessment – presents a conceptual site model (CSM) and identifies potential exposure pathways and potential receptor populations under both current and future land-use scenarios. In addition, methods for calculating EPCs are also presented in this section.
Section 5	Toxicity Assessment – discusses the relevant toxicity information on the identified COPCs
Section 6	Risk Characterization – integrates the toxicity and exposure assessments into quantitative and qualitative expressions of risk, and discusses uncertainties associated with the risk estimates
Section 7	Summary of Risk Assessment – summarizes the results of the risk assessment and presents conclusions based on the results
Section 8	References – lists references cited in this report



Section 2

Site Background and Setting

This section describes the site location and description, site history, geology and hydrogeology, surface water bodies, demography, and land use. This information is used to develop site-specific information on exposure pathways and receptors associated with the site.

2.1 Site Location and Description

The Maunabo Groundwater Contamination site is located in the municipality of Maunabo, in the southeastern coastal area of Puerto Rico (Figure 2-1). The site is located within an isolated alluvial river valley, and is surrounded by mountains to the north, east, and west, and the Caribbean Sea to the southeast. The Maunabo River and several intermittent streams are located within the vicinity and flow southeast toward the Caribbean Sea. Groundwater discharge forms the baseflow of the river and also discharges to smaller tributaries and streams (quebradas) such as Quebrada Arenas. Puerto Rico Beverage and the Former Sugar Mill are located to the north and south of the Maunabo #1 supply well and have been investigated as possible sources of contamination (Figure 2-2).

2.2 Site History

Maunabo's public water system, known as Maunabo Urbano, consists of four groundwater wells: Maunabo #1, Maunabo #2 (Bordaleza), Maunabo #3 (Calzada), and Maunabo #4 (San Pedro). In March 2002, the Puerto Rico Department of Health (PRDOH) ordered the Puerto Rico Aqueduct and Sewer Authority (PRASA) to close Maunabo #1 due to concentrations of tetrachloroethene (PCE) above the maximum contaminant level (MCL). Rather than close the well, PRASA opted to treat the groundwater with activated carbon treatment tanks due to water supply needs. Detections of PCE in pre-treatment samples from Maunabo #1 exceeded the MCL, but PCE was detected in post-treatment samples at levels below the MCL. PRASA has since replaced the tanks with three new tanks. The 2011 monthly data supplied by PRASA show that PCE has been detected in some post-treatment samples, but at levels below the MCL.

In October 2005, EPA's Region 2 Site Assessment Team 2 (SAT 2) collected water samples from each well, and from the distribution water line. Results indicated the presence of PCE, *cis*-1,2-dichloroethene (DCE), and methyltertbutylether (MTBE) in Maunabo #1, and in post treatment samples along the distribution line at levels below their respective MCLs. In addition, 1,1-DCE was also detected in Maunabo #4 at levels below its MCL.

In December 2005, SAT 2 conducted an investigation of possible sources of groundwater contamination at five industrial sites around the Maunabo area. Facilities investigated included the former Maunabo Municipal Solid Waste Landfill, PRASA's Wastewater Treatment Plant, El Negro Auto Body/Parts shop, Total Gas Station, Esso Gas Station, and five light industrial facilities operating under the auspices of the Puerto Rico Industrial Development Corporation (PRIDCO) (Figure 2-2).

Results of the October and December 2005 investigations indicated there was insufficient information to conclusively determine the source(s) of contamination of the drinking water supply well. Subsequently, the Agency for Toxic Substances and Disease Registry (ATSDR) evaluated available data, and conducted a site visit to complete a Public Health Assessment. Results of the Public Health Assessment concluded that the wells exceeded EPA's MCLs for PCE and *cis*-1,2-DCE in the past. However, exceedances were intermittent and did not exceed ATSDR's health based comparison values, and that current and future conditions at the site present no



apparent public health hazard. The Maunabo groundwater contamination site was proposed for the National Priority List (NPL) on April 19, 2006 and was listed on September 27, 2006.

2.3 Site Geology and Hydrogeology

This section provides a brief summary of the lithologic and hydrogeologic characteristics of the site and immediate area. A more detailed description of site geology and hydrogeology can be found in the RI report.

2.3.1 Site Geology

The Maunabo site is located within an alluvial valley surrounded by hills composed of igneous plutonic rocks. The two strata encountered at the site are the Quaternary-age alluvium deposits and the underlying Late Cretaceous-age igneous plutonic rocks mapped as the San Lorenzo Batholith (Rogers *et al.* 1979). Tonalite outcrops of the Punta Guayanes Complex are located southwest and southeast of the site. Other units near the site consist of metavolcanic rocks to the southwest and small outcrops of metamorphic amphibole hornfels to the west and southeast of the site. The units expected to be found beneath and adjacent to the site are described below.

Quaternary Alluvium Deposits

The Quaternary alluvium deposits consist of unconsolidated silt, clay, sand, and gravel and underlie the Maunabo River valley. The lithology varies widely with numerous discontinuous lenses of clay, silt, and sand. The thickest and most permeable deposits are located within the buried ancestral bedrock valleys and can be up to 200 feet thick (Adolphson *et al.* 1977).

San Lorenzo Batholith

The San Lorenzo Batholith, covering an area of 200 square miles, is one of the most geologically prominent features in southeastern Puerto Rico. The batholith, formed during the Late Cretaceous Age, is composed of three major units, which in chronological order (oldest to youngest) include diorite and gabbro, the San Lorenzo granodiorite and tonalite, and the Punta Guayenes plutonic complex. The Punta Guayenes complex ranges from tonalite to quartz monzanite and is generally concentrated in the outer portion of the batholith (Rogers *et al.* 1979).

2.3.2 Site Hydrogeology

Groundwater is most abundant in the shallow unconfined alluvial aquifer of the Maunabo River valley. The underlying igneous plutonic bedrock yields generally small to moderate quantities of water. Groundwater flow within the alluvium was determined to be at an oblique angle toward the river in the direction of river flow (Adolphson *et al.* 1977).

2.4 Demography and Land Use

The Maunabo site is located within the Maunabo Municipality in southeastern Puerto Rico. The Maunabo Municipality is comprised of 21 square miles with a population of 12,225 and a population density of 582 people per square mile (U.S. Census 2010). The primary land use in the vicinity of the site is agricultural with some residential, commercial, and light industrial development.



Section 3

Data Evaluation

Samples of environmental media, including soil, groundwater, surface water, and sediment, were collected in order to characterize the nature and extent of contamination from the site. The data evaluation step consists of reviewing and evaluating available data. Data evaluation allows for the identification of COPCs. The following subsections describe sample collection and analysis, data usability and the suitability of data for risk assessment purposes, analytical data summary, and the approach used to identify COPCs.

3.1 Sample Collection and Analysis

Previous investigations were conducted by SAT 2 in October and December 2005 to identify possible sources of contamination in Maunabo public water supply wells. CDM Smith, on behalf of EPA, conducted an RI field investigation in January through June 2011. The investigation focused on the nature and extent of groundwater contamination, and identification of potential source areas to define the hydrogeologic framework. Soil, groundwater, surface water, and sediment samples were collected as part of this investigation. Appendix A includes tables listing the samples used in the risk assessment.

3.1.1 Soil Sampling

Surface and subsurface soil samples were collected from the Puerto Rico Beverage and the Former Sugar Mill area because they are potential source areas. Elevated levels of *cis-*1,2-DCE were detected in groundwater screening samples near the Puerto Rico Beverage facility and elevated levels of PCE were detected in groundwater screening samples in the vicinity of the Former Sugar Mill area. A third potential source area, upgradient of Maunabo #4 where elevated levels of 1,1-DCE were detected, was also proposed for soil sampling. However, no potential sources were identified for this area during field reconnaissance; therefore, no soil samples were collected from this area. Other potential source areas, such as the gas station and the dry cleaner, were not targeted because groundwater screening sample results downgradient from these areas showed no site related contaminants.

Surface and subsurface soil samples were collected from six locations in the Former Sugar Mill and Puerto Rico Beverage areas (Figure 3-1). Six surface soil samples (0 to 2 feet below the ground surface [bgs]) were collected from each of the six soil boring locations at the Puerto Rico Beverage and Former Sugar Mill areas. Twenty-four and 20 subsurface soil samples were collected from the Former Sugar Mill and Puerto Rico Beverage areas, respectively. Subsurface soil samples were collected at 4-foot intervals from 2 feet bgs to the groundwater table at approximately 12 feet bgs. One sample was collected from the 2 to 4 feet interval and one sample per four feet intervals thereafter (4 to 8 and 8 to 12 feet). Soil samples were analyzed for the full target compound list (TCL) parameters, including pesticides/polychlorinated biphenyls (PCBs), target analyte list (TAL) metals, grain size (one-half of the samples), pH, and total organic carbon (TOC).

3.1.2 Groundwater Sampling

Two rounds of groundwater samples were collected from 16 monitoring wells, including 3 background monitoring wells, installed during the RI and 4 Maunabo supply wells (Figure 3-2). A total of 35 groundwater samples were collected and analyzed for trace-level volatile organic compounds (VOCs), TCL semi-volatile organic compounds (SVOCs), pesticides/PCBs, TAL metals, cyanide, chloride, methane, ethane, ethene, nitrate/nitrite, sulfate, sulfide, TOC, total suspended solid (TSS), total dissolved solid (TDS), ammonia, alkalinity, hardness, and total Kjehldahl nitrogen (TKN).



3.1.3 Surface Water and Sediment Sampling

Surface water and sediment samples were collected at seven co-located locations in the Maunabo River (Figure 3-3). One sample (SW/SD-01) was collected in the Maunabo River upstream of the site to provide background information. Surface water samples were analyzed for trace-level VOCs, TCL SVOCs, pesticides/PCBs, TAL metals, cyanide, hardness, alkalinity, ammonia, nitrate/nitrite, TKN, sulfate, sulfide, chloride, TOC, TDS, and TSS. Sediment samples were analyzed for full TCL parameters including pesticides/PCBs, TAL metals, grain size, pH, and TOC.

3.2 Data Usability

As part of the RI sampling program, field duplicates, matrix spike/matrix spike duplicates, and trip and rinsate blanks were collected and submitted for analyses. These samples provide information on analytical variability and error, the overall performance of the field sampling effort, and the uncertainty surrounding the analytical results. Appendix E in the HHRA presents the usability of the data. Field duplicate samples provide an indication of analytical variability and error. Rinsate blanks are indicators of equipment cleanliness and the effectiveness of equipment decontamination procedures. Trip blanks are used to assess whether cross contamination of samples has occurred during container shipment and storage. Analytical results obtained from field duplicates are used for quality assurance/quality control purposes and are not included in the datasets for risk evaluation.

A goal of 90 percent completeness was established. For groundwater, 87 analytical results were rejected out of 23,857 total results, for a completeness value of 99.64 percent. For surface water and sediment, 7 and 9 analytical results were rejected out of 1,280 and 1,267 total results, for a completeness value of 99.50 percent for surface water and 99.29 percent for sediment. Finally, for soil, 46 analytical results were rejected out of 7,964 total results, for a completeness value of 99.42 percent. Completeness results, therefore, met the project goal.

Generally, data from the RI field investigation were determined to be suitable for risk assessment purposes as defined in the data quality objectives in the Quality Assurance Project Plan (CDM Smith 2010). Rejected data, as indicated by an "R" qualifier, are not used for any reporting purpose or during the risk assessment evaluation.

3.3 Summary of Analytical Results

The evaluation and summary of analytical results are based on those chemicals that were reported at concentrations higher than the reporting limit in one or more samples. Statistical summaries, comprising the minimum and maximum detected concentrations and detection frequency for chemicals, are presented by medium in Tables B-2.1a through B-2.5 in Appendix B. Analytical data results are summarized below.

3.3.1 Soil

3.3.1.1 Former Sugar Mill

Surface Soil

SVOCs, pesticides, and metals were detected in surface soil at the Former Sugar Mill area (Table B-2.1a in Appendix B).

SVOCs: Seventeen SVOCs were detected in the surface soil. Carcinogenic polycyclic aromatic hydrocarbons (PAHs), including benzo(a)pyrene, benzo(a)anthracene, benzo(b)fluoranthene, benzo(k)fluoranthene, chrysene, and dibenz(a,h)anthracene, were detected in at least 2 of the 6 surface soil samples.

Pesticides: Seven pesticides were detected in the surface soil. Dieldrin was the most frequently detected pesticide (2 of 6 samples).



Inorganics: Twenty-two metals were detected in the surface soil. All metals were detected in all of the surface soil samples, with the exception of antimony and silver.

Subsurface Soil

VOCs, SVOCs, pesticides, and metals were detected in subsurface soil at the Former Sugar Mill area (Table B-2.2a in Appendix B).

VOCs: Two VOCs were detected in the subsurface soil. Acetone and 2-butanone were detected in 6 and 2 of the 24 subsurface soil samples, respectively.

SVOCs: Nineteen SVOCs were detected in the subsurface soil. Carcinogenic PAHs were detected in at least 3 of the 24 subsurface soil samples.

Pesticides: Seven pesticides were detected in the subsurface soil. p,p'-dichlorodiphenyltrichloroethane (4,4'-DDT) and dieldrin were the two most frequently detected pesticides (3 of 24 samples).

Inorganics: Twenty-three metals were detected in the subsurface soil. Aluminum, barium, calcium, chromium, cobalt, copper, iron, magnesium, mercury, nickel, potassium, sodium, vanadium, and zinc were detected in all subsurface soil samples.

3.3.1.2 Puerto Rico Beverage

Surface Soil

VOCs, SVOCs, pesticides, and metals were detected in surface soil at the Puerto Rico Beverage area (Table B-2.1b in Appendix B).

VOCs: Two VOCs were detected in the surface soil. Acetone and 2-butanone were detected in 1 of the 6 surface soil samples.

SVOCs: Eleven SVOCs were infrequently detected in the surface soil. Butylbenzylphthalate was the most frequently detected SVOC (3 of 6 samples).

Pesticides: Six pesticides were detected in the surface soil. p,p'-dichlorodiphenyldichloroethylene (4,4'-DDE), gamma-chlordane, and heptachlor epoxide were the three most frequently detected pesticides (2 of 6 samples).

Inorganics: Twenty-one metals were detected in the surface soil. All metals were detected in all of the surface soil samples, except antimony, arsenic, cadmium, cyanide, and lead.

Subsurface Soil

VOCs, SVOCs, pesticides, and metals were detected in subsurface soil at the Puerto Rico Beverage area (Table B-2.2b in Appendix B).

VOCs: Two VOCs were detected in the subsurface soil. Acetone and 2-butanone were detected in 11 and 5 of the 20 subsurface soil samples, respectively.

SVOCs: Eleven SVOCs were detected in the subsurface soil. Butylbenzylphthalate was the most frequently detected SVOCs (3 of 20 samples).

Pesticides: Six pesticides were detected in the subsurface soil. Gamma-chlordane and heptachlor epoxide were the two most frequently detected pesticides (3 of 20 samples).



Inorganics: Twenty-one metals were detected in the subsurface soil. All metals were detected in all of the subsurface soil samples, except antimony, arsenic, cadmium, cyanide, and lead.

3.3.2 Groundwater

VOCs, SVOCs, pesticides, and metals were detected in groundwater at the site (Table B-2.3 in Appendix B).

VOCs: Nineteen VOCs were detected in the groundwater. *cis*-1,2-DCE was detected in 16 of the 35 groundwater samples with a maximum concentration of 300 microgram per liter (μ g/L). *trans*-1,2-DCE was detected in 4 of the 35 groundwater samples with a maximum concentration of 13 μ g/L. PCE was detected in 9 of the 35 groundwater samples with a maximum concentration of 8.5 J μ g/L. Trichloroethene (TCE) was detected in 7 of the 35 groundwater samples with a maximum concentration of 1.9 μ g/L. Vinyl chloride was detected in 3 of the 35 groundwater samples with a maximum concentration of 0.73 μ g/L.

SVOCs: Five SVOCs were detected in the groundwater. Pentachlorophenol was the most frequently detected SVOC (2 of 34 samples).

Pesticides: Four pesticides were detected in the groundwater. Endosulfan I was the most frequently detected pesticide (2 of 34 samples).

Inorganics: Twenty-one metals were detected in the groundwater. The essential nutrient, calcium, magnesium, potassium, sodium were detected in all of the groundwater samples. Barium and manganese were the most frequently detected metals (31 of 31 samples).

3.3.3 Surface Water

VOCs, SVOCs, and metals were detected in surface water at the site (Table B-2.4 in Appendix B).

VOCs: Three VOCs were detected in the surface water samples. Bromodichloromethane and dibromochloromethane were each detected in 3 of the 6 surface water samples. Bromoform was detected in 2 of 6 surface water samples.

SVOCs: One SVOC, bis(2-ethylhexyl)phthalate, was detected in the surface water.

Inorganics: Ten metals were detected in the surface water. Barium, calcium, manganese, potassium, sodium, and zinc were detected in all of the samples.

3.3.4 Sediment

SVOCs, pesticides, and metals were detected in sediment at site (Table B-2.5 in Appendix B).

SVOCs: One SVOC, bis(2-ethylhexyl)phthalate, was detected in the sediment samples.

Pesticides: Six pesticides were detected in the sediment samples. Methoxychlor was the most frequently detected pesticide (2 of 6 samples).

Inorganics: Fifteen metals were detected in the sediment. All inorganics were detected in all of the sediment samples, except arsenic and lead.

3.4 Identification of Chemicals of Potential Concern

Many chemicals have been detected in soil, groundwater, surface water, and sediment from samples collected at the site. Screening of analytical data is conducted to identify COPCs to be further evaluated in the risk assessment. Screening helps to focus the assessment on chemicals that could pose a human health risk.



The screening levels are based on Regional Screening Levels (RSLs) for Chemical Contaminants at Superfund Sites (EPA 2011a). Residential RSLs for soil are used as screening levels for soil and sediment, while tap water RSLs are used as screening levels for groundwater and surface water. To account for exposure to multiple chemicals, RSLs for chemicals based on noncancer health effects are decreased by a factor of 10 to account for a target hazard quotient (HQ) of 0.1.

The maximum detected concentrations are compared to screening levels to identify COPCs. Chemicals are considered COPCs if the maximum detected concentration exceeds the respective screening level. Group A carcinogens (i.e., known human carcinogen) are retained as COPCs even when they are present at the site at concentrations below their respective screening levels. Calcium, magnesium, potassium, and sodium are essential nutrients and are not evaluated as COPCs in health risk assessments. Detection frequency and chemical toxicity are also considered in the identification of COPCs. If a chemical is detected in 5 percent or less of the samples in a data set having at least 20 samples, then the chemical is only considered a COPC if it is a Group A carcinogen. The decision process for identifying COPCs is provided in Tables B-2.1a through B-2.5 in Appendix B.

Risks from exposure to lead are not quantified following the exposure models for other COPCs. EPA considers lead to be a special case because of the difficulty in identifying the "threshold". Health risks from lead are evaluated based on blood lead concentration, which can be modeled using the Integrated Exposure Uptake Biokinetic Model or the Adult Lead Model. The screening levels for lead for residential and industrial soil are 400 and 800 milligram per kilogram (mg/kg), respectively, based on the OSWER Directive 9355.4-12 (EPA 1994). For groundwater, the screening level of 15 μ g/L is based on the Puerto Rico Water Quality Standard and the Federal MCL. The screening process for lead is performed separately in the Lead Worksheet detailed in Table 3-1.

For vapor intrusion, generic screening levels provided by EPA in *Draft Guidance for Evaluating the Vapor Intrusion to Indoor Air Pathway from Groundwater and Soils* (Subsurface Vapor Intrusion Guidance) (EPA 2002a) are used as screening levels. The vapor intrusion screening levels are based on a cancer risk of 10^{-6} and/or a HQ of 1. For some VOCs, where Federal MCLs are listed as vapor intrusion screening levels, risk-based screening level based on a cancer risk of 10^{-4} is adjusted to a 10^{-6} value (2002a). The vapor intrusion screening process is performed in Table E-1 in Appendix E.

COPCs identified in each medium for further quantitative evaluation in the HHRA are presented in Table 3-2.



This page intentionally left blank.

Section 4

Exposure Assessment

As a component of the HHRA, the exposure assessment strives to predict human exposure to COPCs in affected media at the site and in the vicinity. The exposure assessment describes exposure scenarios in which people may come into contact with site-related COPCs, provides equations and parameters to quantify exposure, and summarizes methods for evaluating exposure to lead. Results of the exposure assessment are integrated with chemical-specific toxicity information to characterize potential risks.

4.1 Exposure Pathways

Potential exposure pathways for the site are defined based on current and potential future land uses of the site. Each potential pathway is evaluated considering site-specific conditions to determine if the pathway could be present. The area demography and land use characteristics are taken into consideration when the pathways are developed. If a pathway between the source of contamination and a human receptor could potentially be complete, it is retained for further evaluation.

4.1.1 Conceptual Site Model

Contamination at the site may be linked to previous releases and discharges to the environment. Results of the previous investigations indicated there was insufficient information to conclusively determine the source(s) of contamination of the drinking water supply wells. People living, working or recreating at the site may be exposed to contaminants in soil, groundwater, surface water, and sediment. A CSM, illustrating how chemicals may move from historical release points to locations where human exposure may occur, is developed to provide a roadmap to these possible exposures. The CSM is presented in Figure 4-1 and described in detail in the following sections.

4.1.2 Identification of Exposure Pathways

As defined in the RAGS Part A (EPA 1989), an exposure pathway is composed of the following elements:

- A source and mechanism of chemical release to the environment
- An environmental transport medium (e.g., groundwater) for the released chemical and/or mechanism to transfer the chemical from one medium to another
- A point of potential contact by humans with the contaminated medium
- A route of exposure (i.e., ingestion, inhalation, or dermal contact)

In the risk assessment, pathways are identified for the No Action alternative to evaluate risk if no site remediation occurs. This assessment also assumes that no additional restrictions to site access or use exist. The goal of this evaluation is to establish whether it is feasible for individuals to engage in activities resulting in exposure to site-related contaminants.

Based on the RI, contamination was detected in soil, groundwater, surface water, and sediment at the site. There are three general routes through which individuals could potentially be exposed to chemical contamination in these media: ingestion, inhalation, and dermal contact. A receptor may get small amounts of soil on his hands and subsequently transfer some of this soil to his mouth during common hand-to-mouth



activity. Exposure would occur when this soil is swallowed and some contaminants in soil are absorbed in the gastrointestinal tract.

The following sections describe the potential exposure pathways and receptors under both current and potential future land-use conditions. An identified pathway does not imply that exposure is actually occurring, only that the potential exists for the pathway to be complete.

4.1.2.1 Soil Exposure Pathways

Previous sampling and continued monitoring at the site documented groundwater contamination at the site. However, these chemicals have not been detected in soil at the site. People working, visiting, or living at the site could be exposed to contaminants through incidental ingestion of soil, dermal contact with soil, and inhalation of particulates and volatiles released from soil. Additionally, residents may ingest dust that has settled onto objects, surfaces, floors, and carpeting in their homes.

4.1.2.2 Groundwater Exposure Pathways

Previous sampling and continued monitoring at the site documented groundwater contamination. The site is currently supplied by the Maunabo public water system; no private wells have been identified within the plume area. Current and future residents and commercial/industrial workers may be potentially exposed to groundwater via ingestion of and dermal contact with groundwater, and inhalation of chemical vapor while showering/bathing. In addition, current and future residents and commercial/industrial workers may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. Site groundwater concentrations are compared to the target groundwater concentrations from the 2002 EPA Subsurface Vapor Intrusion Guidance, and the results are presented in Section 6 of this HHRA.

4.1.2.3 Surface Water and Sediment Exposure Pathways

Contaminants at the site may eventually be transported to the Maunabo River via surface runoff, erosion, deposition, and overland flow. Surface water and sediment of the Maunabo River may potentially be impacted. People visiting the river may be exposed to contaminants in surface water and sediment. Routes of exposure include incidental ingestion of and dermal contact with surface water and sediment. In addition, the Maunabo River is classified as Class SD water which is considered a potential potable drinking water source. Although currently residents are using public supply water, in the future, surface water from the Maunabo River could be used as a potable drinking water supply. Residents may be exposed to contaminants in surface water through ingestion of and dermal contact with groundwater and inhalation of vapor while showering /bathing.

4.2 Characterization of Potentially Exposed Populations

The site is currently zoned for residential and commercial/industrial use. The site is currently connected to the public water supply. The Maunabo River may be visited as a recreational area. Based on current and future land uses, exposed populations include or may include at some later date, commercial/industrial workers, trespassers, residents, recreational users, and construction workers. Not all of these populations are expected to be present in all of the areas. The following subsections detail the potential exposure pathways identified for each potentially exposed population. Appendix A includes tables listing the samples used to evaluate each receptors exposure.



4.2.1 Current Receptors

4.2.1.1 Commercial/Industrial Workers

Current commercial/industrial workers at the site may come in contact with contaminants in surface soil through incidental ingestion of and dermal contact with soil, and inhalation of particulates and volatiles released from surface soil. Currently, groundwater at the site is used as drinking water through the Maunabo public water system. To be conservative, workers are assumed to be exposed to groundwater via potable uses through ingestion of and dermal contact with groundwater, and inhalation of VOCs in groundwater while showering at work. In addition, commercial/industrial workers may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. Commercial/industrial workers are evaluated using default parameters recommended by EPA as described in Section 4.5.

4.2.1.2 Trespassers

Trespassers could gain access to most or all areas of the site. When trespassing, these individuals may be exposed to contaminants in surface soil through incidental ingestion of and dermal contact with soil, and inhalation of particulates and volatiles released from surface soil. Adolescent trespassers (7 to 12 years old) are evaluated using default parameters recommended by EPA as described in Section 4.5.

4.2.1.3 Residents

Current residents in the Former Sugar Mill area may come into contact with contaminants through incidental ingestion of soil, dermal contact with soil, and inhalation of particulates and volatiles released from surface soil. Additionally, all residents are connected to the Maunabo public water supply system; thus, current residents are exposed to groundwater through potable water uses. Residents may come into contact with contaminants through ingestion of and dermal contact with groundwater, and inhalation of VOCs in groundwater while bathing or showering. In addition, current residents may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. Current residents are evaluated using default parameters recommended by EPA as described in Section 4.5.

4.2.1.4 Recreational Users

Recreational users who visit the Maunabo River may come into contact with contaminants in surface water and sediment from wading or playing in the river. Routes of exposure may include incidental ingestion of and dermal contact with surface water and sediment. Adolescents (7 to 12 years old) are expected to be present more frequently without adult supervision. Adolescent recreational users are selected as potential receptors. Exposure parameters for adolescent recreational users are described in Section 4.5.

4.2.2 Future Receptors

4.2.2.1 Commercial/Industrial Workers

Similar to current commercial/industrial workers, future workers may come into contact with contaminants in surface soil through incidental ingestion of and dermal contact with soil, and inhalation of particulates and volatiles released from surface soil. Future workers could also be exposed to groundwater via potable uses through ingestion of and dermal contact with groundwater, and inhalation of VOCs in groundwater while showering at work. In addition, future commercial/industrial workers may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. Future commercial/industrial workers are evaluated using default parameters recommended by EPA as described in Section 4.5.



4.2.2.2 Trespassers

Trespassers could gain access to most or all areas of the site. When trespassing, these individuals may be exposed to contaminants in surface soil through incidental ingestion of and dermal contact with soil, and inhalation of particulates and volatiles released from surface soil. Adolescent trespassers (7 to 12 years old) are evaluated using default parameters recommended by EPA as described in Section 4.5.

4.2.2.3 Residents

The Puerto Rico Beverage area may be developed into residential properties in the future. Residents in both the Former Sugar Mill and Puerto Rico Beverage areas may come into contact with contaminants through incidental ingestion of soil, dermal contact with soil, and inhalation of particulates and volatiles released from surface soil. Additionally, all residents are connected to the Maunabo public water supply system; thus, residents are exposed to groundwater through potable water uses. Residents may come into contact with contaminants through ingestion of and dermal contact with groundwater, and inhalation of VOCs in groundwater while bathing or showering. In addition, future residents may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. Residents who use the Maunabo River as potable water uses may come into contact with contaminants through ingestion of and dermal contact with surface water, and inhalation of VOCs in groundwater while bathing or showering. Future residents are evaluated using default parameters recommended by EPA as described in Section 4.5.

4.2.2.4 Recreational Users

Recreational users who visit the Maunabo River may come into contact with contaminants in surface water and sediment from wading or playing in the river. Routes of exposure may include incidental ingestion of and dermal contact with surface water and sediment. Adolescents (7 to 12 years old) are expected to be present more frequently without adult supervision. Adolescent recreational users are selected as potential receptors. Exposure parameters for adolescent recreational users are described in Section 4.5.

4.2.2.5 Construction Workers

If construction takes place at the site in the future, construction workers could have short-term, high intensity exposure to contaminants in surface and subsurface soil via incidental ingestion of and dermal contact with soil, and inhalation of particulates and volatiles released from surface and subsurface soil. Future construction workers are evaluated using default parameters recommended by EPA as described in Section 4.5.

4.3 Summary of Exposure Pathways and Receptors

The following exposure pathways for each receptor at Puerto Rico Beverage and Former Sugar Mill under current and future land-use scenarios are considered to be potentially complete and are evaluated as part of the assessment of exposure to contaminants at the site. A summary of these exposure pathways is illustrated in Figure 4-1 and presented in Table 4-1.

CURRENT LAND-USE SCENARIO

The Site

- Commercial/Industrial Worker
 - Groundwater
 - o Ingestion
 - Dermal contact
 - Inhalation of volatiles during showering
 - o Inhalation of volatiles through vapor intrusion



- Resident
 - Groundwater
 - o Ingestion
 - o Dermal contact
 - o Inhalation of volatiles during showering or bathing
 - o Inhalation of volatiles through vapor intrusion

Puerto Rico Beverage

- Commercial/Industrial Worker
 - Surface Soil
 - o Incidental ingestion
 - Dermal contact
 - Inhalation of particulates and volatiles
- Trespasser (Adolescent [7-12 years])
 - Surface Soil
 - o Incidental ingestion
 - Dermal contact
 - o Inhalation of particulates and volatiles

Former Sugar Mill

- Commercial/Industrial Worker
 - Surface Soil
 - Incidental ingestion
 - Dermal contact
 - Inhalation of particulates and volatiles
- Trespasser (Adolescent [7-12 years])
 - Surface Soil
 - o Incidental ingestion
 - Dermal contact
 - Inhalation of particulates and volatiles
- Resident
 - Surface Soil
 - o Incidental ingestion
 - o Dermal contact
 - o Inhalation of particulates and volatiles

Maunabo River

- Recreational User (Adolescents [7 to 12 years old])
 - Surface Water
 - o Incidental ingestion
 - Dermal contact
 - Sediment
 - o Incidental ingestion
 - Dermal contact



FUTURE LAND-USE SCENARIO

The Site

- Commercial/Industrial Worker
 - Groundwater
 - Ingestion
 - o Dermal contact
 - o Inhalation of volatiles during showering
 - o Inhalation of volatiles through vapor intrusion
- Resident
 - Groundwater
 - o Ingestion
 - o Dermal contact
 - o Inhalation of volatiles during showering or bathing
 - o Inhalation of volatiles through vapor intrusion

Puerto Rico Beverage

- Commercial/Industrial Worker
 - Surface Soil
 - o Incidental ingestion
 - Dermal contact
 - o Inhalation of particulates and volatiles
- Trespasser (Adolescent [7-12 years])
 - Surface Soil
 - o Incidental ingestion
 - Dermal contact
 - Inhalation of particulates and volatiles
- Resident
 - Surface Soil
 - o Incidental ingestion
 - o Dermal contact
 - o Inhalation of particulates and volatiles
- Construction Worker
 - Surface Soil
 - Incidental ingestion
 - Dermal contact
 - o Inhalation of particulates and volatiles

Former Sugar Mill

- Commercial/Industrial Worker
 - Surface Soil
 - o Incidental ingestion
 - Dermal contact
 - Inhalation of particulates and volatiles



- Trespasser (Adolescent [7-12 years])
 - Surface Soil
 - Incidental ingestion
 - Dermal contact
 - Inhalation of particulates and volatiles
- Resident
 - Surface Soil
 - Incidental ingestion
 - Dermal contact
 - Inhalation of particulates and volatiles
- Construction Worker
 - Surface Soil
 - Incidental ingestion
 - Dermal contact
 - Inhalation of particulates and volatiles

Maunabo River

- Recreational User (adolescents [7 to 12 years old])
 - Surface Water
 - o Incidental ingestion
 - Dermal contact
 - Sediment
 - Incidental ingestion
 - Dermal contact
- Resident
 - Surface Water
 - Ingestion
 - Dermal contact
 - o Inhalation of particulates and volatiles

4.4 Calculation of Exposure Point Concentrations

This section presents the methodology that was employed to calculate the EPCs for the COPCs for each medium including ambient air from soil particulates.

4.4.1 Exposure Point Concentrations of Samples Collected

For each data set (representing a single chemical in soil, groundwater, surface water, and sediment) with at least 5 samples with 4 detected values, a 95 percent (or higher) upper confidence limit (UCL) on the arithmetic mean concentration was calculated and compared to the maximum detected concentration for that chemical. The lower value of the UCL and the maximum detected value is selected as the EPC, as recommended by EPA (1992). UCLs are not calculated for data sets with fewer than four detected concentrations. In such cases, maximum concentrations are used as the EPCs.

Several statistical methods can be used to estimate the UCL of a data set, depending upon the data distribution. Therefore, two key steps are required to estimate the UCL of a data set.

Determine the distribution of the data (i.e., normal, lognormal, gamma, or neither)



Compute the UCL using the appropriate procedure for the data distribution

In this assessment, both steps were performed with the ProUCL statistical software (EPA 2010b). The ProUCL program tests the normal, lognormal, gamma, and non-parametric distributions of each data set and the UCLs are calculated with the statistical procedures recommended by EPA, based on the findings of Singh, Singh, and Engelhardt (1997, 1999) (EPA 2010b). ProUCL computes the UCL using 5 parametric and 10 non-parametric methods, depending on the distribution.

- For normal distributions, the Student's t-statistic is used to calculate the UCL.
- For lognormal distributions, one of four different computation methods is used to calculate the UCL depending on the skewness of the data (as indicated by the standard deviation of the log-transformed data) and the sample size.
- For gamma distributions, one of two computation methods is used to calculate the UCL based on a "k value," which is the shape parameter of a gamma distribution. For values of $k \ge 0.1$, the exposure point concentration term is computed using an adjusted gamma UCL of the mean (when $0.1 \le k \le 0.5$) or an approximate gamma UCL of the mean (when k > 0.5). For values of k < 0.1, a UCL is obtained using either the bootstrap-t method or Hall's bootstrap method when the sample size is small (less than 15), or the approximate gamma for larger datasets.
- For data sets that do not fit a normal, a lognormal, or gamma distribution, the ProUCL program calculates and recommends a UCL from 1 of the 10 non-parametric methods (EPA 2010b).

Tables B 3.1a through B 3.5 in Appendix B present the EPCs for each COPC in each medium. As noted previously, the EPC is the lower value of the UCL and the maximum detected value. ProUCL outputs for COPCs are presented in Appendix C.

4.4.2 Exposure Concentrations for Inhalation

In accordance with EPA *Risk Assessment Guidance for Superfund, Part F, Supplemental Guidance for Inhalation Exposure* (EPA 2009), inhalation exposure could be categorized as acute, subchronic, and chronic exposures, based on exposure duration and exposure pattern. Exposure concentrations for inhalation exposure are calculated based on the EPA 2009 RAGS Part F Guidance.

Chronic exposure is generally used for continuous or near-continuous inhalation exposures that occur for seven years or more. Subchronic exposure refers to repeated exposures for more than 30 days up to 7 years. Acute exposure includes exposures lasting 24 hours or less or intermittent exposures that occur at a series of short periods (e.g., 4 hours) separated by several days of no exposure. Based on the exposure duration and exposure pattern, chronic exposure applies to commercial/industrial workers, construction workers, and residents. Acute exposure applies to trespassers.

4.4.3 Indoor Air Exposure Point Concentrations Using the Shower Model

Modeling is required to estimate the indoor air concentrations of VOCs from groundwater while showering. In this scenario, receptors are assumed to inhale VOCs while showering and during time spent in the bathroom after showering. Dermal absorption of volatilized VOCs is assumed to be negligible due to low dermal permeabilities. Methodologies for estimating exposure to VOCs in domestic water supplies from the inhalation exposure route are based on a shower model developed by Schaum *et al.* (1994).

The shower model treats the bathroom as one compartment and yields an air concentration averaged over the time of the actual shower and the time spent in the bathroom after the shower. The model was derived by



assuming that the chemical contaminant volatilizes at a constant rate, instantly mixes uniformly with the bathroom air, and that ventilation with clean air does not occur. This implies that the chemical concentration in the air increases linearly from zero to a maximum at the end of the shower, and then remains constant during the time an individual spends in the bathroom immediately after showering.

The air concentration is estimated using the water concentration. The water concentration is a site-specific value that refers to the concentration of a chemical in water as it enters the shower. The UCL value or the maximum detected value is utilized as the water concentration (i.e., the EPC listed in Table B-3.3 in Appendix B). Chemical-specific fraction volatilized values are calculated from these chemical properties using the equation provided by Schaum *et al.* (1994) (see Tables D-1 and D-2 in Appendix D).

The water flow rate of 1,000 liter (L)/hour is assumed in the model for the reasonable maximum exposure (RME) scenario and 500 L/hour for the central tendency exposure (CTE) scenario (Schaum *et al.* 1994). The bathroom volume of 6 cubic meters (m³) is assumed in the model for the RME scenario and 16 m³ for the CTE scenario (Schaum *et al.* 1994). The time spent in showering is 0.25 and 0.45 hour for adults and young children (0 to 6 years), respectively, under the RME scenario and 0.1 and 0.14 hour under the CTE scenario (EPA 2004). The time spent in the bathroom after showering is assumed to be 0.33 and 0.55 hour for adults and young children, respectively, under the RME scenario and 0.15 and 0.19 hour under the CTE scenario (EPA 2004). Exposure point air concentrations from the shower model are presented in Tables D-3 and D-4 in Appendix D.

4.5 Exposure Parameter Assumptions

Exposure parameters for each scenario are primarily taken from EPA documents (EPA 1989, 1991, 1997, 2002b, 2004, and 2009) and are consistent with EPA Region 2's approach. EPA's standard default assumptions (EPA 1991) or site-specific values are used. Otherwise values from the most recent guidance available are used unless EPA Region 2 has a known preference for a specific value. RME and CTE parameters used in the risk assessment are provided in Tables B-4.1 through B-4.5 in Appendix B.

4.5.1 Commercial/Industrial Workers

Commercial/industrial workers are assumed to be exposed to contaminants in surface soil and groundwater for 250 days per year for the RME scenario (EPA 2004) and 219 days for the CTE scenario (EPA 2004). The exposure duration for workers is 25 years for the RME scenario and 9 years for the CTE scenario (EPA 2004). The exposure time for outdoor workers is 8 hours per day for the RME scenario and 4 hours per day for the CTE scenario. A life expectancy of 70 years (EPA 1989) is used as the averaging time for exposure to carcinogenic contaminants. The averaging time for noncancer effects is equal to the exposure duration, or 25 years under the RME scenario, and 7 years for the CTE scenario (EPA 1989). A body weight of 70 kilogram (kg) is used for both the RME and CTE scenarios (EPA 2002b).

4.5.1.1 Soil

The incidental soil ingestion rate for workers is assumed to be 100 milligram (mg)/day (EPA 2002b) for the RME scenario and 50 mg/day for the CTE scenario (EPA 1997). For dermal contact with soil, the worker is assumed to wear a short-sleeved shirt, long pants, and shoes; therefore, the exposed skin surface is limited to the head, hands, and forearms. The resulting exposed skin surface area is 3,300 square centimeter (cm²), the average of the 50th percentile for males and females greater than 18 years of age (EPA 2004). A dermal adherence factor of 0.2 mg/cm² is assumed for the RME scenario and 0.02 mg/cm² is assumed for the CTE scenario (EPA 2004). The chemical-specific dermal absorption fractions for COPCs are presented in Table B-4.5. A particulate emission factor (PEF) of 1.36x10⁹ m³/kg is used (EPA 2002b).



4.5.1.2 Groundwater

Commercial/industrial workers are assumed to be exposed to groundwater while at work via ingestion of groundwater as drinking water. Workers are assumed to consume 1 L/day of water for both the RME and CTE scenario (EPA 1991). Inhalation and dermal exposure of workers to groundwater may occur through showering. Shower/bathing duration for adults is assumed to be 0.58 and 0.25 hour under the RME and CTE scenarios, respectively (EPA 2004). For surface area exposed, the estimate of total body surface area is 18,000 cm² for adults (EPA 2004). Chemical-specific dermal permeability coefficients for COPCs are presented in Table B-4.5.

4.5.2 Trespassers

Trespassers are assumed to trespass 100 days per year. They are assumed to spend two hours per visit for the RME scenario. One-half of the RME exposure time and frequency are used for the CTE scenario. The RME duration for the trespasser is 6 years for adolescents (7 to 12 years old). A life expectancy of 70 years (EPA 1989) is used as the averaging time for exposure to carcinogenic contaminants. The averaging time for noncancer effects is equal to the exposure duration, or 6 years under both the RME and CTE scenarios. A body weight of 36 kg is used for adolescents (EPA 1997) under both scenarios.

The incidental soil ingestion rate for the trespasser is assumed to be 100 mg/day for adolescents for the RME scenario (EPA 2002b). For the CTE scenario, the soil ingestions rate is assumed to be 50 mg/day for adolescents (EPA 1997). The trespasser is assumed to wear a short-sleeved shirt, shorts, and shoes; therefore, the exposed skin surface is limited to the head, hands, forearms, and lower legs. The exposed skin surface area is 3,600 cm² for adolescents (EPA 2004). The adherence factor is 0.07 mg/cm² and 0.01 mg/cm² is assumed for the RME and CTE scenarios (EPA 2004). The chemical-specific dermal absorption fractions for COPCs are presented in Table B-4.5. A PEF of 1.36x10⁹ m³/kg is used (EPA 2002b).

4.5.3 Residents

All residents are assumed to be exposed for 24 hours per day, for 350 days per year for both the RME and CTE scenarios (EPA 1991). The total RME duration for residents is assumed to be 30 years (EPA 1991): 24 years as an adult and 6 years as a young child. The CTE duration for adult residents is 9 years, based on the 50th percentile value for years living in the current home (EPA 1997). The CTE duration is assumed to be 6 years for children.

A life expectancy of 70 years (EPA 1989) is used for all receptor groups as the averaging time for exposure to carcinogenic contaminants. The averaging time for noncancer effects is equal to the exposure duration, or 24 years for adults under the RME scenario, 9 years for adults under the CTE scenario, and 6 years for children under both scenarios. A body weight of 70 kg is used for adult residents (EPA 2002b) and 15 kg for children (0 to 6 years old) (EPA 2002b) under both scenarios.

Carcinogenic exposure estimates throughout a lifetime are impacted by age-dependent intake factors. To take into account the difference in daily ingestion rates, body weights, and exposure durations for young children and adults, age-adjusted intake factors are used for carcinogenic exposure estimates (EPA 1991). This is accomplished by using factors for a child for the first 6 years of exposure and adult factors for the remaining 24 years of the exposure period.

4.5.3.1 Soil

The incidental soil ingestion rate for adult residents is assumed to be 100 mg/day (EPA 2002b) for the RME scenario and 50 mg/day for the CTE scenario (EPA 1997). For child residents, the incidental soil ingestion rate is assumed to be 200 mg/day and 100 mg/day for the RME and CTE scenarios, respectively (EPA 2002b). For dermal contact with soil, the adult residents are assumed to wear a short-sleeved shirt, shorts, and shoes; therefore, the exposed skin surface is limited to the head, hands, forearms, and lower legs. The resulting



exposed skin surface area is 5,700 cm² (EPA 2004). A dermal adherence factor of 0.07 mg/cm² is assumed for RME scenario and 0.01 mg/cm² is assumed for the CTE scenario for adult residents (EPA 2004). For dermal contact with soil, the child residents are assumed to wear a short-sleeved shirt, shorts, and no shoes; therefore, the exposed skin surface is limited to the head, hands, forearms, lower legs, and feet. The resulting exposed skin surface area is 2,800 cm² (EPA 2004). A dermal adherence factor of 0.2 mg/cm² is assumed for the RME scenario and 0.04 mg/cm² is assumed for the CTE scenario for child residents (EPA 2004). The chemical-specific dermal absorption fractions for COPCs are presented in Table B-4.5. A PEF of 1.36x109 m³/kg is used (EPA 2002b).

4.5.3.2 Groundwater

For groundwater ingestion exposure parameters, adult residents are assumed to consume 2 liters of water per day for the RME scenario (EPA 1991) and 1.4 L/day for the CTE scenario, based on a mean water ingestion rate for adults (EPA 1997). A water intake rate of 1 L/day is assumed for child residents based on a 95th percentile drinking water ingestion rate for children 1 to 10 years old (EPA 1997). The CTE drinking water intake rate for children is assumed to be 0.4 L/day, based on a weighted mean drinking water ingestion rate for children between 1 to 10 years of age (EPA 1997).

Inhalation and dermal exposure of residents to groundwater may occur through showering and other household activities. Shower/bathing duration for adults is assumed to be 0.58 and 0.25 hour for the RME and CTE scenarios, respectively (EPA 2004). Children are assumed to spend 1 and 0.33 hour for the RME and CTE scenarios, respective (EPA 2004). For surface area exposed, the estimate of total body surface area is 18,000 cm² for adults, based on the average 50th percentiles for males and females (EPA 2004). For child residents, the total surface area is 6,600 cm², based on weighted surface area for children between 0 to 6 years of age (EPA 2004). Chemical-specific dermal permeability coefficients for COPCs are presented in Table B-4.5.

4.5.3.3 Surface Water

For surface water ingestion exposure parameters, adult residents are assumed to consume 2 liters of water per day for the RME scenario (EPA 1991) and 1.4 L/day for the CTE scenario, based on a mean water ingestion rate for adults (EPA 1997). A water intake rate of 1 L/day is assumed for child residents based on a 95th percentile drinking water ingestion rate for children 1 to 10 years old (EPA 1997). The CTE drinking water intake rate for children is assumed to be 0.4 L/day, based on a weighted mean drinking water ingestion rate for children between 1 to 10 years of age (EPA 1997).

Inhalation and dermal exposure of residents to surface water as potable water use may occur through showering and other household activities. Shower/bathing duration for adults is assumed to be 0.58 and 0.25 hour for the RME and CTE scenarios, respectively (EPA 2004). Children are assumed to spend 1 and 0.33 hour for the RME and CTE scenarios, respective (EPA 2004). For surface area exposed, the estimate of total body surface area is 18,000 cm² for adults, based on the average 50th percentiles for males and females (EPA 2004). For child residents, the total surface area is 6,600 cm², based on weighted surface area for children between 0 to 6 years of age (EPA 2004). Chemical-specific dermal permeability coefficients for COPCs are presented in Table B-4.5.

4.5.4 Construction Workers

Exposure pathways evaluated for construction workers at the site include incidental ingestion of and dermal contact with surface and subsurface soil and inhalation of particulates. Construction workers are assumed to be exposed to soils for 8 hours per day, for 5 months (100 workdays) per year for a total duration of 1 year for the RME scenario. A life expectancy of 70 years (EPA 1989) is used as the averaging time for exposure to carcinogenic contaminants. The averaging time for noncancer effects is equal to the exposure duration, or 365 days for construction workers. A body weight of 70 kg is used for construction workers (EPA 2002b).



For the soil ingestion exposure pathway, construction workers are assumed to ingest 330 mg of soil per day (EPA 2002b). For dermal contact with soil, the construction worker is assumed to wear a short-sleeved shirt, long pants, and shoes; therefore, the exposed skin surface is limited to the head, hands, and forearms. The exposed skin surface area for workers is 3,300 cm², the average of the 50th percentile for males and females older than 18 years of age (EPA 2004). A dermal adherence factor of 0.3 mg/cm² is assumed (EPA 2004), corresponding to the 95th percentile value that has been measured for construction workers. The chemical-specific dermal absorption factors for COPCs are presented in Table B-4.5.

4.5.5 Recreational Users

All recreational users are assumed to spend 175 days per year for the RME scenario and 100 days per year under the CTE scenario (EPA 2012). The exposure time is assumed to be 1 hour per day for both the RME and CTE scenarios. The duration for recreational users is 6 years for adolescents (7 to 12 years old).

A life expectancy of 70 years (EPA 1989) is used for all receptor groups as the averaging time for exposure to carcinogenic contaminants. The averaging time for noncancer effects is equal to the exposure duration, or 6 years. The averaging time for noncancer effects is 12 years for adolescents and 6 years for children under both scenarios. A body weight of 36 kg is used (EPA 1997) under both scenarios.

4.5.5.1 Surface Water

The incidental ingestion rate recommended by EPA (1989) for surface water while swimming is 50 milliliters per day (ml/day). For dermal contact with surface water in a swimming scenario, the recreational user is assumed to have full body contact with surface water. The exposed skin surface area is 11,000 cm² for adolescents, based on the weighted average surface area for children aged 7 to 12 years (EPA 2004). This skin surface area value is assumed for both the RME and CTE scenarios.

4.5.5.2 Sediment

Ingestion of sediment is limited to sediment that has been suspended in the water column while swimming and sediment which sticks to the feet, hands, or other body parts. In the absence of an ingestion rate for sediment, exposure assumptions are based on the ingestion rate for soil. The incidental ingestion rate for sediment is, therefore, assumed to be 100 mg/day. One-half of the RME rates are used for the CTE scenario. For dermal contact with sediment, the recreational user is assumed to wear a short-sleeved shirt, shorts, and no shoes; therefore, the exposed skin surface is limited to the head, hands, forearms, lower legs, and feet. The exposed skin surface area is 4,400 cm² for adolescent recreational users, the weighted average for children 7 to 12 years of age (EPA 2004). A sediment adherence factor of 0.2 mg/cm² is used for both RME and CTE scenarios, based on the geometric mean soil adherence factor for children playing in wet soil (EPA 2004). The chemical-specific dermal absorption fractions for COPCs are presented in Table B-4.5.



Section 5

Toxicity Assessment

Health criteria used in this risk assessment were obtained from a variety of toxicological sources according to a hierarchy established in the OSWER directive 9285.7-53 (EPA 2003). The toxicity value hierarchy is as follows:

- Tier 1—EPA's IRIS
- Tier 2—EPA's PPRTVs: The Office of Research and Development/National Center for Environmental Assessment (NCEA)/Superfund Health Risk Technical Support Center develops PPRTVs on a chemical-specific basis when requested by EPA's Superfund program.
- Tier 3—Other Toxicity Values: Tier 3 includes additional EPA and non-EPA sources of toxicity information, such as the California Environmental Protection Agency (Cal/EPA) and the ATSDR. Priority should be given to those sources of information that are the most current, the basis for which is transparent and publicly available, and which have been peer-reviewed.

5.1 Health Effects Criteria for Noncarcinogens

For chemicals that exhibit noncancer (e.g., systemic) effects, many authorities consider organisms to have repair and detoxification capabilities that must be exceeded by some critical concentration (threshold) before the health effect is manifested. This threshold view holds that a range of exposures from just above zero to some finite value can be tolerated by the organism without an appreciable risk of adverse effects.

Health criteria for chemicals exhibiting noncancer effects for use in risk assessment are generally EPA-derived reference doses (RfDs) and reference concentrations (RfCs). The RfD or RfC is an estimate of average daily exposure to an individual (including sensitive individuals) that is likely to be without appreciable risk of deleterious effects during a lifetime. The RfD is expressed in units of mg chemical per kg body weight per day (mg/kg-day), while the RfC is expressed in unit of mg chemical per cubic meter of air (mg/m³).

RfDs and RfCs are usually derived either from human studies involving work-place exposures or from animal studies, and are adjusted using uncertainty factors to ensure that they are unlikely to underestimate the potential for adverse noncancer effects to occur. The uncertainty factors reflect scientific judgment regarding the various types of data used to estimate the RfD/RfC and range between 1 and 10. For example, a factor of 10 may be introduced to account for possible differences in response between humans and animals in prolonged exposure studies. Other factors of 10 may be used to account for variation in susceptibility among individuals in the human population, use of data from a study with less-than-lifetime exposure, and/or use of data from a study that did not identify a no-observed-adverse-effect level (NOAEL).

RfDs and RfCs provide benchmarks against which estimated doses (i.e., those projected from human exposures to various environmental conditions) might be compared. Doses that are significantly higher than the RfD/RfC may indicate an increased potential of hazard from the exposure, while doses that are less than the RfD/RfC are not likely to be associated with adverse health effects. Note that an exceedance of a reference dose or concentration does not predict a specific disease.



5.2 Health Effects Criteria for Carcinogens

For chemicals that exhibit cancer effects, EPA and other scientific authorities recognize that one or more molecular events can evoke changes in a single cell or a small number of cells that can lead to malignancy. This non-threshold theory of carcinogenesis purports that any level of exposure to a carcinogen can result in some finite possibility of causing cancer. Generally, regulatory agencies assume the non-threshold hypothesis for carcinogens in the absence of information concerning the mechanisms of cancer action for the chemical. The slope factor (SF) [in units of (mg/kg body weight-day)⁻¹] is a number which, when multiplied by the lifetime average daily dose of a potential carcinogen (in mg/kg body weight-day), yields the upper-bound lifetime excess cancer risk associated with exposure at that dose. The SF is developed for exposure through the oral route.

When the units are risk per microgram per cubic meter ($\mu g/m^3$), it is called the inhalation unit risk (IUR). The IUR is the upper-bound excess lifetime cancer risk estimated to result from continuous exposure to a chemical at a concentration of 1 $\mu g/m^3$ in air. Upper-bound is a term used by EPA to reflect the conservative nature of the SFs and IURs—risks estimated using SFs and IURs are considered unlikely to underestimate actual risks and may overestimate risks for a given exposure. Excess lifetime cancer risks are generally expressed in scientific notation and are probabilities. An excess lifetime cancer risk of 1×10^{-6} (one in one million), for example, represents the incremental probability that an individual will develop cancer as a result of exposure to a cancer chemical over a 70-year lifetime under specified exposure conditions.

In practice, SFs and IURs estimates are derived from the results of human epidemiology studies or chronic animal bioassays. The animal studies are conducted for a range of doses, including a high dose, in order to detect possible adverse effects. Since humans are expected to be exposed at lower doses than those used in animal studies, the data are adjusted via mathematical models. The data from animal studies are typically fitted to the linearized multistage model to obtain a dose-response curve. EPA evaluates a range of possible models based on the available data before conducting the extrapolation. The most appropriate model to reflect the data is selected based on an analysis of the data set.

The 95% UCL slope of the dose-response curve, subject to various adjustments and an inter-species scaling factor, is applied to derive the health protective SF and IUR estimate for humans. Dose-response data from human epidemiological studies are fitted to dose-time-response curves. These models provide rough, but reasonable, estimates of the upper limits on lifetime risk. SF and IUR estimates based on human epidemiological data are also derived using health protective assumptions and, as such, they too are considered unlikely to underestimate risks.

Therefore, while the actual risks associated with exposures to potential carcinogens are unlikely to be higher than the risks calculated using SF and IUR estimates, they could be considerably lower. In addition, there are varying degrees of confidence in the weight of evidence for carcinogenicity of a given chemical. EPA (1986) has proposed a system for characterizing the overall weight of evidence based on the availability of animal, human, and other supportive data. The weight-of-evidence classification is an attempt to determine the likelihood that an agent is a human carcinogen and thus qualitatively affects the estimation of potential health risks. Three major factors are considered in characterizing the overall weight of evidence for human carcinogenicity:

- The availability and quality of evidence from human studies
- The availability and quality of evidence from animal studies
- Other supportive information that is assessed to determine whether the overall weight of evidence should be modified



Under EPA's risk assessment guidelines (EPA 1986, 1996, 1999), classification of the overall weight of evidence has the following five categories:

- Group A Human Carcinogen: There is at least sufficient evidence from human epidemiological studies to support a causal association between an agent and cancer.
- Group B Probable Human Carcinogen: There is at least limited evidence from epidemiological studies of
 carcinogenicity in humans (Group B1), or, in the absence of adequate data in humans, there is sufficient
 evidence of carcinogenicity in animals (Group B2).
- Group C Possible Human Carcinogen: There is inadequate evidence of carcinogenicity in humans.
- Group D Not Classified: There is inadequate data or no existing data for the chemical.
- Group E No Evidence of Carcinogenicity in Humans: There is no evidence for carcinogenicity in at least two adequate animal tests in different species, or in both epidemiological and animal studies.

The 2005 (EPA 2005a) Cancer Guidelines provide an update to the Cancer Guidelines (EPA 1986, 1996, 1999). The 2005 Cancer Guidelines emphasize the value of understanding the biological changes that a chemical can cause and how these changes might lead to the development of cancer. They also discuss methods to evaluate and use such information, including information about an agent's postulated mode of action, or the series of steps and processes that lead to cancer formation. Mode-of-action data, when available and of sufficient quality, may be useful to draw conclusions about the potency of an agent, its potential effects at low doses, whether findings in animals are relevant to humans, and which populations or life stages may be particularly susceptible. In the absence of mode-of-action information, default options are available to allow the risk assessment to proceed.

The 2005 Guidelines recommend that an agent's human cancer potential be described in a weight-of-evidence narrative rather than the previously identified letter categories (A = known, B = probable, C = possible, D = not classifiable, and E = non-human carcinogen). The narrative summarizes the full range of available evidence and describes any conditions associated with conclusions about an agent's hazard potential. For example, the narrative may explain that an agent appears to be carcinogenic by some routes of exposure but not others (e.g., by inhalation but not ingestion). Similarly, a hazard may be attributed to exposures during sensitive life stages of development but not at other times. The narrative also summarizes uncertainties and key default options that have been invoked.

The following are the five recommended standard hazard descriptors:

- Carcinogenic to human
- Likely to be carcinogenic to humans
- Suggestive evidence of carcinogenic potential
- Inadequate information to assess carcinogenic potential
- Not likely to be carcinogenic to humans

EPA is evaluating the carcinogenic weight of evidence of chemicals through the IRIS chemical process. In this process, chemicals are nominated, and all chemicals are evaluated consistent with the 2005 Guidelines and a narrative developed describing the Weight of Evidence. The IRIS chemical file is then reviewed, first through



internal EPA consensus review and then external peer-review. The requirements for in-depth analysis of mode-of-action data and the review process does not allow the equating of a chemical evaluated under the old system with the letter classification using the 2005 Classification narrative; rather, a full analysis of the data is required.

The 2005 Cancer Guidelines also include Supplemental Guidance on the evaluation of early lifetime exposures including the mutagenic mode of action for carcinogenesis. The Supplemental Guidance provides procedures for evaluating chemicals that are carcinogens and either using the data in the development of the potency factors or using age dependent adjustment factors. For chemicals with mutagenic mode of action, the following ratio is applied to the chronic daily intake (EPA 2005b):

Age 0 to less than 2 years: 10

Age 2 to less than 16 years: 3

Age greater than or equal to 16 years: 1

The Supplemental Guidance also provides for the evaluation of data on early lifetime exposures where children may be more susceptible. The application of these adjustments for specific chemicals is noted in the risk assessment and, where appropriate, in the presentation of calculated risks.

5.3 Toxicity Values

Tables 5-1 summarize the chronic RfDs and Tables 5-2 through 5-4 summarize chronic, subchronic, and acute RfCs used to estimate noncancer effects. In accordance with the inhalation guidance (EPA 2009), the RfC based on the next longer duration of exposure duration is used as a conservative estimate where the subchronic or acute RfC is not available. For instance, where the subchronic RfC is not available, the chronic RfC is used. Tables 5-5 and 5-6 summarize the cancer SFs and IURs used to estimate cancer risks. These criteria are the most current data, obtained from the November 2011 on-line version of IRIS, PPRTVs provided by EPA Region 2, the July 2009 on-line version of Cal/EPA Office of Environmental Health Hazard Assessment Toxicity Criteria Database, and the December 2009 on-line version of ATSDR. The use of surrogate toxicity values is noted in Tables 5-1 through 5-6.

Seven PAHs have been classified by EPA as Group 2, probable human carcinogens. Toxicity values are currently available only for benzo(a)pyrene. Dibenzo(a,h)anthracene is assessed using the PAH-specific relative potency factor (RPF) that expresses the potency relative to benzo(a)pyrene (EPA 1993). The RPF is applied to derive an oral SF for dibenzo(a,h)anthracene.

Carcinogenic PAHs have been identified as having mutagenic mode of action and may have a greater cancer impact if exposure occurs during childhood (EPA 2005b). Additionally, TCE is considered carcinogenic by a mutagenic mode of action for induction of kidney tumors, which means those exposed to TCE are assumed to have increased early-life (< 16 years of age) susceptibility to kidney tumors (EPA 2011c). Dose estimates for these mutagens are adjusted upward to include both early-life exposures that may result in the occurrence of cancer during childhood and early-life exposures that may contribute to cancers later in life.



Section 6

Risk Characterization

In this section of the risk assessment, the human health risks potentially associated with the complete human exposure pathways identified in Section 4 are assessed. Potential risks due to exposures to COPCs in soil, groundwater, surface water, and sediment from the site are evaluated by integrating toxicity and exposure assessments into quantitative expressions of cancer risk and noncancer health hazards.

The potential for noncancer health effects is evaluated by comparing an exposure level over a specified time period with an RfD or RfC derived for a similar exposure period. This ratio of exposure to toxicity is referred to as an HQ. The HI is the sum of the HQs from individual chemicals and exposure routes. This HI assumes that there is a level of exposure below which it is unlikely even for sensitive populations to experience adverse health effects. If the HI exceeds unity (one), there may be concern for potential noncancer effects. However, this value should not be interpreted as a probability; generally, the greater the HI is above unity, the greater the level of concern.

Cancer risks are estimated as the incremental probability of an individual to develop cancer over a lifetime as a result of exposure to a potential carcinogen. The upper-bound excess lifetime cancer risk is estimated by multiplying the lifetime exposure estimated in the exposure assessment (Section 4) by the SF or IUR identified in the toxicity assessment (Section 5). Excess lifetime cancer risks are generally expressed in scientific notation and are probabilities. An excess lifetime cancer risk of 1×10^{-6} (one in one million), for example, represents the incremental probability that an individual will develop cancer as a result of exposure to a cancer chemical over a 70-year lifetime under specified exposure conditions. Because there are multiple cancer types for TCE but the finding of a mutagenic mode of action applies to kidney only, cancer risks from TCE are calculated to account for increased early-life susceptibility for kidney cancer and contribution from other cancer types (EPA 2011c).

In general, EPA recommends a target HI value of unity and a target cancer risk range of 1×10^{-6} to 1×10^{-4} as threshold values for potential human health impacts. The results presented in the spreadsheet calculations are compared to these target values. These values aid in determining whether additional response action is necessary at the site. Cancer risk and noncancer hazard calculations for all COPCs are presented in RAGS Part D Tables B-7.1 through B-7.10 and summarized in RAGS Part D Tables B-9.1 through B-9.10 and B-10.1 through B-10.10 in Appendix B.

6.1 Results of Risk Calculations

Risks for all receptors are estimated using RME assumptions. Risks are also estimated using CTE assumptions when the RME assumptions resulted in risk estimates above EPA's thresholds. The comparison of RME and CTE risks provides information about the degree to which variability in and uncertainty associated with receptor behavior (e.g., amount of water a child ingests per day) influence the risk estimates. CTE risks represent typical exposure patterns rather than the highest possible exposure that is reasonably expected to occur. Cancer risk and noncancer health hazard estimates for each receptor by exposure area are summarized in Table 6-1.

6.1.1 Current Land-Use Scenario

6.1.1.1 Commercial/Industrial Worker

6.1.1.1.1 Former Sugar Mill

Current commercial/industrial workers may come into contact with contaminants in surface soil and groundwater. Risk calculations are presented in Tables B-7.1, B-9.1, and B-10.1 in Appendix B for the RME



scenario and Tables F-7.1, F-9.1, and F-10.1 in Appendix F for the CTE scenario. The total estimated excess cancer risks for current commercial/industrial workers (4×10^{-5}) are within EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} for the RME scenario.

Under the RME scenario, total noncancer target organ/effects HIs for current commercial/industrial workers are kidney (5) and respiratory system (4) which are above EPA's threshold of unity. When a more typical exposure is considered under the CTE scenario, the target organ/effect HIs for the kidney (3) and respiratory system (3) are still greater than unity (1). The potential health hazards to the kidney and respiratory system are results of exposure to vanadium in groundwater.

Current commercial/industrial workers may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. A vapor intrusion screening is performed on the groundwater concentration in Table E-1 in Appendix E where five chemicals have maximum concentrations greater than their respective screening criteria. All these chemicals, except bromoform, are selected as COPCs in groundwater. As discussed in Appendix E, vapor intrusion is not a concern because the existing structures are not near the COPC concentrations which exceed the screening levels and no detections of COPCs were above the screening levels at the top of the water table.

6.1.1.1.2 Puerto Rico Beverage

Workers may come into contact with contaminants in surface soil and groundwater. Risk calculations are presented in Tables B-7.5, B-9.5, and B-10.5 in Appendix B for the RME scenario and Tables F-7.3, F-9.3, and F-10.3 in Appendix F for the CTE scenario. The total estimated excess cancer risks for current/future commercial/industrial workers (4×10^{-5}) are within EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} for the RME scenario.

Total noncancer HIs for current commercial/industrial workers under both RME (5) and CTE (3) scenarios are above EPA's threshold of unity. Under the RME scenario, the target organ/effect HIs for the kidney (4) and respiratory system (4) are greater than 1. Under the CTE scenario, the target organ/effect HIs for the kidney (3) and respiratory system (3) are still greater than 1. The potential health hazards to the kidney and respiratory system are results of exposure to vanadium in groundwater.

Similar to the current commercial/industrial workers in the Former Sugar Mill area, current commercial/industrial workers in the Puerto Rico Beverage area may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. As discussed in Section 6.1.1.1.1, vapor intrusion screening is performed on the groundwater concentration in Table E-1 in Appendix E, which concludes vapor intrusion is not a concern.

6.1.1.2 Trespasser

6.1.1.2.1 Former Sugar Mill

Trespassers may come into contact with contaminants in surface soil while trespassing in the Former Sugar Mill area. Risk calculations are presented in Tables B-7.2, B-9.2, and B-10.2 in Appendix B. Under the RME scenario, the total estimated excess cancer risks (9×10^{-7}) are below EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} , and total noncancer HI (0.8) is below EPA's threshold of unity.

6.1.1.2.2 Puerto Rico Beverage

Trespassers may come into contact with contaminants in surface soil while trespassing in the Puerto Rico Beverage area. Risk calculations are presented in Tables B-7.6, B-9.6, and B-10.6 in Appendix B. Under the RME scenario, the total estimated excess cancer risks (1×10^{-6}) are at the lower end of EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} and total noncancer HI (0.7) is below EPA's threshold of unity.



6.1.1.3 Resident at Former Sugar Mill

Current residents may come into contact with contaminants in surface soil and groundwater. Risk calculations are presented in Tables B-7.3, B-9.3, and B-10.3 in Appendix B for the RME scenario and Tables F-7.2, F-9.2, and F-10.2 in Appendix F for the CTE scenario. The total estimated excess cancer risks for residents (2×10^{-4}) are above EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} for the RME scenario but within EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} under the CTE scenario (8×10^{-5}) .

Total noncancer HI for current residents under the RME scenario (36) is above EPA's threshold of unity. The target organ/effect HIs for the kidney (32), respiratory system (30), lung (2), and gastrointestinal (GI) tract (2) are greater than 1. The potential health hazards to the kidney are results of exposure to *cis-*1,2-DCE and vanadium in groundwater, while the potential adverse health effects to the respiratory system are results of exposure of vanadium in soil and groundwater. The potential adverse health effects to the lung and GI tract are mainly results of exposure to arsenic and iron, respectively, in both soil and groundwater. Under the CTE scenario, total noncancer HI for residents (16) is still above EPA's threshold of unity. The target organ/effect HIs for the kidney (14) and respiratory system (13) are greater than 1.

Similar to the commercial/industrial workers, current residents may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. As discussed in Section 6.1.1.1.1 vapor intrusion screening is performed on the groundwater concentration in Table E-1 in Appendix E, which concludes vapor intrusion is not a concern.

6.1.1.4 Recreational User at Maunabo River

Current recreational users may come into contact with contaminants in surface water and sediment at the Maunabo River while recreating at the site. Risk calculations are presented in Tables B-7.9, B-9.9, and B-10.9 in Appendix B. The total estimated excess cancer risks for current recreational users (9×10^{-7}) are below EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} for the RME scenario. Total noncancer HI for recreational users (1) is at EPA's threshold of unity.

6.1.2 Future Land-Use Scenario

6.1.2.1 Commercial/Industrial Worker

6.1.2.1.1 Former Sugar Mill

Similar to current commercial/industrial workers, the future workers may come into contact with contaminants in surface soil and groundwater. Future commercial/industrial workers may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. A vapor intrusion screening is performed on the groundwater concentration in Table E-1 in Appendix E, which concludes vapor intrusion is not a concern. Risk calculations are presented in Tables B-7.1, B-9.1, and B-10.1 in Appendix B for the RME scenario and Tables F-7.1, F-9.1, and F-10.1 in Appendix F for the CTE scenario. The total estimated excess cancer risks for current/future commercial/industrial workers (4×10^{-5}) are within EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} for the RME scenario.

Total noncancer HIs for future commercial/industrial workers for both the RME (5) and CTE (4) scenarios are above EPA's threshold of unity. The target organ/effect HIs for the kidney (5) and respiratory system (4) are greater than 1. When a more typical exposure is considered under the CTE scenario, the target organ/effect HIs for the kidney (3) and respiratory system (3) are still greater than one. The potential health hazards to the kidney and respiratory system are results of exposure of vanadium in groundwater.



6.1.2.1.2 Puerto Rico Beverage

Future commercial/industrial workers may come into contact with contaminants in surface soil and groundwater. Workers may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. A vapor intrusion screening is performed on the groundwater concentration in Table E-1 in Appendix E, which concludes vapor intrusion is not a concern. Risk calculations are presented in Tables B-7.5, B-9.5, and B-10.5 in Appendix B for the RME scenario and Tables F-7.3, F-9.3, and F-10.3 in Appendix F for CTE scenario. The total estimated excess cancer risks for commercial/industrial workers (4×10⁻⁵) are within EPA's target cancer risk range of 1×10⁻⁶ to 1×10⁻⁴ for the RME scenario.

Total noncancer HIs for commercial/industrial workers for both the RME (5) and CTE (3) scenarios are above EPA's threshold of unity. The target organ/effect HIs for the kidney (4) and respiratory system (4) are greater than 1. When a more typical exposure is considered under the CTE scenario, the target organ/effect HIs for the kidney (3) and respiratory system (3) are still greater than 1. The potential health hazards to the kidney and respiratory system are results of exposure of vanadium in groundwater.

6.1.2.2 Trespasser

6.1.2.2.1 Former Sugar Mill

Future trespassers may come into contact with contaminants in surface soil while trespassing in the Former Sugar Mill Area. Risk calculations for the RME are presented in Tables B-7.2, B-9.2, and B-10.2 in Appendix B. Under the RME scenario, the total estimated excess cancer risks for future trespassers (9×10^{-7}) are below EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} , and total noncancer HI for future trespassers (0.8) is below EPA's threshold of unity.

6.1.2.2.2 Puerto Rico Beverage

Future trespassers may come into contact with contaminants in surface soil while trespassing in the Puerto Rico Beverage area. Risk calculations are presented in Tables B-7.6, B-9.6, and B-10.6 in Appendix B. Under the RME scenario, the total estimated excess cancer risks for trespassers (1×10^{-6}) are at the lower end of EPA's target cancer risk range of 1×10^{-6} to 1×10^{-6} , and total noncancer HI for trespassers (0.7) is below EPA's threshold of unity.

6.1.2.3 Resident

6.1.2.3.1 Former Sugar Mill

Future residents may come into contact with contaminants in surface soil and groundwater and may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. A vapor intrusion screening is performed on the groundwater concentration in Table E-1 in Appendix E, which concludes vapor intrusion is not a concern. Risk calculations are presented in Tables B-7.3, B-9.3, and B-10.3 in Appendix B for the RME scenario and Tables F-7.2, F-9.2, and F-10.2 in Appendix F for the CTE scenario. The total estimated excess cancer risks for current/future residents (2×10⁻⁴) are slightly above EPA's target cancer risk range of 1×10⁻⁶ to 1×10⁻⁴ under the CTE scenario (8×10⁻⁵).

Total noncancer HI for current/future residents for under the RME scenario (36) is above EPA's threshold of unity. The target organ/effect HIs for the kidney (32), respiratory system (30), lung (2), and GI tract (2) are greater than 1. The potential health hazards to the kidney are results of exposure to *cis*-1,2-DCE and vanadium in groundwater, while the potential adverse health effects to the respiratory system are results of exposure to vanadium in soil and groundwater. The potential adverse health effects to the lung and GI tract are mainly results of exposure to arsenic and iron, respectively, in both soil and groundwater. Under the CTE scenario, total



noncancer HI for current/future residents (16) is still above EPA's threshold of unity. The target organ/effect HIs for the kidney (14) and respiratory system (13) are still greater than 1.

6.1.2.3.2 Puerto Rico Beverage

Future residents may come into contact with contaminants in surface soil and groundwater and may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. A vapor intrusion screening is performed on the groundwater concentration in Table E-1 in Appendix E, which concludes vapor intrusion is not a concern. Risk calculations are presented in Tables B-7.7, B-9.7, and B-10.7 in Appendix B for the RME scenario and Tables F-7.4, F-9.4, and F-10.4 in Appendix F for the CTE scenario. The total estimated excess cancer risks for current/future residents (2×10⁻⁴) are slightly above EPA's target cancer risk range of 1×10⁻⁶ to 1×10⁻⁴ under the CTE scenario (8×10⁻⁵).

Total noncancer HI for current/future residents under the RME scenario (34) is above EPA's threshold of unity. The target organ/effect HIs for the kidney (31), respiratory system (29), and lung (2) are greater than 1. The potential health hazards to the kidney are results of exposure to *cis*-1,2-DCE and vanadium in groundwater, while the potential adverse health effects to the respiratory system are results of exposure of vanadium in soil and groundwater. The potential adverse health effects to the lung are mainly results of exposure to arsenic in both soil and groundwater. When a more typical exposure is considered, under the CTE scenario, total noncancer HI for current/future residents (15) is still above EPA's threshold of unity. The target organ/effect HIs for the kidney (13) and respiratory system (13) are still greater than 1.

6.1.2.3.3 Maunabo River

Future residents may come into contact with contaminants in surface water from the Maunabo River as potable water uses. Risk calculations are presented in Tables B-7.10, B-9.10, and B-10.10 in Appendix B. Under the RME scenario, the total estimated excess cancer risks for future residents (2×10^{-5}) are within EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} , and total noncancer HI for future residents (0.007) is below EPA's threshold of unity.

6.1.2.4 Future Construction Worker

6.1.2.4.1 Former Sugar Mill

Future construction workers may come into contact with contaminants in surface and subsurface soil while working at the site. Risk calculations are presented in Tables B-7.4, B-9.4, and B-10.4 in Appendix B. The total estimated excess cancer risks for future construction workers (2×10^{-7}) are below EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} for the RME scenario. Total noncancer HI for future construction workers (2) is above EPA's threshold of unity. The target organ/effect HIs for the kidney (2) and respiratory system (2) are greater than 1. The potential health hazards to the kidney and respiratory system are results of exposure to vanadium in soil.

6.1.2.4.2 Puerto Rico Beverage

Future construction workers may come into contact with contaminants in surface and subsurface soil while working at the site. Risk calculations are presented in Tables B-7.8, B-9.8, and B-10.8 in Appendix B. The total estimated excess cancer risks for future construction workers (8×10^{-8}) are below EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} for the RME scenario. Total noncancer HI for future construction workers (2) is above EPA's threshold of unity. The target organ/effect HIs for the kidney (2) and respiratory system (2) are greater than 1. The potential health hazards to the kidney and respiratory system are results of exposure of vanadium in soil.

6.1.2.5 Future Recreational User at Maunabo River

Future recreational users may come into contact with contaminants in surface water and sediment at the Maunabo River while recreating at the site. Risk calculations are presented in Tables B-7.9, B-9.9, and B-10.9 in



Appendix B. The total estimated excess cancer risks for future recreational users (9×10^{-7}) are below EPA's target cancer risk range of 1×10^{-6} to 1×10^{-4} for the RME scenario. Total noncancer HI for recreational users (1) is at EPA's threshold of unity.

6.2 Risk Associated with Exposure to Lead

As shown in Table 3-1, for residential exposure scenario, mean concentrations of lead in groundwater and in surface soil at the Former Sugar Mill and Puerto Rico Beverage areas are below EPA Regional Screening Level of 400 mg/kg in soil and 15 µg/L, Puerto Rico Water Quality Standard for Class SG Groundwater.

For non-residential exposure scenario, similar to the residential exposure scenario, surface soil, subsurface soil collected at both Former Sugar Mill and Puerto Rico Beverage areas have lead concentrations below EPA Regional Screening Levels for surface soil of 400 mg/kg and 800 mg/kg for surface/subsurface soil. Lead concentration in groundwater is also below Puerto Rico Water Quality Standard for Class SG Groundwater (15 μ g/L). In addition, lead concentration in sediment at Maunabo River is also below EPA Regional Screening Level of 400 mg/kg.

6.3 Uncertainty in Risk Assessment

As in any risk assessment, the estimates of potential health threats (cancer risks and noncancer health hazards) have numerous associated uncertainties. The primary areas of uncertainty and limitations are qualitatively discussed here. The main areas of uncertainty in this HHRA include environmental data, exposure parameter assumptions, toxicological data, and risk characterization.

6.3.1 Environmental Data

Uncertainty is often associated with the estimation of chemical concentrations. Errors in the analytical data may stem from errors inherent in sampling and/or laboratory procedures. One of the most effective methods to minimize procedural or systematic error is to subject the data to a strict QC review. The QC review procedure helps to eliminate many laboratory errors. However, even with all data rigorously validated, it must be realized that error is inherent in all laboratory procedures.

Samples were collected from known and suspected areas of contamination (biased sampling) to delineate the nature and extent of contamination. Although this sampling methodology provided a reasonable estimation of the level of confidence at known or suspected contaminated areas within the site, the possibility exists that the data sets formed by these samples do not accurately represent the level of overall contamination at the site. The large number of soil, groundwater, surface water, and sediment samples taken from the site, reduces uncertainty to an acceptable level in most cases.

The groundwater data that were used in this assessment contribute a significant degree of uncertainty to the overall assessment. Among the factors that should be considered is our ability to estimate risk in the future. The presumption that contaminant concentrations will remain the same over time may overestimate the potential risk because dispersion and other natural processes are not accounted for.

6.2.2 Exposure Parameter Estimation

There are two major areas of uncertainty associated with exposure parameter estimation. The first relates to the calculation of EPCs. The second relates to parameter values used to estimate chemical intake.

6.2.2.1 Exposure Point Concentrations

A baseline risk assessment evaluates mean concentrations over an exposure unit, considering all exposures within that area as equally possible. Risks associated with exposures are then assessed by evaluating those

average or mean concentrations with exposure factors and the appropriate exposure/toxicity values. In accordance with ProUCL recommendation (EPA 2010b), when 5 or more samples are collected with at least 4 samples are detected, the EPC for a specific chemical in a particular medium is based on the 95 percent or higher UCL on the mean or the maximum detected concentration, whichever is less. Use of a 95 percent or higher UCL of the mean is simply to ensure that the average concentration is not underestimated.

When calculating EPCs from sampling data, any approach dealing with non-detected chemical concentrations is associated with some degree of uncertainty. This is because the non-detected result does not indicate whether the chemical is absent from the medium, present at a concentration just above zero, or present at a concentration just below the reporting limit. For chemicals that are infrequently detected, many of the values used to estimate the EPCs are based on reporting limits. High reporting limits for non-detects can lead to overestimation of risk if the actual concentrations are well below the reporting limit. However, reporting limits for the COPCs were generally toward the lower end of the detected concentrations, so the 95 percent or higher UCLs on the mean were minimally influenced by the reporting limits.

6.2.2.2 Exposure Parameters

Uncertainty is associated with the exposure parameter values used; however, assumptions are chosen to be conservative so as not to underestimate risk. For example, assumptions are made for the exposure time, frequency, and duration of potential chemical exposures, as well as for the quantity of material ingested, inhaled, or absorbed. In general, assumptions are made based on reasonable maximum exposures and, in most cases, values are specified by EPA Region 2, EPA guidance documents, or site-specific information.

The choices made for exposure parameters are protective and are unlikely to underestimate risks. Cancer risks and health hazards could be overestimated based on use of conservative exposure parameters in estimating risks. Certainly, the goal of estimating risks well above the average and at the upper end of possible risks was likely achieved. Such estimates typically form the basis for risk management.

Vapor concentrations in bathrooms were modeled using the shower model. The model is very conservative; thus, this approach tends to produce conservative indoor air concentrations that could result in overestimation of actual risk to current and future residents and commercial/industrial workers.

In the case of the dermal absorption factor, chemical-specific values based on EPA guidance are not available for the VOCs and most metals. Therefore, dermal risk associated with these chemicals cannot be quantitatively evaluated for the risk assessment, which introduces some uncertainty in total risk and total hazard estimates. However, for most chemicals, ingestion is expected to be the primary exposure pathway of concern.

6.2.3 Toxicological Data

A potentially large source of uncertainty is inherent in the derivation of the EPA toxicity values (i.e., RfDs, RfCs, SFs, and IURs). In many cases, data are extrapolated from animals to sensitive humans by the application of uncertainty factors to an estimated NOAEL or lowest-observed-adverse-effect level for noncancer health effects. While designed to be protective, it is likely in many cases that uncertainty factors overestimate the magnitude of differences that may exist between humans and animals, and among humans.

In some cases, however, toxicity values may be based on studies that did not detect the most sensitive adverse effects. For example, many past studies have not measured possible toxic effects on the immune system. Moreover, some chemicals may cause subtle effects not easily recognized in animal studies.

In addition, derivation of cancer SFs often involves linear extrapolation of effects at high doses to potential effects at lower doses commonly seen in environmental exposure settings. Currently, it is not known whether



linear extrapolation is appropriate. It is probable that the shape of the dose response curve for carcinogenesis varies with different chemicals and mechanisms of action. It is not possible at this time, however, to describe such differences in quantitative terms.

It is likely that the assumption of linearity is conservative and yields SFs that are unlikely to lead to underestimation of risks. Yet, for specific chemicals, current methodology could cause SFs and, hence, risks to be underestimated.

Use of SFs for arsenic, especially the oral SF based on exposure of a large Taiwanese population to dissolved arsenic in drinking water, is controversial. Some evidence exists that metabolism of arsenic in the body may greatly reduce possible cancer risks at lower levels of exposure.

Acute RfCs are not available for some metals. In accordance with RAGS Part F (EPA 2009), the RfC based on the next longer exposure duration is used as a conservative estimate that would be protective for the shorter exposure duration. This source of uncertainty may overestimate the potential inhalation hazard for trespassers and recreational users.

6.2.4 Risk Characterization

There is also uncertainty in assessing the risks associated with a mixture of chemicals. In this assessment, the effects of exposure to each contaminant present have initially been considered separately. However, these substances occur together at the site, and individuals may be exposed to mixtures of the chemicals. Predictions of how these mixtures of chemicals will interact must be based on an understanding of the mechanisms of such interactions. Individual chemicals may interact chemically in the body, yielding a new toxic component or causing different effects at different target organs. Suitable data are not currently available to rigorously characterize the effects of chemical mixtures. Consequently, as recommended by EPA (1989), chemicals present at the site are assumed to act additively, and potential health risks are evaluated by summing excess lifetime cancer risks and calculating HIs for noncancer health effects.

This approach to assessing risk associated with mixtures of chemicals assumes that there are no synergistic or antagonistic interactions among the chemicals and that all chemicals have the same toxic endpoint and mechanisms of action. To the extent that these assumptions are correct, the actual risks could be underestimated or overestimated.

As a result of the uncertainties described above, this risk assessment should not be construed as presenting absolute risks or hazards. Rather, it is a conservative analysis intended to indicate the potential for adverse impacts to occur based on the RME and the CTE scenarios.

The bedrock in the Maunabo area is composed of the San Lorenzo Batholith, granitic rock that includes a variety of igneous rock types, including granodiorite, diorite, gabbro, and tonalite. These igneous rock types are generally composed of minerals with significant percentage of iron and manganese. The batholith weathers to form the alluvial material within the Maunabo river valley. Therefore, the elevated detections of some metals in groundwater result from the natural alluvial material that has weathered from the igneous bedrock and are not indicative of metal sources of contamination.



Section 7

Summary of Risk Assessment

7.1 Approach

COPCs are identified based on criteria outlined in RAGS (EPA 1989), primarily through comparison to risk-based screening levels. COPCs identified for further quantitative evaluation in the HHRA are primarily VOCs, SVOCs, and inorganics as listed in Table 3-2.

In the HHRA, contaminants in various media at the site are evaluated for potential health threats to the following receptors:

- Current Land-Use Scenario
 - Commercial Industrial Workers
 - o Former Sugar Mill
 - Puerto Rico Beverage
 - Trespassers
 - o Former Sugar Mill
 - o Puerto Rico Beverage
 - Residents
 - o Former Sugar Mill
 - Recreational Users
 - o Maunabo River
- Future Land-Use Scenario
 - Commercial Industrial Workers
 - o Former Sugar Mill
 - o Puerto Rico Beverage
 - Trespassers
 - o Former Sugar Mill
 - o Puerto Rico Beverage
 - Residents
 - o Former Sugar Mill
 - o Puerto Rico Beverage
 - o Maunabo River
 - Recreational Users
 - o Maunabo River
 - Construction Workers
 - o Former Sugar Mill
 - o Puerto Rico Beverage

Exposure routes and human receptor groups are identified and quantitative estimates of the magnitude, frequency, and duration of exposure are made. Exposure point concentrations are estimated using the lower of the UCL and the maximum detected concentration. Daily intakes are calculated based on the RME scenario (the highest exposure reasonably expected to occur at a site). The intent is to estimate a conservative exposure case that is still within the range of possible exposures. CTE assumptions are also developed, which reflect more typical exposures.



In the toxicity assessment, current toxicological human health data (i.e., RfDs, RfCs, SFs, and IURs) are obtained from various sources and are utilized in the order specified by EPA (2003).

Risk characterization involves integrating the exposure and toxicity assessments into quantitative expressions of risks/health effects. Specifically, daily intakes are compared with concentrations known or suspected to present health risks or hazards. The estimates of cancer risk and noncancer health hazards, and the greatest chemical contributors to these estimates, are identified.

In general, EPA recommends target values or ranges (i.e., cancer risk of 10^{-6} to 10^{-4} or HI of 1) as threshold values for potential human health impacts (EPA 1989). These target values aid in determining whether additional response action is necessary at the site.

7.2 Site Risks

This section presents a summary of the cancer risks and noncancer health hazards for exposures to contaminants in various media at the site that are quantitatively evaluated for potential health threats.

7.2.1 Current Land-Use Scenario

7.2.1.1 Cancer Risk

The total incremental lifetime cancer risk estimates for the RME scenario, except risks are above EPA's target range of 1×10^{-6} to 1×10^{-6} , for current land-use receptors are listed below.

- Commercial Industrial Workers
 - Former Sugar Mill: 4×10⁻⁵
 - Puerto Rico Beverage: 4×10⁻⁵
- Trespassers
 - Former Sugar Mill: 9×10⁻⁷
 - Puerto Rico Beverage: 1×10⁻⁶
- Residents
 - Former Sugar Mill: RME: 2×10⁻⁴; CTE: 8×10⁻⁵
- Recreational Users
 - Maunabo River: 9×10⁻⁷

Based on the results above, the estimated cancer risks for all current receptors are either below or within EPA's target range of 1×10^{-6} to 1×10^{-4} for the RME scenario, except residents at the Former Sugar Mill area. The estimated cancer risk for residents (2×10^{-4}) exceeds EPA's target range of 1×10^{-6} to 1×10^{-4} . When a more typical exposure is considered under the CTE scenario, cancer risks for residents (8×10^{-5}) are within EPA's target range of 1×10^{-6} to 1×10^{-4} .

7.2.1.2 Noncancer Health Hazard

HIs greater than 1 indicate the potential for noncancer health hazards. The estimated organ/effect HIs for the RME scenario, except HIs are above EPA's threshold of unity, are listed below.

- Commercial Industrial Workers
 - Former Sugar Mill:
 - o RME: Total HI: 5, HI Kidney: 5, HI Respiratory System: 4
 - o CTE: Total HI: 4, HI Kidney: 3, HI Respiratory System: 3



- Puerto Rico Beverage:
 - RME: Total HI: 5, HI Kidney: 4, HI Respiratory System: 4
 CTE: Total HI: 3, HI Kidney: 3, HI Respiratory System: 3
- Trespassers
 - Former Sugar Mill: 0.8Puerto Rico Beverage: 0.7
- Residents
 - Former Sugar Mill:
 - o RME: Total HI: 36, HI Kidney: 32, HI Respiratory System: 30, HI Lung: 2, HI GI Tract: 2
 - o CTE: Total HI: 16, HI Kidney: 14, HI Respiratory System: 13
- Recreational Users
 - Maunabo River: 1

Based on the results above, the total HIs for all current receptors, except commercial/industrial workers and residents at the Former Sugar Mill area, are either below or at EPA's threshold of unity (1). Current commercial/industrial workers have noncancer HIs for kidney and respiratory system exceeding EPA's threshold of 1 under both RME and CTE scenarios. The potential health hazards are mostly attributed to vanadium. The current residents have noncancer HIs for the kidney, respiratory system, lung, and GI tract exceeding EPA threshold of 1 under the RME scenario. The potential health hazards to the kidney are results of exposure to *cis*-1,2-DCE and vanadium in groundwater, while the potential adverse health effects to the respiratory system are results of exposure to vanadium in soil and groundwater. The potential adverse health effects to the lung and GI tract are mainly results of exposure of arsenic and iron, respectively, in both soil and groundwater. Under the CTE scenario, total noncancer HIs for the kidney and respiratory system still exceed EPA's threshold of unity.

7.2.2 Future Land-Use Scenario

Risk characterization results for all future receptors remain the same as those for the current receptors, except for the receptors summarized below.

7.2.2.1 Cancer Risk

The total incremental lifetime cancer risk estimates are listed below.

- Residents
 - Puerto Rico Beverage: RME: 2×10⁻⁴; CTE: 8×10⁻⁵
 - Maunabo River: 2×10⁻⁵
- Future Construction Workers
 - Former Sugar Mill: 2×10⁻⁷
 - Puerto Rico Beverage: 8×10⁻⁸

Based on the results above and results presented in Section 7.2.1.1, the estimated cancer risks for all future receptors are either below or within EPA's target range of 1×10^{-6} to 1×10^{-4} for the RME scenario except residents at both the Former Sugar Mill area and the Puerto Rico Beverage area. The estimated cancer risk for these residents (2×10^{-4}) exceeds EPA's target range of 1×10^{-6} to 1×10^{-4} . When a more typical exposure is considered under the CTE scenario, cancer risks for residents are (8×10^{-5}) within EPA's target range of 1×10^{-6} to 1×10^{-4} .



7.2.2.2 Noncancer Health Hazard

The estimated HIs are listed below.

- Residents
 - Puerto Rico Beverage:

o RME: Total HI: 34, HI Kidney: 31, HI Respiratory System: 29, HI Lung: 2, HI GI Tract: 2

o CTE: Total HI: 15, HI Kidney: 13, HI Respiratory System: 13

Maunabo River: 0.007

- Construction Workers
 - Former Sugar Mill: Total HI: 2, HI Kidney:2, HI Respiratory System: 2
 - Puerto Rico Beverage: Total HI: 2, HI Kidney:2, HI Respiratory System: 2

Based on the results above and results presented in Section 7.2.1.2, the total HIs for all future receptors, except commercial/industrial workers, construction workers, and residents at the Former Sugar Mill area and the Puerto Rico Beverage area, are either below or at EPA's threshold of unity. Future commercial/industrial workers have noncancer HIs for kidney and respiratory system exceeding EPA's threshold of unity under the RME scenario. The potential health hazards are mostly attributed to vanadium. When a more typical exposure is considered under the CTE scenario, the total HI is still above EPA's threshold of unity. Future construction workers have noncancer HIs for kidney and respiratory system exceeding EPA's threshold of unity under the RME scenario. The potential health hazards are mostly attributed to vanadium.

The future residents have noncancer HIs for the kidney, respiratory system, lung, and GI tract exceeding EPA's threshold of unity under the RME scenario. The potential health hazards to the kidney are results of exposure to cis-1,2-DCE and vanadium in groundwater, while the potential adverse health effects to the respiratory system are results of exposure to vanadium in soil and groundwater. The potential adverse health effects to the lung and GI tract are mainly results of exposure to arsenic and iron, respectively, in both soil and groundwater. Under the CTE scenario, total noncancer HI for the kidney and respiratory system still exceeds EPA's threshold of unity.

7.3 Summary and Conclusions

For the current and future land-use scenarios, total estimated cancer risks are within EPA's target range (cancer risk of 1×10^{-6} to 1×10^{-4}) for all receptors under the RME scenario, except residents at both the Former Sugar Mill and Puerto Rico Beverage areas. However, under the CTE scenario, the total cancer risks are within EPA's target range of 1×10^{-6} to 1×10^{-4} .

For the current and future land-use scenarios, total noncancer health hazards are within EPA's target threshold (HI of 1) for all receptors under the RME scenario, except commercial and industrial workers, construction workers, and residents at both the Former Sugar Mill and Puerto Rico Beverage areas. The current and future commercial/industrial workers, construction workers, and residents have noncancer HIs exceeding EPA's threshold of unity under the RME scenario for the kidney, respiratory system, lung, and GI tract. Noncancer health hazards for current and future commercial/industrial workers and construction workers are almost entirely due to the hypothetical use of contaminated groundwater as a potable water supply.

For current and future residents, the potential health hazards to the kidney are results of exposure of *cis*-1,2-DCE and vanadium in groundwater, while the potential adverse health effects to the respiratory system are results of exposure to vanadium in soil and groundwater. The potential adverse health effects to the lung and GI tract are mainly results of exposure to arsenic and iron, respectively, in both soil and groundwater. Under the CTE scenario, the HIs still exceed EPA's threshold of unity for the same target organs/effects, except lung and GI tract, affected under the RME.



Current and future commercial/industrial workers and residents may potentially be exposed to volatile COPCs via inhalation of vapor emanating from groundwater into enclosed structures via vapor intrusion and into ambient air via vaporization. However, vapor intrusion is currently not a concern because the existing structures are not near the COPC concentrations which exceed the screening levels and no detections of COPCs were above the screening levels at the top of the water table.



This page intentionally left blank.

Section 8

References

Adolphson D.G., M.A. Seijo, and T.M. Robison. 1977. Water Resources of the Maunabo Valley, Puerto Rico. U.S. Geological Survey Water Resources Investigation 115-76. May.

CDM Smith. 2010. Final Quality Assurance Project Plan for the Maunabo Groundwater Contamination Site. January 28.

United States Environmental Protection Agency (EPA). 1986. "Guidelines for Carcinogen Risk Assessment," in Federal Register, Vol. 51, No. 185. September 24.

EPA. 1989. Risk Assessment Guidance for Superfund: Human Health Evaluation Manual, Part A, EPA/540/1-89/002. EPA Office of Emergency and Remedial Response, Washington, D.C., OSWER Directive 9285.701A. NTIS PB90-155581.

EPA. 1991. Human Health Evaluation Manual, Supplemental Guidance: Standard Default Exposure Factors. March 25.

EPA. 1992. Final Guidance on Data Usability In Risk Assessment (Part A). EPA Office of Emergency and Remedial Response, Washington, D.C., OSWER Directive 9285.7-09A.

EPA.1993. Provisional Guidance for Quantitative Assessment of Polycyclic Aromatic Hydrocarbons. EPA/600/R-93/089. July.

EPA. 1994. Memorandum, Revised Interim Soil Lead Guidance for CERCLA Sites and RCRA Corrective Action Facilities. Office of Solid Waste and Emergency Response, OSWER Directive 9355.4-12. August.

EPA. 1996. Provisional Guidelines for Carcinogen Risk Assessment. EPA/600/P-92/003c. April.

EPA. 1997. Exposure Factors Handbook, Vols. I, II, and III. EPA/600/P-95/002Fa, 002Fb, and 002Fc. Office of Research and Development.

EPA. 1999. Guidelines for Carcinogen Risk Assessment. NCEA-F-0644. July.

EPA. 2001. Risk Assessment Guidance for Superfund, Volume I: Human Health Evaluation Manual (Part D, Standardized Planning, Reporting, and Review of Superfund Risk Assessments). EPA Office of Emergency and Remedial Response, Washington, D.C., OSWER Directive 9285.7-47. December.

EPA. 2002a. Draft Guidance for Evaluating the Vapor Intrusion to Indoor Air Pathway from Groundwater and Soils (Subsurface Vapor Intrusion Guidance).

EPA. 2002b. Supplemental Guidance for Developing Soil Screening Levels for Superfund Sites.

EPA. 2003. Memorandum, Human Health Toxicity Values in Superfund Risk Assessments. Michael B. Cook, Director of Superfund Remediation and Technology Innovation, OSWER Directive 9285.7-53. December 5.



EPA. 2004. Risk Assessment Guidance for Superfund, Volume I: Human Health Evaluation Manual, Part E, Supplemental Guidance for Dermal Risk Assessment, Final, EPA/540/R/99/005. EPA Office of Emergency and Remedial Response, Washington, D.C., OSWER Directive. July.

EPA. 2005a. Guidelines for Carcinogen Risk Assessment, Final, EPA 630/P-03/001F. March 25.

EPA. 2005b. Supplemental Guidance for Assessing Susceptibility from Early-Life Exposure to Carcinogens. EPA 630/R-03/003F. March 25.

EPA. 2009. Risk Assessment Guidance for Superfund: Human Health Evaluation Manual, Part F, Supplemental Guidance for Inhalation Risk Assessment. EPA-540-R-070-002. OSWER 9285.7-82. January.

EPA. 2010a. ProUCL Version 4.1 User Guide (Draft). EPA/600/R-07/041. May.

EPA. 2010b. ProUCL Version 4.00.05 Technical Guide (Draft). EPA/600/R-07/041. May.

EPA. 2011a. Regional Screening Levels for Chemical Contaminants at Superfund Sites. November.

EPA. 2011b. Integrated Risk Information System (online database of toxicity measures). Website: http://www.epa.gov/iris.

EPA. 2011c. Toxicological Review of Trichloroethylene: In Support of Summary Information on the Integrated Risk Information System (IRIS). September.

Rogers C. L., C.M. Cram, M. H. Pease Jr., and M.S. Tischler. 1979. Geologic Map of the Yabucoa and Punta Tuna Quadrangles, Puerto Rico. U.S. Geological Survey Miscellaneous Geologic Investigations Map I-1086.

Schaum, J., K. Hoang, R. Kinerson, J. Moya, and R. Wang. 1994. "Estimating Dermal and Inhalation Exposure to Volatile Chemicals in Domestic Water," in Water Contamination and Health: Integration of Exposure Assessment, Toxicology, and Risk Assessment. Edited by Rhoda G. M. Wang. New York: Marcel Dekker, Inc.

Singh, A. K., A. Singh, and M. Engelhardt. 1997. The Lognormal Distribution in Environmental Applications, EPA/600/R-97/006. December.

Singh, A. K., A. Singh, and M. Engelhardt. 1999. Some Practical Aspects of Sample Size and Power Computations for Estimating the Mean of Positively Skewed Distributions in Environmental Applications, EPA/600/S-99/006. November.

United States Census Bureau Data, Year 2010 Census.



Tables

TABLE 3-1 LEAD WORKSHEET

Site Name: Maunabo Groundwater Contamination Site, Maunabo, Puerto Rico

Receptor: Resident (Adult and Child [0-6 years])

A. EXPOSURE SCENARIO: RESIDENTIAL

1. Lead Screening Questions

Medium	Mean Con	centration	Screening Level		Basis for Screening		
	Value	Unit	Value	Unit	Level Value		
Surface Soil (Former Sugar Mill)	177	mg/kg	400	mg/kg	EPA Regional Screening Level for residential soil		
Surface Soil (Puerto Rico Beverage)	33.3	mg/kg	400	mg/kg	EPA Regional Screening Level for residential soil		
Groundwater	0.294	μg/L	15	μg/L	Puerto Rico Water Quality Standards for Class SG Groundwater		

Note: If the Adult Lead Model is used, designate the baseline blood lead level and geometric standard deviation used to calculate the screening level.

2. Lead Model Questions

Question	Response for Non-Residential Lead Model
Was a lead model used? (If "no" explain rationale)	No. The mean lead concentrations are below the screening levels. Therefore, further analysis using a lead model is not warranted.
Which lead model and what version/date was used?	NA
Where are the input values located in the risk assessment report?	NA
Where are the output values located in the risk assessment report?	NA
Was the model run using default values only?	NA
If non-default values were used, where are the rationale for those values located in the risk assessment report?	NA

3. Final Result

Medium	Result	Comment
NA	NA	NA



TABLE 3-1 LEAD WORKSHEET

Site Name: Maunabo Groundwater Contamination Site, Maunabo, Puerto Rico Receptor: Site Worker (Adult), Commercial/Industrial Worker (Adult), Construction Worker (Adult), Recreational User (Adolescent [7-12 years]), Trespasser (Adolescent [7-12 years])

B. EXPOSURE SCENARIO: NON-RESIDENTIAL

1. Lead Screening Questions

Medium	Mean Concentration		Screen	ing Level	Basis for Screening
	Value	Unit	Value	Unit	Level Value
Surface Soil (Former Sugar Mill)	177	mg/kg	400	mg/kg	EPA Regional Screening Level for residential soil
Surface Soil (Puerto Rico Beverage)	33.3	mg/kg	400	mg/kg	EPA Regional Screening Level for residential soil
Surface/Subsurface Soil (Former Sugar Mill)	81.14	mg/kg	800	mg/kg	EPA Regional Screening Level for industrial soil
Surface/Subsurface Soil (Puerto Rico Beverage)	6.147	mg/kg	800	mg/kg	EPA Regional Screening Level for industrial soil
Groundwater	0.294	μg/L	15	μg/L	Puerto Rico Water Quality Standards for Class SG Groundwater
Sediment (Maunabo River)	0.994	mg/kg	400	mg/kg	EPA Regional Screening Level for residential soil

Note: If the Adult Lead Model is used, designate the baseline blood lead level and geometric standard deviation used to calculate the screening level.



TABLE 3-1 LEAD WORKSHEET

Site Name: Maunabo Groundwater Contamination Site, Maunabo, Puerto Rico Receptor: Site Worker (Adult), Commercial/Industrial Worker (Adult), Construction Worker (Adult), Recreational User (Adolescent [7-12 years]), Trespasser (Adolescent [7-12 years])

2. Lead Model Questions

Question	Response for Non-Residential Lead Model
Was a lead model used? (If "no" explain rationale)	No. The mean lead concentrations are below respective screening levels. Therefore, further analysis using a lead model is not warranted.
Which lead model and what version/date was used?	NA
Where are the input values located in the risk assessment report?	NA
Where are the output values located in the risk assessment report?	NA
Was the model run using default values only?	NA
If non-default values were used, where are the rationale for those values located in the risk assessment report?	NA

3. Final Result

Medium	Result	Comment
NA	NA	NA



TABLE 3-2 LIST OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

	Former S	Sugar Mill	Puerto Rice	o Beverage	The Site	Maunak	o River
Chemicals	Surface Soil	Surface/ Subsurface Soil	Surface Soil	Surface/ Subsurface Soil	Groundwater	Surface Water	Sediment
Volatile Organic Compounds							
Bromodichloromethane						Yes	
cis-1,2-Dichloroethene					Yes		
Dibromochloromethane					No	Yes	
Tetrachloroethene					Yes	-	
trans-1,2-Dichloroethene					Yes		
Trichloroethene					Yes		
Vinyl Chloride					Yes	-	
Semi-volatile Organic Compounds							
Benzo(a)pyrene	Yes	Yes	No	No			
Dibenzo(a,h)anthracene	Yes	Yes					
Inorganics							
Aluminum	Yes	Yes	Yes	Yes	Yes	No	No
Arsenic	Yes	Yes	Yes	Yes	Yes		Yes
Barium	No	No	No	No	Yes	No	No
Chromium	Yes	Yes	Yes	Yes	Yes	-	Yes
Cobalt	Yes	Yes	Yes	Yes	Yes	-	Yes
Copper	No	No	No	No	Yes	No	No
Iron	Yes	Yes	Yes	Yes	Yes		Yes
Manganese	Yes	Yes	Yes	Yes	Yes	No	Yes
Thallium	No	Yes	No	No	No		
Vanadium	Yes	Yes	Yes	Yes	Yes		Yes

Yes = Selected as COPC

No = Not Selected as COPC

-- = Not Detected

The site = Maunabo Groundwater Contamination Site



TABLE 4-1 SELECTION OF EXPOSURE PATHWAYS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe	Medium	Exposure Medium	Exposure Point	Receptor Population	Receptor (Age)	Exposure Route	Type of Analysis	Rationale for Selection or Exclusion of Exposure Pathway
Current	Soil	Surface Soil	Former Sugar		Adult	Dermal	Quant	Workers may come into contact with
			Mill	Industrial Worker		Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
				WOIKEI		Inhalation	Quant	working at the site.
				Trespasser	Adolescent	Dermal	Quant	Trespassers may come into contact with
					(7-12 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
						Inhalation	Quant	visiting the site.
				Resident	Adult and	Dermal	Quant	Residents may come into contact with
					Child	Ingestion	Quant	contaminants in surface soil and/or inhale
					(0-6 yrs)	Inhalation	Quant	fugitive dust and volatile chemicals while at their residence.
			Puerto Rico	Commercial/	Adult	Dermal	Quant	Workers may come into contact with
			Beverage	Industrial Worker		Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
				Worker		Inhalation	Quant	working at the site.
				Trespasser	Adolescent	Dermal	Quant	Trespassers may come into contact with
					(7-12 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
						Inhalation	Quant	visiting the site.
	Groundwater	Groundwater	Groundwater	Commercial/	Adult	Dermal	Quant	Groundwater is used as drinking water.
				Industrial Worker		Ingestion	Quant	
				VVOIREI		Inhalation	Quant	
				Resident	Adult and	Dermal	Quant	Residents use groundwater as drinking
					Child (0-6 yrs)	Ingestion	Quant	water.
					(0 0 y13)	Inhalation	Quant	
		Indoor Air	Indoor Air	Commercial/ Industrial Worker	Adult	Inhalation		Workers and residents may be exposed to contaminants in indoor air via vapor intrusion pathway from groundwater. Groundwater
				Resident	Adult and Child (0-6 yrs)	Inhalation		concentration is screened against the groundwater for indoor air screening level in the risk assessment.



TABLE 4-1 SELECTION OF EXPOSURE PATHWAYS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe	Medium	Exposure Medium	Exposure Point	Receptor Population	Receptor (Age)	Exposure Route	Type of Analysis	Rationale for Selection or Exclusion of Exposure Pathway
Current	Surface	Surface Water	Maunabo	Recreational	Adolescent	Dermal	Quant	Recreational users may come into contact
	Water		River	User	(7-12 yrs)	Ingestion	Quant	with contaminants in surface water through incidental ingestion of and dermal contact
						Inhalation	Quant	while visiting the site.
	Sediment	Sediment	Maunabo	Recreational	Adolescent	Dermal	Quant	Recreational users may come into contact
			River	User	(7-12 yrs)	Ingestion	Quant	with contaminants in sediment through incidental ingestion of and dermal contact
						Inhalation	Quant	while visiting the site.
Future	Soil	Surface Soil	Former Sugar	Commercial/	Adult	Dermal	Quant	Workers may come into contact with
			Mill	Industrial Worker		Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
				VVOINGI		Inhalation	Quant	working at the site.
				Trespasser	Adolescent	Dermal	Quant	Trespassers may come into contact with
					(7-12 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
						Inhalation		visiting the site.
				Resident	Adult and	Dermal	Quant	Residents may come into contact with
					Child (0-6 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while at
					(0 0).0)	Inhalation	Quant	their residence.
			Puerto Rico	Commercial/	Adult	Dermal	Quant	Workers may come into contact with
			Beverage	Industrial Worker		Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
						Inhalation	Quant	working at the site.
				Trespasser	Adolescent	Dermal	Quant	Trespassers may come into contact with
					(7-12 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
						Inhalation		visiting the site.
				Resident	Adult and	Dermal		Residents may come into contact with
					Child (0-6 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while at
					(= -):-)	Inhalation	Quant	their residence.



TABLE 4-1 SELECTION OF EXPOSURE PATHWAYS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe	Medium	Exposure Medium	Exposure Point	Receptor Population	Receptor (Age)	Exposure Route	Type of Analysis	Rationale for Selection or Exclusion of Exposure Pathway		
Future	Soil	Surface and	Former Sugar		Adult	Dermal	Quant	Construction workers may come into contact		
		Subsurface Soil	Mill	Worker		Ingestion	Quant	with contaminants in soil and/or inhale fugitive dust and volatile chemicals while		
						Inhalation	Quant	working at the site.		
			Puerto Rico	Construction	Adult	Dermal	Quant	Construction workers may come into contact		
			Beverage	Worker		Ingestion	Quant	with contaminants in soil and/or inhale fugitive dust and volatile chemicals while		
						Inhalation	Quant	working at the site.		
	Groundwater	Groundwater	Groundwater	Commercial/	Adult	Dermal	Quant	Groundwater is used as drinking water.		
				Industrial Worker		Ingestion	Quant			
						Inhalation	Quant			
				Resident	Adult and	Dermal	Quant	Residents use groundwater as drinking		
					Child (0-6 yrs)	Ingestion	Quant	water.		
					(0 0) 10)	Inhalation	Quant			
		Indoor Air	Indoor Air	Commercial/ Industrial Worker	Adult	Inhalation		Workers and residents may be exposed to contaminants in indoor air via vapor intrusion pathway from groundwater. Groundwater		
				Resident	Adult and Child (0-6 yrs)	Inhalation		concentration is screened against the groundwater for indoor air screening level in the risk assessment.		
	Surface	Surface Water	Maunabo	Recreational	Adolescent	Dermal	Quant	Recreational users may come into contact		
	Water		River	User	(7-12 yrs)	Ingestion	Quant	with contaminants in surface water through incidental ingestion of and dermal contact		
						Inhalation	Quant	while visiting the site.		
				Resident	Adult and	Dermal	Quant	Residents may use surface water as drinking		
					Child (0-6 yrs)	Ingestion	Quant	water.		
						Inhalation	Quant			
	Sediment	Sediment	Maunabo River	Recreational User	Adolescent	Dermal	Quant	Recreational users may come into contact with contaminants in sediment through		
			Kivei	USEI	(7-12 yrs)	Ingestion	Quant	incidental ingestion of and dermal contact		
						Inhalation	Quant	while visiting the site.		

Quant = Quantitative risk analysis performed
Qual = Qualitative risk analysis performed



TABLE 5-1 NONCANCER TOXICITY DATA - ORAL/DERMAL

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chemical of Potential Chronic				Oral Absorption	(:	D for Dermal	Primary Target Organ	Combined Uncertainty/	Source	Date ⁽³⁾
Concern	Subchronic	Value	Unit	Efficiency for Dermal ⁽¹⁾	Value	Unit	Tilliary Target Organ	Modifying Factor	Source	Date
Volatile Organic Compounds										
Bromodichloromethane	Chronic	2.0E-02	mg/kg-day	1	2.0E-02	mg/kg-day	Liver	1,000	IRIS	12/2/2011
cis-1,2-Dichloroethene	Chronic	2.0E-03	mg/kg-day	1	2.0E-03	mg/kg-day	Kidney	3,000	IRIS	12/2/2011
Dibromochloromethane	Chronic	2.0E-02	mg/kg-day	1	2.0E-02	mg/kg-day	Liver	1,000	IRIS	12/2/2011
Tetrachloroethene	Chronic	6.0E-03	mg/kg-day	1	6.0E-03	mg/kg-day	Liver	1,000	IRIS	3/20/2012
trans-1,2-Dichloroethene	Chronic	2.0E-02	mg/kg-day	1	2.0E-02	mg/kg-day	Blood	3,000	IRIS	12/2/2011
Trichloroethene	Chronic	5.0E-04	mg/kg-day	1	5.0E-04	mg/kg-day	Heart/ Immunogical/ Developmental/Kidney	10 to 1,000	IRIS	12/2/2011
Vinyl Chloride	Chronic	3.0E-03	mg/kg-day	1	3.0E-03	mg/kg-day	Liver	30	IRIS	12/2/2011
Semi-volatile Organic Cor	npounds									
Benzo(a)pyrene	Chronic	NA	NA	1	NA	NA	NA	NA	NA	NA
Dibenzo(a,h)anthracene	Chronic	NA	NA	1	NA	NA	NA	NA	NA	NA
Inorganics										
Aluminum	Chronic	1.0E+00	mg/kg-day	1	1.0E+00	mg/kg-day	Neurological	100	PPRTV	10/23/2006
Arsenic	Chronic	3.0E-04	mg/kg-day	1	3.0E-04	mg/kg-day	Skin	3	IRIS	12/2/2011
Barium	Chronic	2.0E-01	mg/kg-day	0.07	1.4E-02	mg/kg-day	Kidney	300	IRIS	12/2/2011
Chromium ⁽⁴⁾	Chronic	3.0E-03	mg/kg-day	0.025	7.5E-05	mg/kg-day	None reported	300	IRIS	12/2/2011
Cobalt	Chronic	3.0E-04	mg/kg-day	1	3.0E-04	mg/kg-day	Thyroid	3,000	PPRTV	8/25/2008
Copper	Chronic	4.0E-02	mg/kg-day	1	4.0E-02	mg/kg-day	GI Tract	NA	HEAST	7/1/1997
Iron	Chronic	7.0E-01	mg/kg-day	1	7.0E-01	mg/kg-day	GI Tract	1.5	PPRTV	9/11/2006
Manganese	Chronic	1.4E-01	mg/kg-day	0.04	5.6E-03	mg/kg-day	CNS	1	IRIS	12/2/2011
Thallium	Chronic	1.0E-05	mg/kg-day	1	1.0E-05	mg/kg-day	Skin/Hair	3,000	PPRTV-S	10/8/2010
Vanadium	Chronic	7.0E-05	mg/kg-day	0.026	1.8E-06	mg/kg-day	Kidney	3,000	PPRTV	9/30/2009

⁽¹⁾ Oral Absorption Efficiency for Dermal from Risk Assessment Guidance for Superfund Part E, Supplemental Guidance for Dermal Risk Assessment

Definition:

ATSDR = Agency for Toxic Substances and Disease Registry

CNS = central nervous system

GI = gastrointestinal

HEAST = Health Effect Assessment Summary Tables

IRIS = Integrated Risk Information System

mg/kg-day = milligram per kilogram per day

NA = not available

PPRTV = Provisional Peer Reviewed Toxicity Value

PPRTV-S = Screening Provisional Peer Reviewed Toxicity Value

RfD = reference dose



⁽²⁾ Adjusted RfD for Dermal = Oral RfD x Oral Absorption Efficiency for Dermal.

⁽³⁾ Date shown for IRIS is the date IRIS was searched. http://www.epa.gov/iris/Date shown for other sources is the publication date.

⁽⁴⁾ based on chromium (VI)

TABLE 5-2 NONCANCER TOXICITY DATA - INHALATION (CHRONIC)

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chemical of Potential	Inhalatio	on RfC	Primary Target Organ	Combined Uncertainty/		fC t Organ
Concern	Value	Unit	Timary Parget Organ	Modifying Factor	Source (1)	Date (2)
Volatile Organic Compounds						
Bromodichloromethane	NA	NA	NA	NA	NA	NA
cis-1,2-Dichloroethene	NA	NA	NA	NA	NA	NA
Dibromochloromethane	NA	NA	NA	NA	NA	NA
Tetrachloroethene	4.0E-02	mg/m ³	Liver	1,000	IRIS	3/20/2012
trans-1,2-Dichloroethene	6.0E-02	mg/m ³	Lung/Liver	3,000	PPRTV	3/1/2006
Trichloroethene	2.0E-03	mg/m ³	Heart/Immunological	10 to 100	IRIS	12/2/2011
Vinyl Chloride	1.0E-01	mg/m ³	Liver	30	IRIS	12/2/2011
Semi-volatile Organic Comp	ounds	3				
Benzo(a)pyrene	NA	NA	NA	NA	NA	NA
Dibenzo(a,h)anthracene	NA	NA	NA	NA	NA	NA
Inorganics						
Aluminum	5.0E-03	mg/m ³	Neurological	300	PPRTV	10/23/2006
Arsenic	1.5E-05	mg/m³	Developmental/Cardiovascular System/CNS/Lung/Skin	30	Cal/EPA	12/18/2008
Barium	5.0E-04	mg/m ³	Fetus	1,000	HEAST	7/1/1997
Chromium ⁽³⁾	1.0E-04	mg/m ³	Lung	300	IRIS	12/2/2011
Cobalt	6.0E-06	mg/m ³	Respiratory System/Lung	300	PPRTV	8/25/2008
Copper	NA	ŇA	NA	NA	NA	NA
Iron	NA	NA	NA	NA	NA	NA
Manganese	5.0E-05	mg/m ³	CNS	1,000	IRIS	12/2/2011
Thallium	NA	ŇA	NA	NA	NA	NA
Vanadium	1.0E-04	mg/m ³	Respiratory System	30	ATSDR	5/3/2011

⁽¹⁾ ATSDR chronic inhalation minimal risk level (MRL)

MRL is converted from units in ppmv to mg/m^3 using the following equation:

MRL $(mg/m^3) = (ppmv)(1 kg/1000 g)(P/RT)(molecular weight)$

where:

P = ambient air pressure, 1 atmosphere (atm)

R = ideal gas constant, 8.2×10^{-5} atm-m³/mol-⁰K

T = absolute temperature, 298.15 Kelvin (⁰K)

Definition:

ATSDR = Agency for Toxic Substances and Disease Registry

Cal/EPA = California Environmental Protection Agency

CNS = central nervous system

HEAST = Health Effects Assessment Summary Tables

IRIS = Integrated Risk Information System

mg/m³ = milligram per cubic meter

NA = not available

ppmv = part per million by volume

PPRTV = Provisional Peer Reviewed Toxicity Value

RfC = reference concentration



⁽²⁾ Date shown for IRIS is the date IRIS was searched. http://www.epa.gov/iris/Date shown for other sources is the publication date.

⁽³⁾ based on chromium (VI) particulates

TABLE 5-3 NONCANCER TOXICITY DATA - INHALATION (ACUTE)

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chemical of Potential	Inhalation RfC		Primary Target Organ	Combined Uncertainty/	RfC Target Organ	
Concern	Value	Unit	Timaly ranger engan	Modifying Factor	Source (1)	Date (2)
Volatile Organic Compounds						
Bromodichloromethane	NA	NA	NA	NA	NA	NA
cis-1,2-Dichloroethene	NA	NA	NA	NA	NA	NA
Dibromochloromethane	NA	NA	NA	NA	NA	NA
Tetrachloroethene	2.0E+01	mg/m ³	CNS/Eye/Respiratory System	60	Cal/EPA	12/18/2008
trans-1,2-Dichloroethene	7.9E-01	mg/m ³	Liver	1,000	ATSDR	5/3/2011
Trichloroethene	1.1E+01	mg/m ³	CNS	30	ATSDR	5/3/2011
Vinyl Chloride	1.8E+02	mg/m ³	CNS/Eye/Respiratory System	10	Cal/EPA	12/18/2008
Semi-volatile Organic Compounds		J				
Benzo(a)pyrene	NA	NA	NA	NA	NA	NA
Dibenzo(a,h)anthracene	NA	NA	NA	NA	NA	NA
Inorganics						
Aluminum	NA	NA	NA	NA	NA	NA
Arsenic	2.0E-04	mg/m ³	Developmental/Cardiovascular System/CNS	1,000	Cal/EPA	12/18/2008
Barium	NA	NA	NA	NA	NA	NA
Chromium	NA	NA	NA	NA	NA	NA
Cobalt	NA	NA	NA	NA	NA	NA
Copper	1.0E-01	mg/m ³	Respiratory System	10	Cal/EPA	12/18/2008
Iron	NA	ΝA	NA	NA	NA	NA
Manganese	1.7E-04	mg/m ³	CNS	300	Cal/EPA	12/18/2008
Thallium	NA	ŇA	NA	NA	NA	NA
Vanadium ⁽³⁾	3.0E-02	mg/m ³	Respiratory System/Eyes	10	Cal/EPA	12/18/2008

⁽¹⁾ ATSDR chronic inhalation minimal risk level (MRL)

MRL is converted from units in ppmv to $\mbox{mg/m}^3$ using the following equation:

MRL $(mg/m^3) = (ppmv)(1 kg/1000 g)(P/RT)(molecular weight)$ where:

P = ambient air pressure, 1 atmosphere (atm)

R = ideal gas constant, 8.2×10⁻⁵ atm-m³/mol-⁰K

T = absolute temperature, 298.15 Kelvin (⁰K)

Definition:

ATSDR = Agency for Toxic Substances and Disease Registry

Cal/EPA = California Environmental Protection Agency

CNS = central nervous system

mg/m³ = milligram per cubic meter

NA = not available

ppmv = part per million by volume

RfC = reference concentration



⁽²⁾ Date shown is the publication date.

⁽³⁾ based on vanadium pentoxide

TABLE 5-4 CANCER TOXICITY DATA - ORAL/DERMAL

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Chemical of Potential	Oral Slo	ope Factor	Oral Absorption Efficiency for		lope Factor for	Mutagen (3)	Weight of Evidence/ Source		Date (4)
Concern	Value	Unit	Dermal (1)	Value	Unit	J	Cancer Guideline Description		
Volatile Organic Compoun	ds								
Bromodichloromethane	6.2E-02	(mg/kg-day) ⁻¹	1	6.2E-02	(mg/kg-day) ⁻¹		B2	IRIS	12/2/2011
cis-1,2-Dichloroethene	NA	NA	1	NA	NA		inadequate information to assess the carcinogenic potential	IRIS	12/2/2011
Dibromochloromethane	8.4E-02	(mg/kg-day) ⁻¹	1	8.4E-02	(mg/kg-day) ⁻¹		С	IRIS	12/2/2011
Tetrachloroethene	2.1E-03	(mg/kg-day) ⁻¹	1	2.1E-03	(mg/kg-day) ⁻¹		Likely to be carcinogenic to humans	IRIS	3/20/2012
trans-1,2-Dichloroethene	NA	NA	1	NA	NA		inadequate information to assess the carcinogenic potential	IRIS	12/2/2011
Trichloroethene	4.6E-02	(mg/kg-day) ⁻¹	1	4.6E-02	(mg/kg-day) ⁻¹	М	carcinogenic to humans	IRIS	12/2/2011
Vinyl Chloride	7.2E-01	(mg/kg-day) ⁻¹	1	7.2E-01	(mg/kg-day) ⁻¹	M	A	IRIS	12/2/2011
Semi-volatile Organic Com	pounds								
Benzo(a)pyrene	7.3E+00	(mg/kg-day) ⁻¹	1	7.3E+00	(mg/kg-day) ⁻¹	М	B2	IRIS	12/2/2011
Dibenzo(a,h)anthracene	7.3E+00	(mg/kg-day) ⁻¹	1	7.3E+00	(mg/kg-day) ⁻¹	М	B2	EPA	7/1/1993
Inorganics									
Aluminum	NA	NA	1	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	10/23/2006
Arsenic	1.5E+00	(mg/kg-day) ⁻¹	0.025	1.5E+00	(mg/kg-day) ⁻¹		A	IRIS	12/2/2011
Barium	NA	NA	0.07	NA	NA		D	IRIS	12/2/2011
Chromium ⁽⁵⁾	5.0E-01	(mg/kg-day) ⁻¹	1	5.0E-01	(mg/kg-day) ⁻¹		likely to be carcinogenic to humans	NJDEP	4/8/2009
Cobalt	NA	NA	1	NA	NA		NA	NA	NA
Copper	NA	NA	1	NA	NA		D	IRIS	12/2/2011
Iron	NA	NA	1	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	9/11/2006
Manganese	NA	NA	0.04	NA	NA		D	IRIS	12/2/2011
Thallium	NA	NA	1	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	10/8/2010
Vanadium	NA	NA	0.026	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	9/30/2009

⁽¹⁾ Oral Absorption Efficiency for Dermal from Risk Assessment Guidance for Superfund Part E, Supplemental Guidance for Dermal Risk Assessment

EPA Weight of Evidence (EPA 1986, EPA 1996):

A - Human Carcinogen

B1 - Probable human carcinogen

indicates that limited human data are available

B2 - Probable human carcinogen - indicates sufficient evidence in animals and inadequate or no evidence in humans

C - Possible human carcinogen

D - Not classifiable as human carcinogen

Definition:

Cal/EPA = California Environmental Protection Agency

EPA = EPA Provisional Guidance for Quantitative Assessment of Polycyclic Aromatic Hydrocarbons

IRIS = Integrated Risk Information System

M = mutagen

mg/kg-day = milligram per kilogram per day

NA = not available

NJDEP = New Jersey Department of Environmental Protection

PPRTV = Provisional Peer Reviewed Toxicity Value

EPA Weight of Evidence Narrative (EPA 2005):

Carcinogenic to human

Likely to be carcinogenic to humans

Suggestive evidence of carcinogenic potential

Inadequate information to assess carcinogenic potential

Not likely to be carcinogenic to humans



 $^{^{(2)}}$ Oral cancer slope factor (CSF) for Dermal = Oral CSF

⁽³⁾ Identified as a mutagen on the Regional Screening Level (RSL) Table, June 2011 http://www.epa.gov/region09/waste/sfund/prg/index.html

⁽⁴⁾ Date shown for IRIS is the date IRIS was searched. http://www.epa.gov/iris/ Date shown for other sources is the publication date.

⁽⁵⁾ based on chromium (VI)

TABLE 5-5 CANCER TOXICITY DATA - INHALATION

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chemical of Potential Inh.		Unit Risk	(4)		Inhalation Unit Risk	
Concern	Value	Unit	Mutagen ⁽¹⁾	Weight of Evidence/ Cancer Guideline Description	Source	Date (2)
Volatile Organic Compounds						
Bromodichloromethane	3.7E-05	(µg/m³) ⁻¹		B2	Cal/EPA	7/21/2009
cis-1,2-Dichloroethene	NA	NA		inadequate information to assess the carcinogenic potential	IRIS	12/2/2011
Dibromochloromethane	2.7E-05	(µg/m³) ⁻¹		С	Cal/EPA	7/21/2009
Tetrachloroethene	2.6E-07	(µg/m ³) ⁻¹		Likely to be carcinogenic to humans	IRIS	3/20/2012
trans-1,2-Dichloroethene	NA	NA		inadequate information to assess the carcinogenic potential	IRIS	12/2/2011
Trichloroethene	4.1E-06	(µg/m³) ⁻¹	М	carcinogenic to humans	IRIS	12/2/2011
Vinyl Chloride	4.4E-06	(µg/m ³) ⁻¹	M	A	IRIS	12/2/2011
Semi-volatile Organic Compounds		5				
Benzo(a)pyrene	1.1E-03	(µg/m³) ⁻¹	М	B2	Cal/EPA	7/21/2009
Dibenzo(a,h)anthracene	1.2E-03	(µg/m ³) ⁻¹	M	B2	Cal/EPA	7/21/2009
Inorganics						
Aluminum	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	10/23/2006
Arsenic	4.3E-03	(µg/m³) ⁻¹		A	IRIS	12/2/2011
Barium	NA	NA		D	IRIS	12/2/2011
Chromium ⁽³⁾	1.2E-02	(µg/m³) ⁻¹		A	IRIS	12/2/2011
Cobalt	9.0E-03	(µg/m³) ⁻¹		likely to be carcinogenic to humans	PPRTV	8/25/2008
Copper	NA	NA		D	IRIS	12/2/2011
Iron	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	9/11/2006
Manganese	NA	NA		D	IRIS	12/2/2011
Thallium	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	10/8/2010
Vanadium ⁽⁴⁾	8.3E-03	(µg/m ³) ⁻¹		suggestive evidence of carcinogenic potential	PPRTV	4/30/2008

⁽¹⁾ Idenitified as a mutagen on the Regional Screening Level (RSL) Table, June 2011, http://www.epa.gov/region09/waste/sfund/prg/index.html

EPA Weight of Evidence (EPA 1986, EPA 1996):

- A Human Carcinogen
- B1 Probable human carcinogen indicates that limited human data are available
- B2 Probable human carcinogen indicates sufficient evidence in animals and inadequate or no evidence in humans
- C Possible human carcinogen

Definition:

Cal/EPA = California Environmental Protection Agency

IRIS = Integrated Risk Information System

M = mutagen

NA = not available

 $\mu g/m^3 = microgram per cubic meter$

PPRTV = Provisional Peer Reviewed Toxicity Value

EPA Weight of Evidence Narrative (EPA 2005):

Carcinogenic to human

Likely to be carcinogenic to humans

Suggestive evidence of carcinogenic potential

Inadequate information to assess carcinogenic potential

Not likely to be carcinogenic to humans

IARC Classification:

2A - The agent is probably carcinogenic to humans



⁽²⁾ Date shown for IRIS is the date IRIS was searched. http://www.epa.gov/iris/ Date shown for other sources is the publication date.

⁽³⁾ based on inhalation unit risk of chromium (VI)

⁽⁴⁾ based on vanadium pentoxide

TABLE 6-1 SUMMARY OF CANCER RISKS AND NONCANCER HEALTH HAZARDS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

	Cancer Risk ⁽¹⁾		Noncancer Hazard Index ⁽²⁾						
Receptor	RME	CTE	RME CTE						
			Total Organ/Effect (Risk Driver)		Total	Organ/Effect (Risk Driver)			
Current Land-Use									
Commercial/Industrial Work			-	LII Videou E (vanadium in graundurator)		LII Kidaay 2 (yanadiya in grayadyyatar)			
Former Sugar Mill	4 x 10 ⁻⁵		5	HI Kidney: 5 (vanadium in groundwater) HI Respiratory System: 4 (vanadium in groundwater)	4	HI Kidney: 3 (vanadium in groundwater) HI Respiratory System: 3 (vanadium in groundwater)			
Puerto Rico Beverage	4 x 10 ⁻⁵		5	HI Kidney: 4 (vanadium in groundwater) HI Respiratory System: 4 (vanadium in groundwater)	3	HI Kidney: 3 (vanadium in groundwater) HI Respiratory System: 3 (vanadium in groundwater)			
Trespasser				(variation)		The resonatory Systems & (variations in great anator			
Former Sugar Mill	9 x 10 ⁻⁷		0.8						
Puerto Rico Beverage	1 x 10 ⁻⁶		0.7						
Resident ⁽³⁾	1 X 10		• • • •						
Former Sugar Mill	2 x 10 ⁻⁴	8 x 10 ⁻⁵	36	HI Kidney: 32 (vanadium in soil and groundwater) HI Respiratory System: 30 (vanadium in soil and groundwater) HI Lung: 2 (arsenic and chromium in soil and groundwater GI Tract: 2 (iron in soil and groundwater)	16	HI Kidney: 14 (vanadium in soil and groundwater) HI Respiratory System: 13 (vanadium in soil and groundwater)			
Recreational User	l .			Gi Traci. 2 (iron in soil and groundwater)					
Maunabo River	9 x 10 ⁻⁷		1						
Future Land-Use	9 X 10		<u> </u>						
Commercial/Industrial Work	or								
Former Sugar Mill	_		5	HI Kidney: 5 (vanadium in groundwater)	4	HI Kidney: 3 (vanadium in groundwater)			
•	4 x 10 ⁻⁵			HI Respiratory System: 4 (vanadium in groundwater)		HI Respiratory System: 3 (vanadium in groundwater)			
Puerto Rico Beverage	4 x 10 ⁻⁵		5	HI Kidney: 4 (vanadium in groundwater) HI Respiratory System: 4 (vanadium in groundwater)	3	HI Kidney: 3 (vanadium in groundwater) HI Respiratory System: 3 (vanadium in groundwater)			
Trespasser									
Former Sugar Mill	9 x 10 ⁻⁷		0.8						
Puerto Rico Beverage	1 x 10 ⁻⁶		0.7						
Resident ⁽³⁾									
Former Sugar Mill	2 x 10 ⁻⁴	8 x 10 ⁻⁵	36	HI Kidney: 32 (vanadium in soil and groundwater) HI Respiratory System: 30 (vanadium in soil and groundwater) HI Lung: 2 (arsenic and chromium in soil and groundwater) GI Tract: 2 (iron in soil and groundwater)	16	HI Kidney: 14 (vanadium in soil and groundwater) HI Respiratory System: 13 (vanadium in soil and groundwater)			
Puerto Rico Beverage	2 x 10 ⁻⁴	8 x 10 ⁻⁵	34	HI Kidney: 31 (vanadium in soil and groundwater) HI Respiratory System: 29 (vanadium in soil and groundwater) HI Lung: 2 (arsenic and chromium in soil and groundwater)	15	HI Kidney: 13 (vanadium in soil and groundwater) HI Respiratory System: 13 (vanadium in soil and groundwater)			
Maunabo River	2 x 10 ⁻⁵		0.007						
Construction Worker									
Former Sugar Mill	2 x 10 ⁻⁷		2	HI Kidney: 2 (vanadium in soil and groundwater) HI Respiratory System: 2 (vanadium in soil and groundwater)					
Puerto Rico Beverage	8 x 10 ⁻⁸		2	HI Kidney: 2 (vanadium in soil and groundwater) HI Respiratory System: 2 (vanadium in soil and groundwater)	-				
Recreational User				,		-			
Maunabo River	9 x 10 ⁻⁷		1						

RME = Reasonable Maximum Exposure
CTE = Central Tendency Exposure





⁽¹⁾ EPA's target range = 1×10^{-6} to 1×10^{-4}


⁽²⁾ EPA's threshold = unity (1)

⁽³⁾ For residents, carcinogenic risk is based on age-adjusted scenario and non-carcinogenic hazard index is based on child exposure scenario.


Figures


















Appendix A List of Samples Used in the Risk Assessment

Appendix A Contents Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

- A-1 Soil Sample List A-2 Groundwater Sample List
- A-3 Surface Water Sample List A-4 Sediment Sample List



TABLE A-1 SOIL SAMPLE LIST

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

		Sample			
Location	Sample ID	Depth	Collection	Comment	Use In Risk
	•	(feet)	Date		Assessment
Former Sug	gar Mill				
Surface Soil					
	FSM-SB-1-1	0 - 2	1/4/2011		Y
	FSM-SB-2-1	0 - 2	1/4/2011		Υ
	FSM-SB-3-1	0 - 2	1/4/2011		Υ
	FSM-SB-4-1	0 - 2	1/4/2011		Y
	FSM-SB-5-1	0 - 2	1/4/2011		Y
FSM-SB-6	FSM-SB-6-1	0 - 2	1/4/2011		Y
	2 "		Т	otal Surface Soil Samples	6
Subsurface					
	FSM-SB-1-2	2 - 4	1/4/2011		Y
FSM-SB-1	FSM-SB-1-3	4 - 8	1/4/2011		Y
FSM-SB-1	FSM-SB-1-4	8 - 12	1/4/2011		Y
	FSM-SB-2-2	2 - 4	1/4/2011		Y
	FSM-SB-2-3	4 - 8	1/4/2011	 	Y
	FSM-SB-2-4	8 - 12	1/4/2011		Y
	FSM-SB-3-2 FSM-SB-3-3	2 - 4 4 - 8	1/4/2011 1/4/2011		Y
				Dunlingto of FOM OD O C	N ⁽¹⁾
FSM-SB-3	FSM-SB-3-3DUP	4 - 8	1/4/2011	Duplicate of FSM-SB-3-3	
FSM-SB-3 FSM-SB-4	FSM-SB-3-4	8 - 12	1/4/2011		Y
	FSM-SB-4-2 FSM-SB-4-3	2 - 4	1/4/2011		Y
	FSM-SB-4-3	4 - 8 8 - 12	1/4/2011 1/4/2011		Y
	FSM-SB-5-2	2 - 4			Y
		4 - 8	1/4/2011		Y
FSM-SB-5	FSM-SB-5-3	8 - 12	1/4/2011		Y
FSM-SB-5 FSM-SB-6	FSM-SB-5-4 FSM-SB-6-2	2 - 4	1/4/2011 1/4/2011		Y
	FSM-SB-6-3	4 - 8	1/4/2011		Y
FSM-SB-6	FSM-SB-6-4	8 - 12	1/4/2011		Y
1 3IVI-3D-0	1 31VI-3D-0-4			Subsurface Soil Samples	24
Puerto Rico	Beverage	Total	ourrace and	Oubsurface Con Campies	27
Surface Soil					
PRB-SB-1	PRB-SB-1-1	0 - 2	1/3/2011		Υ
PRB-SB-2	PRB-SB-2-1	0 - 2	1/3/2011		Y
	PRB-SB-3-1	0 - 2	1/3/2011		Ϋ́
	PRB-SB-4-1	0 - 2	1/3/2011		Ϋ́
PRB-SB-5	PRB-SB-5-1	0 - 2	1/5/2011		Ϋ́
PRB-SB-6	PRB-SB-6-1	0 - 2	1/5/2011		Ϋ́
		<u> </u>		otal Surface Soil Samples	6
Subsurface	Soil				
	PRB-SB-1-2	2 - 4	1/3/2011		Υ
PRB-SB-1	PRB-SB-1-3	4 - 8	1/3/2011		Υ
	PRB-SB-1-4	8 - 12	1/3/2011		Υ
	PRB-SB-2-2	2 - 4	1/3/2011		Υ
	PRB-SB-2-2DUP	2 - 4	1/3/2011	Duplicate of PRB-SB-2-2	N ⁽¹⁾
	PRB-SB-2-3	4 - 8	1/3/2011		Υ
PRB-SB-2	PRB-SB-2-4	8 - 12	1/3/2011		Υ
	PRB-SB-3-2	2 - 4	1/3/2011		Y
PRB-SB-3	PRB-SB-3-3	4 - 8	1/3/2011	_	Υ
PRB-SB-3	PRB-SB-3-4	8 - 12	1/3/2011	_	Υ
PRB-SB-4	PRB-SB-4-2	2 - 4	1/3/2011		Υ
	PRB-SB-4-3	4 - 8	1/3/2011		Υ
PRB-SB-4	PRB-SB-4-4	8 - 12	1/3/2011		Υ
PRB-SB-5	PRB-SB-5-2	2 - 4	1/5/2011		Υ
PRB-SB-5	PRB-SB-5-2DUP	2 - 4	1/5/2011	Duplicate of PRB-SB-5-2	N ⁽¹⁾
PRB-SB-6	PRB-SB-6-2	2 - 4	1/5/2011		Y
	-			Subsurface Soil Samples	20

Y = Yes. Used in risk assessment.



N = No. Not used in risk assessment.

Note:

⁽¹⁾ Duplicate samples are collected for quality assurance/quality control purposes, but are not included in risk assessment evaluations.

TABLE A-2 GROUNDWATER SAMPLE LIST

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Location	Sample ID	Collection Date	Comment	Use In Risk Assessment
MAUNABO-1	M1-INF	9/24/2010		Υ
MAUNABO-1	MAUNABO-1-R1	3/2/2011		Υ
MAUNABO-1	MAUNABO-1-R1-DUP	3/2/2011	Duplicate of MAUNABO-1-R1	N ⁽¹⁾
MAUNABO-1	MAUNABO-1-R2	6/8/2011		Υ
MAUNABO-1	MAUNABO-1-R2-DUP	6/8/2011	Duplicate of MAUNABO-1-R2	N ⁽¹⁾
MAUNABO-2	MAUNABO-2-R1	3/4/2011	i i	Υ
MAUNABO-2	MAUNABO-2-R2	6/8/2011		Υ
MAUNABO-3	MAUNABO-3-R1	3/7/2011		Υ
MAUNABO-3	MAUNABO-3-R2	6/9/2011		Υ
MAUNABO-4	MAUNABO-4-R1	3/3/2011		Υ
MAUNABO-4	MAUNABO-4-R2	6/9/2011		Υ
MW-AD	MW-AD-R1	3/2/2011		Υ
MW-AD	MW-AD-R2	6/7/2011		Υ
MW-AS	MW-AS-R1	3/2/2011		Υ
MW-AS	MW-AS-R2	6/7/2011		Υ
MW-B	MW-B-R1	3/2/2011		Υ
MW-B	MW-B-R2	6/9/2011		Υ
MW-C	MW-C-R1	3/8/2011		Υ
MW-C	MW-C-R2	6/10/2011		Υ
MW-D	MW-D-R1	3/8/2011	Background	N ⁽²⁾
MW-D	MW-D-R2	6/8/2011	Background	N ⁽²⁾
MW-E	MW-E-R1	3/7/2011		Υ
MW-E	MW-E-R2	6/9/2011		Υ
MW-FD	MW-FD-R1	3/7/2011		Υ
MW-FD	MW-FD-R1-DUP	3/7/2011	Duplicate of MW-FD-R1	N ⁽¹⁾
MW-FD	MW-FD-R2	6/7/2011		Υ
MW-FD	MW-FD-R2-DUP	6/7/2011	Duplicate of MW-FD-R2	N ⁽¹⁾
MW-FS	MW-FS-R1	3/7/2011	i i	Υ
MW-FS	MW-FS-R2	6/7/2011		Υ
MW-H	MW-H-R1	3/4/2011	Background	N ⁽²⁾
MW-H	MW-H-R2	6/10/2011	Background	N ⁽²⁾
MW-I	MW-I-R1	3/3/2011		Y
MW-I	MW-I-R2	6/8/2011		· Y
MW-J	MW-J-R1	3/3/2011		Y
MW-J	MW-J-R2	6/8/2011		Ϋ́
MW-K	MW-K-R1	3/3/2011		Y
MW-K	MW-K-R2	6/10/2011		Υ
MW-L	MW-L-R1	3/4/2011		Υ
MW-L	MW-L-R2	6/10/2011		Υ
MW-M	MW-M-R1	3/4/2011		Υ
MW-M	MW-M-R2	6/9/2011		Υ
MW-N	MW-N-R1	3/4/2011		Υ
MW-N	MW-N-R2	6/9/2011		Υ
MW-O	MW-O-R1	3/8/2011	Background	N ⁽²⁾
MW-O	MW-O-R2	6/8/2011	Background	N ⁽²⁾
			Total Groundwater Samples	35

Y = Yes. Used in risk assessment.

Notes:



N = No. Not used in risk assessment.

⁽¹⁾ Duplicate samples are collected for quality assurance/quality control purposes, but are not included in risk assessment evaluations.

⁽²⁾ Background samples are used to establish background levels. They are not included in risk assessment evaluations.

TABLE A-3 SURFACE WATER SAMPLE LIST

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Location	Sample ID	Collection Date	Comment	Use In Risk Assessment
SW-01	SW-01	5/10/2011	Background	N ⁽¹⁾
SW-02	SW-02	5/10/2011		Y
SW-03	SW-03	5/10/2011		Υ
SW-03	SW-03-DUP	5/10/2011	Duplicate of SW-03	N ⁽²⁾
SW-04	SW-04	5/10/2011		Υ
SW-05	SW-05	5/9/2011		Υ
SW-06	SW-06	5/9/2011		Υ
SW-07	SW-07	5/9/2011		Υ
		Total	Surface Water Samples	6

Y = Yes. Used in risk assessment.

N = No. Not used in risk assessment.

Notes:



Page 1 of 1 6/29/2012

⁽¹⁾ Background samples are used to establish background levels. They are not included in risk assessment evaluations.

⁽²⁾ Duplicate samples are collected for quality assurance/quality control purposes, but are not included in risk assessment evaluations.

TABLE A-4 SEDIMENT SAMPLE LIST

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Location	Sample ID	Sample Depth	Collection Date	Comment	Use In Risk Assessment
SD-01	SD-01	0 - 6	5/10/2011	Background	N ⁽¹⁾
SD-02	SD-02	0 - 6	5/10/2011		Υ
SD-03	SD-03	0 - 6	5/10/2011		Υ
SD-03	SD-03-DUP	0 - 6	5/10/2011	Duplicate of SD-03	N ⁽²⁾
SD-04	SD-04	0 - 6	5/10/2011		Υ
SD-05	SD-05	0 - 6	5/9/2011		Υ
SD-06	SD-06	0 - 6	5/9/2011		Υ
SD-07	SD-07	0 - 6	5/9/2011		Υ
				Total Sediment Samples	6

Y = Yes. Used in risk assessment.

Notes:



Page 1 of 1 6/29/2012

N = No. Not used in risk assessment.

⁽¹⁾ Background samples are used to establish background levels. They are not included in risk assessment evaluations.

⁽²⁾ Duplicate samples are collected for quality assurance/quality control purposes, but are not included in risk assessment evaluations.

Appendix B RAGS D Tables – RME Scenario

B-1	Selection	of Exposure Pathways
B-2	Occurren	ce, Distribution and Selection of Chemicals of Potential Concern
	B-2.1a	Current/Future Surface Soil - Former Sugar Mill
	B-2.1b	Current/Future Surface Soil - Puerto Rico Beverage
	B-2.2a	Future Surface/Subsurface Soil - Former Sugar Mill
	B-2.2b	Future Surface/Subsurface Soil - Puerto Rico Beverage
	B-2.3	Current/Future Groundwater
	B-2.4	Current/Future Surface Water
	B-2.5	Current/Future Sediment
B-3	Medium-S	Specific Exposure Point Concentration Summary
	B-3.1a	Current/Future Surface Soil - Former Sugar Mill
	B-3.1b	Current/Future Surface Soil - Puerto Rico Beverage
	B-3.2a	Current/Future Surface/Subsurface Soil - Former Sugar Mill
	B-3.2b	Current/Future Surface/Subsurface Soil - Puerto Rico Beverage
	B-3.3	Current/Future Groundwater
	B-3.4	Current/Future Surface Water
	B-3.5	Current/Future Sediment
B-4	Values ar	nd Equations Used for Intake Calculations
	B-4.1	Soil
	B-4.2	Groundwater
	B-4.3	Surface Water
	B-4.4	Sediment
	B-4.5	Chemical-Specific Information Used for Daily Intake Calculations
B-5	Noncance	er Toxicity Data
	B-5.1	Oral/Dermal
	B-5.2a	Inhalation (Chronic)
	B-5.2b	Inhalation (Acute)
B-6	Cancer To	oxicity Data
	B-6.1	Oral/Dermal
	B-6.2	Inhalation
B-7	Calculation	on of Chemical Cancer Risks and Noncancer Hazards - Reasonable Maximum Exposure
	B-7.1	Current/Future Commercial/Industrial Worker - Former Sugar Mill
	B-7.2	Current/Future Trespasser (Adolescent [7-12 years]) - Former Sugar Mill
	B-7.3	Current/Future Resident - Former Sugar Mill
	B-7.4	Future Construction Worker - Former Sugar Mill
	B-7.5	Current/Future Commercial/Industrial Worker - Puerto Rico Beverage
	B-7.6	Current/Future Trespasser (Adolescent [7-12 years]) - Puerto Rico Beverage
	B-7.7	Future Resident - Puerto Rico Beverage
	B-7.8	Future Construction Worker - Puerto Rico Beverage
	B-7.9	Current/Future Recreational User (Adolescent [7-12 years])
	B-7.10	Future Resident - Maunabo River
B-8	Calculation	on of Radiation Cancer Risks - NOT APPLICABLE TO THIS SITE
B-9		of Receptor Risks and Hazards for Chemical of Potential Concerns - Reasonable Maximum Exposure
	B-9.1	Current/Future Commercial/Industrial Worker - Former Sugar Mill
	B-9.2	Current/Future Trespasser (Adolescent [7-12 years]) - Former Sugar Mill
	B-9.3	Current/Future Resident - Former Sugar Mill
	B-9.4	Future Construction Worker - Former Sugar Mill
	B-9.5	Current/Future Commercial/Industrial Worker - Puerto Rico Beverage
	B-9.6	Current/Future Trespasser (Adolescent [7-12 years]) - Puerto Rico Beverage
	B-9.7	Future Resident - Puerto Rico Beverage
	B-9.8	Future Construction Worker - Puerto Rico Beverage
	B-9.9	Current/Future Recreational User (Adolescent [7-12 years])
	B-9.10	Future Resident - Maunabo River
R-10		essment Summary - Reasonable Maximum Exposure
٠.٠	B-10.1	Current/Future Commercial/Industrial Worker - Former Sugar Mill
	B-10.2	Current/Future Trespasser (Adolescent [7-12 years]) - Former Sugar Mill
	B-10.2 B-10.3	Current/Future Resident - Former Sugar Mill
	B-10.3 B-10.4	Future Construction Worker - Former Sugar Mill
	B-10.4 B-10.5	Current/Future Commercial/Industrial Worker - Puerto Rico Beverage
	B-10.5 B-10.6	Current/Future Trespasser (Adolescent [7-12 years]) - Puerto Rico Beverage
	B-10.6 B-10.7	Future Resident - Puerto Rico Beverage
	B-10.7 B-10.8	Future Construction Worker - Puerto Rico Beverage
	B-10.8 B-10.9	Current/Future Recreational User (Adolescent [7-12 years])
	ق.∪ ب	Carrengi atare recreational coor (nacioocent [1-12 years])



TABLE B-1 SELECTION OF EXPOSURE PATHWAYS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe	Medium	Exposure Medium	Exposure Point	Receptor Population	Receptor (Age)	Exposure Route	Type of Analysis	Rationale for Selection or Exclusion of Exposure Pathway
Current	Soil	Surface Soil	Former Sugar	Commercial/	Adult	Dermal	Quant	Workers may come into contact with
			Mill	Industrial Worker		Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
				VVOIREI		Inhalation	Quant	working at the site.
				Trespasser	Adolescent	Dermal	Quant	Trespassers may come into contact with
					(7-12 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
						Inhalation	Quant	visiting the site.
				Resident	Adult and	Dermal	Quant	Residents may come into contact with
					Child (0-6 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while at
					(U-6 yis)	Inhalation	Quant	their residence.
			Puerto Rico	Commercial/	Adult	Dermal	Quant	Workers may come into contact with
			Beverage	Industrial		Ingestion	Quant	contaminants in surface soil and/or inhale
			-	Worker Trespasser		Inhalation	Quant	fugitive dust and volatile chemicals while working at the site.
					Adolescent	Dermal	Quant	Trespassers may come into contact with
					(7-12 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while
						Inhalation	Quant	visiting the site.
	Groundwater	Groundwater	Groundwater	Commercial/	Adult	Dermal	Quant	Groundwater is used as drinking water.
				Industrial Worker		Ingestion	Quant	
				VVOIRGI		Inhalation	Quant	
				Resident	Adult and	Dermal	Quant	Residents use groundwater as drinking
					Child (0-6 yrs)	Ingestion	Quant	water.
					(0-0 yis)	Inhalation	Quant	
		Indoor Air	Indoor Air	Commercial/ Industrial Worker	Adult	Inhalation	Qual	Workers and residents may be exposed to contaminants in indoor air via vapor intrusion pathway from groundwater. Groundwater
				Resident	Adult and Child (0-6 yrs)	Inhalation	Qual	concentration is screened against the groundwater for indoor air screening level in the risk assessment.



TABLE B-1 SELECTION OF EXPOSURE PATHWAYS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe	Medium	Exposure Medium	Exposure Point	Receptor Population	Receptor (Age)	Exposure Route	Type of Analysis	Rationale for Selection or Exclusion of Exposure Pathway				
Current	Surface	Surface Water	Maunabo	Recreational	Adolescent	Dermal	Quant	Recreational users may come into contact				
	Water		River	User	(7-12 yrs)	Ingestion	Quant	with contaminants in surface water through incidental ingestion of and dermal contact				
						Inhalation	Quant	while visiting the site.				
	Sediment	Sediment	Maunabo	Recreational	Adolescent	Dermal	Quant	Recreational users may come into contact				
			River	User	(7-12 yrs)	Ingestion	Quant	with contaminants in sediment through incidental ingestion of and dermal contact				
						Inhalation	Quant	while visiting the site.				
Future	Soil	Surface Soil	Former Sugar	Commercial/	Adult	Dermal	Quant	Workers may come into contact with				
			Mill	Industrial Worker		Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while				
				VVOINGI		Inhalation Quant		working at the site.				
				Trespasser	Adolescent	Dermal	Quant	Trespassers may come into contact with				
					(7-12 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while				
						Inhalation		visiting the site.				
				Resident	Adult and	Dermal	Quant	Residents may come into contact with				
					Child (0-6 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while at				
					(0 0).0)	Inhalation	Quant	their residence.				
			Puerto Rico	Commercial/	Adult	Dermal	Quant	Workers may come into contact with				
			Beverage	Industrial Worker		Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while				
						Inhalation	Quant	working at the site.				
				Trespasser	Adolescent	Dermal	Quant	Trespassers may come into contact with				
					(7-12 yrs)	Ingestion	Quant	contaminants in surface soil and/or inhale fugitive dust and volatile chemicals while				
	Resident Adult and Child (0-6 yrs)			Inhalation		visiting the site.						
				Dermal		Residents may come into contact with						
			Ingestion	Quant	fugitive dust and volatile chemicals while							
		0-0)		(= -)/	Inhalation	Quant	their residence.					



TABLE B-1 SELECTION OF EXPOSURE PATHWAYS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe	Medium	Exposure Medium	Exposure Point	Receptor Population	Receptor (Age)	Exposure Route	Type of Analysis	Rationale for Selection or Exclusion of Exposure Pathway
Future	Soil	Surface and	Former Sugar		Adult	Dermal	Quant	Construction workers may come into contact
		Subsurface Soil	Mill	Worker		Ingestion	Quant	with contaminants in soil and/or inhale fugitive dust and volatile chemicals while
						Inhalation	Quant	working at the site.
			Puerto Rico	Construction	Adult	Dermal	Quant	Construction workers may come into contact
			Beverage	Worker		Ingestion	Quant	with contaminants in soil and/or inhale fugitive dust and volatile chemicals while
						Inhalation	Quant	working at the site.
	Groundwater	Groundwater	Groundwater	Commercial/	Adult	Dermal	Quant	Groundwater is used as drinking water.
				Industrial Worker		Ingestion	Quant	
				VVOINOI		Inhalation	Quant	
				Resident	Adult and	Dermal	Quant	Residents use groundwater as drinking
					Child (0-6 yrs)	Ingestion	Quant	water.
					(0 0 j.0)	Inhalation	Quant	
		Indoor Air	Indoor Air	Commercial/ Industrial Worker	Adult	Inhalation		Workers and residents may be exposed to contaminants in indoor air via vapor intrusion pathway from groundwater. Groundwater
				Resident	Adult and Child (0-6 yrs)	Inhalation	Qual	concentration is screened against the groundwater for indoor air screening level in the risk assessment.
	Surface	Surface Water	Maunabo	Recreational	Adolescent	Dermal	Quant	Recreational users may come into contact
	Water		River	User	(7-12 yrs)	Ingestion	Quant	with contaminants in surface water through incidental ingestion of and dermal contact
						Inhalation	Quant	while visiting the site.
				Resident	Adult and	Dermal	Quant	Residents may use surface water as drinking
					Child (0-6 yrs)	Ingestion	Quant	water.
					(5 5): -)	Inhalation	Quant	
	Sediment	t Sediment	Maunabo I River	Recreational	Adolescent	Dermal		Recreational users may come into contact
				User	(7-12 yrs)	Ingestion	Quant	with contaminants in sediment through incidental ingestion of and dermal contact
						Inhalation	Quant	while visiting the site.

Quant = Quantitative risk analysis performed
Qual = Qualitative risk analysis performed



TABLE B-2.1a OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Medium: Soil

Exposure Medium: Surface Soil - Former Sugar Mill

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of Reporting Limit	Concentration Used for Screening (1)	Background Value	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	COPC Flag (Yes/No)	Rationale for Selection or Deletion ⁽³⁾
Surface Soil	Semi-volatile	Organic Compounds													
	91-57-6	2-Methylnaphthalene	14 J	14 J	μg/kg	FSM-SB-3	1 / 6	85 - 85	14	NA	31000 n	15000	SSL ⁽⁴⁾	No	BSL
	208-96-8	Acenaphthylene	11 J	13 J	μg/kg	FSM-SB-3	2 / 6	85 - 85	13	NA	340000 n ⁽⁵⁾	NA	SSL ⁽⁴⁾	No	BSL
	120-12-7	Anthracene	5.3 J	5.3 J	μg/kg	FSM-SB-3	1 / 6	85 - 85	5.3	NA	1700000 n	7200000	SSL ⁽⁴⁾	No	BSL
	56-55-3	Benzo(a)anthracene	8.2 J	78 J	μg/kg	FSM-SB-3	4 / 6	85 - 85	78	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
	50-32-8	Benzo(a)pyrene	7.9 J	76 J	μg/kg	FSM-SB-3	4/6	85 - 85	76	NA	15 c	4800	SSL ⁽⁴⁾	Yes	ASL
	205-99-2	Benzo(b)fluoranthene	8.2 J	89 J	μg/kg	FSM-SB-3	4 / 6	85 - 85	89	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
	191-24-2	Benzo(g,h,i)perylene	6.3 J	56 J	μg/kg	FSM-SB-3	5 / 6	85 - 85	56	NA	170000 n ⁽⁶⁾	NA	SSL ⁽⁴⁾	No	BSL
	207-08-9	Benzo(k)fluoranthene	5.5 J	64 J	μg/kg	FSM-SB-3	4 / 6	85 - 85	64	NA	1500 c	NA	SSL ⁽⁴⁾	No	BSL
	85-68-7	Butylbenzylphthalate	13 J	120	μg/kg	FSM-SB-6	6 / 6	85 - 85	120	NA	260000 c	10200	SSL ⁽⁴⁾	No	BSL
	86-74-8	Carbazole	4.2 J	4.2 J	μg/kg	FSM-SB-3	1 / 6	85 - 85	4.2	NA	NA	NA	SSL ⁽⁴⁾	No	NTX
	218-01-9	Chrysene	10 J	96 J	μg/kg	FSM-SB-3	4 / 6	85 - 85	96	NA	15000 c	NA	SSL ⁽⁴⁾	No	BSL
	53-70-3	Dibenzo(a,h)anthracene	12 J	18 J	μg/kg	FSM-SB-3	2/6	85 - 85	18	NA	15 c	NA	SSL ⁽⁴⁾	Yes	ASL
	206-44-0	Fluoranthene	11 J	130	μg/kg	FSM-SB-3	4 / 6	85 - 85	130	NA	230000 n	3200000	SSL ⁽⁴⁾	No	BSL
	193-39-5	Indeno(1,2,3-cd)pyrene	7 J	62 J	μg/kg	FSM-SB-3	4 / 6	85 - 85	62	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
	91-20-3	Naphthalene	12 J	12 J	μg/kg	FSM-SB-3	1 / 6	85 - 85	12	NA	3600 c	9.4	SSL ⁽⁴⁾	No	BSL
	85-01-8	Phenanthrene	5.5 J	81 J	μg/kg	FSM-SB-3	4 / 6	85 - 85	81	NA	1700000 n ⁽⁷⁾	NA	SSL ⁽⁴⁾	No	BSL
	129-00-0	Pyrene	5.2 J	140	μg/kg	FSM-SB-3	5 / 6	85 - 85	140	NA	170000 n	2400000	SSL ⁽⁴⁾	No	BSL
	Pesticides/Po	lychlorinated Biphenyls													
	72-55-9	4,4'-DDE	5.7 J	5.7 J	μg/kg	FSM-SB-3	1 / 6	0.17 - 0.17	5.7	NA	1400 c	920	SSL ⁽⁴⁾	No	BSL
	50-29-3	4,4'-DDT	9.1	9.1	μg/kg	FSM-SB-3	1 / 6	0.17 - 0.17	9.1	NA	1700 c	1340	SSL ⁽⁴⁾	No	BSL
	309-00-2	Aldrin	0.84	0.84	μg/kg	FSM-SB-2	1 / 6	0.085 - 0.085	0.84	NA	29 c	13	SSL ⁽⁴⁾	No	BSL
	5103-71-9	Alpha-Chlordane	0.19 NJ	0.19 NJ	μg/kg	FSM-SB-6	1 / 6	0.085 - 0.085	0.19	NA	1600 c ⁽⁸⁾	260	SSL ⁽⁴⁾	No	BSL
	60-57-1	Dieldrin	0.2	3.2	μg/kg	FSM-SB-2	2 / 6	0.17 - 0.17	3.2	NA	30 c	3.4	SSL ⁽⁴⁾	No	BSL
	1031-07-8	Endosulfan Sulfate	0.44 NJ	0.44 NJ	μg/kg	FSM-SB-6	1 / 6	0.17 - 0.17	0.44	NA	37000 n ⁽⁹⁾	60000	SSL ⁽⁴⁾	No	BSL
	5103-74-2	Gamma-Chlordane	0.52	0.52	μg/kg	FSM-SB-2	1 / 6	0.085 - 0.085	0.52	NA	1600 c ⁽⁸⁾	260	SSL ⁽⁴⁾	No	BSL
	Inorganics														
	7429-90-5	Aluminum	5140	15800	mg/kg	FSM-SB-4	6 / 6	20 - 20	15800	NA	7700 n	1100000	SSL ⁽⁴⁾	Yes	ASL
	7440-36-0	Antimony	0.016 J	0.14 J	mg/kg	FSM-SB-2	4 / 6	1 - 1	0.14	NA	3.1 n	13.2	SSL ⁽⁴⁾	No	BSL
	7440-38-2	Arsenic	0.84 J	4.6	mg/kg	FSM-SB-3	6 / 6	1 - 1	4.6	NA	0.39 с	0.026	SSL ⁽⁴⁾	Yes	ASL
	7440-39-3	Barium	53.5	192	mg/kg	FSM-SB-4	6 / 6	20 - 20	192	NA	1500 n	6000	SSL ⁽⁴⁾	No	BSL
	7440-43-9	Cadmium	0.13 J	2.5	mg/kg	FSM-SB-4	6 / 6	0.5 - 0.5	2.5	NA	7 n	28	SSL ⁽⁴⁾	No	BSL
	7440-70-2	Calcium	2660	65200	mg/kg	FSM-SB-5	6 / 6	500 - 500	65200	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7440-47-3	Chromium	3	17.1	mg/kg	FSM-SB-4	6 / 6	1 - 1	17.1	NA	0.29 c ⁽¹⁰⁾	3600000	SSL ⁽⁴⁾	Yes	ASL
	7440-48-4	Cobalt	3 J	10.5	mg/kg	FSM-SB-4	6 / 6	5 - 5	10.5	NA	2.3 n	9.8	SSL ⁽⁴⁾	Yes	ASL
	7440-50-8	Copper	22.2	105	mg/kg	FSM-SB-4	6 / 6	2.5 - 2.5	105	NA	310 n	1020	SSL ⁽⁴⁾	No	BSL
	57-12-5	Cyanide	0.13 J	0.37 J	mg/kg	FSM-SB-1	6 / 6	0.5 - 0.5	0.37	NA	160 n	148	SSL ⁽⁴⁾	No	BSL
	7439-89-6	Iron	16600	41800	mg/kg	FSM-SB-4	6 / 6	10 - 10	41800	NA	5500 n	12800	SSL ⁽⁴⁾	Yes	ASL
	7439-92-1	Lead	2.2	710	mg/kg	FSM-SB-4	6 / 6	1 - 1	710	NA	400 n ⁽¹¹⁾	280	SSL ⁽⁴⁾	No	(15)
	7439-95-4	Magnesium	1610	3610	mg/kg	FSM-SB-4	6 / 6	500 - 500	3610	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7439-96-5	Manganese	221	547	mg/kg	FSM-SB-4	6 / 6	1.5 - 1.5	547	NA	180 n	1140	SSL ⁽⁴⁾	Yes	ASL
	7439-97-6	Mercury	0.026 J	0.67 J	mg/kg	FSM-SB-4	6 / 6	0.1 - 0.1	0.67	NA	2.3 n ⁽¹²⁾	NA	SSL ⁽⁴⁾	No	BSL
	7440-02-0	Nickel	1.8 J	19.2	mg/kg	FSM-SB-4	6 / 6	4 - 4	19.2	NA	150 n ⁽¹³⁾	960	SSL ⁽⁴⁾	No	BSL



OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Medium: Soil

Exposure Medium: Surface Soil - Former Sugar Mill

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of Reporting Limit	Concentration Used for Screening (1)	Background Value	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	Flag	Rationale for Selection or Deletion (3)
Surface Soil	7440-09-7	Potassium	560 J	1650	mg/kg	FSM-SB-4	6 / 6	500 - 500	1650	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7440-22-4	Silver	0.92 J	3.5	mg/kg	FSM-SB-4	3 / 6	1 - 1	3.5	NA	39 n	32	SSL ⁽⁴⁾	No	BSL
	7440-23-5	Sodium	106 J	272 J	mg/kg	FSM-SB-3	6 / 6	500 - 500	272	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7440-28-0	Thallium	0.0094 J	0.05 J	mg/kg	FSM-SB-3	6 / 6	0.5 - 0.5	0.05	NA	0.078 n	0.52	SSL ⁽⁴⁾	No	BSL
	7440-62-2	Vanadium	24.3	69.3	mg/kg	FSM-SB-3	6 / 6	5 - 5	69.3	NA	39 n ⁽¹⁴⁾	3600	SSL ⁽⁴⁾	Yes	ASL
	7440-66-6	Zinc	33.5	742	mg/kg	FSM-SB-4	6 / 6	6 - 6	742	NA	2300 n	13600	SSL ⁽⁴⁾	No	BSL

⁽¹⁾ Maximum detected concentration used for screening

(3) Rationale Codes:

Selection Reason: ASL = above screening level
Deletion Reason: BSL = below screening level
NUT = essential nutrient

NTX = no toxicity information available

- (5) screening value for acenaphthene
- (6) screening value for pyrene
- (7) screening value for anthracene
- (8) screening value for chlordane
- (9) screening value for endosulfan
- (10) screening value for chromium VI
- (11) OSWER screening value for residential soil
- (12) screening value for mercuric chloride (and other mercury salts)
- (13) screening value for nickel soluble salts
- (14) screening value for vanadium and compounds
- (15) Mean concentration of lead is less than the screening criteria.

NA = not available

ND = not detected

n = screening toxicity value based on noncancer effects

c = screening toxicity value based on cancer effects

SSL = soil screening level

COPC = chemical of potential concern

ARAR/TBC = Applicable or Relevant and Appropriate Requirement/To Be Considered

J = qualifier for estimated value

NJ = qualifier for tentatively identified and estimated value

μg/kg = micrograms per kilogram

mg/kg = milligrams per kilogram

4,4'-DDE = p,p'-dichlorodiphenyldichloroethylene

4,4'-DDT = p,p'-dichlorodiphenyltrichloroethane



Page 2 of 2 6/28/2012

⁽²⁾ Screened against Regional Screening Levels, November 2011, for residential soil, adjusted to a cancer risk of 1x1(6 and hazard quotient of 0.1. http://www.epa.gov/region09/waste/sfund/prg/index.html

⁽⁴⁾ Potential ARAR/TBC value from Regional Screening Levels, June 2011, for protection of groundwater soil screening levels, based on a dilution factor of 20.

TABLE B-2.1b OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Medium: Soil

Exposure Medium: Surface Soil - Puerto Rico Beverage

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of Reporting Limit	Concentration Used for Screening (1)	Background Value	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	COPC Flag (Yes/No)	Rationale for Selection or Deletion ⁽³⁾
Surface Soil	Volatile Organ	ic Compounds													
	78-93-3	2-Butanone	5.2 J	5.2 J	μg/kg	PRB-SB-3	1 / 6	10 - 10	5.2	NA	2800000 n	30000	SSL ⁽⁴⁾	No	BSL
		Acetone	31	31	μg/kg	PRB-SB-3	1 / 6	10 - 10	31	NA	6100000 n	90000	SSL ⁽⁴⁾	No	BSL
		Organic Compounds													
		3-Nitroaniline	54 J	54 J	μg/kg	PRB-SB-1	1 / 6	170 - 170	54	NA	NA	NA	SSL ⁽⁴⁾	No	NTX
		Benzo(a)anthracene	3.9 J	3.9 J	μg/kg	PRB-SB-6	1 / 6	85 - 85	3.9	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
		Benzo(a)pyrene	4.4 J	4.4 J	μg/kg	PRB-SB-6	1 / 6	85 - 85	4.4	NA	15 c	4800	SSL ⁽⁴⁾	No	BSL
		Benzo(b)fluoranthene	4.4 J	4.4 J	μg/kg	PRB-SB-6	1 / 6	85 - 85	4.4	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
		Benzo(g,h,i)perylene	4 J	4 J	μg/kg	PRB-SB-6	1 / 6	85 - 85	4	NA	170000 n ⁽⁵⁾	NA	SSL ⁽⁴⁾	No	BSL
		Bis(2-Ethylhexyl)Phthalate	1100	1100	μg/kg	PRB-SB-5	1/6	85 - 85	1100	NA	35000 c	22000	SSL ⁽⁴⁾	No	BSL
		Butylbenzylphthalate	39 J	200	μg/kg	PRB-SB-5	3 / 6	85 - 85	200	NA	260000 c	10200	SSL ⁽⁴⁾	No	BSL
		Chrysene	4.6 J	6.4 J	μg/kg	PRB-SB-5	2/6	85 - 85	6.4	NA	15000 c	NA	SSL ⁽⁴⁾	No	BSL
	206-44-0 193-39-5	Fluoranthene	4.8 J 4 J	4.8 J	μg/kg	PRB-SB-6 PRB-SB-6	1 / 6 1 / 6	85 - 85 85 - 85	4.8 4	NA NA	230000 n 150 c	3200000 NA	SSL ⁽⁴⁾	No No	BSL BSL
		Indeno(1,2,3-cd)pyrene	5.5 J	4 J 5.5 J	μg/kg	PRB-SB-6	1/6	85 - 85 85 - 85	5.5	NA NA	170000 n	2400000	SSL ⁽⁴⁾	No No	BSL
		Pyrene	5.5 J	5.5 J	μg/kg	PRD-5D-0	1/6	65 - 65	5.5	INA	170000 11	2400000	SSL ⁽⁴⁾	NO	BOL
		lychlorinated Biphenyls	0.04	40.11		DDD 0D 5	0 / 0	0.47 0.47	4.0		4.400	000	(4)		DO1
		4,4'-DDE	0.31	1.3 NJ	μg/kg	PRB-SB-5	2 / 6	0.17 - 0.17	1.3	NA	1400 c	920	SSL ⁽⁴⁾	No	BSL
		4,4'-DDT	0.98 J	0.98 J	μg/kg	PRB-SB-5	1/6	0.17 - 0.17	0.98	NA	1700 c	1340	SSL ⁽⁴⁾	No	BSL
	5103-71-9	Alpha-Chlordane	4 NJ	4 NJ	μg/kg	PRB-SB-5	1/6	0.085 - 0.085	4	NA	1600 c ⁽⁶⁾	260	SSL ⁽⁴⁾	No	BSL BSL
		Gamma-Chlordane	1.4	5.6	μg/kg	PRB-SB-5	2/6	0.085 - 0.085	5.6	NA	1600 c ⁽⁶⁾	260	SSL ⁽⁴⁾	No	_
	76-44-8 1024-57-3	Heptachlor	1.2 NJ 0.16 J	1.2 NJ 1.5 J	μg/kg	PRB-SB-5 PRB-SB-5	1 / 6 2 / 6	0.085 - 0.085 0.085 - 0.085	1.2 1.5	NA NA	110 c 53 c	24 3	SSL ⁽⁴⁾	No No	BSL BSL
	Inorganics	Heptachlor Epoxide	0.16 J	1.5 J	μg/kg	PKD-5D-5	2/6	0.065 - 0.065	1.5	INA	53 0	3	SSL ⁽⁴⁾	NO	BOL
	_	Aluminum	7060	15700	mg/kg	PRB-SB-3	6 / 6	20 - 20	15700	NA	7700 n	1100000	SSL ⁽⁴⁾	Yes	ASL
	7440-36-0	Antimony	0.013 J	0.013 J	mg/kg	PRB-SB-6	1/6	1 - 1	0.013	NA NA	3.1 n	13.2	SSL ⁽⁴⁾	No	BSL
		Arsenic	0.43 J	2.9	mg/kg	PRB-SB-5	2/6	1 - 1	2.9	NA	0.39 c	0.026	SSL ⁽⁴⁾	Yes	ASL
		Barium	57.5	106	mg/kg	PRB-SB-3	6/6	20 - 20	106	NA NA	1500 n	6000	SSL ⁽⁴⁾	No	BSL
	7440-43-9	Cadmium	0.13 J	1.1	mg/kg	PRB-SB-5	2/6	0.5 - 0.5	1.1	NA	7 n	28	SSL ⁽⁴⁾	No	BSL
	7440-70-2	Calcium	868	2860	mg/kg	PRB-SB-3	6/6	500 - 500	2860	NA	NA.	NA	SSL ⁽⁴⁾	No	NUT
		Chromium	1.6	27.5	mg/kg	PRB-SB-5	6/6	1 - 1	27.5	NA	0.29 c ⁽⁷⁾	3600000	SSL ⁽⁴⁾	Yes	ASL
		Cobalt	2.1 J	7.5	mg/kg	PRB-SB-3	6 / 6	5 - 5	7.5	NA	2.3 n	9.8	SSL ⁽⁴⁾	Yes	ASL
		Copper	33.5	107	mg/kg	PRB-SB-5	6 / 6	2.5 - 2.5	107	NA	310 n	1020	SSL ⁽⁴⁾	No	BSL
	57-12-5	Cyanide	0.088 J	0.27 J	mg/kg	PRB-SB-5	4 / 6	0.5 - 0.5	0.27	NA	160 n	148	SSL ⁽⁴⁾	No	BSL
	7439-89-6	Iron	16400	35900	mg/kg	PRB-SB-1	6 / 6	10 - 10	35900	NA	5500 n	12800	SSL ⁽⁴⁾	Yes	ASL
	7439-92-1	Lead	23.3	83.3	mg/kg	PRB-SB-5	2 / 6	1 - 1	83.3	NA	400 n ⁽⁸⁾	280	SSL ⁽⁴⁾	No	BSL
	7439-95-4	Magnesium	2060	3170	mg/kg	PRB-SB-1	6 / 6	500 - 500	3170	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7439-96-5	Manganese	135	365	mg/kg	PRB-SB-6	6 / 6	1.5 - 1.5	365	NA	180 n	1140	SSL ⁽⁴⁾	Yes	ASL
	7439-97-6	Mercury	0.034 J	0.9	mg/kg	PRB-SB-5	6 / 6	0.1 - 0.1	0.9	NA	2.3 n ⁽⁹⁾	NA	SSL ⁽⁴⁾	No	BSL
	7440-02-0	Nickel	0.32 J	6	mg/kg	PRB-SB-5	6 / 6	4 - 4	6	NA	150 n ⁽¹⁰⁾	960	SSL ⁽⁴⁾	No	BSL
	7440-09-7	Potassium	597 J	1290	mg/kg	PRB-SB-2	6 / 6	500 - 500	1290	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7440-23-5	Sodium	105 J	361 J	mg/kg	PRB-SB-1	6 / 6	500 - 500	361	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7440-28-0	Thallium	0.021 J	0.039 J	mg/kg	PRB-SB-1	6 / 6	0.5 - 0.5	0.039	NA	0.078 n	0.52	SSL ⁽⁴⁾	No	BSL



OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Medium: Soil

Exposure Medium: Surface Soil - Puerto Rico Beverage

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)		Location of Maximum Concentration	Detection Frequency	Range of Reporting Limit	Concentration Used for Screening (1)	Background Value	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	Flag	Rationale for Selection or Deletion (3)
Surface Soil	7440-62-2	Vanadium	31.9	71.8	mg/kg	PRB-SB-3	6 / 6	5 - 5	71.8	NA	39 n ⁽¹¹⁾	3600	SSL ⁽⁴⁾	Yes	ASL
	7440-66-6	Zinc	27.4	438	mg/kg	PRB-SB-5	6 / 6	6 - 6	438	NA	2300 n	13600	SSL ⁽⁴⁾	No	BSL

⁽¹⁾ Maximum detected concentration used for screening

Selection Reason: ASL = above screening level
Deletion Reason: BSL = below screening level
NUT = essential nutrient

NTX = no toxicity information available

NA = not available

ND = not detected

n = screening toxicity value based on noncancer effects

c = screening toxicity value based on cancer effects

SSL = soil screening level

COPC = chemical of potential concern

ARAR/TBC = Applicable or Relevant and Appropriate Requirement/To Be Considered

J = qualifier for estimated value

NJ = qualifier for tentatively identified and estimated value

 μ g/kg = micrograms per kilogram

mg/kg = milligrams per kilogram

4,4'-DDE = p,p'-dichlorodiphenyldichloroethylene

4,4'-DDT = p,p'-dichlorodiphenyltrichloroethane



Page 2 of 2 6/28/2012

R2-0002157

⁽²⁾ Screened against Regional Screening Levels, November 2011, for residential soil, adjusted to a cancer risk of 1x1(6 and hazard quotient of 0.1. http://www.epa.gov/region09/waste/sfund/prg/index.html

⁽³⁾ Rationale Codes:

⁽⁴⁾ Potential ARAR/TBC value from Regional Screening Levels, June 2011, for protection of groundwater soil screening levels, based on a dilution factor of 20.

⁽⁵⁾ screening value for pyrene

⁽⁶⁾ screening value for chlordane

⁽⁷⁾ screening value for chromium VI

⁽⁸⁾ OSWER screening value for residential soil

⁽⁹⁾ screening value for mercuric chloride (and other mercury salts)

⁽¹⁰⁾ screening value for nickel soluble salts

⁽¹¹⁾ screening value for vanadium and compounds

OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Future
Medium: Soil

Exposure Medium: Surface/Subsurface Soil - Former Sugar Mill

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of Reporting Limit	Concentration Used for Screening (1)	Background Value	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	COPC Flag (Yes/No)	Rationale for Selection or Deletion (3)
Surface/	Volatile Organ	ic Compounds													
Subsurface	78-93-3	2-Butanone	8.5 J	35	μg/kg	FSM-SB-4	2 / 24	10 - 10	35	NA	2800000 n	30000	SSL ⁽⁴⁾	No	BSL
Soil	67-64-1	Acetone	5.2 J	180	μg/kg	FSM-SB-4	6 / 24	10 - 10	180	NA	6100000 n	90000	SSL ⁽⁴⁾	No	BSL
	Semi-volatile (Organic Compounds													
	91-57-6	2-Methylnaphthalene	5.7 J	14 J	μg/kg	FSM-SB-3	2 / 24	85 - 85	14	NA	31000 n	15000	SSL ⁽⁴⁾	No	BSL
	208-96-8	Acenaphthylene	7.9 J	13 J	μg/kg	FSM-SB-3	3 / 24	85 - 85	13	NA	340000 n ⁽⁵⁾	NA	SSL ⁽⁴⁾	No	BSL
	120-12-7	Anthracene	5.3 J	5.3 J	μg/kg	FSM-SB-3	1 / 24	85 - 85	5.3	NA	1700000 n	7200000	SSL ⁽⁴⁾	No	IFD
	100-52-7	Benzaldehyde	10 J	10 J	μg/kg	FSM-SB-2	1 / 24	85 - 85	10	NA	780000 n	16200	SSL ⁽⁴⁾	No	IFD
	56-55-3	Benzo(a)anthracene	7.7 J	78 J	μg/kg	FSM-SB-3	7 / 24	85 - 85	78	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
	50-32-8	Benzo(a)pyrene	7.9 J	76 J	μg/kg	FSM-SB-3	7 / 24	85 - 85	76	NA	15 c	4800	SSL ⁽⁴⁾	Yes	ASL
	205-99-2	Benzo(b)fluoranthene	7.2 J	89 J	μg/kg	FSM-SB-3	7 / 24	85 - 85	89	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
	191-24-2	Benzo(g,h,i)perylene	5.6 J	56 J	μg/kg	FSM-SB-3	9 / 24	85 - 85	56	NA	170000 n ⁽⁶⁾	NA	SSL ⁽⁴⁾	No	BSL
	207-08-9	Benzo(k)fluoranthene	5.5 J	64 J	μg/kg	FSM-SB-3	7 / 24	85 - 85	64	NA	1500 c	NA	SSL ⁽⁴⁾	No	BSL
	85-68-7	Butylbenzylphthalate	4.5 J	120	μg/kg	FSM-SB-6	12 / 24	85 - 85	120	NA	260000 c	10200	SSL ⁽⁴⁾	No	BSL
	86-74-8	Carbazole	4.2 J	4.2 J	μg/kg	FSM-SB-3	1 / 24	85 - 85	4.2	NA	NA	NA	SSL ⁽⁴⁾	No	IFD
	218-01-9	Chrysene	9.4 J	96 J	μg/kg	FSM-SB-3	7 / 24	85 - 85	96	NA	15000 c	NA	SSL ⁽⁴⁾	No	BSL
	53-70-3	Dibenzo(a,h)anthracene	8.6 J	18 J	μg/kg	FSM-SB-3	3 / 24	85 - 85	18	NA	15 c	NA	SSL ⁽⁴⁾	Yes	ASL
	206-44-0	Fluoranthene	4.5 J	130	μg/kg	FSM-SB-3	8 / 24	85 - 85	130	NA	230000 n	3200000	SSL ⁽⁴⁾	No	BSL
	193-39-5	Indeno(1,2,3-cd)pyrene	7 J	62 J	μg/kg	FSM-SB-3	7 / 24	85 - 85	62	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
	91-20-3	Naphthalene	12 J	12 J	μg/kg	FSM-SB-3	1 / 24	85 - 85	12	NA	3600 c	9.4	SSL ⁽⁴⁾	No	IFD
	87-86-5	Pentachlorophenol	2.1 J	2.7 J	μg/kg	FSM-SB-4	2 / 24	1.7 - 3.4	2.7	NA	890 c	34	SSL ⁽⁴⁾	No	BSL
	85-01-8	Phenanthrene	5.1 J	81 J	μg/kg	FSM-SB-3	7 / 24	85 - 85	81	NA	1700000 n ⁽⁷⁾	NA	SSL ⁽⁴⁾	No	BSL
	129-00-0	Pyrene	4.9 J	140	μg/kg	FSM-SB-3	10 / 24	85 - 85	140	NA	170000 n	2400000	SSL ⁽⁴⁾	No	BSL
		ychlorinated Biphenyls													
	72-55-9	4,4'-DDE	0.26	5.7 J	μg/kg	FSM-SB-3	2 / 24	0.17 - 0.17	5.7	NA	1400 c	920	SSL ⁽⁴⁾	No	BSL
	50-29-3	4,4'-DDT	0.13 J	9.1	μg/kg	FSM-SB-3	3 / 24	0.17 - 0.17	9.1	NA	1700 c	1340	SSL ⁽⁴⁾	No	BSL
	309-00-2	Aldrin	0.16 J	0.84	μg/kg	FSM-SB-2	2 / 24	0.085 - 0.085	0.84	NA	29 c	13	SSL ⁽⁴⁾	No	BSL
	5103-71-9	Alpha-Chlordane	0.19 NJ	0.19 NJ	μg/kg	FSM-SB-6	1 / 24	0.085 - 0.085	0.19	NA	1600 c ⁽⁸⁾	260	SSL ⁽⁴⁾	No	IFD
	60-57-1	Dieldrin	0.2	3.2	μg/kg	FSM-SB-2	3 / 24	0.17 - 0.17	3.2	NA	30 c	3.4	SSL ⁽⁴⁾	No	BSL
	1031-07-8	Endosulfan Sulfate	0.44 NJ	0.44 NJ	μg/kg	FSM-SB-6	1 / 24	0.17 - 0.17	0.44	NA	37000 n ⁽⁹⁾	60000	SSL ⁽⁴⁾	No	IFD
	5103-74-2	Gamma-Chlordane	0.38	0.52	μg/kg	FSM-SB-2	2 / 24	0.085 - 0.085	0.52	NA	1600 c ⁽⁸⁾	260	SSL ⁽⁴⁾	No	BSL
	Inorganics				_										
	7429-90-5	Aluminum	5140	28500	mg/kg	FSM-SB-2	24 / 24	20 - 20	28500	NA	7700 n	1100000	SSL ⁽⁴⁾	Yes	ASL
	7440-36-0	Antimony	0.016 J	0.14 J	mg/kg	FSM-SB-2	5 / 24	1 - 1	0.14	NA	3.1 n	13.2	SSL ⁽⁴⁾	No	BSL
	7440-38-2	Arsenic	0.29 J	4.6	mg/kg	FSM-SB-3	14 / 24	1 - 1	4.6	NA	0.39 c	0.026	SSL ⁽⁴⁾	Yes	ASL
	7440-39-3	Barium	53.5	213	mg/kg	FSM-SB-2	24 / 24	20 - 20	213	NA	1500 n	6000	SSL ⁽⁴⁾	No	BSL
	7440-43-9	Cadmium	0.13 J	2.5	mg/kg	FSM-SB-4	14 / 24	0.5 - 0.5	2.5	NA	7 n	28	SSL ⁽⁴⁾	No	BSL
	7440-70-2	Calcium	2660	141000	mg/kg	FSM-SB-2	24 / 24	500 - 500	141000	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7440-47-3	Chromium	3	20.8	mg/kg	FSM-SB-2	24 / 24	1 - 1	20.8	NA	0.29 c ⁽¹⁰⁾	3600000	SSL ⁽⁴⁾	Yes	ASL
	7440-48-4	Cobalt	3 J	14.7	mg/kg	FSM-SB-2	24 / 24	5 - 5	14.7	NA	2.3 n	9.8	SSL ⁽⁴⁾	Yes	ASL
	7440-50-8	Copper	22.2	105	mg/kg	FSM-SB-4	24 / 24	2.5 - 2.5	105	NA	310 n	1020	SSL ⁽⁴⁾	No	BSL
	57-12-5	Cyanide	0.071 J	1.3 J	mg/kg	FSM-SB-2	19 / 24	0.5 - 0.5	1.3	NA	160 n	148	SSL ⁽⁴⁾	No	BSL
II	7439-89-6	Iron	6780	41800	mg/kg	FSM-SB-4	24 / 24	10 - 10	41800	NA	5500 n	12800	SSL ⁽⁴⁾	Yes	ASL



OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future

Medium: Soil

Exposure Medium: Surface/Subsurface Soil - Former Sugar Mill

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of		Background	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	Flag	Rationale for Selection or Deletion (3)
Surface/	7439-92-1	Lead	0.86 J	710	mg/kg	FSM-SB-4	14 / 24	1 - 1	710	NA	800 n ⁽¹¹⁾	280	SSL ⁽⁴⁾	No	BSL
Subsurface	7439-95-4	Magnesium	1610	4810	mg/kg	FSM-SB-2	24 / 24	500 - 500	4810	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
Soil	7439-96-5	Manganese	191	650	mg/kg	FSM-SB-3	24 / 24	1.5 - 1.5	650	NA	180 n	1140	SSL ⁽⁴⁾	Yes	ASL
	7439-97-6	Mercury	0.022 J	0.67 J	mg/kg	FSM-SB-4	24 / 24	0.1 - 0.1	0.67	NA	2.3 n ⁽¹²⁾	NA	SSL ⁽⁴⁾	No	BSL
	7440-02-0	Nickel	1.4 J	19.2	mg/kg	FSM-SB-4	24 / 24	4 - 4	19.2	NA	150 n ⁽¹³⁾	960	SSL ⁽⁴⁾	No	BSL
	7440-09-7	Potassium	204 J	1920	mg/kg	FSM-SB-1	24 / 24	500 - 500	1920	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7782-49-2	Selenium	1.7 J	1.7 J	mg/kg	FSM-SB-2	1 / 24	3.5 - 3.5	1.7	NA	39 n	19	SSL ⁽⁴⁾	No	IFD
	7440-22-4	Silver	0.92 J	3.5	mg/kg	FSM-SB-4	14 / 24	1 - 1	3.5	NA	39 n	32	SSL ⁽⁴⁾	No	BSL
	7440-23-5	Sodium	106 J	527 J	mg/kg	FSM-SB-2	24 / 24	500 - 500	527	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7440-28-0	Thallium	0.0066 J	0.8 J	mg/kg	FSM-SB-3	23 / 24	0.5 - 0.5	0.8	NA	0.078 n	0.52	SSL ⁽⁴⁾	Yes	ASL
	7440-62-2	Vanadium	24.3	192	mg/kg	FSM-SB-2	24 / 24	5 - 5	192	NA	39 n ⁽¹⁴⁾	3600	SSL ⁽⁴⁾	Yes	ASL
	7440-66-6	Zinc	31.3	742	mg/kg	FSM-SB-4	24 / 24	6 - 6	742	NA	2300 n	13600	SSL ⁽⁴⁾	No	BSL

⁽¹⁾ Maximum detected concentration used for screening

(3) Rationale Codes:

Selection Reason: ASL = above screening level Deletion Reason: BSL = below screening level

IFD = detection frequency less than 5%

NUT = essential nutrient

NTX = no toxicity information available

NA = not available

ND = not detected

n = screening toxicity value based on noncancer effects

c = screening toxicity value based on cancer effects

SSL = soil screening level

COPC = chemical of potential concern

ARAR/TBC = Applicable or Relevant and Appropriate Requirement/To Be Considered

J = qualifier for estimated value

NJ = qualifier for tentatively identified and estimated value

μg/kg = micrograms per kilogram

mg/kg = milligrams per kilogram

4,4'-DDE = p,p'-dichlorodiphenyldichloroethylene

4,4'-DDT = p,p'-dichlorodiphenyltrichloroethane



Page 2 of 2 6/28/2012

⁽²⁾ Screened against Regional Screening Levels, November 2011, for residential soil, adjusted to a cancer risk of 1x1(6 and hazard quotient of 0.1. http://www.epa.gov/region09/waste/sfund/prg/index.html

⁽⁴⁾ Potential ARAR/TBC value from Regional Screening Levels, June 2011, for protection of groundwater soil screening levels, based on a dilution factor of 20.

⁽⁵⁾ screening value for acenaphthene

⁽⁶⁾ screening value for pyrene

⁽⁷⁾ screening value for anthracene

⁽⁸⁾ screening value for chlordane

 $^{^{\}left(9\right) }$ screening value for endosulfan

⁽¹⁰⁾ screening value for chromium VI

⁽¹¹⁾ OSWER screening value for industrial soil

⁽¹²⁾ screening value for mercuric chloride (and other mercury salts)

⁽¹³⁾ screening value for nickel soluble salts

⁽¹⁴⁾ screening value for vanadium and compounds

OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Future

Medium: Soil

Exposure Medium: Surface/Subsurface Soil - Puerto Rico Beverage

									ir —		ı			1	T T
Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of Reporting Limit	Concentration Used for Screening (1)	Background Value	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	COPC Flag (Yes/No)	Rationale for Selection or Deletion (3)
Surface/	Volatile Organ	ic Compounds							,						
Subsurface	78-93-3	2-Butanone	4.2 J	21	μg/kg	PRB-SB-5	5 / 20	10 - 10	21	NA	2800000 n	30000	SSL ⁽⁴⁾	No	BSL
Soil	67-64-1	Acetone	14	100	μg/kg	PRB-SB-3	11 / 20	10 - 10	100	NA	6100000 n	90000	SSL ⁽⁴⁾	No	BSL
	Semi-volatile	Organic Compounds													
	99-09-2	3-Nitroaniline	54 J	54 J	μg/kg	PRB-SB-1	1 / 20	170 - 170	54	NA	NA	NA	SSL ⁽⁴⁾	No	NTX
	56-55-3	Benzo(a)anthracene	3.9 J	3.9 J	μg/kg	PRB-SB-6	1 / 20	85 - 85	3.9	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
	50-32-8	Benzo(a)pyrene	4.4 J	4.4 J	μg/kg	PRB-SB-6	1 / 20	85 - 85	4.4	NA	15 c	4800	SSL ⁽⁴⁾	No	BSL
	205-99-2	Benzo(b)fluoranthene	4.4 J	4.4 J	μg/kg	PRB-SB-6	1 / 20	85 - 85	4.4	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
	191-24-2	Benzo(g,h,i)perylene	4 J	4 J	μg/kg	PRB-SB-6	1 / 20	85 - 85	4	NA	170000 n ⁽⁵⁾	NA	SSL ⁽⁴⁾	No	BSL
	117-81-7	Bis(2-Ethylhexyl)Phthalate	1100	1100	μg/kg	PRB-SB-5	1 / 20	85 - 85	1100	NA	35000 c	22000	SSL ⁽⁴⁾	No	BSL
	85-68-7	Butylbenzylphthalate	39 J	200	μg/kg	PRB-SB-5	3 / 20	85 - 85	200	NA	260000 c	10200	SSL ⁽⁴⁾	No	BSL
	218-01-9	Chrysene	4.6 J	6.4 J	μg/kg	PRB-SB-5	2 / 20	85 - 85	6.4	NA	15000 c	NA	SSL ⁽⁴⁾	No	BSL
	206-44-0	Fluoranthene	4.8 J	4.8 J	μg/kg	PRB-SB-6	1 / 20	85 - 85	4.8	NA	230000 n	3200000	SSL ⁽⁴⁾	No	BSL
	193-39-5	Indeno(1,2,3-cd)pyrene	4 J	4 J	μg/kg	PRB-SB-6	1 / 20	85 - 85	4	NA	150 c	NA	SSL ⁽⁴⁾	No	BSL
	129-00-0	Pyrene	5.5 J	5.5 J	μg/kg	PRB-SB-6	1 / 20	85 - 85	5.5	NA	170000 n	2400000	SSL ⁽⁴⁾	No	BSL
	Pesticides/Po	lychlorinated Biphenyls													
	72-55-9	4,4'-DDE	0.31	1.3 NJ	μg/kg	PRB-SB-5	2 / 20	0.17 - 0.17	1.3	NA	1400 c	920	SSL ⁽⁴⁾	No	BSL
	50-29-3	4,4'-DDT	0.98 J	0.98 J	μg/kg	PRB-SB-5	1 / 20	0.17 - 0.17	0.98	NA	1700 c	1340	SSL ⁽⁴⁾	No	BSL
	5103-71-9	Alpha-Chlordane	0.24 J	4 NJ	μg/kg	PRB-SB-5	2 / 20	0.085 - 0.085	4	NA	1600 c ⁽⁶⁾	260	SSL ⁽⁴⁾	No	BSL
	5103-74-2	Gamma-Chlordane	0.14 J	5.6	μg/kg	PRB-SB-5	3 / 20	0.085 - 0.085	5.6	NA	1600 c ⁽⁶⁾	260	SSL ⁽⁴⁾	No	BSL
	76-44-8	Heptachlor	1.2 NJ	1.2 NJ	μg/kg	PRB-SB-5	1 / 20	0.085 - 0.085	1.2	NA	110 c	24	SSL ⁽⁴⁾	No	BSL
	1024-57-3	Heptachlor Epoxide	0.12 J	1.5 J	μg/kg	PRB-SB-5	3 / 20	0.085 - 0.085	1.5	NA	53 c	3	SSL ⁽⁴⁾	No	BSL
	Inorganics														
	7429-90-5	Aluminum	7060	37800	mg/kg	PRB-SB-1	20 / 20	20 - 20	37800	NA	7700 n	1100000	SSL ⁽⁴⁾	Yes	ASL
	7440-36-0	Antimony	0.0034 J	0.013 J	mg/kg	PRB-SB-6	9 / 20	1 - 1	0.013	NA	3.1 n	13.2	SSL ⁽⁴⁾	No	BSL
	7440-38-2	Arsenic	0.27 J	2.9	mg/kg	PRB-SB-5	4 / 20	1 - 1	2.9	NA	0.39 с	0.026	SSL ⁽⁴⁾	Yes	ASL
	7440-39-3	Barium	57.5	268	mg/kg	PRB-SB-1	20 / 20	20 - 20	268	NA	1500 n	6000	SSL ⁽⁴⁾	No	BSL
	7440-43-9	Cadmium	0.1 J	1.1	mg/kg	PRB-SB-5	4 / 20	0.5 - 0.5	1.1	NA	7 n	28	SSL ⁽⁴⁾	No	BSL
	7440-70-2	Calcium	868	5150	mg/kg	PRB-SB-1	20 / 20	500 - 500	5150	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7440-47-3	Chromium	0.9 J	27.5	mg/kg	PRB-SB-5	20 / 20	1 - 1	27.5	NA	0.29 c ⁽⁷⁾	3600000	SSL ⁽⁴⁾	Yes	ASL
	7440-48-4	Cobalt	2.1 J	16.1	mg/kg	PRB-SB-1	20 / 20	5 - 5	16.1	NA	2.3 n	9.8	SSL ⁽⁴⁾	Yes	ASL
	7440-50-8	Copper	27.3	140	mg/kg	PRB-SB-1	20 / 20	2.5 - 2.5	140	NA	310 n	1020	SSL ⁽⁴⁾	No	BSL
	57-12-5	Cyanide	0.039 J	0.88	mg/kg	PRB-SB-6	13 / 20	0.5 - 0.5	0.88	NA	160 n	148	SSL ⁽⁴⁾	No	BSL
	7439-89-6	Iron	13200	44700	mg/kg	PRB-SB-1	20 / 20	10 - 10	44700	NA	5500 n	12800	SSL ⁽⁴⁾	Yes	ASL
	7439-92-1	Lead	0.68 J	83.3	mg/kg	PRB-SB-5	7 / 20	1 - 1	83.3	NA	800 n ⁽⁸⁾	280	SSL ⁽⁴⁾	No	BSL
	7439-95-4	Magnesium	1120	5490	mg/kg	PRB-SB-1	20 / 20	500 - 500	5490	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7439-96-5	Manganese	89.6	474	mg/kg	PRB-SB-1	20 / 20	1.5 - 1.5	474	NA	180 n	1140	SSL ⁽⁴⁾	Yes	ASL
	7439-97-6	Mercury	0.023 J	0.9	mg/kg	PRB-SB-5	20 / 20	0.1 - 0.1	0.9	NA	2.3 n ⁽⁹⁾	NA	SSL ⁽⁴⁾	No	BSL
	7440-02-0	Nickel	0.32 J	6	mg/kg	PRB-SB-5	20 / 20	4 - 4	6	NA	150 n ⁽¹⁰⁾	960	SSL ⁽⁴⁾	No	BSL
	7440-09-7	Potassium	333 J	1420	mg/kg	PRB-SB-5	20 / 20	500 - 500	1420	NA	NA	NA	SSL ⁽⁴⁾	No	NUT
	7440-23-5	Sodium	95.3 J	399 J	mg/kg	PRB-SB-2	20 / 20	500 - 500	399	NA	NA	NA	SSL ⁽⁴⁾	No	NUT



OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Future

Medium: Soil

Exposure Medium: Surface/Subsurface Soil - Puerto Rico Beverage

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of Reporting Limit	Concentration Used for Screening (1)	Background Value	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	Flag	Rationale for Selection or Deletion (3)
Surface/	7440-28-0	Thallium	0.014 J	0.069 J	mg/kg	PRB-SB-1	20 / 20	0.5 - 0.5	0.069	NA	0.078 n	0.52	SSL ⁽⁴⁾	No	BSL
Subsurface	7440-62-2	Vanadium	31.9	162	mg/kg	PRB-SB-1	20 / 20	5 - 5	162	NA	39 n ⁽¹¹⁾	3600	SSL ⁽⁴⁾	Yes	ASL
Soil	7440-66-6	Zinc	11.3	438	mg/kg	PRB-SB-5	20 / 20	6 - 6	438	NA	2300 n	13600	SSL ⁽⁴⁾	No	BSL

(1) Maximum detected concentration used for screening

(2) Screened against Regional Screening Levels, November 2011, for residential soil, adjusted to a cancer risk of 1x1(⁶ and hazard quotient of 0.1. http://www.epa.gov/region09/waste/sfund/prg/index.html

(3) Rationale Codes:

Selection Reason: ASL = above screening level Deletion Reason: BSL = below screening level

NUT = essential nutrient

NTX = no toxicity information available

(4) Potential ARAR/TBC value from Regional Screening Levels, June 2011, for protection of groundwater soil screening levels, based on a dilution factor of 20.

(5) screening value for pyrene

(6) screening value for chlordane

(7) screening value for chromium VI

(8) OSWER screening value for industrial soil

(9) screening value for mercuric chloride (and other mercury salts)

(10) screening value for nickel soluble salts

(11) screening value for vanadium and compounds

NA = not available

ND = not detected

n = screening toxicity value based on noncancer effects

c = screening toxicity value based on cancer effects

SSL = soil screening level

COPC = chemical of potential concern

ARAR/TBC = Applicable or Relevant and Appropriate Requirement/To Be Considered

J = qualifier for estimated value

NJ = qualifier for tentatively identified and estimated value

μg/kg = micrograms per kilogram mg/kg = milligrams per kilogram

4,4'-DDE = p,p'-dichlorodiphenyldichloroethylene

4,4'-DDT = p,p'-dichlorodiphenyltrichloroethane



Page 2 of 2 6/28/2012

R2-0002161

OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Medium: Groundwater

Exposure Medium: Groundwater

Exposure CAS No. Chemical Concentration Concentration Light Maximum Location of Detection Range of Range of Light Maximum Screening Potential Concentration Background Screening Potential Potential Concentration Background Screening Potential Potential CONCENTRATION CO						,										
F6-154		CAS No.	Chemical	Concentration	Concentration	Unit	Maximum		-	n Used for		Toxicity Value	ARAR/TBC	ARAR/TBC	Flag	Rationale for Selection or Deletion
F3-34-3	Groundwater	Volatile Organ	nic Compounds													
F3-34-3		_		3.2	23	ua/L	MW-AD	5 / 35	0.5 - 0.5	23	NA	5300 n	NL	PRWQS	No	BSL
F5-554 1-1-Ole-Incordemen				0.27 J			MW-I		0.5 - 0.5		NA		NL	PRWQS	No	
107-06-2 12-Deckhorechane			· ·													_
F8-87-5 12-Dichloropropane 0.52 0.52 191 1			,									_			11	_
67-64-1			*													
75-25-2 Bromoform													_			
75-15-0 Carbon Disulfide										11					11	_
Total Tota										-			-			
156-59-2																
124-48-1 Dibromochloromelhane 0.54 0.54 ujul. MW-K 8 / 35 0.5 - 0.5 0.54 NA 0.15 c 4 PRWQS No IFD 127-184 Tetrachloroethene 0.1 J 3. 1.7 ujul. MW-K 8 / 35 0.5 - 0.5 2. NA 12 c NA															11	
1634-04-4 Molthy Tart-Bury Ether 0.27 J 2 ujul. MW-F 4 / 35 0.5 - 0.5 2 NA 12 c NL PRWQS No BSL 127-18-4 Tetrachloroethene 0.1 J 8.5 J ujul. MW-F 0 / 35 0.5 - 0.5 1.7 NA 4.7 c 46 PRWQS No BSL 127-18-4 Tetrachloroethene 0.1 J 8.5 J ujul. MW-F 0 / 35 0.5 - 0.5 1.7 NA 0.072 c 5 PRWQS Yes ASL 10061-02-6 Trichforethene 0.29 J 0.2 J ujul. MW-F 0 / 35 0.5 - 0.5 1.3 NA 0.072 c 5 PRWQS Yes ASL NA 0.072 c 0.0 PRWQS Yes ASL NA 0.072 c 0.0 PRWQS Yes ASL NA 0.072 c 0.0 PRWQS Yes ASL Yes NA 0.0 PRWQS Yes ASL Yes NA Yes Yes NA Yes NA Yes NA Yes NA Yes NA Yes NA Yes Yes NA Yes NA Yes Yes NA Yes NA Yes NA Yes NA Yes Yes NA Yes NA Yes NA Yes Yes NA Yes NA Yes NA Yes NA Yes NA Yes Yes NA Yes NA Yes Yes Yes NA Yes Ye	ll .		*									_	_			
Type															H	
127-18-4																
156-60-5 trans-1,2-Dichloropropene 0.2 J 0.2 J Jug/L MW-B 1/35 0.2 - 0.2 0.2 0.2 NA 0.41 c ⁴¹ 3.4 0.40 c ⁴¹ 3.4 0.41 c ⁴¹ 3.4 0.			,							11		-	-		11	_
10061-02-6 trans-1/3-Dichloropropene		-											_			_
79-01-6			*													
Trichloromethane												-	-		11	
TS-01-4										11			_			
Semi-volatile Organic Compounds 117-81-7 Bis(2-Ethylbexy) Phthalate 56 56 µg/L MW-AD 1 / 34 2.5 - 2.5 56 NA 0.071 c 12 PRWQS No IFD Residence Residenc										-						
117-81-7 Bis(2-Ethylhexyl)Phthalate 56 56 19				0.22	0.73	μg/L	MW-B	3 / 35	0.2 - 0.2	0.73	NA	0.015 c	0.25	PRWQS	Yes	тох
S5-68-7 Butylbenzylphthalate 0.52 J 0.52 J µg/L MW-FS 1 / 34 2.5 - 2.5 0.52 NA 14 c 1500 PRWGS No IFD R7-86-5 Pentachlorophenol 0.049 J 0.1 J µg/L MW-K 1 / 34 0.05 - 0.05 0.096 NA 0.093 c 0.05 PRWGS No IFD R7-86-5 Pentachlorophenol 0.049 J 0.1 J µg/L MAUNABO-1 2 / 34 0.1 - 0.1 0.1 0.1 NA 0.003 c 0.05 PRWGS No IFD MAUNABO-1 1 / 34 0.05 - 0.05 0.096 NA 0.093 c 0.05 PRWGS No IFD MAUNABO-1 2 / 34 0.1 - 0.1 0.1 0.1 NA 0.003 c 0.05 PRWGS No IFD MAUNABO-1 1 / 34 0.002 c 0.093 c 0.093 c 0.05 PRWGS No IFD MAUNABO-1 1 / 34 0.002 c 0.093 c 0.093 c 0.003 c 0.05 PRWGS No IFD MW-K 1 / 34 0.002 c 0.093 c 0.093 c 0.093 c 0.095 PRWGS No IFD MW-K 1 / 34 0.002 c 0.093 c 0.093 c 0.093 c 0.095 NA 450 n 21000 PRWGS No IFD MW-K 1 / 34 0.002 c 0.093 c						_										
621-64-7 N-Nitrosc-Di-N-Propylamine 0.096 0.096 0.096 0.095 0.096 0.095 0.096 0.095 0.096 0.095 0.095 0.096 0.095 0.096 0.095 0.096 0.097 0.1 J J J J J J J J J J			` , ,,												11	
87-86-5							_			11					11	
108-95-2 Phenol 0.93 J 0.93 J 1.93 J 1.93 J 1.94 1.74 2.5 - 2.5 0.93 NA 450 n 21000 PRWQS No IFD Pesticides/Polychlorinated Biphenyls 72-54-8 4.4 -DDD 0.019 NJ 0.019 NJ 0.019 NJ 1.72 1.74 0.0025 0.005 0.0019 NA 0.28 c 0.0022 PRWQS No IFD 319-85-7 Beta-BHC 0.003 J 0.0038 J 0.0038 J 1.74 0.0013 - 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 1.74 0.0013 - 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 1.74 0.0013 - 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 1.74 0.0013 - 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 1.74 0.0013 - 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 1.74 0.0013 - 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.091 PRWQS No IFD 0.0013 0.0025 0.0038 NA 0.022 c 0.0038 NA 0.022 c 0.0038 NA 0.022 c 0.0013 NA 0.0025 0.0038 NA 0.022 c 0.0038 NA 0.022 c 0.0038 NA 0.022 c 0.0038 NA 0.022 c 0.0038		-														
Pesticides/Polychlorinated Biphenyls 72-54-8			· ·							11			1		11	
72-54-8				0.93 J	0.93 J	μg/L	MW-AS	1 / 34	2.5 - 2.5	0.93	NA	450 n	21000	PRWQS	No	IFD
319-85-7 Beta-BHC 0.002 J 0.002 J 1.9JL 1.7 34 0.0013 - 0.0025 0.002 0.002 0.0038																
319-86-8 Delta-BHC Delta																
959-98-8 Endosulfan		319-85-7		0.002 J	0.002 J	μg/L	MW-K	1 / 34	0.0013 - 0.0025	0.002	NA	0.022 c	0.091	PRWQS	No	
Inorganics			Delta-BHC	0.0038 J	0.0038 J	μg/L	MW-I		0.0013 - 0.0025	0.0038		0.022 c ⁽⁵⁾	NL		No	
7429-90-5 7440-38-2 Aluminum Arsenic 48.2 0.41 J 8190 J 7.2 10.41 J μg/L 10.41 J MW-C 10.41 J 22 / 31 16 / 31 20 - 20 16 / 31 8190 J 10 - 10 NA 0.045 c NA 1600 n 0.045 c 10 NL PRWQS PRW		959-98-8	Endosulfan I	0.027	0.051	μg/L	MW-K	2 / 34	0.0013 - 0.0025	0.051	NA	7.8 n ⁽⁶⁾	62	PRWQS	No	BSL
7440-38-2 Arsenic 7440-39-3 Barium 27.8 346 J μg/L MW-K 31 / 31 10 - 10 346 NA 290 n 2000 DWR Yes ASL 7440-41-7 Beryllium 0.13 J 0.13 J μg/L MW-C 1 / 31 1 - 1 0.13 NA 1.6 n 4 DWR No IFD NA NA NL NL PRWQS Yes ASL NA NA NA NA NA NA NA N		Inorganics														
T440-39-3 Barium 27.8 346 J μg/L MW-K 31 / 31 10 - 10 346 NA 290 n 2000 DWR Yes ASL				48.2	8190 J	μg/L	MW-C	22 / 31	20 - 20	8190	NA		NL		Yes	_
7440-41-7 Beryllium 24800 105000 μg/L μg/L MAUNABO-1 31 / 31 500 - 500 105000 NA NA NA NA NA NA NA		7440-38-2		0.41 J	7.2	μg/L	MW-J	16 / 31	1 - 1	7.2	NA	0.045 c	10	PRWQS	Yes	ASL
7440-70-2 Calcium 24800 105000 μg/L MAUNABO-1 31 / 31 500 - 500 105000 NA NA NA NA NA NA NA		7440-39-3		27.8	346 J	μg/L	MW-K	31 / 31	10 - 10	346	NA	290 n	2000	DWR	Yes	ASL
T440-47-3 Chromium Chromiu	ll .	7440-41-7		0.13 J	0.13 J	μg/L	MW-C	1 / 31	1 - 1	0.13	NA	1.6 n	4	DWR	No	IFD
7440-48-4 Cobalt 0.12 J 6.5 μg/L MW-C 13 / 31 1 - 1 6.5 NA 0.47 n NL PRWQS Yes ASL 7440-50-8 Copper 0.45 J 211 μg/L MAUNABO-1 23 / 31 2 - 2 211 NA 62 n 1300 PRWQS Yes ASL 57-12-5 Cyanide 2.4 J 11.2 μg/L MW-C 8 / 31 10 - 10 11.2 NA 31 n 200 PRWQS No BSL 7439-89-6 Iron 28 J 16600 μg/L MW-C 28 / 31 200 - 200 16600 NA 1100 n NL PRWQS Yes ASL 7439-95-4 Magnesium 11600 46300 μg/L MW-C 15 / 31 1 - 1 1.5 NA 15 (®) 15 PRWQS No BSL 7439-95-4 Magnesium 11600 46300 μg/L MAUNABO-1 31 / 31 500 - 500 46300 NA	ll .	7440-70-2	Calcium	24800	105000	μg/L	MAUNABO-1	31 / 31	500 - 500	105000	NA	NA	NL	PRWQS	No	NUT
7440-50-8 (57-12-5) Copper (Cyanide) 0.45 J (2.4 J) 211 (2.4 J) Mg/L (2.4 J) MW-AD (2.4 J) 31 (2.2 J) 211 (2.4 J) MW-AD	ll .	7440-47-3	Chromium	2.2	33.4	μg/L	MW-C	6 / 31	2 - 2	33.4	NA	0.031 c ⁽⁷⁾	100	PRWQS	Yes	ASL
57-12-5 Cyanide 2.4 J 11.2 μg/L MW-AD 8 / 31 10 - 10 11.2 NA 31 n 200 PRWQS No BSL 7439-89-6 Iron 28 J 16600 μg/L MW-C 28 / 31 200 - 200 16600 NA 1100 n NL PRWQS Yes ASL 7439-92-1 Lead 0.08 J 1.5 μg/L MW-C 15 / 31 1 - 1 1.5 NA 15 (8) 15 PRWQS No BSL 7439-95-4 Magnesium 11600 46300 μg/L MAUNABO-1 31 / 31 500 - 500 46300 NA NA NA NA NA NA NA NA NO NUT	ll .	7440-48-4	Cobalt	0.12 J	6.5	μg/L	MW-C	13 / 31	1 - 1	6.5	NA	0.47 n	NL	PRWQS	Yes	ASL
57-12-5 Cyanide 2.4 J 11.2 µg/L MW-AD 8 / 31 10 - 10 11.2 NA 31 n 200 PRWQS No BSL 7439-89-6 Iron 28 J 16600 µg/L MW-C 28 / 31 200 - 200 16600 NA 1100 n NL PRWQS Yes ASL 7439-92-1 Lead 0.08 J 1.5 µg/L MW-C 15 / 31 1 - 1 1.5 NA 15 (8) 15 PRWQS No BSL 7439-95-4 Magnesium 11600 46300 µg/L MAUNABO-1 31 / 31 500 - 500 46300 NA	ll .	7440-50-8	Copper	0.45 J	211	μg/L	MAUNABO-1	23 / 31	2 - 2	211	NA	62 n	1300	PRWQS	Yes	ASL
7439-89-6 Iron 28 J 16600 μg/L MW-C 28 / 31 200 - 200 16600 NA 1100 n NL PRWQS Yes ASL 7439-92-1 Lead 0.08 J 1.5 μg/L MW-C 15 / 31 1 - 1 1.5 NA 15 (8) 15 PRWQS No BSL 7439-95-4 Magnesium 11600 46300 μg/L MAUNABO-1 31 / 31 500 - 500 46300 NA NA NA NI PRWQS No NUT	ll .	57-12-5	Cyanide	2.4 J	11.2		MW-AD	8 / 31	10 - 10	11.2	NA	31 n	200	PRWQS	No	BSL
7439-92-1 Lead 0.08 J 1.5 µg/L MW-C 15 / 31 1 - 1 1.5 NA 15 ⁽⁸⁾ 15 PRWQS No BSL 7439-95-4 Magnesium 11600 46300 µg/L MAUNABO-1 31 / 31 500 - 500 46300 NA NA NA NL PRWQS No NUT	ll .		*												H	
7439-95-4 Magnesium 11600 46300 µg/L MAUNABO-1 31 / 31 500 - 500 46300 NA NA NL PRWQS No NUT	ll .	7439-92-1							1 - 1	11		15 (8)	15			
	ll .						MAUNABO-1		500 - 500	11	NA	NA	NL		No	
	ll .		o .							11					11	



OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future Medium: Groundwater Groundwater Exposure Medium:

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of Reporting Limit	Concentratio n Used for Screening (1)	Background Value	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	COPC Flag (Yes/No)	Rationale for Selection or Deletion
Groundwater	7439-97-6	Mercury	0.054 J	0.054 J	μg/L	MAUNABO-1	1 / 31	0.2 - 0.2	0.054	NA	0.43 n ⁽⁹⁾	0.05	PRWQS	No	IFD
	7440-02-0	Nickel	0.19 J	18.4	μg/L	MW-C	13 / 31	1 - 1	18.4	NA	30 n ⁽¹⁰⁾	610	PRWQS	No	BSL
	7440-09-7	Potassium	714	19700	μg/L	MW-FD	31 / 31	500 - 500	19700	NA	NA	NL	PRWQS	No	NUT
	7782-49-2	Selenium	1.5 J	1.5 J	μg/L	MAUNABO-4	1 / 31	5 - 5	1.5	NA	7.8 n	50	PRWQS	No	IFD
	7440-23-5	Sodium	33500	97200	μg/L	MW-AS	31 / 31	500 - 500	97200	NA	NA	NL	PRWQS	No	NUT
	7440-28-0	Thallium	1.6 J	1.6 J	μg/L	MAUNABO-4	1 / 31	1 - 1	1.6	NA	0.016 n	0.24	PRWQS	No	IFD
	7440-62-2	Vanadium	0.72 J	68.2	μg/L	MW-C	26 / 31	5 - 5	68.2	NA	7.8 n ⁽¹¹⁾	NL	PRWQS	Yes	ASL
	7440-66-6	Zinc	1.8 J	34.3 J	μg/L	MW-C	27 / 31	2 - 2	34.3	NA	470 n	NL	PRWQS	No	BSL

⁽¹⁾ Maximum detected concentration used for screening

Selection Reason: ASL = above screening level Deletion Reason: BSL = below screening level IFD = detection frequency less than 5% NUT = essential nutrient

NA = not available

ND = not detected

n = screening toxicity value based on noncancer effects c = screening toxicity value based on cancer effects

PRWQS = Puerto Rico Water Quality Standard

DWR = National Primary Drinking Water Regulation

COPC = chemical of potential concern

ARAR/TBC = Applicable or Relevant and Appropriate Requirement/To Be Considered

J = qualifier for estimated value

NJ = qualifier for tentatively identified and estimated value

μg/L = micrograms per liter

4,4'-DDD = p,p'-dichlorodiphenyldichloroethane

BHC = benzene hexachloride



Page 2 of 2 6/28/2012

 $^{^{(2)}}$ Screened against Regional Screening Levels, November 2011, for tap water, adjusted to a cancer risk of 1×10 $^{-6}$ and hazard quotient of 0.1. http://www.epa.gov/region09/waste/sfund/prg/index.html

⁽³⁾ Rationale Codes:

⁽⁴⁾ screening value for 1,3-dichloropropene

⁽⁵⁾ screening value for hexachlorocyclohexane

⁽⁶⁾ screening value for endosulfan

⁽⁷⁾ screening value for chromium VI

⁽⁸⁾ Puerto Rico Water Quality Standard

⁽⁹⁾ screening value for mercuric chloride (and other mercury salts)

⁽¹⁰⁾ screening value for nickel soluble salts

⁽¹¹⁾ screening value for vanadium and compounds

OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Medium: Surface Water

Exposure Medium: Surface Water

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of Reporting Limit	Concentration Used for Screening (1)	Background	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	COPC Flag (Yes/No)	Rationale for Selection or Deletion ⁽³⁾
Surface Water	Volatile Organ	ic Compounds													
	75-27-4	Bromodichloromethane	0.38 J	1	μg/L	SW-06	3 / 6	0.5 - 0.5	1	NA	0.12 c	5.5	PRWQS	Yes	ASL
	75-25-2	Bromoform	0.43 J	0.64	μg/L	SW-06	2 / 6	0.5 - 0.5	0.64	NA	8.5 c	43	PRWQS	No	BSL
	124-48-1	Dibromochloromethane	0.57	1.3	μg/L	SW-06	3 / 6	0.5 - 0.5	1.3	NA	0.15 c	4	PRWQS	Yes	ASL
	Semi-volatile	Organic Compounds													
	117-81-7	Bis(2-Ethylhexyl)Phthalate	1.1 J	2.5	μg/L	SW-07	3 / 6	2.5 - 2.5	2.5	NA	4.8 c	12	PRWQS	No	BSL
	Inorganics														
	7429-90-5	Aluminum	27.4	41.3	μg/L	SW-07	3 / 6	20 - 20	41.3	NA	3700 n	NL	PRWQS	No	BSL
	7440-39-3	Barium	34.4	50.5	μg/L	SW-05	6 / 6	10 - 10	50.5	NA	730 n	NL	PRWQS	No	BSL
	7440-70-2	Calcium	15800	24500	μg/L	SW-05	6 / 6	500 - 500	24500	NA	NA	NL	PRWQS	No	NUT
	7440-50-8	Copper	2.1	3.3	μg/L	SW-03	4 / 6	2 - 2	3.3	NA	150 n	12	PRWQS	No	BSL
	57-12-5	Cyanide	4.3 J	4.3 J	μg/L	SW-03	1 / 6	10 - 10	4.3	NA	73 n	5.2	PRWQS	No	BSL
	7439-95-4	Magnesium	7850	9650	μg/L	SW-05	5 / 6	500 - 500	9650	NA	NA	NL	PRWQS	No	NUT
	7439-96-5	Manganese	1.8	44.8	μg/L	SW-04	6 / 6	1 - 1	44.8	NA	88 n	NL	PRWQS	No	BSL
	7440-09-7	Potassium	1240	2300	μg/L	SW-05	6 / 6	500 - 500	2300	NA	NA	NL	PRWQS	No	NUT
	7440-23-5	Sodium	21300	1910000	μg/L	SW-03	6 / 6	500 - 500	1910000	NA	NA	NL	PRWQS	No	NUT
	7440-66-6	Zinc	0.52 J	3.8	μg/L	SW-06	6 / 6	2 - 2	3.8	NA	1100 n	105	PRWQS	No	BSL

⁽¹⁾ Maximum detected concentration used for screening

Selection Reason: ASL = above screening level
Deletion Reason: BSL = below screening level
NUT = essential nutrient

NA = not available

ND = not detected

n = screening toxicity value based on noncancer effects

c = screening toxicity value based on cancer effects

PRWQS = Puerto Rico Water Quality Standard

COPC = chemical of potential concern

ARAR/TBC = Applicable or Relevant and Appropriate Requirement/To Be Considered

J = qualifier for estimated value

μg/L = micrograms per liter



⁽²⁾ Screened against Regional Screening Levels, November 2011, for tap water, adjusted to a cancer risk of 1x1(⁶ and hazard quotient of 0.1. http://www.epa.gov/region09/waste/sfund/prg/index.html

⁽³⁾ Rationale Codes:

OCCURRENCE, DISTRIBUTION, AND SELECTION OF CHEMICALS OF POTENTIAL CONCERN

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future Medium: Sediment Exposure Medium: Sediment

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of	Concentration Used for Screening (1)	Background Value	Screening Toxicity Value (n/c) (2)	Potential ARAR/TBC Value	Potential ARAR/TBC Source	COPC Flag (Yes/No)	Rationale for Selection or Deletion
Sediment	Semi-volatile	Organic Compounds													
	117-81-7	Bis(2-Ethylhexyl)Phthalate	81 J	81 J	μg/kg	SD-05	1 / 6	85 - 85	81	NA	35000 c	NA	NA	No	BSL
	Pesticides/Po	lychlorinated Biphenyls													
	72-54-8	4,4'-DDD	0.31 J	0.31 J	μg/kg	SD-05	1 / 6	0.17 - 0.17	0.31	NA	2000 с	NA	NA	No	BSL
	72-55-9	4,4'-DDE	0.3 J	0.3 J	μg/kg	SD-05	1 / 6	0.17 - 0.17	0.3	NA	1400 c	NA	NA	No	BSL
	50-29-3	4,4'-DDT	0.55 J	0.55 J	μg/kg	SD-05	1 / 6	0.17 - 0.17	0.55	NA	1700 c	NA	NA	No	BSL
	11097-69-1	Aroclor 1254	9.2 J	9.2 J	μg/kg	SD-07	1 / 6	33 - 33	9.2	NA	110 n	NA	NA	No	BSL
	319-85-7	Beta-BHC	0.014 J	0.014 J	μg/kg	SD-03	1 / 6	0.085 - 0.085	0.014	NA	270 c	NA	NA	No	BSL
	72-43-5	Methoxychlor	0.051 J	0.062 J	μg/kg	SD-03	2 / 6	0.85 - 0.85	0.062	NA	31000 n	NA	NA	No	BSL
	Inorganics														
	7429-90-5	Aluminum	2580 J	5350 J	mg/kg	SD-05	6 / 6	20 - 20	5350	NA	7700 n	NA	NA	No	BSL
	7440-38-2	Arsenic	0.65	2.7	mg/kg	SD-04	2/6	0.5 - 0.5	2.7	NA	0.39 с	NA	NA	Yes	ASL
	7440-39-3	Barium	27	71.9	mg/kg	SD-05	6 / 6	5 - 5	71.9	NA	1500 n	NA	NA	No	BSL
	7440-70-2	Calcium	1040	1670	mg/kg	SD-05	6 / 6	500 - 500	1670	NA	NA	NA	NA	No	NUT
	7440-47-3	Chromium	2.1 J	6 J	mg/kg	SD-05	6 / 6	1 - 1	6	NA	0.29 c ⁽⁴⁾	NA	NA	Yes	ASL
	7440-48-4	Cobalt	2.5	7.1	mg/kg	SD-05	6 / 6	0.5 - 0.5	7.1	NA	2.3 n	NA	NA	Yes	ASL
	7440-50-8	Copper	10.6	31.8	mg/kg	SD-05	6 / 6	1 - 1	31.8	NA	310 n	NA	NA	No	BSL
	7439-89-6	Iron	5220 J	13500 J	mg/kg	SD-05	6 / 6	10 - 10	13500	NA	5500 n	NA	NA	Yes	ASL
	7439-92-1	Lead	0.6 J	2.1 J	mg/kg	SD-05	5 / 6	0.5 - 0.5	2.1	NA	800 n ⁽⁵⁾	NA	NA	No	BSL
	7439-95-4	Magnesium	794	1890	mg/kg	SD-05	6 / 6	500 - 500	1890	NA	NA	NA	NA	No	NUT
		Manganese	237	333	mg/kg	SD-02	6 / 6	0.5 - 0.5	333	NA	180 n	NA	NA	Yes	ASL
	7440-02-0	Nickel	0.63	2.9	mg/kg	SD-04	6 / 6	0.5 - 0.5	2.9	NA	150 n ⁽⁶⁾	NA	NA	No	BSL
		Potassium	273 J	790	mg/kg	SD-03	6 / 6	500 - 500	790	NA	NA	NA	NA	No	NUT
	7440-62-2	Vanadium	33.5 J	70.6 J	mg/kg	SD-05	6 / 6	2.5 - 2.5	70.6	NA	39 n ⁽⁷⁾	NA	NA	Yes	ASL
	7440-66-6	Zinc	11.9	36.1	mg/kg	SD-04	6 / 6	1 - 1	36.1	NA	2300 n	NA	NA	No	BSL

⁽¹⁾ Maximum detected concentration used for screening

Selection Reason: ASL = above screening level

ASL2 = above ARAR/TBC level TOX = group A carcinogen

Deletion Reason: BSL = below screening level

BSL2 = below ARAR/TBC level

IFD = detection frequency less than 5%

NUT = essential nutrient

NTX = no toxicity information available

NA = not available

ND = not detected

n = screening toxicity value based on noncancer effects

c = screening toxicity value based on cancer effects

COPC = chemical of potential concern

ARAR/TBC = Applicable or Relevant and Appropriate Requirement/To Be Considered

J = qualifier for estimated value μg/kg = micrograms per kilogram

mg/kg = milligrams per kilogram



⁽²⁾ Screened against Regional Screening Levels, November 2011, for residential soil, adjusted to a cancer risk of 1×10⁶ and hazard quotient of 0.1. http://www.epa.gov/region09/waste/sfund/prg/index.html

⁽³⁾ Rationale Codes:

⁽⁴⁾ screening value for chromium VI

⁽⁵⁾ OSWER screening value for industrial soil

⁽⁶⁾ screening value for nickel soluble salts

⁽⁷⁾ screening value for vanadium and compounds

TABLE B-3.1a MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe Current/Future

Medium: Soil

Exposure Medium: Surface Soil - Former Sugar Mill

Exposure Point	Chemical of Potential Concern	Unit	Mean Concentration	Upper Confidence	Maximum Concentration		Exposi	ure Point Cond	centration (2)
·			(1)	Limit (1)	(Qualifier)	Value	Unit	Statistic	Rationale (3)
Surface Soil	Semi-volatile Organic Compounds								
	Benzo(a)pyrene	μg/kg	33	66	76 J	66	μg/kg	UCL-NP	95% KM (t) UCL
	Dibenzo(a,h)anthracene	μg/kg	15	NA	18 J	18	μg/kg	Max	<4 detected values
	Inorganics								
	Aluminum	mg/kg	10513	13777	15800	13777	mg/kg	UCL-N	95% Student's-t UCL
	Arsenic	mg/kg	2.6	3.6	4.6	3.6	mg/kg	UCL-N	95% Student's-t UCL
	Chromium	mg/kg	9.8	15.0	17.1	15.0	mg/kg	UCL-N	95% Student's-t UCL
	Cobalt	mg/kg	6.4	8.8	10.5	8.8	mg/kg	UCL-N	95% Student's-t UCL
	Iron	mg/kg	28117	37435	41800	37435	mg/kg	UCL-N	95% Student's-t UCL
	Manganese	mg/kg	387	489	547	489	mg/kg	UCL-N	95% Student's-t UCL
	Vanadium	mg/kg	48.8	63.7	69.3	63.7	mg/kg	UCL-N	95% Student's-t UCL

μg/kg = microgram per kilogram

J = qualifier for estimated value

mg/kg = milligram per kilogram Notes:

(1) Mean and upper confidence limit (UCL) concentrations are calculated using ProUCL version 4.1.00 for chemicals with at least 5 samples in a dataset and 4 detected values.

(2) Exposure point concentration is lower of maximum concentration and UCL.

(3) Rationale: UCL-N = upper confidence limit of mean of normal distribution

UCL-NP = upper confidence limit of mean of non-parametric distribution

Max = maximum detected concentration



TABLE B-3.1b MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Medium: Soil

Exposure Medium: Surface Soil - Puerto Rico Beverage

Exposure Point	Chemical of Potential Concern	Unit	Mean Concentration	Upper Confidence	Maximum Concentration		Expos	sure Point Cor	ncentration (2)
			(1)	Limit ⁽¹⁾	(Qualifier)	Value	Unit	Statistic	Rationale (3)
Surface Soil	Inorganics								
	Aluminum	mg/kg	10240	13040	15700	13040	mg/kg	UCL-N	95% Student's-t UCL
	Arsenic	mg/kg	0.8	NA	2.9	2.9	mg/kg	Max	<4 detected values
	Chromium	mg/kg	7.0	25.1	27.5	25.1	mg/kg	UCL-NP	95% Chebyshev (Mean, Sd) UCL
	Cobalt	mg/kg	4.8	6.4	7.5	6.4	mg/kg	UCL-N	95% Student's-t UCL
	Iron	mg/kg	23467	29438	35900	29438	mg/kg	UCL-N	95% Student's-t UCL
	Manganese	mg/kg	269	349	365	349	mg/kg	UCL-N	95% Student's-t UCL
	Vanadium	mg/kg	44.0	56.6	71.8	56.6	mg/kg	UCL-N	95% Student's-t UCL

μg/kg = microgram per kilogram mg/kg = milligram per kilogram J = qualifier for estimated value

NA = not available

Notes:

(1) Mean and upper confidence limit (UCL) concentrations are calculated using ProUCL version 4.1.00 for chemicals with at least 5 samples in a dataset and 4 detected values.

(2) Exposure point concentration is lower of maximum concentration and UCL.

(3) Rationale:

UCL-N = upper confidence limit of mean of normal distribution

UCL-NP = upper confidence limit of mean of non-parametric distribution

Max = maximum detected concentration



Page 1 of 1 6/28/2012

TABLE B-3.2a MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe Future Medium: Soil

Exposure Medium: Surface/Subsurface Soil - Former Sugar Mill

Exposure Point	Chemical of Potential Concern	Unit	Mean Concentration	Upper Confidence	Maximum Concentration		Exposi	ure Point Cond	centration (2)
			(1)	Limit (1)	(Qualifier)	Value	Unit	Statistic	Rationale (3)
Surface/	Semi-volatile Organic Compounds								
Subsurface Soil	Benzo(a)pyrene	μg/kg	29	46	76 J	46	μg/kg	UCL-NP	95% KM (t) UCL
	Dibenzo(a,h)anthracene	μg/kg	13	NA	18 J	18	μg/kg	Max	<4 detected values
	Inorganics								
	Aluminum	mg/kg	15516	17264	28500	17264	mg/kg	UCL-N	95% Student's-t UCL
	Arsenic	mg/kg	1.5	1.9	4.6	1.9	mg/kg	UCL-N	95% Student's-t UCL
	Chromium	mg/kg	8.3	9.9	20.8	9.9	mg/kg	UCL-N	95% Modified-t UCL
	Cobalt	mg/kg	9.9	10.9	14.7	10.9	mg/kg	UCL-N	95% Student's-t UCL
	Iron	mg/kg	26099	29045	41800	29045	mg/kg	UCL-N	95% Student's-t UCL
	Manganese	mg/kg	386	435	650	435	mg/kg	UCL-N	95% Student's-t UCL
	Thallium	mg/kg	0.1	0.2	0.8 J	0.2	mg/kg	UCL-NP	95% KM (Chebyshev) UCL
	Vanadium	mg/kg	84	96	192	96	mg/kg	UCL-N	95% Student's-t UCL

μg/kg = microgram per kilogram mg/kg = milligram per kilogram J = qualifier for estimated value

Notes:

UCL-N = upper confidence limit of mean of normal distribution

UCL-NP = upper confidence limit of mean of non-parametric distribution



⁽¹⁾ Mean and upper confidence limit (UCL) concentrations are calculated using ProUCL version 4.1.00 for chemicals with at least 5 samples in a dataset and 4 detected values.

⁽²⁾ Exposure point concentration is lower of maximum concentration and UCL.

⁽³⁾ Rationale:

TABLE B-3.2b MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe Future Medium: Soil

Exposure Medium: Surface/Subsurface Soil - Puerto Rico Beverage

Exposure Point	Chemical of Potential Concern	Unit	Mean Concentration	Upper Confidence	Maximum Concentration		Exposi	ure Point Con	centration (2)
			(1)	Limit (1)	(Qualifier)	Value	Unit	Statistic	Rationale (3)
Surface/	Inorganics								
Subsurface Soil	Aluminum	mg/kg	13551	16378	37800	16378	mg/kg	UCL-G	95% Approximate Gamma UCL
	Arsenic	mg/kg	0.5	0.7	2.9	0.7	mg/kg	UCL-NP	95% KM (t) UCL
	Chromium	mg/kg	4.1	5.8	27.5	5.8	mg/kg	UCL-G	95% Approximate Gamma UCL
	Cobalt	mg/kg	6.62	8.12	16.1	8.12	mg/kg	UCL-G	95% Approximate Gamma UCL
	Iron	mg/kg	24125	27988	44700	27988	mg/kg	UCL-G	95% Approximate Gamma UCL
	Manganese	mg/kg	285.1	327	474	327	mg/kg	UCL-N	95% Student's-t UCL
	Vanadium	mg/kg	69.3	85.5	162	85.5	mg/kg	UCL-G	95% Approximate Gamma UCL

μg/kg = microgram per kilogram mg/kg = milligram per kilogram J = qualifier for estimated value

Notes:

(3) Rationale: UCL-N = upper confidence limit of mean of normal distribution

UCL-G = upper confidence limit of mean of gamma distribution

UCL-NP = upper confidence limit of mean of non-parametric distribution



⁽¹⁾ Mean and upper confidence limit (UCL) concentrations are calculated using ProUCL version 4.1.00 for chemicals with at least 5 samples in a dataset and 4 detected values.

⁽²⁾ Exposure point concentration is lower of maximum concentration and UCL.

TABLE B-3.3 MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe Current/Future Medium: Groundwater Exposure Medium: Groundwater

Exposure Point	Chemical of Potential Concern	Unit	Mean Concentration	Upper Confidence	Maximum Concentration	Exposure Point Concentration (2)				
			(1)	Limit (1)	(Qualifier)	Value	Unit	Statistic	Rationale ⁽³⁾	
Groundwater	Volatile Organic Compounds									
	cis-1,2-Dichloroethene	μg/L	30.7	54.5	300	54.5	μg/L	UCL-NP	95% KM (t) UCL	
	Tetrachloroethene	μg/L	0.54	0.99	8.5 J	0.99	μg/L	UCL-NP	95% KM (t) UCL	
	trans-1,2-Dichloroethene	μg/L	1.5	2.3	13	2.3	μg/L	UCL-NP	95% KM (t) UCL	
	Trichloroethene	μg/L	0.45	0.56	1.9	0.56	μg/L	UCL-NP	95% KM (t) UCL	
	Vinyl Chloride	μg/L	0.25	NA	0.73	0.73	μg/L	Max	<4 detected values	
	Inorganics									
	Aluminum	μg/L	397.8	2038	8190 J	2038	μg/L	UCL-NP	97.5% KM (Chebyshev) UCL	
	Arsenic	μg/L	2.9	3.8	7.2	3.8	μg/L	UCL-NP	95% KM (t) UCL	
	Barium	μg/L	176	204	346 J	204	μg/L	UCL-N	95% Student's-t UCL	
	Chromium	μg/L	4.87	8.35	33.4	8.35	μg/L	UCL-NP	95% KM (t) UCL	
	Cobalt	μg/L	0.7	1.1	6.5	1.1	μg/L	UCL-NP	95% KM (t) UCL	
	Copper	μg/L	9.5	52.2	211	52.2	μg/L	UCL-NP	95% KM (t) UCL	
	Iron	μg/L	1587	8196	16600	8196	μg/L	UCL-NP	99% KM (Chebyshev) UCL	
	Manganese	μg/L	229	412	2340 J	412	μg/L	UCL-G	95% Adjusted Gamma UCL	
	Vanadium	μg/L	12.5	17.0	68.2	17.0	μg/L	UCL-NP	95% KM (BCA) UCL	

μg/L = microgram per liter

J = qualifier for estimated value

Notes:

(3) Rationale: UCL-G = upper confidence limit of mean of gamma distribution

UCL-NP = upper confidence limit of mean of non-parametric distribution



⁽¹⁾ Mean and upper confidence limit (UCL) concentrations are calculated using ProUCL version 4.1.00 for chemicals with at least 5 samples in a dataset and 4 detected values.

 $^{^{(2)}}$ Exposure point concentration is lower of maximum concentration and UCL.

TABLE B-3.4 MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe Current/Future
Medium: Surface Water
Exposure Medium: Surface Water

Exposure Point	Chemical of Potential Concern	Unit	Mean Concentration	Upper Confidence	Maximum Concentration	Exposure Point Concentration (2)					
			(1)	Limit (1)	(Qualifier)	Value	Unit	Statistic	Rationale (3)		
Surface Water	Volatile Organic Compounds										
	Bromodichloromethane	μg/L	0.5	NA	1	1	μg/L	Max	<4 detected values		
	Dibromochloromethane	μg/L	0.8	NA	1.3	1.3	μg/L	Max	<4 detected values		

μg/L = microgram per liter

Notes:

(1) Mean and upper confidence limit (UCL) concentrations are calculated using ProUCL version 4.1.00 for chemicals with at least 5 samples in a dataset and 4 detected values.

(2) Exposure point concentration is lower of maximum concentration and UCL.

(3) Rationale: UCL-NP = upper confidence limit of mean of non-parametric distribution



TABLE B-3.5 MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe Current/Future
Medium: Sediment
Exposure Medium: Sediment

Exposure Point	Chemical of Potential Concern	Unit	Mean Concentration	Upper Confidence	Maximum Concentration	Exposure Point Concentration (2)				
			(1)	Limit (1)	(Qualifier)	Value	Unit	Statistic	Rationale (3)	
Sediment	Inorganics									
	Arsenic	mg/kg	1.0	NA	2.7	2.7	mg/kg	Max	<4 detected values	
	Chromium	mg/kg	3.6	4.7	6 J	4.7	mg/kg	UCL-N	95% Student's-t UCL	
	Cobalt	mg/kg	3.9	5.3	7.1	5.3	mg/kg	UCL-N	95% Student's-t UCL	
	Iron	mg/kg	8155	10517	13500 J	10517	mg/kg	UCL-N	95% Student's-t UCL	
	Manganese	mg/kg	284	310	333	310	mg/kg	UCL-N	95% Student's-t UCL	
	Vanadium	mg/kg	41.3	54.1	70.6 J	54.1	mg/kg	UCL-N	95% Modified-t UCL	

μg/kg = microgram per kilogram

J = qualifier for estimated value

NA = not available

mg/kg = milligram per kilogram

Notes:

Max = maximum detected concentration



⁽¹⁾ Mean and upper confidence limit (UCL) concentrations are calculated using ProUCL version 4.1.00 for chemicals with at least 5 samples in a dataset and 4 detected values.

⁽²⁾ Exposure point concentration is lower of maximum concentration and UCL.

⁽³⁾ Rationale: UCL-N = upper confidence limit of mean of normal distribution

TABLE B-4.1

VALUES AND EQUATIONS USED FOR DAILY INTAKE CALCULATIONS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Medium: Soil
Exposure Medium: Soil

Exposure	Receptor	D	Fun a sum Delint	Parameter	December Deficition	1.1-24	R	ME	С	TE	Intake Equation/
Route	Population	Receptor Age	Exposure Point	Code	Parameter Definition	Unit	Value	Rationale/Reference	Value	Rationale/Reference	Model Name
Ingestion	Commercial/	Adult	Puerto Rico	CS	Chemical Concentration in Soil	mg/kg	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Daily Intake (mg/kg-day) =
	Industrial		Beverage/	CF	Conversion Factor	kg/mg	1E-06		1E-06		CS x CF x IR-S x EF x ED x
			Former Sugar Mill		Ingestion Rate of Soil	mg/day	100	EPA 2002	50	EPA 1997	1/BW x 1/AT
				EF	Exposure Frequency	days/year	250	EPA 2004	219	EPA 2004	
				ED	Exposure Duration	years	25	EPA 2004	9	EPA 2004	
				BW	Body Weight	kg	70	EPA 2002	70	EPA 2002	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
	Trespasser	Adolescent	Puerto Rico	AT-N CS	Averaging Time (Noncancer) Chemical Concentration in Soil	days	9,125	EPA 1989	3,285	EPA 1989	Daily Intake (mg/kg-day) =
	rrespasser	(7-12 yrs)	Beverage/	CF	Conversion Factor	mg/kg kg/mg	1E-06	1 ables 6-3.1a 01 6-3.1b	1E-06	Tables 6-3.18 01 6-3.10	CS x CF x IR-S x EF x ED x
		(7-12 yis)	Former Sugar Mill		Ingestion Rate of Soil	mg/day	100	EPA 2002	50	(1)	1/BW x 1/AT
			onner ougar will	EF.	Exposure Frequency	days/year	100	EPA 2009	50	(2)	1/BW X 1/A1
				ED	Exposure Duration	years	6	EPA 1989	6	EPA 1989	
				BW	Body Weight	kg	36	EPA 1997 ⁽³⁾	36	EPA 1997 ⁽³⁾	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
				AT-N	Averaging Time (Noncancer)	days	2,190	EPA 1989	2,190	EPA 1989	
	Resident	Adult and	Puerto Rico	CS	Chemical Concentration in Soil	mg/kg	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Daily Intake (mg/kg-day):
		Child (0-6 yrs)	Beverage/	CF	Conversion Factor	kg/mg	1E-06		1E-06		for nonmutagen =
			Former Sugar Mill		Ingestion Rate of Soil - adult	mg/day	100	EPA 2002	50	EPA 2002	CS x CF x {(IR-S _a xED _a /BW _a) +
				IR-S _c	Ingestion Rate of Soil - child	mg/day	200	EPA 2002	100	EPA 2002	(IR-S _c xED _c /BW _c)) x EF x 1/AT
				EF	Exposure Frequency	days/year	350	EPA 2002	350	EPA 2002	
				ED_a	Exposure Duration - adult	years	24	EPA 2002	9		for mutagen =
				ED _c	Exposure Duration - child	years	6	EPA 2002	6	EPA 2002	for RME: CS x {(2xIR-S _c x10/BW _c)+
				BW _a	Body Weight - adult	kg	70	EPA 2002	70	EPA 2002	(4xIR-S _c x3/BW _c)+(10xIR-S _a x3/BW _a)
				BW _c	Body Weight - child	kg	15	EPA 2002	15	EPA 2002	+(14xIR-S _a x1/BW _a)} x EF x CF / AT
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	for CTE: CS x {(2xIR-S _c x10/BW _c)+
				AT-N _a AT-N _c	Averaging Time (Noncancer) - adult Averaging Time (Noncancer) - child	days	8,760 2.190	EPA 1989 EPA 1989	3,285 2.190	EPA 1989 EPA 1989	$(4xIR-S_cx3/BW_c)+(9xIR-S_ax3/BW_a)$ x EF x CF / AT
	Construction	Adult	Puerto Rico	CS	Chemical Concentration in Soil	days mg/kg		Tables B-3.2a or B-3.2b		raluated	Daily Intake (mg/kg-day) =
	Worker	Adult	Beverage/	CF	Conversion Factor	kg/mg	1E-06		NOI EV	aluateu	CS x CF x IR-S x EF x ED x
	VVOIKEI		Former Sugar Mill		Ingestion Rate of Soil	mg/day	330	EPA 2002			1/BW x 1/AT
			onner oagar will	EF	Exposure Frequency	days/year	100	(4)			175W X 17/11
				ED	Exposure Duration	years	1	(4)			
				BW	Body Weight	kg	70	EPA 2002			
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989			
				AT-N	Averaging Time (Noncancer)	days	365	EPA 1989			
Dermal	Commercial/	Adult	Puerto Rico	CS	Chemical Concentration in Soil	mg/kg	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Daily Intake (mg/kg-day) =
Contact	Industrial Worker		Beverage/	CF	Conversion Factor	kg/mg	1E-06		1E-06		CS x CF x SA x AF x ABS x
			Former Sugar Mill		Skin Surface Area Available for Contact	cm ²	3,300	EPA 2004	3,300	EPA 2004	EF x ED x 1/BW x 1/AT
				AF	Adherence Factor	mg/cm ²	0.2	EPA 2004	0.02	EPA 2004	
				ABS	Absorption Factor	unitless	chemical specific	Table B-4.5	chemical specific	Table B-4.5	
				EF	Exposure Frequency	days/year	250	EPA 2002	219	EPA 2004	
				ED	Exposure Duration	years	25	EPA 2002	9	EPA 2004	
				BW	Body Weight	kg	70	EPA 2002	70	EPA 2002	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
	_		D . D:	AT-N	Averaging Time (Noncancer)	days	9,125	EPA 1989	3,285	EPA 1989	
	Trespasser	Adolescent	Puerto Rico	CS	Chemical Concentration in Soil	mg/kg		ables B-3.1a or B-3.1b		ables B-3.1a or B-3.1b	Daily Intake (mg/kg-day) =
		(7-12 yrs)	Beverage/	CF SA	Conversion Factor	kg/mg	1E-06 3,600		1E-06 3,600	 	CS x CF x SA x AF x ABS x EF x ED x 1/BW x 1/AT
			Former Sugar Mill		Skin Surface Area Available for Contact	cm ²		EPA 2004		EPA 2004	EF X ED X 1/BW X 1/AT
				AF	Adherence Factor	mg/cm ²	0.07	EPA 2004	0.01	EPA 2004	
				ABS	Absorption Factor	unitless	chemical specific	Table B-4.5	chemical specific	Table B-4.5	
				EF	Exposure Frequency	days/year	100	EPA 2009	50	* *	
				ED BW	Exposure Duration Body Weight	years	6 36	EPA 1989	6 36	EPA 1989	
				AT-C	Averaging Time (Cancer)	kg davs	25.550	EPA 1997 ⁽³⁾ EPA 1989	25.550	EPA 1997 ⁽³⁾ EPA 1989	
				AT-C	Averaging Time (Cancer) Averaging Time (Noncancer)	days	2,190	EPA 1989 EPA 1989	2,190	EPA 1989 EPA 1989	
1			1	731.13	r tranaging time (rechainder)	uuys	2,100	LI // 1000	2,100	LI // 1505	l



TABLE B-4.1

VALUES AND EQUATIONS USED FOR DAILY INTAKE CALCULATIONS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Medium: Soil
Exposure Medium: Soil

Exposure	Receptor	Receptor Age	Exposure Point	Parameter	Parameter Definition	Unit	RI	ME	C	TE	Intake Equation/
Route	Population	Receptor Age	Exposure i oint	Code	r arameter Definition	Offic	Value	Rationale/Reference	Value	Rationale/Reference	Model Name
Dermal	Resident	Adult and	Puerto Rico	CS	Chemical Concentration in Soil	mg/kg	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Daily Intake (mg/kg-day):
Contact		Child (0-6 yrs)		CF	Conversion Factor	kg/mg	1E-06		1E-06		for nonmutagen =
			Former Sugar Mill	SA_a	Skin Surface Area Available for Contact - adult	cm ²	5,700	EPA 2004	5,700	EPA 2004	CS x CF x {(SA _a xAF _a xED _a x1/BWa) +
				SA_c	Skin Surface Area Available for Contact - child	cm ²	2,800	EPA 2004	2,800	EPA 2004	(SA _c xAF _c xED _c x1/BW _c)} x ABS x
				AF_a	Adherence Factor - adult	mg/cm ²	0.07	EPA 2004	0.01	EPA 2004	EF x 1/AT
				AF_c	Adherence Factor - child	mg/cm ²	0.2	EPA 2004	0.04	EPA 2004	
				ABS	Absorption Factor	unitless	chemical specific	Table B-4.5	chemical specific	Table B-4.5	for mutagen =
				EF	Exposure Frequency	days/year	350	EPA 2004	350	EPA 2004	for RME: CS x {(2xSA _c xAF _c x10/BW _c)+
				ED_a	Exposure Duration - adult	years	24	EPA 2004	9	EPA 2004	(4xSA _c xAF _c x3/BW _c)+(10xSA _a xAF _a x3/BW _a)+
				ED_c	Exposure Duration - child	years	6	EPA 2004	6	EPA 2002	(14xSA _a xAF _a x1/BW _a)} x ABS x EF x CF / AT
				u	Body Weight - adult	kg	70	EPA 2004	70	EPA 2004	for CTE: CS x {(2xSA _c xAF _c x10/BW _c)+
					Body Weight - child	kg	15	EPA 2004	15	EPA 2004	(4xSA _c xAF _c x3/BW _c)+(9xSA _a xAF _a x3/BW _a)}
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	x ABS x EF x CF / AT
				AT-N _a	Averaging Time (Noncancer) - adult	days	8,760	EPA 1989	3,285	EPA 1989	
	0		D . D:	AT-N _c	Averaging Time (Noncancer) - child Chemical Concentration in Soil	days	2,190	EPA 1989	2,190	EPA 1989 aluated	5 11 1 1 1 1
	Construction Worker	Adult	Puerto Rico Beverage/	CF	Conversion Factor	mg/kg	1E-06	Tables B-3.2a or B-3.2b	NOI EV	alualeu	Daily Intake (mg/kg-day) = CS x CF x SA x AF x ABS x
	vvorker		Former Sugar Mill	SA	Skin Surface Area Available for Contact	kg/mg cm ²	3.300	EPA 2004			EF x ED x 1/BW x 1/AT
			Former Sugar Willi	AF	Adherence Factor		0.3	EPA 2004			EF X ED X 1/BW X 1/A1
				ABS		mg/cm ²					
				EF	Absorption Factor Exposure Frequency	unitless days/year	chemical specific 100	Table B-4.5			
				ED	Exposure Duration	years	1 1	(4)			
				BW	Body Weight	kg	70	EPA 2004			
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989			
				AT-N	Averaging Time (Noncancer)	days	365	EPA 1989			
Inhalation	Commercial/	Adult	Puerto Rico	CS	Chemical Concentration in Soil	mg/kg	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Exposure Concentration (mg/m³) =
	Industrial Worker		Beverage/	CA	Chemical Concentration in Air	mg/m ³	calculated	calculated	calculated	calculated	CA x ET x EF x ED x 1/AT
			Former Sugar Mill	ET	Exposure Time	hrs/day	8	EPA 2009	4	(2)	where:
			-	EF	Exposure Frequency	days/year	250	EPA 2002	219	EPA 2004	CA = CS/PEF
				ED	Exposure Duration	years	25	EPA 2002	9	EPA 2004	
				PEF	Particulate Emission Factor	m ³ /kg	1.36E+09	EPA 2002	1.36E+09	EPA 2002	
				AT-C	Averaging Time (Cancer)	hrs	613,200	EPA 1989	613,200	EPA 1989	
				AT-N	Averaging Time (Noncancer)	hrs	219,000	EPA 1989	78,840	EPA 1989	
	Trespasser	Adolescent	Puerto Rico	CS	Chemical Concentration in Soil	mg/kg	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Tables B-3.1a or B-3.1b	Exposure Concentration (mg/m³):
		(7-12 yrs)	Beverage/	CA	Chemical Concentration in Air	mg/m ³	calculated	calculated	calculated	calculated	for cancer =
			Former Sugar Mill	ET	Exposure Time	hrs/day	2	EPA 2009	1	EPA 2009	CA x ET x EF x ED x 1/AT
				EF	Exposure Frequency	days/year	100	EPA 2009	50	(1)	for noncancer =
				ED	Exposure Duration	years	6	EPA 1989	6	EPA 1989	CA
				PEF	Particulate Emission Factor	m³/kg	1.36E+09	EPA 2002	1.36E+09	EPA 2002	where:
				AT-C	Averaging Time (Cancer)	hrs	613,200	EPA 1989	613,200	EPA 1989	CA = CS/PEF
				AT-N	Averaging Time (Noncancer)	hrs	52,560	EPA 1989	52,560	EPA 1989	
	Resident	Adult and	Puerto Rico	CS	Chemical Concentration in Soil	mg/kg					Exposure Concentration (mg/m³) =
		Child (0-6 yrs)		CA	Chemical Concentration in Air	mg/m ³	calculated	calculated	calculated	calculated	for nonmutagen =
			Former Sugar Mill	ET _a	Exposure Time - adult	hrs/day	24	EPA 2009	24	EPA 2009	CA x ET x EF x ED x 1/AT
				ET _c	Exposure Time - child	hrs/day	24	EPA 2009	24	EPA 2009	for mutagen =
					Exposure Frequency	days/year	350	EPA 2002	350	EPA 2002	for RME: CS x {(2 x 10)+(4 x 3)+(10 x 3)+
				ED _a ED _c	Exposure Duration - adult	years	24 6	EPA 2002	9	EPA 1997	(14 x 1)} x ET x EF / AT
				Ü	Exposure Duration - child	years	-	EPA 2002	ŭ	EPA 2002	for CTE: CS x {(2 x 10)+(4 x 3)+(9 x 3)}
				PEF	Particulate Emission Factor	m³/kg	1.36E+09	EPA 2002	1.36E+09	EPA 2002	x ET x EF / AT
				AT-C AT-N _a	Averaging Time (Cancer)	hrs	613,200	EPA 1989	613,200	EPA 1989	where: CA = CS/PEF
				a	Averaging Time (Noncancer) - adult	hrs	210,240	EPA 1989	78,840	EPA 1989	CA = CS/PEF
				AT-N _c	Averaging Time (Noncancer) - child	hrs	52,560	EPA 1989	52,560	EPA 1989	



TABLE B-4.1

VALUES AND EQUATIONS USED FOR DAILY INTAKE CALCULATIONS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Medium: Soil
Exposure Medium: Soil

Exposure	Receptor	Pecentor Age	Exposure Point	Parameter	Parameter Definition	Unit	RME			CTE	Intake Equation/
Route	Population	Receptor Age	Exposure i oint	Code	i alameter Definition	Offic	Value	Rationale/Reference	Value	Rationale/Reference	Model Name
Inhalation	Construction	Adult	Puerto Rico	CS	Chemical Concentration in Soil	mg/kg	Tables B-3.2a or B-3.2b	Tables B-3.2a or B-3.2b	Not	Evaluated	Exposure Concentration (mg/m3) =
	Worker		Beverage/	CA	Chemical Concentration in Air	mg/m ³	calculated	calculated			CA x ET x EF x ED x 1/AT
			Former Sugar Mill	ET	Exposure Time	hrs/day	8	EPA 2009			where:
				EF	Exposure Frequency	days/year	100	(4)			CA = CS/PEF
				ED	Exposure Duration	years	1	(4)			
				PEF	Particulate Emission Factor	m ³ /kg	1.36E+09	EPA 2002			
				AT-C	Averaging Time (Cancer)	hrs	613,200	EPA 1989			
				AT-N	Averaging Time (Noncancer)	hrs	8,760	EPA 1989			

RME = Reasonable Maximum Exposure; CTE = Central Tendency Exposure

Notes:

⁽¹⁾ CTE ingestion rate is assumed to be one half the RME value.

(2) assumes one-half RME exposure frequency or exposure time

(3) based on the weighted average weight for children 7 to 12 years in age

(4) assumes 5 months (100 workdays) per year for one year

(5) based on the weighted average surface area for head, hands, forearms, lower legs, and feet for children ages 7 to 12 years

Sources:

EPA 1989. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part A. OERR. EPA/540/1-89/002.

EPA 1991. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Supplemental Guidance, Standard Default Exposure Factors. Interim Final. OSWER Directive 9285.6-03.

EPA 1997. Exposure Factors Handbook, Vols. I, II, and III. EPA/600/P-95/002Fa, 002Fb, and 002Fc.

EPA 2002. Supplemental Guidance for Developing Soil Screening Levels for Superfund Sites. OSWER 9355.4-24.

EPA 2004. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part E, Supplemental Guidance for Dermal Risk Assessment Final. EPA/540/R/99/005.

EPA 2009. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part F, Supplemental Guidance for Inhalation Risk Assessment. EPA-540-R-070-002.



TABLE B-4.2

VALUES USED FOR DAILY INTAKE CALCULATIONS FOR GROUNDWATER EXPOSURE PATHWAYS Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Current/Future Medium: Groundwater Exposure Medium: Groundwater

	_	_	_	_			RM	1E	CT	E	
Exposure Route	Receptor Population	Receptor	Exposure Point	Parameter Code	Parameter Definition	Unit		Rationale/	.,.	Rationale/	Intake Equation/ Model Name
Roule	Population	Age	Politi	Code			Value	Reference	Value	Reference	iviodei Name
Ingestion	Commercial/	Adult	Tap Water	CW	Chemical Concentration in Water	μg/L	Table B-3.3	Table B-3.3	Table B-3.3	Table B-3.3	Daily Intake (mg/kg-day) =
	Industrial Worker			CF1	Conversion Factor 1	mg/µg	0.001		0.001		CW x CF1 x IR-W x EF x ED x 1/BW x 1/AT
				IR-W	Ingestion Rate of Water	L/day	1	EPA 1991	1	EPA 1991	
				EF	Exposure Frequency	days/year	250	EPA 2002	219	EPA 2004	
				ED	Exposure Duration	years	25	EPA 2002	9	EPA 2004	
				BW	Body Weight	kg	70	EPA 1991	70	EPA 1991	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
				AT-N	Averaging Time (Noncancer)	days	9,125	EPA 1989	3,285	EPA 1989	
	Resident	Adult/Child	Tap Water	CW	Chemical Concentration in Water	μg/L	Table B-3.3	Table B-3.3	Table B-3.3	Table B-3.3	Daily Intake (mg/kg-day):
				CF1	Conversion Factor 1	mg/µg	0.001		0.001		for nonmutagen =
				IR-W _a	Ingestion Rate of Water, adult	L/day	2	EPA 1991	1.4	EPA 1997	CW x CF1 x {(IR-W _a x ED _a x 1/BW _a +
				IR-W _c	Ingestion Rate of Water, child	L/day	1	EPA 1997	0.4	EPA 1997	IR-W _c x ED _c x 1/BW _c)} x EF x 1/AT
				BW_a	Body Weight, adult	kg	70	EPA 2002	70	EPA 2002	for mutagen =
				BW _c	Body Weight, child	kg	15	EPA 2002	15	EPA 2002	for RME: CW x CF1 x {(2xIR-W _c x10/BW _c)+
				EDa	Exposure Duration, adult	years	24	EPA 2004	9	EPA 1997	(4xIR-W _c x3/BW _c)+(10xIR-W _a x3/BW _a)+
				ED _c	Exposure Duration, child	years	6	EPA 2004	6	EPA 1991	(14xIR-W _a x1/BW _a)} x EF x 1/AT
				EF	Exposure Frequency	days/year	350	EPA 2002	350	EPA 2002	for CTE: CW x CF1 x {(2xIR-W _c x10/BW _c)+
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	(4xIR-W _c x3/BW _c)+(9xIR-W _a x3/BW _a)) x EF x 1/AT
				AT-Na	Averaging Time (Noncancer) - adult	days	8,760	EPA 1989	3,285	EPA 1989	
			- w.	AT-N _c	Averaging Time (Noncancer) - child	days	2,190	EPA 1989	2,190	EPA 1989	
Dermal	Commercial/	Adult	Tap Water	CW	Chemical Concentration in Water	μg/L	Table B-3.3	Table B-3.3	Table B-3.3	Table B-3.3	Dermally Absorbed Dose (mg/kg-day) =
Contact	Industrial Worker		(Showering	CF1 SA	Conversion Factor 1	mg/µg	0.001	 EDA 2004	0.001 18.000	EPA 2004	SA x DA _{event} x EDx 1/BW x EF x 1/AT
			and Bathing)		Skin Surface Area Available for Contact	cm ²	18,000	EPA 2004	-,		
				DA _{event}	Absorbed dose	mg/cm ²	chemical specific	Table B-4.5	chemical specific	Table B-4.5	
				CF2	Conversion Factor 2	L/cm ³	0.001		0.001		
				ET	Exposure Time	hr/day	0.58	EPA 2004	0.25	EPA 2004	
				EF	Exposure Frequency	days/year	250	EPA 2002	219	EPA 2004	
				ED	Exposure Duration	years	25	EPA 2002	9	EPA 2004	
				BW	Body Weight	kg	70	EPA 2004	70	EPA 2004	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
	Resident	Adult/Child	Tap Water	AT-N CW	Averaging Time (Noncancer) Chemical Concentration in Water	days μg/L	9,125 Table B-3.3	EPA 1989 Table B-3.3	3,285 Table B-3.3	EPA 1989 Table B-3.3	Dermally Absorbed Dose (mg/kg-day) =
	Resident	Addit/Critic	(Showering	CF1	Conversion Factor 1	mg/µg	0.001		0.001		for nonmutagen =
			and Bathing)	SAa	Skin Surface Area Available for Contact - adult	cm ²	18,000	EPA 2004	18.000	EPA 2004	$\{(SA_axDA_{event-a}xED_ax1/BW_a)+$
			and Datining)	SA _c	Skin Surface Area Available for Contact - child	cm ²	6,600	EPA 2004	6.600	EPA 2004	(SA _c xDA _{event-c} xED _c x1/BW _c)} x EF x 1/AT
				DA _{event}	Absorbed dose	mg/cm ²	chemical specific	Table B-4.5	chemical specific	Table B-4.5	(Ontent event executive (O) X 21 X () X
				CF2	Conversion Factor 2	L/cm ³	0.001		0.001		for mutagen =
				ET _a	Exposure Time - adult	hr/day	0.58	EPA 2004	0.001	EPA 2004	for RME: {(2xSA _c xDA _{event-c} x10/BW _c)+
				ET _c	Exposure Time - addit Exposure Time - child	hr/day	0.56	EPA 2004 EPA 2004	0.23	EPA 2004 EPA 2004	(4xSA _c xDA _{event-c} x3/BW _c)+(10xSA _a xDA _{event-a} x3/BW _a)
				EF	Exposure Frequency	days/year	350	EPA 2004 EPA 2004	350	EPA 2004 EPA 2004	+(14xSA _a xDA _{event-a} x5/BW _a) +(14xSA _a xDA _{event-a} x1/BW _a)} x EF x 1/ AT
				ED _a	Exposure Duration - adult	vears	24	EPA 2004	9	EPA 2004	for CTE: {(2xSA _c xDA _{event-a} X10/BW _c)+
				ED _c	Exposure Duration - addit	years	6	EPA 2004	6	EPA 1991	(4xSA _c xDA _{event-c} x3/BW _c)+(9xSA _a xDA _{event-2} x3/BW _a)}
				BW _a	Body Weight	kg	70	EPA 2004	70	EPA 2004	x EF x 1/ AT
				BW _c	Body Weight - child	kg	15	EPA 2004	15	EPA 2004	X = X " /
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25.550	EPA 1989	
				AT-N _a	Averaging Time (Noncancer) - adult	days	8,760	EPA 1989	3,285	EPA 1989	
					Averaging Time (Noncancer) - child	days	2,190	EPA 1989	2,190	EPA 1989	



TABLE B-4.2

VALUES USED FOR DAILY INTAKE CALCULATIONS FOR GROUNDWATER EXPOSURE PATHWAYS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Medium: Groundwater
Exposure Medium: Groundwater

F.,,,	Desertes	Receptor		Davamatas			RN	ИΕ	С	TE	Intake Equation/
Exposure Route	Receptor Population	Age	Exposure Point	Parameter Code	Parameter Definition	Unit	Value	Rationale/ Reference	Value	Rationale/ Reference	Model Name
Inhalation	Commercial/	Adult	Tap Water	CW	Chemical concentration in groundwater	μg/L	Table B-3.3	Table B-3.3	Table B-3.3	Table B-3.3	Exposure Concentration (mg/m³) =
	Industrial Worker		(Showering	CA	Chemical concentration in air	μg/m ³	Table D-3	Table D-3	Table D-3	Table D-3	CA x CF x ET x ED x EF x 1/AT
			and Bathing)	CF	Conversion factor	mg/µg	0.001	-	0.001	-	
				ET	Exposure time	hr/day	0.58	EPA 2004	0.25	EPA 2004	
				EF	Exposure frequency	days/yr	250	EPA 2002	219	EPA 2004	
				ED	Exposure Duration	years	25	EPA 2002	9	EPA 2004	
				AT-C	Averaging time (Cancer)	hrs	613,200	EPA 2009	613,200	EPA 2009	
				AT-N	Averaging time (Noncancer)	hrs	219,000	EPA 2009	78,840	EPA 2009	
	Resident	Adult/Child	Tap Water	CW	Chemical concentration in groundwater	μg/L	Table B-3.3	Table B-3.3	Table B-3.3	Table B-3.3	Exposure Concentration (mg/m³) =
			(Showering	CA	Chemical concentration in air	μg/m ³	Tables D-3 or D-4	Tables D-3 or D-4	Tables D-3 or D-4	Tables D-3 or D-4	CA x CF x {(ET _a x ED _a)+(ET _c x ED _c)} x EF x 1/AT
			and Bathing)	CF	Conversion factor	mg/µg	0.001	-	0.001	-	
				ETa	Exposure time - adult	hr/day	0.58	EPA 2004	0.25	EPA 2004	EC (mg/m ³) for mutagen =
				ET _c	Exposure time - child	hr/day	1	EPA 2004	0.33	EPA 2004	for RME: CF x {(CA _c x2x10xET _c)+(CA _c x4x3xET _c)+
				EF	Exposure frequency	days/yr	350	EPA 2004	350	EPA 2004	(CA _a x10x3xET _a)+(CA _a x14x1xET _a)} x EF / AT
				ED_a	Exposure Duration, adult	years	24	EPA 2004	9	EPA 1997	
				EDc	Exposure duration, child	years	6	EPA 2004	6	EPA 1991	for CTE: CF x {(CA _c x2x10xET _c)+(CA _c x4x3xET _c)+
				AT-C	Averaging time (Cancer)	hrs	613,200	EPA 2009	613,200	EPA 2009	(CA _a x9x3xET _a)} x EF / AT
				AT-N _a	Averaging time (Noncancer) - adult	hrs	210,240	EPA 2009	78,840	EPA 2009	
				AT-N _c	Averaging time (Noncancer) - child	hrs	52,560	EPA 2009	52,560	EPA 2009	

RME = Reasonable Maximum Exposure; CTE = Central Tendency Exposure

Sources

EPA 1989. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part A. OERR. EPA/540/1-89/002

EPA 1991. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Supplemental Guidance, Standard Default Exposure Factors. Interim Final. OSWER Directive 9285.6-03

EPA 1997. Exposure Factors Handbook, Vols. I, II, and III. EPA/600/P-95/002Fa, 002Fb, and 002Fc.

EPA 2002. Supplemental Guidance for Developing Soil Screening Levels for Superfund Sites. OSWER 9355.4-24

EPA 2004. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part E, Supplemental Guidance for Dermal Risk Assessment Final. EPA/540/R/99/005

EPA 2009. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part F, Supplemental Guidance for Inhalation Risk Assessment. EPA-540-R-070-002



Page 2 of 2 6/28/2012

TABLE B-4.3 VALUES AND EQUATIONS USED FOR DAILY INTAKE CALCULATIONS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Medium: Surface Water
Exposure Medium: Surface Water

-	December	Danantas	Fymany	Dozomotor			RN.	ИΕ	СТ	E	
Exposure Route	Receptor Population	Receptor Age	Exposure Point	Parameter Code	Parameter Definition	Unit	Value	Rationale/	Value	Rationale/	Chronic Daily Intake (CDI)
Route	Fopulation	Age	FOIII	Code			value	Reference	value	Reference	
Ingestion	Recreational	Adolescent	Maunabo	CW	Chemical Concentration in Water	μg/L	Table B-3.4	Table B-3.4	Table B-3.4	Table B-3.4	Daily Intake (mg/kg-day) =
	User	(7-12 yrs)	River	CF1	Conversion Factor 1	mg/µg	0.001		0.001		CW x CF1 x IR-W x EF x ED x 1/BW x 1/AT
				IR-W	Ingestion Rate of Water	L/day	0.05	EPA 1989	0.05	EPA 1989	
				EF	Exposure Frequency	days/year	175	EPA 2012	100	EPA 2012	
				ED	Exposure Duration	years	6	EPA 1989	6	EPA 1989	
				BW	Body Weight	kg	36	EPA 1997 ⁽¹⁾	36	EPA 1997 ⁽¹⁾	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
				AT-N	Averaging Time (Noncancer)	days	2,190	EPA 1989	2,190	EPA 1989	
	Resident	Adult/Child	Tap Water	CW	Chemical Concentration in Water	μg/L	Table B-3.4	Table B-3.4	Table B-3.4	Table B-3.4	Daily Intake (mg/kg-day):
				CF1	Conversion Factor 1	mg/µg	0.001		0.001		CW x CF1 x {(IR-W _a x ED _a x 1/BW _a +
				IR-W _a	Ingestion Rate of Water, adult	L/day	2	EPA 1991	1.4	EPA 1997	IR-W _c x ED _c x 1/BW _c)} x EF x 1/AT
				IR-W _c	Ingestion Rate of Water, child	L/day	1	EPA 1997	0.4	EPA 1997	
				BW_a	Body Weight, adult	kg	70	EPA 2002	70	EPA 2002	
				BW_c	Body Weight, child	kg	15	EPA 2002	15	EPA 2002	
				EDa	Exposure Duration, adult	years	24	EPA 2004	9	EPA 1997	
				ED _c	Exposure Duration, child	years	6	EPA 2004	6	EPA 1991	
				EF	Exposure Frequency	days/year	350	EPA 2002	350	EPA 2002	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
				AT-N _a	Averaging Time (Noncancer) - adult	days	8,760	EPA 1989	3,285	EPA 1989	
				AT-N _c	Averaging Time (Noncancer) - child	days	2,190	EPA 1989	2,190	EPA 1989	
Dermal	Recreational	Adolescent	Maunabo	CW	Chemical Concentration in Water	μg/L	Table B-3.4	Table B-3.4	Table B-3.4	Table B-3.4	Dermally Absorbed Dose (mg/kg-day) =
Contact	User	(7-12 yrs)	River	CF1	Conversion Factor 1	mg/µg	0.001		0.001		SA x DA _{event} x EF x ED x 1/BW x 1/AT
				SA	Skin Surface Area Available for Contact	cm ²	11,000	EPA 2004	11,000	EPA 2004	
				DA _{event}	Absorbed dose	mg/cm ²	chemical specific	Table B-4.5	chemical specific	Table B-4.5	
				CF2	Conversion Factor 2	L/cm ³	0.001		0.001		
				ET	Exposure Time	hrs/day	1	(2)	1	(2)	
				EF	Exposure Frequency	days/year	175	EPA 2012	100	EPA 2012	
				ED	Exposure Duration	years	6	EPA 1989	6	EPA 1989	
				BW	Body Weight	kg	36	EPA 1997 ⁽¹⁾	36	EPA 1997 ⁽¹⁾	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
				AT-N	Averaging Time (Noncancer)	days	2,190	EPA 1989	2,190	EPA 1989	
	Resident	Adult/Child	Tap Water	CW	Chemical Concentration in Water	μg/L	Table B-3.4	Table B-3.4	Table B-3.4	Table B-3.4	Dermally Absorbed Dose (mg/kg-day) =
			(Showering	CF1	Conversion Factor 1	mg/µg	0.001		0.001		{(SA _a xDA _{event-a} xED _a x1/BW _a)+
			and Bathing)	SA _a	Skin Surface Area Available for Contact - adult	cm ²	18,000	EPA 2004	18,000	EPA 2004	(SA _c xDA _{event-c} xED _c x1/BW _c)} x EF x 1/AT
				SA _c	Skin Surface Area Available for Contact - child	cm ²	6,600	EPA 2004	6,600	EPA 2004	
				DA _{event}	Absorbed dose	mg/cm ²	chemical specific	Table B-4.5	chemical specific	Table B-4.5	
				CF2	Conversion Factor 2	L/cm ³	0.001		0.001		
				ETa	Exposure Time - adult	hr/day	0.58	EPA 2004	0.25	EPA 2004	
				ET _c	Exposure Time - child	hr/day	1	EPA 2004	0.33	EPA 2004	
				EF	Exposure Frequency	days/year	350	EPA 2004	350	EPA 2004	
				EDa	Exposure Duration - adult	years	24	EPA 2004	9	EPA 2004	
				ED _c	Exposure Duration - child	years	6	EPA 2004	6	EPA 1991	
				BW _a	Body Weight	kg	70	EPA 2004	70	EPA 2004	
				BW _c	Body Weight - child	kg	15	EPA 2004	15	EPA 2004	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
				AT-N _a	Averaging Time (Noncancer) - adult	days	8,760	EPA 1989	3,285	EPA 1989	
Ш				AT-N _c	Averaging Time (Noncancer) - child	days	2,190	EPA 1989	2,190	EPA 1989	



TABLE B-4.3 VALUES AND EQUATIONS USED FOR DAILY INTAKE CALCULATIONS

Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Medium: Surface Water
Exposure Medium: Surface Water

Exposure	Receptor	Receptor	Evnouro	Parameter			RN	ИE	C-	ГЕ	
Route	Population	Age	Exposure Point	Code	Parameter Definition	Unit	Value	Rationale/ Reference	Value	Rationale/ Reference	Chronic Daily Intake (CDI)
Inhalation	Resident	Adult/Child	Tap Water	CW	Chemical concentration in groundwater	μg/L	Table B-3.4	Table B-3.4	Table B-3.4	Table B-3.4	Exposure Concentration (mg/m³) =
			(Showering	CA	Chemical concentration in air	μg/m³	Tables D-5 or D-6	Tables D-5 or D-6	Tables D-5 or D-6	Tables D-5 or D-6	$CA \times CF \times \{(ET_a \times ED_a) + (ET_c \times ED_c)\} \times$
			and Bathing)	CF	Conversion factor	mg/µg	0.001	-	0.001	-	EF x 1/AT
				ETa	Exposure time - adult	hr/day	0.58	EPA 2004	0.25	EPA 2004	
				ET _c	Exposure time - child	hr/day	1	EPA 2004	0.33	EPA 2004	
				EF	Exposure frequency	days/yr	350	EPA 2004	350	EPA 2004	
				ED_a	Exposure Duration, adult	years	24	EPA 2004	9	EPA 1997	
				ED_c	Exposure duration, child	years	6	EPA 2004	6	EPA 1991	
				AT-C	Averaging time (Cancer)	hrs	613,200	EPA 2009	613,200	EPA 2009	
				AT-N _a	Averaging time (Noncancer) - adult	hrs	210,240	EPA 2009	78,840	EPA 2009	
				AT-N _c	Averaging time (Noncancer) - child	hrs	52,560	EPA 2009	52,560	EPA 2009	

RME = Reasonable Maximum Exposure; CTE = Central Tendency Exposure

Notes:

Sources:

EPA 1989. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part A. OERR. EPA/540/1-89/002

EPA 1991. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Supplemental Guidance, Standard Default Exposure Factors. Interim Final. OSWER Directive 9285.6-03

EPA 1997. Exposure Factors Handbook, Vols. I, II, and III. EPA/600/P-95/002Fa, 002Fb, and 002Fc.

EPA 2004. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part E, Supplemental Guidance for Dermal Risk Assessment Final. EPA/540/R/99/005

EPA 2009. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part F, Supplemental Guidance for Inhalation Risk Assessment. EPA-540-R-070-002

EPA 2012. Conference call with Julie McPherson of EPA on February 27.



⁽¹⁾ based on the weighted average weight for children 7 to 12 years in age

⁽¹⁾ assume children spend 1 hour per day swimming

TABLE B-4.4

VALUES AND EQUATIONS USED FOR DAILY INTAKE CALCULATIONS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Medium: Sediment
Exposure Medium: Sediment

	December			Davamatav			RI	ME	C.	ГЕ	
Exposure Route	Receptor Population	Receptor Age	Exposure Point	Parameter Code	Parameter Definition	Unit	Value	Rationale/ Reference	Value	Rationale/ Reference	Chronic Daily Intake (CDI)
Ingestion	Recreational	Adolescent	Maunabo	CS	Chemical Concentration in Sediment	mg/kg	Table B-3.5	Table B-3.5	Table B-3.5	Table B-3.5	Daily Intake (mg/kg-day) =
	User	(7-12 yrs)	River	CF	Conversion Factor 1	kg/mg	1E-06		1E-06		CS x CF x IR-S x EF x ED x
				IR-S	Ingestion Rate of Sediment	mg/day	100	EPA 2002 ⁽¹⁾	50	EPA 2002 ⁽¹⁾	1/BW x 1/AT
				EF	Exposure Frequency	days/year	175	EPA 2012	100	EPA 2012	
				ED	Exposure Duration	years	6	EPA 1989	6	EPA 1989	
				BW	Body Weight	kg	36	EPA 1997 ⁽²⁾	36	EPA 1997 ⁽²⁾	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
				AT-N	Averaging Time (Noncancer)	days	2,190	EPA 1989	2,190	EPA 1989	
Dermal	Recreational	Adolescent	Maunabo	CS	Chemical Concentration in Sediment	mg/kg	Table B-3.5	Table B-3.5	Table B-3.5	Table B-3.5	Daily Intake (mg/kg-day) =
Contact	User	(7-12 yrs)	River	CF	Conversion Factor 1	kg/mg	1E-06		1E-06		CS x CF x SA x AF x ABS x
				SA	Skin Surface Area Available for Contact	cm ²	4,400	EPA 2004 ⁽³⁾	4,400	EPA 2004 ⁽³⁾	EF x ED x 1/BW x 1/AT
				AF	Adherence Factor	mg/cm ²	0.2	EPA 2004 ⁽⁴⁾	0.2	EPA 2004 ⁽⁴⁾	
				ABS	Absorption Factor	unitless	chemical specific	Table B-4.5	chemical specific	Table B-4.5	
				EF	Exposure Frequency	days/year	175	EPA 2012	100	EPA 2012	
				ED	Exposure Duration	years	6	EPA 1989	6	EPA 1989	
				BW	Body Weight	kg	36	EPA 1997 ⁽²⁾	36	EPA 1997 ⁽²⁾	
				AT-C	Averaging Time (Cancer)	days	25,550	EPA 1989	25,550	EPA 1989	
				AT-N	Averaging Time (Noncancer)	days	2,190	EPA 1989	2,190	EPA 1989	

RME = Reasonable Maximum Exposure; CTE = Central Tendency Exposure

Notes:

Sources:

EPA 1989. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part A. OERR. EPA/540/1-89/002

EPA 1997. Exposure Factors Handbook, Vols. I, II, and III. EPA/600/P-95/002Fa, 002Fb, and 002Fc.

EPA 2004. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part E, Supplemental Guidance for Dermal Risk Assessment Final. EPA/540/R/99/005

EPA 2009. Risk Assessment Guidance for Superfund. Vol. 1: Human Health Evaluation Manual, Part F, Supplemental Guidance for Inhalation Risk Assessment. EPA-540-R-070-002

EPA 2012. Conference call with Julie McPherson of EPA on February 27.



⁽¹⁾ based on the soil ingestion rate for children. CTE is assumed to be one half the RME value.

 $^{^{\}left(2\right)}$ based on the weighted average weight for children 7 to 12 years in age

⁽³⁾ based on the weighted average surface area for head, hands, forearms, lower legs, and feet for children ages 6 to <21 years

⁽⁴⁾ based on adherence factor for children playing in wet soil

TABLE B-4.5 CHEMICAL-SPECIFIC INFORMATION USED FOR DAILY INTAKE CALCULATIONS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

	D		Fraction		T			DA _{event} (2)					
	Dermal Absorption	Permeability	absorbed	Lag time per	Time to reach steady	B ⁽¹⁾	Commercial/	Recreational		Henry's Law	Diffusivity	Diffusivity in	Fraction
Chemical	Fraction (1)	Coefficient (1)	water ⁽¹⁾	event ⁽¹⁾	state ⁽¹⁾	B. ,	Industrial	User	Resident	Constant (3)	in Air ⁽³⁾	Water ⁽³⁾	Volatilized ⁽⁴⁾
	Fraction		water		State		Worker	(7-12 yrs)					
	(Unitless)	(cm/hr)	Unitless	(hr/event)	(hr)	(Unitless)	(mg/cm ²)	(mg/cm ²)	(mg/cm ²)	(atm-m3/mole)	(cm ² /s)	(cm ² /s)	Unitless
Volatile Organic Compour	nds												
Bromodichloromethane	NA	4.6E-03	1.0E+00	8.8E-01	2.1E+00	0.0E+00	NA	1.2E-08	NA	2.1E-03	5.6E-02	1.1E-05	5.4E-01
cis-1,2-Dichloroethene	NA	NA	NA	NA	NA	NA	NA	NA	NA	4.1E-03	8.8E-02	1.1E-05	5.6E-01
Dibromochloromethane	NA	3.2E-03	1.0E+00	1.6E+00	3.8E+00	0.0E+00	NA	1.4E-08	NA	7.8E-04	3.7E-02	1.1E-05	5.4E-01
Tetrachloroethene	NA	3.3E-02	1.0E+00	9.1E-01	2.2E+00	2.0E-01	6.6E-08	NA	7.0E-08	1.8E-02	5.0E-02	9.5E-06	5.0E-01
trans-1,2-Dichloroethene	NA	7.7E-03	1.0E+00	3.7E-01	8.9E-01	0.0E+00	2.3E-08	NA	2.4E-08	4.1E-03	8.8E-02	1.1E-05	5.6E-01
Trichloroethene	NA	1.2E-02	1.0E+00	5.8E-01	1.4E+00	1.0E-01	1.1E-08	NA	1.2E-08	9.9E-03	6.9E-02	1.0E-05	5.3E-01
Vinyl Chloride	NA	5.6E-03	1.0E+00	2.4E-01	5.7E-01	0.0E+00	4.3E-09	NA	4.7E-09	2.8E-02	1.1E-01	1.2E-05	5.9E-01
Semi-volatile Organic Con	npounds												
Benzo(a)pyrene	1.3E-01	7.0E-01	1.0E+00	2.7E+00	1.2E+01	4.3E+00	NA	NA	NA	4.6E-07	4.8E-02	5.6E-06	NA
Dibenzo(a,h)anthracene	1.3E-01	1.5E+00	6.0E-01	3.9E+00	1.8E+01	9.7E+00	NA	NA	NA	1.4E-07	4.5E-02	5.2E-06	NA
Inorganics													
Aluminum	NA	1.0E-03	NA	NA	NA	NA	1.2E-06	NA	1.4E-06	NA	NA	NA	NA
Arsenic	3.0E-02	1.0E-03	NA	NA	NA	NA	2.2E-09	NA	2.5E-09	NA	NA	NA	NA
Barium	NA	1.0E-03	NA	NA	NA	NA	1.2E-07	NA	1.4E-07	NA	NA	NA	NA
Chromium	NA	1.0E-03	NA	NA	NA	NA	4.8E-09	NA	5.5E-09	NA	NA	NA	NA
Cobalt	NA	4.0E-04	NA	NA	NA	NA	2.5E-10	NA	2.9E-10	NA	NA	NA	NA
Copper	NA	1.0E-03	NA	NA	NA	NA	3.0E-08	NA	3.5E-08	NA	NA	NA	NA
Iron	NA	1.0E-03	NA	NA	NA	NA	4.8E-06	NA	5.4E-06	NA	NA	NA	NA
Lead	NA	1.0E-04	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Manganese	NA	1.0E-03	NA	NA	NA	NA	2.4E-07	NA	2.7E-07	NA	NA	NA	NA
Thallium	NA	1.0E-03	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Vanadium	NA	1.0E-03	NA	NA	NA	NA	9.8E-09	NA	1.1E-08	NA	NA	NA	NA

NA - Not applicable

Notes:

 $^{(2)}$ Absorbed dose per event is calculated using Equations 3.2, 3.3, and 3.4 from EPA 2004) (p.3-4)

$$If \ t_{event} \leq t^*, DA_{event} = 2FA \times K_p \times C_W \sqrt{\frac{6\tau_{event} \times t_{event}}{\pi}} \\ If \ t_{event} > t^*, DA_{event} = FA \times K_p \times C_W \left[\frac{t_{event}}{1+B} + 2\tau_{event} \left(\frac{1+3B+3B^2}{(1+B)^2}\right)\right]$$

for inorganics:

$$DA_{event} = K_p \times C_W \times t_{event}$$

Where:

DA_{event} = absorbed dose per event, mg/cm²

FA = fraction absorbed water

K_p = permeability coefficient, cm/hr

CW = chemical concentration in water, µg/L (Tables B-3.3 and B-3.4)

Tevent = lag time per event, hr

t_{event} = event duration, hr

t* = time to reach steady-state, hr

B = dimensionless ratio of the permeability coefficient of a compound through the stratum corneum relative to its permeability coefficient across the viable epidermis

⁽³⁾ Source: EPA 2011. Regional Screening Levels for Chemical Contaminanats at Superfund Sites. June.

(4) Estimated for volatile chemicals using Equation 5 from Schaum et al (1994) (p. 308), with radon as the reference chemical (j): $f_i = f_j \times \frac{\left(2.5/D_W^{0.67} + RT/D_a^{0.67}H\right)_j}{\left(2.5/D_W^{0.67} + RT/D_a^{0.67}H\right)_i}$

$$f_i = f_j \times \frac{(2.5/D_W^{0.67} + RT/D_a^{0.67}H)_j}{(2.5/D_W^{0.67} + RT/D_a^{0.67}H)}$$

Where:

f_i = volatilization fraction for chemical i

f_i = volatilization fraction for chemical j = Radon

R = gas constant, atm-m³/mol-K = 8.21 x 10⁻⁵ H = Henry's law constant, atm-m3/mol T = temperature, K = 293

D_a = diffusion coefficient in air, m²/s D_w = diffusion coefficient in water, m²/s

 D_a for Radon = 2.0 x 10⁻⁵

 D_{w} for Radon = 1.4 x 10⁻⁹



6/28/2012 Page 1 of 1

⁽¹⁾ Source: EPA 2004. Risk Assessment Guidance for Superfund. Part E.

TABLE B-5.1 NONCANCER TOXICITY DATA - ORAL/DERMAL

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chemical of Potential	Chronic/	Ora	al RfD	Oral Absorption	(:	D for Dermal	Primary Target Organ	Combined Uncertainty/	Source	Date ⁽³⁾
Concern	Subchronic	Value	Unit	Efficiency for Dermal ⁽¹⁾	Value	Unit	Tilliary Target Organ	Modifying Factor	Source	Date
Volatile Organic Compou	nds									
Bromodichloromethane	Chronic	2.0E-02	mg/kg-day	1	2.0E-02	mg/kg-day	Liver	1,000	IRIS	12/2/2011
cis-1,2-Dichloroethene	Chronic	2.0E-03	mg/kg-day	1	2.0E-03	mg/kg-day	Kidney	3,000	IRIS	12/2/2011
Dibromochloromethane	Chronic	2.0E-02	mg/kg-day	1	2.0E-02	mg/kg-day	Liver	1,000	IRIS	12/2/2011
Tetrachloroethene	Chronic	6.0E-03	mg/kg-day	1	6.0E-03	mg/kg-day	Liver	1,000	IRIS	3/20/2012
trans-1,2-Dichloroethene	Chronic	2.0E-02	mg/kg-day	1	2.0E-02	mg/kg-day	Blood	3,000	IRIS	12/2/2011
Trichloroethene	Chronic	5.0E-04	mg/kg-day	1	5.0E-04	mg/kg-day	Heart/ Immunogical/ Developmental/Kidney	10 to 1,000	IRIS	12/2/2011
Vinyl Chloride	Chronic	3.0E-03	mg/kg-day	1	3.0E-03	mg/kg-day	Liver	30	IRIS	12/2/2011
Semi-volatile Organic Cor	npounds									
Benzo(a)pyrene	Chronic	NA	NA	1	NA	NA	NA	NA	NA	NA
Dibenzo(a,h)anthracene	Chronic	NA	NA	1	NA	NA	NA	NA	NA	NA
Inorganics										
Aluminum	Chronic	1.0E+00	mg/kg-day	1	1.0E+00	mg/kg-day	Neurological	100	PPRTV	10/23/2006
Arsenic	Chronic	3.0E-04	mg/kg-day	1	3.0E-04	mg/kg-day	Skin	3	IRIS	12/2/2011
Barium	Chronic	2.0E-01	mg/kg-day	0.07	1.4E-02	mg/kg-day	Kidney	300	IRIS	12/2/2011
Chromium ⁽⁴⁾	Chronic	3.0E-03	mg/kg-day	0.025	7.5E-05	mg/kg-day	None reported	300	IRIS	12/2/2011
Cobalt	Chronic	3.0E-04	mg/kg-day	1	3.0E-04	mg/kg-day	Thyroid	3,000	PPRTV	8/25/2008
Copper	Chronic	4.0E-02	mg/kg-day	1	4.0E-02	mg/kg-day	GI Tract	NA	HEAST	7/1/1997
Iron	Chronic	7.0E-01	mg/kg-day	1	7.0E-01	mg/kg-day	GI Tract	1.5	PPRTV	9/11/2006
Manganese	Chronic	1.4E-01	mg/kg-day	0.04	5.6E-03	mg/kg-day	CNS	1	IRIS	12/2/2011
Thallium	Chronic	1.0E-05	mg/kg-day	1	1.0E-05	mg/kg-day	Skin/Hair	3,000	PPRTV-S	10/8/2010
Vanadium	Chronic	7.0E-05	mg/kg-day	0.026	1.8E-06	mg/kg-day	Kidney	3,000	PPRTV	9/30/2009

⁽¹⁾ Oral Absorption Efficiency for Dermal from Risk Assessment Guidance for Superfund Part E, Supplemental Guidance for Dermal Risk Assessment

Definition:

ATSDR = Agency for Toxic Substances and Disease Registry

CNS = central nervous system

GI = gastrointestinal

HEAST = Health Effect Assessment Summary Tables

IRIS = Integrated Risk Information System

mg/kg-day = milligram per kilogram per day

NA = not available

PPRTV = Provisional Peer Reviewed Toxicity Value

PPRTV-S = Screening Provisional Peer Reviewed Toxicity Value

RfD = reference dose



⁽²⁾ Adjusted RfD for Dermal = Oral RfD x Oral Absorption Efficiency for Dermal.

⁽³⁾ Date shown for IRIS is the date IRIS was searched. http://www.epa.gov/iris/ Date shown for other sources is the publication date.

⁽⁴⁾ based on chromium (VI)

TABLE B-5.2a NONCANCER TOXICITY DATA - INHALATION (CHRONIC)

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chemical of Potential	Inhalatio	on RfC	Primary Target Organ	Combined Uncertainty/		fC t Organ
Concern	Value	Unit	Timary Parget Organ	Modifying Factor	Source (1)	Date (2)
Volatile Organic Compound	S					
Bromodichloromethane	NA	NA	NA	NA	NA	NA
cis-1,2-Dichloroethene	NA	NA	NA	NA	NA	NA
Dibromochloromethane	NA	NA	NA	NA	NA	NA
Tetrachloroethene	4.0E-02	mg/m ³	Liver	1,000	IRIS	3/20/2012
trans-1,2-Dichloroethene	6.0E-02	mg/m ³	Lung/Liver	3,000	PPRTV	3/1/2006
Trichloroethene	2.0E-03	mg/m ³	Heart/Immunological	10 to 100	IRIS	12/2/2011
Vinyl Chloride	1.0E-01	mg/m ³	Liver	30	IRIS	12/2/2011
Semi-volatile Organic Comp	ounds	3				
Benzo(a)pyrene	NA	NA	NA	NA	NA	NA
Dibenzo(a,h)anthracene	NA	NA	NA	NA	NA	NA
Inorganics						
Aluminum	5.0E-03	mg/m ³	Neurological	300	PPRTV	10/23/2006
Arsenic	1.5E-05	mg/m ³	Developmental/Cardiovascular System/CNS/Lung/Skin	30	Cal/EPA	12/18/2008
Barium	5.0E-04	mg/m ³	Fetus	1,000	HEAST	7/1/1997
Chromium ⁽³⁾	1.0E-04	mg/m ³	Lung	300	IRIS	12/2/2011
Cobalt	6.0E-06	mg/m ³	Respiratory System/Lung	300	PPRTV	8/25/2008
Copper	NA	ŇA	NA	NA	NA	NA
Iron	NA	NA	NA	NA	NA	NA
Manganese	5.0E-05	mg/m ³	CNS	1,000	IRIS	12/2/2011
Thallium	NA	ŇA	NA	NA	NA	NA
Vanadium	1.0E-04	mg/m ³	Respiratory System	30	ATSDR	5/3/2011

⁽¹⁾ ATSDR chronic inhalation minimal risk level (MRL)

MRL is converted from units in ppmv to mg/m^3 using the following equation:

MRL $(mg/m^3) = (ppmv)(1 kg/1000 g)(P/RT)(molecular weight)$

where:

P = ambient air pressure, 1 atmosphere (atm)

R = ideal gas constant, 8.2×10^{-5} atm-m³/mol-⁰K

T = absolute temperature, 298.15 Kelvin (⁰K)

Definition:

ATSDR = Agency for Toxic Substances and Disease Registry

Cal/EPA = California Environmental Protection Agency

CNS = central nervous system

HEAST = Health Effects Assessment Summary Tables

IRIS = Integrated Risk Information System

mg/m³ = milligram per cubic meter

NA = not available

ppmv = part per million by volume

PPRTV = Provisional Peer Reviewed Toxicity Value

RfC = reference concentration



⁽²⁾ Date shown for IRIS is the date IRIS was searched. http://www.epa.gov/iris/ Date shown for other sources is the publication date.

⁽³⁾ based on chromium (VI) particulates

TABLE B-5.2b NONCANCER TOXICITY DATA - INHALATION (ACUTE)

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chemical of Potential	Inhalatio	on RfC	Primary Target Organ	Combined Uncertainty/		RfC et Organ
Concern	Value	Unit	Timaly ranger engan	Modifying Factor	Source (1)	Date (2)
Volatile Organic Compou	nds					
Bromodichloromethane	NA	NA	NA	NA	NA	NA
cis-1,2-Dichloroethene	NA	NA	NA	NA	NA	NA
Dibromochloromethane	NA	NA	NA	NA	NA	NA
Tetrachloroethene	2.0E+01	mg/m ³	CNS/Eye/Respiratory System	60	Cal/EPA	12/18/2008
trans-1,2-Dichloroethene	7.9E-01	mg/m ³	Liver	1,000	ATSDR	5/3/2011
Trichloroethene	1.1E+01	mg/m ³	CNS	30	ATSDR	5/3/2011
Vinyl Chloride	1.8E+02	mg/m ³	CNS/Eye/Respiratory System	10	Cal/EPA	12/18/2008
Semi-volatile Organic Cor	npounds	g,	, , ,			
Benzo(a)pyrene	NA	NA	NA	NA	NA	NA
Dibenzo(a,h)anthracene	NA	NA	NA	NA	NA	NA
Inorganics						
Aluminum	NA	NA	NA	NA	NA	NA
Arsenic	2.0E-04	mg/m ³	Developmental/Cardiovascular System/CNS	1,000	Cal/EPA	12/18/2008
Barium	NA	NA	NA	NA	NA	NA
Chromium	NA	NA	NA	NA	NA	NA
Cobalt	NA	NA	NA	NA	NA	NA
Copper	1.0E-01	mg/m ³	Respiratory System	10	Cal/EPA	12/18/2008
Iron	NA	ΝA	NA	NA	NA	NA
Lead	NA	NA	NA	NA	NA	NA
Manganese	1.7E-04	mg/m ³	CNS	300	Cal/EPA	12/18/2008
Thallium	NA	NA	NA	NA	NA	NA
Vanadium ⁽³⁾	3.0E-02	mg/m ³	Respiratory System/Eyes	10	Cal/EPA	12/18/2008

⁽¹⁾ ATSDR chronic inhalation minimal risk level (MRL)

MRL is converted from units in ppmv to mg/m³ using the following equation:

MRL $(mg/m^3) = (ppmv)(1 kg/1000 g)(P/RT)(molecular weight)$ where:

P = ambient air pressure, 1 atmosphere (atm)

R = ideal gas constant, 8.2×10⁻⁵ atm-m³/mol-⁰K

T = absolute temperature, 298.15 Kelvin (⁰K)

Definition:

ATSDR = Agency for Toxic Substances and Disease Registry

Cal/EPA = California Environmental Protection Agency

CNS = central nervous system

mg/m³ = milligram per cubic meter

NA = not available

ppmv = part per million by volume

RfC = reference concentration



⁽²⁾ Date shown is the publication date.

⁽³⁾ based on vanadium pentoxide

TABLE B-6.1

CANCER TOXICITY DATA - ORAL/DERMAL

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Chemical of Potential	Oral Slo	ppe Factor	Oral Absorption		lope Factor for mal (2)	Mutagen	Weight of Evidence/	Source	Date (4)
Concern	Value	Unit	Efficiency for Dermal (1)	Value	Unit	(3)	Cancer Guideline Description	Course	Date
Volatile Organic Compour	ıds								
Bromodichloromethane	6.2E-02	(mg/kg-day) ⁻¹	1	6.2E-02	(mg/kg-day) ⁻¹		B2	IRIS	12/2/2011
cis-1,2-Dichloroethene	NA	NA NA	1	NA	NA NA		inadequate information to assess the carcinogenic potential	IRIS	12/2/2011
Dibromochloromethane	8.4E-02	(mg/kg-day) ⁻¹	1	8.4E-02	(mg/kg-day) ⁻¹		С	IRIS	12/2/2011
Tetrachloroethene	2.1E-03	(mg/kg-day) ⁻¹	1	2.1E-03	(mg/kg-day) ⁻¹		Likely to be carcinogenic to humans	IRIS	3/20/2012
trans-1,2-Dichloroethene	NA	NA ,	1	NA	NA ,		inadequate information to assess the carcinogenic potential	IRIS	12/2/2011
Trichloroethene	4.6E-02	(mg/kg-day) ⁻¹	1	4.6E-02	(mg/kg-day) ⁻¹	M	carcinogenic to humans	IRIS	12/2/2011
Vinyl Chloride	7.2E-01	(mg/kg-day) ⁻¹	1	7.2E-01	(mg/kg-day) ⁻¹	M	A	IRIS	12/2/2011
Semi-volatile Organic Con	npounds	(3 3 · · ·) /			(3 3 - 3)				
Benzo(a)pyrene	7.3E+00	(mg/kg-day) ⁻¹	1	7.3E+00	(mg/kg-day) ⁻¹	M	B2	IRIS	12/2/2011
Dibenzo(a,h)anthracene	7.3E+00	(mg/kg-day) ⁻¹	1	7.3E+00	(mg/kg-day) ⁻¹	M	B2	EPA	7/1/1993
Inorganics		, , ,			, , ,				
Aluminum	NA	NA	1	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	10/23/2006
Arsenic	1.5E+00	(mg/kg-day) ⁻¹	0.025	1.5E+00	(mg/kg-day) ⁻¹		A	IRIS	12/2/2011
Barium	NA	NA	0.07	NA	NA		D	IRIS	12/2/2011
Chromium ⁽⁵⁾	5.0E-01	(mg/kg-day) ⁻¹	1	5.0E-01	(mg/kg-day) ⁻¹		likely to be carcinogenic to humans	NJDEP	4/8/2009
Cobalt	NA	NA	1	NA	NA		NA	NA	NA
Copper	NA	NA	1	NA	NA		D	IRIS	12/2/2011
Iron	NA	NA	1	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	9/11/2006
Lead	NA	NA	1	NA	NA		NA	NA	NA
Manganese	NA	NA	0.04	NA	NA	-	D	IRIS	12/2/2011
Thallium	NA	NA	1	NA	NA	-	inadequate information to assess the carcinogenic potential	PPRTV	10/8/2010
Vanadium	NA	NA	0.026	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	9/30/2009

⁽¹⁾ Oral Absorption Efficiency for Dermal from Risk Assessment Guidance for Superfund Part E, Supplemental Guidance for Dermal Risk Assessment

EPA Weight of Evidence (EPA 1986, EPA 1996):

- A Human Carcinogen
- B1 Probable human carcinogen indicates that limited human data are available
- B2 Probable human carcinogen indicates sufficient evidence in animals and inadequate or no evidence in humans
- C Possible human carcinogen
- D Not classifiable as human carcinogen

Definition:

Cal/EPA = California Environmental Protection Agency

EPA = EPA Provisional Guidance for Quantitative Assessment of Polycyclic Aromatic Hydrocarbons

IRIS = Integrated Risk Information System

M = mutagen

mg/kg-day = milligram per kilogram per day

NA = not available

NJDEP = New Jersey Department of Environmental Protection

PPRTV = Provisional Peer Reviewed Toxicity Value

EPA Weight of Evidence Narrative (EPA 2005):

Carcinogenic to human

Likely to be carcinogenic to humans

Suggestive evidence of carcinogenic potential

Inadequate information to assess carcinogenic potential

Not likely to be carcinogenic to humans



⁽²⁾ Oral cancer slope factor (CSF) for Dermal = Oral CSF

⁽³⁾ Identified as a mutagen on the Regional Screening Level (RSL) Table, June 2011 http://www.epa.gov/region09/waste/sfund/prg/index.html

⁽⁴⁾ Date shown for IRIS is the date IRIS was searched. http://www.epa.gov/iris/ Date shown for other sources is the publication date.

⁽⁵⁾ based on chromium (VI)

TABLE B-6.2 CANCER TOXICITY DATA - INHALATION

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chemical of Potential	Inhalation U	Jnit Risk	(1)		Inhalation	Unit Risk
Concern	Value	Unit	Mutagen (1)	Weight of Evidence/ Cancer Guideline Description	Source	Date (2)
Volatile Organic Compounds	i					
Bromodichloromethane	3.7E-05	(µg/m³) ⁻¹		B2	Cal/EPA	7/21/2009
cis-1,2-Dichloroethene	NA	NA		inadequate information to assess the carcinogenic potential	IRIS	12/2/2011
Dibromochloromethane	2.7E-05	(µg/m³) ⁻¹		С	Cal/EPA	7/21/2009
Tetrachloroethene	2.6E-07	(µg/m³) ⁻¹		Likely to be carcinogenic to humans	IRIS	3/20/2012
trans-1,2-Dichloroethene	NA	NA		inadequate information to assess the carcinogenic potential	IRIS	12/2/2011
Trichloroethene	4.1E-06	(µg/m³) ⁻¹	M	carcinogenic to humans	IRIS	12/2/2011
Vinyl Chloride	4.4E-06	(µg/m ³) ⁻¹	M	A	IRIS	12/2/2011
Semi-volatile Organic Compo	ounds					
Benzo(a)pyrene	1.1E-03	(µg/m³) ⁻¹	M	B2	Cal/EPA	7/21/2009
Dibenzo(a,h)anthracene	1.2E-03	(µg/m ³) ⁻¹	M	B2	Cal/EPA	7/21/2009
Inorganics		0				
Aluminum	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	10/23/2006
Arsenic	4.3E-03	(µg/m³) ⁻¹		A	IRIS	12/2/2011
Barium	NA	NA		D	IRIS	12/2/2011
Chromium ⁽³⁾	1.2E-02	(µg/m³) ⁻¹		A	IRIS	12/2/2011
Cobalt	9.0E-03	(µg/m³) ⁻¹		likely to be carcinogenic to humans	PPRTV	8/25/2008
Copper	NA	NA		D	IRIS	12/2/2011
Iron	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	9/11/2006
Lead	NA	NA		NA	NA	NA
Manganese	NA	NA		D	IRIS	12/2/2011
Thallium	NA	NA		inadequate information to assess the carcinogenic potential	PPRTV	10/8/2010
Vanadium ⁽⁴⁾	8.3E-03	(µg/m ³) ⁻¹		suggestive evidence of carcinogenic potential	PPRTV	4/30/2008

⁽¹⁾ Idenitified as a mutagen on the Regional Screening Level (RSL) Table, June 2011, http://www.epa.gov/region09/waste/sfund/prg/index.html

EPA Weight of Evidence (EPA 1986, EPA 1996):

- A Human Carcinogen
- B1 Probable human carcinogen indicates that limited human data are available
- B2 Probable human carcinogen indicates sufficient evidence in animals and inadequate or no evidence in humans
- C Possible human carcinogen

Definition:

Cal/EPA = California Environmental Protection Agency

IRIS = Integrated Risk Information System

M = mutagen

NA = not available

 $\mu g/m^3 = microgram per cubic meter$

PPRTV = Provisional Peer Reviewed Toxicity Value

EPA Weight of Evidence Narrative (EPA 2005):

Carcinogenic to human

Likely to be carcinogenic to humans

Suggestive evidence of carcinogenic potential

Inadequate information to assess carcinogenic potential

Not likely to be carcinogenic to humans

IARC Classification:

2A - The agent is probably carcinogenic to humans



⁽²⁾ Date shown for IRIS is the date IRIS was searched. http://www.epa.gov/iris/ Date shown for other sources is the publication date.

⁽³⁾ based on inhalation unit risk of chromium (VI)

⁽⁴⁾ based on vanadium pentoxide

TABLE B-7.1 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Commercial/Industrial Worker
Receptor Age: Adult

	Exposure	Exposure	Exposure		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	zard Calcu	lation	
Medium	Medium	Point	Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposur	e Concentration	RfD	/RfC	Hazard
	Wediam	1 Ollik	rtouto		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface Soil	Former Sugar	Ingestion	Semi-volatile Organic Compounds												
Soil		Mill		Benzo(a)pyrene	6.56E-02	mg/kg	2.29E-08	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	1.67E-07	6.42E-08	mg/kg-day	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	6.29E-09	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	4.59E-08	1.76E-08	mg/kg-day	NA	NA	NA
				Inorganics												
				Aluminum	1.38E+04	mg/kg	4.81E-03	mg/kg-day	NA	NA	NA	1.35E-02	mg/kg-day	1.00E+00	mg/kg-day	1.35E-02
				Arsenic	3.64E+00	mg/kg	1.27E-06	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.91E-06	3.56E-06	mg/kg-day	3.00E-04	mg/kg-day	1.19E-02
				Chromium	1.50E+01	mg/kg		mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	2.63E-06	1.47E-05	mg/kg-day	3.00E-03	mg/kg-day	4.90E-03
				Cobalt	8.79E+00	mg/kg	3.07E-06	mg/kg-day	NA	NA	NA	8.60E-06	mg/kg-day	3.00E-04	mg/kg-day	2.87E-02
				Iron	3.74E+04	mg/kg	1.31E-02	mg/kg-day	NA	NA	NA	3.66E-02	mg/kg-day	7.00E-01	mg/kg-day	5.23E-02
				Manganese	4.89E+02	mg/kg		mg/kg-day	NA	NA	NA	4.78E-04	mg/kg-day		mg/kg-day	3.41E-03
				Vanadium	6.37E+01	mg/kg	2.23E-05	mg/kg-day	NA	NA	NA	6.23E-05	mg/kg-day	7.00E-05	mg/kg-day	8.91E-01
			Exp. Route To	tal							4.74E-06					1.01E+00
Surface	Surface Soil	Former Sugar	Dermal	Semi-volatile Organic Compounds												
Soil		Mill	Contact	Benzo(a)pyrene	6.56E-02	mg/kg	1.97E-08	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	1.44E-07	5.51E-08	mg/kg-day	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	5.40E-09	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	3.94E-08	1.51E-08	mg/kg-day	NA	NA	NA
				Inorganics												
				Aluminum	1.38E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
				Arsenic	3.64E+00	mg/kg	2.52E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	3.77E-07	7.04E-07	mg/kg-day	3.00E-04	mg/kg-day	2.35E-03
				Chromium	1.50E+01	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	8.79E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	3.74E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	4.89E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	6.37E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal							5.60E-07					2.35E-03
Surface	Surface Soil	Former Sugar	Inhalation	Semi-volatile Organic Compounds												
Soil		Mill		Benzo(a)pyrene	6.56E-02	mg/kg	3.93E-09	μg/m³	1.10E-03	(µg/m ³) ⁻¹	4.33E-12	1.10E-11	mg/m ³	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	1.08E-09	μg/m³	1.20E-03	(µg/m ³) ⁻¹	1.30E-12	3.02E-12	mg/m ³	NA	NA	NA
				Inorganics												
				Aluminum	1.38E+04	mg/kg	8.26E-04	μg/m³	NA	NA	NA	2.31E-06	mg/m ³	5.00E-03	mg/m ³	4.63E-04
				Arsenic	3.64E+00	mg/kg	2.18E-07	μg/m³	4.30E-03	(µg/m³) ⁻¹	9.37E-10	6.10E-10	mg/m ³	1.50E-05	mg/m ³	4.07E-05
				Chromium	1.50E+01	mg/kg	9.01E-07	μg/m³	1.20E-02	(µg/m ³) ⁻¹	1.08E-08	2.52E-09	mg/m ³	1.00E-04	mg/m ³	2.52E-05
				Cobalt	8.79E+00	mg/kg	5.27E-07	μg/m³	9.00E-03	$(\mu g/m^3)^{-1}$	4.74E-09	1.48E-09	mg/m ³	6.00E-06	mg/m ³	2.46E-04
				Iron	3.74E+04	mg/kg	2.24E-03	μg/m³	NA	NA	NA	6.28E-06	mg/m ³	NA	NA	NA
				Manganese	4.89E+02	mg/kg	2.93E-05	μg/m³	NA	NA	NA	8.20E-08	mg/m ³	5.00E-05	mg/m ³	1.64E-03
				Vanadium	6.37E+01	mg/kg	3.82E-06	µg/m³	8.30E-03	(µg/m³) ⁻¹	3.17E-08	1.07E-08	mg/m³	1.00E-04	mg/m³	1.07E-04
	Exp. Route Total										4.82E-08					2.52E-03
	Exposure Point Total										5.35E-06					1.01E+00

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-7.1 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Commercial/Industrial Worker
Receptor Age: Adult

	_	_	_		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	zard Calcu	lation	
Medium	Exposure Medium	Exposure Point	Exposure Route	Chemical of Potential Concern	Concent		Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposu	re Concentration	RfD)/RfC	Hazard
	iviedium	Point	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Groundwater	Groundwater	Groundwater	Ingestion	Volatile Organic Compounds			ĺ									
				cis-1,2-Dichloroethene	5.45E+01	μg/L	1.90E-04	mg/kg-day	NA	NA	NA	5.33E-04	mg/kg-day	2.00E-03	mg/kg-day	2.66E-01
				Tetrachloroethene	9.92E-01	μg/L	3.47E-06	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	7.28E-09	9.71E-06	mg/kg-day	6.00E-03	mg/kg-day	1.62E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	7.98E-06	mg/kg-day	NA	NA	NA	2.23E-05	mg/kg-day	2.00E-02	mg/kg-day	1.12E-03
				Trichloroethene	5.64E-01	μg/L	1.97E-06	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	9.07E-08	5.52E-06	mg/kg-day	5.00E-04	mg/kg-day	1.10E-02
				Vinyl Chloride	7.30E-01	μg/L	2.55E-06	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	1.84E-06	7.14E-06	mg/kg-day	3.00E-03	mg/kg-day	2.38E-03
				Inorganics												
				Aluminum	2.04E+03	μg/L	7.12E-03	mg/kg-day	NA	NA	NA	1.99E-02	mg/kg-day	1.00E+00	mg/kg-day	1.99E-02
				Arsenic	3.80E+00	μg/L	1.33E-05	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.99E-05	3.71E-05	mg/kg-day	3.00E-04	mg/kg-day	1.24E-01
				Barium	2.04E+02	μg/L	7.11E-04	mg/kg-day	NA	NA	NA	1.99E-03	mg/kg-day	2.00E-01	mg/kg-day	9.96E-03
				Chromium	8.35E+00	μg/L	2.92E-05	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	1.46E-05	8.17E-05	mg/kg-day	3.00E-03	mg/kg-day	2.72E-02
				Cobalt	1.07E+00	μg/L	3.75E-06	mg/kg-day	NA	NA	NA	1.05E-05	mg/kg-day	3.00E-04	mg/kg-day	3.50E-02
				Copper	5.22E+01	μg/L	1.83E-04	mg/kg-day	NA	NA	NA	5.11E-04	mg/kg-day	4.00E-02		1.28E-02
				Iron	8.20E+03	μg/L	2.86E-02	mg/kg-day	NA	NA	NA	8.02E-02	mg/kg-day	7.00E-01	mg/kg-day	1.15E-01
				Manganese	4.12E+02	μg/L	1.44E-03	mg/kg-day	NA	NA	NA	4.03E-03	mg/kg-day	1.40E-01	mg/kg-day	2.88E-02
				Vanadium	1.70E+01	μg/L	5.93E-05	mg/kg-day	NA	NA	NA	1.66E-04	mg/kg-day	7.00E-05	mg/kg-day	2.37E+00
			Exp. Route To	tal			Ì				3.64E-05					3.03E+00
Groundwater	Groundwater	Groundwater	Dermal	Volatile Organic Compounds			ĺ									
			Contact	cis-1,2-Dichloroethene	5.45E+01	μg/L	NA	NA	NA	NA	NA	NA	NA	2.00E-03	mg/kg-day	NA
				Tetrachloroethene	9.92E-01	μg/L	4.13E-06	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	8.68E-09	1.16E-05	mg/kg-day	6.00E-03	mg/kg-day	1.93E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	1.42E-06	mg/kg-day	NA	NA	NA	3.96E-06	mg/kg-day	2.00E-02	mg/kg-day	1.98E-04
				Trichloroethene	5.64E-01	μg/L	6.82E-07	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	3.14E-08	1.91E-06	mg/kg-day	5.00E-04	mg/kg-day	3.82E-03
				Vinyl Chloride	7.30E-01	μg/L	2.73E-07	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	1.96E-07	7.63E-07	mg/kg-day	3.00E-03	mg/kg-day	2.54E-04
				Inorganics												
				Aluminum	2.04E+03	μg/L	7.44E-05	mg/kg-day	NA	NA	NA	2.08E-04	mg/kg-day	1.00E+00	mg/kg-day	2.08E-04
				Arsenic	3.80E+00	μg/L	1.38E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	2.08E-07	3.88E-07	mg/kg-day	3.00E-04	mg/kg-day	1.29E-03
				Barium	2.04E+02	μg/L	7.43E-06	mg/kg-day	NA	NA	NA	2.08E-05	mg/kg-day	1.40E-02	mg/kg-day	1.49E-03
				Chromium	8.35E+00	μg/L	3.05E-07	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	1.52E-07	8.53E-07	mg/kg-day	7.50E-05	mg/kg-day	1.14E-02
				Cobalt	1.07E+00	μg/L	1.57E-08	mg/kg-day	NA	NA	NA	4.39E-08	mg/kg-day	3.00E-04	mg/kg-day	1.46E-04
				Copper	5.22E+01	μg/L	1.91E-06	mg/kg-day	NA	NA	NA	5.34E-06	mg/kg-day	4.00E-02	mg/kg-day	1.33E-04
				Iron	8.20E+03	μg/L	2.99E-04	mg/kg-day	NA	NA	NA	8.37E-04	mg/kg-day	7.00E-01	mg/kg-day	1.20E-03
				Manganese	4.12E+02	μg/L	1.50E-05	mg/kg-day	NA	NA	NA	4.21E-05	mg/kg-day		mg/kg-day	7.52E-03
				Vanadium	1.70E+01	μg/L	6.19E-07	mg/kg-day	NA	NA	NA	1.73E-06	mg/kg-day	1.82E-06	mg/kg-day	9.52E-01
			Exp. Route To	tal							5.96E-07					9.81E-01
Groundwater	Groundwater	Groundwater	Inhalation	Volatile Organic Compounds												
				cis-1,2-Dichloroethene	1.00E+03	µg/m³	5.92E+00	μg/m³	NA	NA	NA	1.66E-02	mg/m ³	NA	NA	NA
				Tetrachloroethene	1.62E+01	µg/m³	9.58E-02	μg/m³	2.60E-07	(µg/m ³) ⁻¹	2.49E-08	2.68E-04	mg/m ³	4.00E-02	mg/m ³	6.70E-03
				trans-1,2-Dichloroethene	4.18E+01	µg/m³	2.47E-01	μg/m³	NA	NA	NA	6.91E-04	mg/m ³	6.00E-02	mg/m ³	1.15E-02
				Trichloroethene	9.69E+00	µg/m³	5.73E-02	μg/m³	4.10E-06	(µg/m ³) ⁻¹	2.35E-07	1.60E-04	mg/m ³	2.00E-03	mg/m ³	8.02E-02
				Vinyl Chloride	1.40E+01	µg/m°	8.27E-02	μg/m ⁻	4.40E-06	(µg/m ²) ⁻¹	3.64E-07	2.32E-04	mg/m³	1.00E-01	mg/m ⁻	2.32E-03
			Exp. Route To	tal						6.24E-07					1.01E-01	
		Exposure Point	Total								3.76E-05					4.11E+00

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-7.2 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Trespasser
Receptor Age: Adolescent (7-12 yrs)

	_	_	_		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer H	azard Calcu	lation	
Medium	Exposure Medium	Exposure Point	Exposure Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fa	ctor/Unit Risk	Cancer	Intake/ Exposu	re Concentration	RfD)/RfC	Hazard
	Medium	Politi	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface Soil	Former Sugar	Ingestion	Semi-volatile Organic Compounds								,				
Soil		Mill		Benzo(a)pyrene	6.56E-02	mg/kg	4.28E-09	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	3.13E-08	4.99E-08	mg/kg-day	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	1.17E-09	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	8.57E-09	1.37E-08	mg/kg-day	NA	NA	NA
				Inorganics												
				Aluminum	1.38E+04	mg/kg	8.99E-04	mg/kg-day	NA	NA	NA	1.05E-02	mg/kg-day	1.00E+00	mg/kg-day	1.05E-02
				Arsenic	3.64E+00	mg/kg	2.37E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	3.56E-07	2.77E-06	mg/kg-day	3.00E-04	mg/kg-day	9.22E-03
				Chromium	1.50E+01	mg/kg	9.80E-07	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	4.90E-07	1.14E-05	mg/kg-day	3.00E-03	mg/kg-day	3.81E-03
				Cobalt	8.79E+00	mg/kg	5.73E-07	mg/kg-day	NA	NA	NA	6.69E-06	mg/kg-day	3.00E-04	mg/kg-day	2.23E-02
				Iron	3.74E+04	mg/kg	2.44E-03	mg/kg-day	NA	NA	NA	2.85E-02	mg/kg-day	7.00E-01	mg/kg-day	4.07E-02
				Manganese	4.89E+02	mg/kg	3.19E-05	mg/kg-day	NA	NA	NA	3.72E-04	mg/kg-day	1.40E-01	mg/kg-day	2.66E-03
				Vanadium	6.37E+01	mg/kg	4.16E-06	mg/kg-day	NA	NA	NA	4.85E-05	mg/kg-day	7.00E-05	mg/kg-day	6.93E-01
			Exp. Route To	tal							8.86E-07					7.82E-01
Surface	Surface Soil	Former Sugar	Dermal	Semi-volatile Organic Compounds												
Soil		Mill	Contact	Benzo(a)pyrene	6.56E-02	mg/kg	1.40E-09	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	1.02E-08	1.64E-08	mg/kg-day	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	3.85E-10	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	2.81E-09	4.49E-09	mg/kg-day	NA	NA	NA
				Inorganics												
				Aluminum	1.38E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
				Arsenic	3.64E+00	mg/kg	1.79E-08	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	2.69E-08	2.09E-07	mg/kg-day	3.00E-04	mg/kg-day	6.97E-04
				Chromium	1.50E+01	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
					8.79E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
					3.74E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	4.89E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	
				Vanadium	6.37E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal							3.99E-08					6.97E-04
Surface	Surface Soil	Former Sugar	Inhalation	Semi-volatile Organic Compounds												
Soil		Mill		Benzo(a)pyrene	6.56E-02	mg/kg	9.44E-11	μg/m ³	1.10E-03	(µg/m ³) ⁻¹	1.04E-13	4.83E-11	mg/m ³	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	2.59E-11	μg/m³	1.20E-03	(µg/m ³) ⁻¹	3.11E-14	1.32E-11	mg/m ³	NA	NA	NA
				Inorganics				_							_	
				Aluminum	1.38E+04	mg/kg	1.98E-05	μg/m ³	NA	NA	NA	1.01E-05	mg/m ³	5.00E-03	mg/m ³	2.03E-03
				Arsenic	3.64E+00	mg/kg	5.23E-09	μg/m ³	4.30E-03	(µg/m ³) ⁻¹	2.25E-11	2.67E-09	mg/m ³	2.00E-04	mg/m ³	1.34E-05
				Chromium	1.50E+01	mg/kg	2.16E-08	μg/m ³	1.20E-02	(µg/m ³) ⁻¹	2.60E-10	1.11E-08	mg/m ³	1.00E-04	mg/m ³	1.11E-04
					8.79E+00	mg/kg	1.26E-08	μg/m ³	9.00E-03	(µg/m³) ⁻¹	1.14E-10	6.46E-09	mg/m ³	6.00E-06	mg/m ³	1.08E-03
					3.74E+04	mg/kg	5.39E-05	μg/m ³	NA	NA	NA	2.75E-05	mg/m ³	NA	NA	NA
				o a	4.89E+02	mg/kg	7.03E-07	μg/m³	NA	NA	NA	3.59E-07	mg/m ³	1.70E-04	mg/m ³	2.11E-03
					6.37E+01	mg/kg	9.17E-08	μg/m³	8.30E-03	(µg/m³) ⁻¹	7.61E-10	4.68E-08	mg/m³	3.00E-02	mg/m³	1.56E-06
			Exp. Route To	tal							1.16E-09					5.34E-03
		Exposure Point	Total								9.27E-07		•			7.88E-01

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-7.3 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Resident
Receptor Age: Lifetime

	_	_	_		Exposure	Point		Cancer	Risk Calcula	ition			Noncancer Ha	azard Calcu	lation	
Medium	Exposure	Exposure	Exposure	Chemical of Potential Concern	Concent		Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposur	re Concentration	RfD)/RfC	Hazard
	Medium	Point	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface Soil	Former Sugar	Ingestion	Semi-volatile Organic Compounds												
Soil		Mill	Ü	Benzo(a)pyrene	6.56E-02	mg/kg	4.40E-07	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	3.21E-06	8.39E-07	mg/kg-day	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	1.21E-07	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	8.81E-07	2.30E-07	mg/kg-day	NA	NA	NA
				Inorganics		0 0		0 0 7					0 0 7			
				Aluminum	1.38E+04	mg/kg	2.16E-02	mg/kg-day	NA	NA	NA	1.76E-01	mg/kg-day	1.00E+00	mg/kg-day	1.76E-01
				Arsenic	3.64E+00	mg/kg	5.69E-06	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	8.54E-06	4.65E-05	mg/kg-day	3.00E-04	mg/kg-day	1.55E-01
				Chromium	1.50E+01	mg/kg	2.35E-05	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	1.18E-05	1.92E-04	mg/kg-day	3.00E-03	mg/kg-day	6.41E-02
				Cobalt	8.79E+00	mg/kg	1.38E-05	mg/kg-day	NA	NA	NA	1.12E-04	mg/kg-day	3.00E-04	mg/kg-day	3.75E-01
				Iron	3.74E+04	mg/kg	5.86E-02	mg/kg-day	NA	NA	NA	4.79E-01	mg/kg-day	7.00E-01	mg/kg-day	6.84E-01
				Manganese	4.89E+02	mg/kg	7.65E-04	mg/kg-day	NA	NA	NA	6.25E-03	mg/kg-day	1.40E-01	mg/kg-day	4.46E-02
				Vanadium	6.37E+01	mg/kg	9.97E-05	mg/kg-day	NA	NA	NA	8.15E-04	mg/kg-day	7.00E-05	mg/kg-day	1.16E+01
			Exp. Route To	tal							2.44E-05					1.31E+01
Surface	Surface Soil	Former Sugar	Dermal	Semi-volatile Organic Compounds												
Soil		Mill	Contact	Benzo(a)pyrene	6.56E-02	mg/kg	1.69E-07	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	1.23E-06	3.05E-07	mg/kg-day	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	4.63E-08	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	3.38E-07	8.38E-08	mg/kg-day	NA	NA	NA
				Inorganics												
				Aluminum	1.38E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
				Arsenic	3.64E+00	mg/kg	5.39E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	8.08E-07	3.90E-06	mg/kg-day	3.00E-04	mg/kg-day	1.30E-02
				Chromium	1.50E+01	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	8.79E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	3.74E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	4.89E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	6.37E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal							2.38E-06					1.30E-02
Surface	Surface Soil	Former Sugar	Inhalation	Semi-volatile Organic Compounds												
Soil		Mill		Benzo(a)pyrene	6.56E-02	mg/kg	5.02E-08	μg/m³	1.10E-03	$(\mu g/m^3)^{-1}$	5.53E-11	4.63E-11	mg/m ³	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	1.38E-08	μg/m³	1.20E-03	$(\mu g/m^3)^{-1}$	1.65E-11	1.27E-11	mg/m ³	NA	NA	NA
				Inorganics				_					_		_	
				Aluminum	1.38E+04	mg/kg	4.16E-03	μg/m ³	NA	NA	NA	9.71E-06	mg/m ³	5.00E-03	mg/m ³	1.94E-03
				Arsenic	3.64E+00	mg/kg	1.10E-06	µg/m³	4.30E-03	(µg/m ³) ⁻¹	4.72E-09	2.56E-09	mg/m ³	1.50E-05	mg/m ³	1.71E-04
				Chromium	1.50E+01	mg/kg	4.54E-06	μg/m ³	1.20E-02	(µg/m ³) ⁻¹	5.45E-08	1.06E-08	mg/m ³	1.00E-04	mg/m ³	1.06E-04
				Cobalt	8.79E+00	mg/kg	2.66E-06	μg/m ³	9.00E-03	$(\mu g/m^3)^{-1}$	2.39E-08	6.20E-09	mg/m ³	6.00E-06	mg/m ³	1.03E-03
				Iron	3.74E+04	mg/kg	1.13E-02	μg/m³	NA	NA	NA	2.64E-05	mg/m ³	NA	NA 3	NA
				Manganese	4.89E+02	mg/kg	1.48E-04	μg/m³	NA	NA	NA	3.44E-07	mg/m³	5.00E-05	mg/m ³	6.89E-03
				Vanadium	6.37E+01	mg/kg	1.93E-05	μg/m³	8.30E-03	(µg/m³) ⁻¹	1.60E-07	4.49E-08	mg/m³	1.00E-04	mg/m³	4.49E-04
			Exp. Route To	tal							2.43E-07					1.06E-02
		Exposure Point	Total							<u> </u>	2.70E-05					1.32E+01

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-7.3 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Resident
Receptor Age: Lifetime

				1	Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	ulation	
Medium	Exposure	Exposure	Exposure	Chemical of Potential Concern	Concent		Intake/ Exposu	re Concentration		ctor/Unit Risk	Cancer	Intake/ Exposu	re Concentration		D/RfC	Hazard
	Medium	Point	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Groundwater	Groundwater	Groundwater	Ingestion	Volatile Organic Compounds			Ì					i				
				cis-1.2-Dichloroethene	5.45E+01	μg/L	8.10E-04	mg/kg-day	NA	NA	NA	3.48E-03	mg/kg-day	2.00E-03	mg/kg-day	1.74E+00
				Tetrachloroethene	9.92E-01	μg/L	1.48E-05	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	3.10E-08	6.34E-05	mg/kg-day	6.00E-03		1.06E-02
				trans-1.2-Dichloroethene	2.28E+00	μg/L	3.40E-05	mg/kg-day	NA	NA	NA	1.46E-04	mg/kg-day	2.00E-02		7.30E-03
				Trichloroethene	5.64E-01	μg/L	2.62E-05	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	5.54E-07	3.61E-05	mg/kg-day	5.00E-04		7.21E-02
				Vinyl Chloride	7.30E-01	μg/L	5.95E-05	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	4.29E-05	4.67E-05	mg/kg-day	3.00E-03	0 0 ,	1.56E-02
				Inorganics		1.5		3 3 1 1					3 3,		3 3,	
				Aluminum	2.04E+03	μg/L	3.03E-02	mg/kg-day	NA	NA	NA	1.30E-01	mg/kg-day	1.00E+00	mg/kg-day	1.30E-01
				Arsenic	3.80E+00	μg/L	5.64E-05	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	8.47E-05	2.43E-04	mg/kg-day	3.00E-04		8.09E-01
				Barium	2.04E+02	μg/L	3.03E-03	mg/kg-day	NA	NA ,	NA	1.30E-02	mg/kg-day	2.00E-01	mg/kg-day	6.51E-02
				Chromium	8.35E+00	μg/L	1.24E-04	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	6.21E-05	5.34E-04	mg/kg-day	3.00E-03	mg/kg-day	1.78E-01
				Cobalt	1.07E+00	μg/L	1.60E-05	mg/kg-day	NA	NA NA	NA	6.87E-05	mg/kg-day	3.00E-04		2.29E-01
				Copper	5.22E+01	μg/L	7.77E-04	mg/kg-day	NA	NA	NA.	3.34E-03	mg/kg-day	4.00E-02		
				Iron	8.20E+03	μg/L	1.22E-01	mg/kg-day	NA	NA.	NA NA	5.24E-01	mg/kg-day	7.00E-01	mg/kg-day	7.48E-01
				Manganese	4.12E+02	μg/L	6.13E-03	mg/kg-day	NA	NA NA	NA.	2.63E-02	mg/kg-day	1.40E-01	mg/kg-day	
				Vanadium	1.70E+01	μg/L	2.52E-04	mg/kg-day	NA	NA.	NA.	1.08E-03	mg/kg-day		mg/kg-day	
	<u> </u>		Exp. Route To		02.101	P9'-	1 2.022 0 .	grag day	101	10.	1.90E-04	1.002 00	g.n.g aay	1.002 00	mgmg day	1.98E+01
Carriadoratas	C	Groundwater		Volatile Organic Compounds			<u> </u>			1	1.30L-04		1			1.30L+01
Groundwater	Groundwater	Groundwater	Dermal Contact	cis-1.2-Dichloroethene	5.45E+01	μg/L	NA	NA	NA	NA	NA	NA NA	NA	2.00E-03	mg/kg-day	NA
			Contact	Tetrachloroethene	9.92E-01		8.49E-06			(mg/kg-day) ⁻¹	1.78E-08	2.97E-05		6.00E-03	3 3 ,	4.95E-03
				trans-1,2-Dichloroethene	9.92E-01 2.28E+00	μg/L	8.49E-06 2.91E-06	mg/kg-day	2.10E-03 NA	(Hig/kg-day) NA	1.78E-08 NA	2.97E-05 1.02E-05	mg/kg-day	2.00E-03		4.95E-03 5.08E-04
						μg/L		mg/kg-day				II .	mg/kg-day	5.00E-02		
				Trichloroethene	5.64E-01	μg/L	4.04E-06 2.62E-06	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	8.94E-08 1.89E-06	4.90E-06 1.97E-06	mg/kg-day			9.80E-03
				Vinyl Chloride	7.30E-01	μg/L	2.02E-06	mg/kg-day	7.20E-01	(mg/kg-day)	1.89E-06	1.97E-06	mg/kg-day	3.00E-03	mg/kg-day	6.58E-04
				Inorganics Aluminum	2.04E+03	/1	1.63E-04		NA	NA	NIA.	5.71E-04		4.005.00		5.71E-04
						μg/L		mg/kg-day		(mg/kg-day) ⁻¹	NA 4 FOE OZ		mg/kg-day	1.00E+00		
				Arsenic	3.80E+00	μg/L	3.04E-07	mg/kg-day	1.50E+00		4.56E-07	1.06E-06	mg/kg-day	3.00E-04	0 0 ,	3.54E-03
				Barium	2.04E+02	μg/L	1.63E-05	mg/kg-day	NA	NA	NA	5.70E-05	mg/kg-day	1.40E-02		4.07E-03
				Chromium	8.35E+00	μg/L	6.69E-07	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	3.35E-07	2.34E-06	mg/kg-day	7.50E-05		3.12E-02
				Cobalt	1.07E+00	μg/L	3.44E-08	mg/kg-day	NA	NA	NA	1.20E-07	mg/kg-day	3.00E-04		4.01E-04
				Copper	5.22E+01	μg/L	4.19E-06	mg/kg-day	NA	NA	NA	1.46E-05	mg/kg-day	4.00E-02	0 0 ,	
				Iron	8.20E+03	μg/L	6.57E-04	mg/kg-day	NA	NA	NA	2.30E-03	mg/kg-day	7.00E-01	mg/kg-day	3.28E-03
				Manganese	4.12E+02	μg/L	3.30E-05	mg/kg-day	NA	NA	NA	1.15E-04	mg/kg-day	5.60E-03		2.06E-02
				Vanadium	1.70E+01	μg/L	1.36E-06	mg/kg-day	NA	NA	NA	4.75E-06	mg/kg-day	1.82E-06	mg/kg-day	
	-		Exp. Route To								2.79E-06					2.69E+00
Groundwater	Groundwater	Groundwater	Inhalation	Volatile Organic Compounds												
				cis-1,2-Dichloroethene	5.45E+01	μg/L	1.41E+01	µg/m³	NA	NA	NA	7.12E-02	mg/m³	NA	NA .	NA
				Tetrachloroethene	9.92E-01	μg/L	2.27E-01	μg/m ³	2.60E-07	(µg/m ³) ⁻¹	5.91E-08	1.15E-03	mg/m³	4.00E-02	mg/m ³	2.88E-02
				trans-1,2-Dichloroethene	2.28E+00	μg/L	5.86E-01	μg/m ³	NA	NA	NA	2.97E-03	mg/m ³	6.00E-02	mg/m ³	4.95E-02
				Trichloroethene	5.64E-01	μg/L	4.56E-01	μg/m³	4.10E-06	(µg/m³) ⁻¹	8.78E-10	6.89E-04	mg/m ³	2.00E-03		3.44E-01
				Vinyl Chloride	7.30E-01	μg/L	1.20E+00	μg/m [°]	4.40E-06	(µg/m [°]) ⁻ '	5.26E-06	9.94E-04	mg/m [°]	1.00E-01	mg/m ⁻	9.94E-03
	-		Exp. Route To	tal					•		5.32E-06					4.32E-01
	1	Exposure Point							1.98E-04	i				2.29E+01		
		Enpoduro i Ollit	· · · · · ·								1.000 04	11				2.20E :01

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-7.4 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Receptor Population: Future

: Construction Worker

Receptor Age: Adult

	F	F.,,,,,,,,,,	F		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	ulation	
Medium	Exposure Medium	Exposure Point	Exposure Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposul	re Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposur	e Concentration	RfI	D/RfC	Hazard
	Medium	Folit	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface/	Surface/	Former Sugar	Ingestion	Semi-volatile Organic Compounds												
Subsurface	Subsurface	Mill	Ü	Benzo(a)pyrene	4.61E-02	mg/kg	8.51E-10	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	6.21E-09	5.96E-08	mg/kg-day	NA	NA	NA
Soil	Soil			Dibenzo(a,h)anthracene	1.80E-02	mg/kg	3.32E-10	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	2.42E-09	2.32E-08	mg/kg-day	NA	NA	NA
				Inorganics												
				Aluminum	1.73E+04	mg/kg	3.19E-04	mg/kg-day	NA	NA	NA	2.23E-02	mg/kg-day	1.00E+00	mg/kg-day	2.23E-02
				Arsenic	1.93E+00	mg/kg	3.56E-08	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	5.34E-08	2.49E-06	mg/kg-day	3.00E-04	mg/kg-day	8.30E-03
				Chromium	9.89E+00	mg/kg	1.83E-07	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	9.13E-08	1.28E-05	mg/kg-day	3.00E-03		4.26E-03
				Cobalt	1.09E+01	mg/kg	2.01E-07	mg/kg-day	NA	NA	NA	1.41E-05	mg/kg-day	3.00E-04	0 0 ,	4.70E-02
				Iron	2.90E+04	mg/kg	5.36E-04	mg/kg-day	NA	NA	NA	3.75E-02	mg/kg-day	7.00E-01	mg/kg-day	5.36E-02
				Manganese	4.35E+02	mg/kg	8.03E-06	mg/kg-day	NA	NA	NA	5.62E-04	mg/kg-day	1.40E-01	mg/kg-day	4.02E-03
				Thallium	2.07E-01	mg/kg	3.82E-09	mg/kg-day	NA	NA	NA	2.67E-07	mg/kg-day	1.00E-05		2.67E-02
				Vanadium	9.62E+01	mg/kg	1.78E-06	mg/kg-day	NA	NA	NA	1.24E-04	mg/kg-day	7.00E-05	mg/kg-day	1.78E+00
			Exp. Route Tot	tal							1.53E-07					1.94E+00
Surface/	Surface/	Former Sugar	Dermal	Semi-volatile Organic Compounds												
Subsurface	Subsurface	Mill	Contact	Benzo(a)pyrene	4.61E-02	0 0	3.32E-10	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	2.42E-09	2.32E-08	mg/kg-day	NA	NA	NA
Soil	Soil			Dibenzo(a,h)anthracene	1.80E-02	mg/kg	1.30E-10	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	9.46E-10	9.07E-09	mg/kg-day	NA	NA	NA
				Inorganics												
				Aluminum	1.73E+04			NA	NA	NA	NA	NA	NA		mg/kg-day	
				Arsenic	1.93E+00	mg/kg	3.20E-09	mg/kg-day	1.50E+00	(mg/kg-day)	4.80E-09	2.24E-07	mg/kg-day	3.00E-04	mg/kg-day	
				Chromium	9.89E+00	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05		NA
				Cobalt	1.09E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	0 0 ,	
				Iron	2.90E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	
				Manganese	4.35E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Thallium	2.07E-01	mg/kg	NA NA	NA	NA	NA	NA	NA	NA		mg/kg-day	
				Vanadium	9.62E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route Tot						1		8.17E-09			•		7.47E-04
Surface/	Surface/	Former Sugar	Inhalation	Semi-volatile Organic Compounds				, 3		31	_		, 3			
Subsurface	Subsurface	Mill		Benzo(a)pyrene	4.61E-02	0 0	4.42E-11	μg/m ³	1.10E-03	(µg/m ³) ⁻¹	4.87E-14	3.10E-12	mg/m ³	NA	NA	NA
Soil	Soil			Dibenzo(a,h)anthracene	1.80E-02	mg/kg	1.73E-11	μg/m³	1.20E-03	(µg/m ³) ⁻¹	2.07E-14	1.21E-12	mg/m ³	NA	NA	NA
				Inorganics	4 705 : 04		4 005 05	3				4.405.00	3	F 00F 00	mg/m ³	0.005.04
				Aluminum	1.73E+04	0 0	1.66E-05	µg/m³	NA 4 20E 02	NA (μg/m ³) ⁻¹	NA ZOEF 40	1.16E-06	mg/m ³ mg/m ³	5.00E-03	mg/m ³	2.32E-04
	l			Arsenic	1.93E+00	mg/kg	1.85E-09	μg/m³ μg/m³	4.30E-03	(μg/m²) ⁻¹	7.95E-12	1.29E-10	mg/m³	1.50E-05	mg/m³	8.63E-06 6.64E-06
	l			Chromium Cobalt	9.89E+00 1.09E+01	mg/kg	9.49E-09 1.05E-08	μg/m³	1.20E-02 9.00E-03	(μg/m²) ⁻¹	1.14E-10 9.43E-11	6.64E-10 7.33E-10	mg/m³	1.00E-04 6.00E-06	mg/m³	6.64E-06 1.22E-04
	l			Iron	2.90E+01	mg/kg mg/kg	2.79E-05	μg/m ³	9.00E-03 NA	(μg/III) NA	9.43E-11 NA	1.95E-06	mg/m ³	NA	NA	1.22E-04 NA
				Manganese	4.35E+02	mg/kg	4.18E-07	μg/m ³	NA NA	NA NA	NA NA	2.92E-08	mg/m ³	5.00E-05	mg/m ³	5.85E-04
				Thallium	4.35E+02 2.07E-01	mg/kg	4.18E-07 1.99E-10	μg/m ³	NA NA	NA NA	NA NA	2.92E-08 1.39E-11	mg/m ³	NA	NA	0.85E-04 NA
				Vanadium	9.62E+01		9.23E-08	μg/m³	8.30E-03	(μg/m³) ⁻¹	7.66E-10	6.46E-09	mg/m³	1.00E-04	mg/m³	6.46E-05
<u> </u>		<u></u>	Exp. Route Tot		5.02LT01	mg/kg	9.23L-00	F5	0.00L-03	(F3)	9.82E-10	0.401-09		1.00L-04		1.02E-03
<u> </u>	-			ldi												
		Exposure Point	ıotaı								1.62E-07					1.94E+00

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-7.5 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Commercial/Industrial Worker
Receptor Age: Adult

	Exposure	Exposure	Exposure		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer H	azard Calcu	ılation	
Medium	Medium	Point	Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposul	re Concentration	RfE	D/RfC	Hazard
	Wediam	1 Ollit	Noute		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface Soil	Puerto Rico	Ingestion	Inorganics												
Soil		Beverage		Aluminum	1.30E+04	mg/kg	4.56E-03	mg/kg-day	NA	NA	NA	1.28E-02	mg/kg-day	1.00E+00	mg/kg-day	1.28E-02
				Arsenic	2.90E+00	mg/kg	1.01E-06	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.52E-06	2.84E-06	mg/kg-day	3.00E-04	mg/kg-day	9.46E-03
				Chromium	2.51E+01	mg/kg	8.76E-06	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	4.38E-06	2.45E-05	mg/kg-day	3.00E-03	mg/kg-day	8.18E-03
				Cobalt	6.36E+00	mg/kg	2.22E-06	mg/kg-day	NA	NA	NA	6.22E-06	mg/kg-day	3.00E-04	mg/kg-day	2.07E-02
				Iron	2.94E+04	mg/kg	1.03E-02	mg/kg-day	NA	NA	NA	2.88E-02	mg/kg-day	7.00E-01	mg/kg-day	4.11E-02
				Manganese	3.49E+02	mg/kg	1.22E-04	mg/kg-day	NA	NA	NA	3.41E-04	mg/kg-day	1.40E-01	mg/kg-day	2.44E-03
				Vanadium	5.66E+01	mg/kg	1.98E-05	mg/kg-day	NA	NA	NA	5.54E-05	mg/kg-day	7.00E-05	mg/kg-day	7.91E-01
			Exp. Route To	tal							5.90E-06					8.85E-01
Surface	Surface Soil	Puerto Rico	Dermal	Inorganics												
Soil		Beverage	Contact	Aluminum	1.30E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
		-		Arsenic	2.90E+00	mg/kg	2.01E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	3.01E-07	5.62E-07	mg/kg-day	3.00E-04	mg/kg-day	1.87E-03
				Chromium	2.51E+01	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	6.36E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	2.94E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	3.49E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	5.66E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal							3.01E-07					1.87E-03
Surface	Surface Soil	Puerto Rico	Inhalation	Inorganics												
Soil		Beverage		Aluminum	1.30E+04	mg/kg	7.82E-04	μg/m ³	NA	NA	NA	2.19E-06	mg/m ³	5.00E-03	mg/m ³	4.38E-04
		-		Arsenic	2.90E+00	mg/kg	1.74E-07	μg/m ³	4.30E-03	(µg/m ³) ⁻¹	7.48E-10	4.87E-10	mg/m ³	1.50E-05	mg/m ³	3.25E-05
				Chromium	2.51E+01	mg/kg	1.50E-06	μg/m ³	1.20E-02	(µg/m ³) ⁻¹	1.80E-08	4.21E-09	mg/m ³	1.00E-04	mg/m ³	4.21E-05
				Cobalt	6.36E+00	mg/kg	3.81E-07	μg/m ³	9.00E-03	$(\mu g/m^3)^{-1}$	3.43E-09	1.07E-09	mg/m ³	6.00E-06	mg/m ³	1.78E-04
				Iron	2.94E+04	mg/kg	1.76E-03	μg/m ³	NA	NA	NA	4.94E-06	mg/m ³	NA	NA	NA
				Manganese	3.49E+02	mg/kg	2.09E-05	μg/m ³	NA	NA	NA	5.85E-08	mg/m ³	5.00E-05	mg/m ³	1.17E-03
				Vanadium	5.66E+01	mg/kg	3.39E-06	μg/m³	8.30E-03	(µg/m³) ⁻¹	2.82E-08	9.50E-09	mg/m³	1.00E-04	mg/m³	9.50E-05
	•	•	Exp. Route To	tal				•		•	5.04E-08		•	•	•	1.96E-03
		Exposure Point	Total								6.25E-06					8.89E-01
				D(D(·				

NA = not applicable RfD = reference dose mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-7.5 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Commercial/Industrial Worker
Receptor Age: Adult

	E	F	F		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	zard Calcu	lation	
Medium	Exposure Medium	Exposure Point	Exposure Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposul	re Concentration	RfE)/RfC	Hazard
	Medium	Politi	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Groundwater	Groundwater	Groundwater	Ingestion	Volatile Organic Compounds												
			_	cis-1,2-Dichloroethene	5.45E+01	μg/L	1.90E-04	mg/kg-day	NA	NA	NA	5.33E-04	mg/kg-day	2.00E-03	mg/kg-day	2.66E-01
				Tetrachloroethene	9.92E-01	μg/L	3.47E-06	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	7.28E-09	9.71E-06	mg/kg-day	6.00E-03	mg/kg-day	1.62E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	7.98E-06	mg/kg-day	NA	NA	NA	2.23E-05	mg/kg-day	2.00E-02	mg/kg-day	1.12E-03
				Trichloroethene	5.64E-01	μg/L	1.97E-06	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	9.07E-08	5.52E-06	mg/kg-day	5.00E-04	mg/kg-day	1.10E-02
				Vinyl Chloride	7.30E-01	μg/L	2.55E-06	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	1.84E-06	7.14E-06	mg/kg-day	3.00E-03	mg/kg-day	2.38E-03
				Inorganics												
				Aluminum	2.04E+03	μg/L	7.12E-03	mg/kg-day	NA	NA	NA	1.99E-02	mg/kg-day	1.00E+00	mg/kg-day	1.99E-02
				Arsenic	3.80E+00	μg/L	1.33E-05	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.99E-05	3.71E-05	mg/kg-day	3.00E-04	mg/kg-day	1.24E-01
				Barium	2.04E+02	μg/L	7.11E-04	mg/kg-day	NA	NA	NA	1.99E-03	mg/kg-day	2.00E-01	mg/kg-day	9.96E-03
				Chromium	8.35E+00	μg/L	2.92E-05	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	1.46E-05	8.17E-05	mg/kg-day	3.00E-03	mg/kg-day	2.72E-02
				Cobalt	1.07E+00	μg/L	3.75E-06	mg/kg-day	NA	NA	NA	1.05E-05	mg/kg-day	3.00E-04	mg/kg-day	3.50E-02
				Copper	5.22E+01	μg/L	1.83E-04	mg/kg-day	NA	NA	NA	5.11E-04	mg/kg-day	4.00E-02	mg/kg-day	1.28E-02
				Iron	8.20E+03	μg/L	2.86E-02	mg/kg-day	NA	NA	NA	8.02E-02	mg/kg-day	7.00E-01	mg/kg-day	1.15E-01
				Manganese	4.12E+02	μg/L	1.44E-03	mg/kg-day	NA	NA	NA	4.03E-03	mg/kg-day	1.40E-01	mg/kg-day	2.88E-02
				Vanadium	1.70E+01	μg/L	5.93E-05	mg/kg-day	NA	NA	NA	1.66E-04	mg/kg-day	7.00E-05	mg/kg-day	2.37E+00
			Exp. Route To	ital							3.64E-05					3.03E+00
Groundwater	Groundwater	Groundwater	Dermal	Volatile Organic Compounds												i i
			Contact	cis-1,2-Dichloroethene	5.45E+01	μg/L	NA	NA	NA	NA	NA	NA	NA	2.00E-03	mg/kg-day	NA
				Tetrachloroethene	9.92E-01	μg/L	4.13E-06	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	8.68E-09	1.16E-05	mg/kg-day		mg/kg-day	1.93E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	1.42E-06	mg/kg-day	NA	NA NA	NA	3.96E-06	mg/kg-day	2.00E-02		1.98E-04
				Trichloroethene	5.64E-01	μg/L	6.82E-07	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	3.14E-08	1.91E-06	mg/kg-day	5.00E-04	mg/kg-day	3.82E-03
				Vinyl Chloride	7.30E-01	μg/L	2.73E-07	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	1.96E-07	7.63E-07	mg/kg-day		mg/kg-day	2.54E-04
				Inorganics				0 0 7					0 0 7			
				Aluminum	2.04E+03	μg/L	7.44E-05	mg/kg-day	NA	NA	NA	2.08E-04	mg/kg-day	1.00E+00	mg/kg-day	2.08E-04
				Arsenic	3.80E+00	μg/L	1.38E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	2.08E-07	3.88E-07	mg/kg-day	3.00E-04	mg/kg-day	1.29E-03
				Barium	2.04E+02	μg/L	7.43E-06	mg/kg-day	NA	NA	NA	2.08E-05	mg/kg-day	1.40E-02	mg/kg-day	1.49E-03
				Chromium	8.35E+00	μg/L	3.05E-07	mg/kg-day	5.00E-01	(mg/kg-day)-1	1.52E-07	8.53E-07	mg/kg-day		mg/kg-day	1.14E-02
				Cobalt	1.07E+00	μg/L	1.57E-08	mg/kg-day	NA	NA	NA	4.39E-08	mg/kg-day	3.00E-04		1.46E-04
				Copper	5.22E+01	μg/L	1.91E-06	mg/kg-day	NA	NA	NA	5.34E-06	mg/kg-day		mg/kg-day	1.33E-04
				Iron	8.20E+03	μg/L	2.99E-04	mg/kg-day	NA	NA	NA	8.37E-04	mg/kg-day	7.00E-01		1.20E-03
				Manganese	4.12E+02	μg/L	1.50E-05	mg/kg-day	NA	NA	NA	4.21E-05	mg/kg-day		mg/kg-day	7.52E-03
				Vanadium	1.70E+01	μg/L	6.19E-07	mg/kg-day	NA	NA	NA	1.73E-06	mg/kg-day		mg/kg-day	9.52E-01
			Exp. Route To	ital							5.96E-07					9.81E-01
Groundwater	Groundwater	Groundwater	Inhalation	Volatile Organic Compounds												
				cis-1,2-Dichloroethene	1.00E+03	μg/m³	5.92E+00	µg/m³	NA	NA	NA	1.66E-02	mg/m³	NA	NA	NA
				Tetrachloroethene	1.62E+01	μg/m ³	9.58E-02	µg/m³	2.60E-07	(µg/m³) ⁻¹	2.49E-08	2.68E-04	mg/m³	4.00E-02	mg/m ³	6.70E-03
				trans-1,2-Dichloroethene	4.18E+01	μg/m ³	2.47E-01	µg/m³	NA	NA	NA	6.91E-04	mg/m ³	6.00E-02	mg/m ³	1.15E-02
				Trichloroethene	9.69E+00	µg/m³	5.73E-02	µg/m³	4.10E-06	(µg/m³)-1	2.35E-07	1.60E-04	mg/m ³	2.00E-03	mg/m ³	8.02E-02
				Vinyl Chloride	1.40E+01	µg/m°	8.27E-02	μg/m ັ	4.40E-06	(µg/m ²) ⁻¹	3.64E-07	2.32E-04	mg/m ⁻	1.00E-01	mg/m ⁻	2.32E-03
			Exp. Route To	otal .	•						6.24E-07		•		•	1.01E-01
		Exposure Point	Total				1				3.76E-05					4.11E+00

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-7.6 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Trespasser
Receptor Age: Adolescent (7-12 yrs)

	Exposure	Exposure	Exposure		Exposure	Point		Cancer	Risk Calcula	ition			Noncancer Ha	azard Calcu	lation	
Medium	Medium	Point	Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposur	e Concentration	RfD)/RfC	Hazard
	Wediam	1 Ollit	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface Soil	Puerto Rico	Ingestion	Inorganics												
Soil		Beverage		Aluminum	1.30E+04	mg/kg	8.51E-04	mg/kg-day	NA	NA	NA	9.92E-03	mg/kg-day	1.00E+00	mg/kg-day	9.92E-03
				Arsenic	2.90E+00	mg/kg	1.89E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	2.84E-07	2.21E-06	mg/kg-day	3.00E-04	mg/kg-day	7.36E-03
				Chromium	2.51E+01	mg/kg	1.64E-06	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	8.18E-07	1.91E-05	mg/kg-day	3.00E-03	mg/kg-day	6.36E-03
				Cobalt	6.36E+00	mg/kg	4.15E-07	mg/kg-day	NA	NA	NA	4.84E-06	mg/kg-day	3.00E-04	mg/kg-day	1.61E-02
				Iron	2.94E+04	mg/kg	1.92E-03	mg/kg-day	NA	NA	NA	2.24E-02	mg/kg-day	7.00E-01	mg/kg-day	3.20E-02
				Manganese	3.49E+02	mg/kg	2.27E-05	mg/kg-day	NA	NA	NA	2.65E-04	mg/kg-day	1.40E-01	mg/kg-day	1.90E-03
				Vanadium	5.66E+01	mg/kg	3.69E-06	mg/kg-day	NA	NA	NA	4.31E-05	mg/kg-day	7.00E-05	mg/kg-day	6.15E-01
			Exp. Route To	tal							1.10E-06					6.89E-01
Surface	Surface Soil	Puerto Rico	Dermal	Inorganics												
Soil		Beverage	Contact	Aluminum	1.30E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
				Arsenic	2.90E+00	mg/kg	1.43E-08	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	2.15E-08	1.67E-07	mg/kg-day	3.00E-04	mg/kg-day	5.56E-04
				Chromium	2.51E+01	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	6.36E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	2.94E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	3.49E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	5.66E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal							2.15E-08					5.56E-04
Surface	Surface Soil	Puerto Rico	Inhalation	Inorganics												
Soil		Beverage		Aluminum	1.30E+04	mg/kg	1.88E-05	μg/m ³	NA	NA	NA	9.59E-06	mg/m ³	5.00E-03	mg/m ³	1.92E-03
		•		Arsenic	2.90E+00	mg/kg	4.17E-09	μg/m ³	4.30E-03	$(\mu g/m^3)^{-1}$	1.79E-11	2.13E-09	mg/m ³	2.00E-04	mg/m ³	1.07E-05
				Chromium	2.51E+01	mg/kg	3.61E-08	μg/m ³	1.20E-02	(µg/m ³) ⁻¹	4.33E-10	1.84E-08	mg/m ³	1.00E-04	mg/m ³	1.84E-04
				Cobalt	6.36E+00	mg/kg	9.15E-09	μg/m ³	9.00E-03	$(\mu g/m^3)^{-1}$	8.23E-11	4.67E-09	mg/m ³	6.00E-06	mg/m ³	7.79E-04
				Iron	2.94E+04	mg/kg	4.24E-05	μg/m ³	NA	NA	NA	2.16E-05	mg/m ³	NA	NA	NA
				Manganese	3.49E+02	mg/kg	5.02E-07	μg/m ³	NA	NA	NA	2.56E-07	mg/m ³	1.70E-04	mg/m ³	1.51E-03
				Vanadium	5.66E+01	mg/kg	8.14E-08	μg/m³	8.30E-03	(µg/m³)-1	6.76E-10	4.16E-08	mg/m³	3.00E-02	mg/m³	1.39E-06
			Exp. Route To	tal	·						1.21E-09			·		4.40E-03
		Exposure Point	Total								1.12E-06					6.94E-01
<u> </u>				D(D(·				

NA = not applicable RfD = reference dose mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day






TABLE B-7.7 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

	Exposure	F.,,,,,,,,,	F		Exposure	Point		Cancer	Risk Calcula	ition			Noncancer Ha	azard Calcu	lation	
Medium	Medium	Exposure Point	Exposure Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fa	ctor/Unit Risk	Cancer	Intake/ Exposur	e Concentration	RfD)/RfC	Hazard
	Medium	1 Ollit	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface Soil	Puerto Rico	Ingestion	Inorganics												
Soil		Beverage		Aluminum	1.30E+04	mg/kg	2.04E-02	mg/kg-day	NA	NA	NA	1.67E-01	mg/kg-day	1.00E+00	mg/kg-day	1.67E-01
				Arsenic	2.90E+00	mg/kg	4.54E-06	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	6.81E-06	3.71E-05	mg/kg-day	3.00E-04	mg/kg-day	1.24E-01
				Chromium	2.51E+01	mg/kg	3.92E-05	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	1.96E-05	3.21E-04	mg/kg-day	3.00E-03	mg/kg-day	1.07E-01
				Cobalt	6.36E+00	mg/kg	9.95E-06	mg/kg-day	NA	NA	NA	8.13E-05	mg/kg-day	3.00E-04	mg/kg-day	2.71E-01
				Iron	2.94E+04	mg/kg	4.61E-02	mg/kg-day	NA	NA	NA	3.76E-01	mg/kg-day	7.00E-01	mg/kg-day	5.38E-01
				Manganese	3.49E+02	mg/kg	5.46E-04	mg/kg-day	NA	NA	NA	4.46E-03	mg/kg-day	1.40E-01	mg/kg-day	3.18E-02
				Vanadium	5.66E+01	mg/kg	8.86E-05	mg/kg-day	NA	NA	NA	7.23E-04	mg/kg-day	7.00E-05	mg/kg-day	1.03E+01
			Exp. Route To	tal							2.64E-05					1.16E+01
Surface	Surface Soil	Puerto Rico	Dermal	Inorganics												
Soil		Beverage	Contact	Aluminum	1.30E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
		_		Arsenic	2.90E+00	mg/kg	4.30E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	6.45E-07	3.11E-06	mg/kg-day	3.00E-04	mg/kg-day	1.04E-02
				Chromium	2.51E+01	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	6.36E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	2.94E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	3.49E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	5.66E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal							6.45E-07					1.04E-02
Surface	Surface Soil	Puerto Rico	Inhalation	Inorganics												
Soil		Beverage		Aluminum	1.30E+04	mg/kg	3.94E-03	μg/m³	NA	NA	NA	9.19E-06	mg/m ³	5.00E-03	mg/m ³	1.84E-03
				Arsenic	2.90E+00	mg/kg	8.76E-07	μg/m³	4.30E-03	$(\mu g/m^3)^{-1}$	3.77E-09	2.04E-09	mg/m ³	1.50E-05	mg/m ³	1.36E-04
				Chromium	2.51E+01	mg/kg	7.58E-06	μg/m³	1.20E-02	(µg/m³) ⁻¹	9.09E-08	1.77E-08	mg/m ³	1.00E-04	mg/m ³	1.77E-04
				Cobalt	6.36E+00	mg/kg	1.92E-06	μg/m³	9.00E-03	$(\mu g/m^3)^{-1}$	1.73E-08	4.48E-09	mg/m ³	6.00E-06	mg/m ³	7.47E-04
				Iron	2.94E+04	mg/kg	8.90E-03	μg/m³	NA	NA	NA	2.08E-05	mg/m ³	NA	NA	NA
				Manganese	3.49E+02	mg/kg	1.05E-04	μg/m³	NA	NA	NA	2.46E-07	mg/m ³	5.00E-05	mg/m ³	4.92E-03
				Vanadium	5.66E+01	mg/kg	1.71E-05	μg/m³	8.30E-03	(µg/m³)-1	1.42E-07	3.99E-08	mg/m³	1.00E-04	mg/m³	3.99E-04
			Exp. Route To	tal							2.54E-07		•		·	8.22E-03
		Exposure Point	Total	-			·	·			2.73E-05		·			1.16E+01
NIA makan				DfD reference door			/l:ll:									

NA = not applicable RfD = reference dose mg/kg = milligram per kilogram $\mu g/m^3 = microgram per cubic meter$ mg/kg-day = milligram per kilogram per day $mg/m^3 = milligram per cubic meter$



TABLE B-7.7 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

				1	Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	ulation	
Medium	Exposure	Exposure	Exposure	Chemical of Potential Concern	Concent		Intake/ Exposu	re Concentration		ctor/Unit Risk	Cancer	Intake/ Exposu	re Concentration		D/RfC	Hazard
	Medium	Point	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Groundwater	Groundwater	Groundwater	Ingestion	Volatile Organic Compounds			Ì					i				
				cis-1.2-Dichloroethene	5.45E+01	μg/L	8.10E-04	mg/kg-day	NA	NA	NA	3.48E-03	mg/kg-day	2.00E-03	mg/kg-day	1.74E+00
				Tetrachloroethene	9.92E-01	μg/L	1.48E-05	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	3.10E-08	6.34E-05	mg/kg-day	6.00E-03		1.06E-02
				trans-1.2-Dichloroethene	2.28E+00	μg/L	3.40E-05	mg/kg-day	NA	NA	NA	1.46E-04	mg/kg-day	2.00E-02		7.30E-03
				Trichloroethene	5.64E-01	μg/L	2.62E-05	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	5.54E-07	3.61E-05	mg/kg-day	5.00E-04		7.21E-02
				Vinyl Chloride	7.30E-01	μg/L	5.95E-05	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	4.29E-05	4.67E-05	mg/kg-day	3.00E-03	0 0 ,	1.56E-02
				Inorganics		1.5		3 3 1 1		, ,			3 3,		3 3,	
				Aluminum	2.04E+03	μg/L	3.03E-02	mg/kg-day	NA	NA	NA	1.30E-01	mg/kg-day	1.00E+00	mg/kg-day	1.30E-01
				Arsenic	3.80E+00	μg/L	5.64E-05	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	8.47E-05	2.43E-04	mg/kg-day	3.00E-04		8.09E-01
				Barium	2.04E+02	μg/L	3.03E-03	mg/kg-day	NA	NA ,	NA	1.30E-02	mg/kg-day	2.00E-01	mg/kg-day	6.51E-02
				Chromium	8.35E+00	μg/L	1.24E-04	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	6.21E-05	5.34E-04	mg/kg-day	3.00E-03	mg/kg-day	1.78E-01
				Cobalt	1.07E+00	μg/L	1.60E-05	mg/kg-day	NA	NA NA	NA	6.87E-05	mg/kg-day	3.00E-04		2.29E-01
				Copper	5.22E+01	μg/L	7.77E-04	mg/kg-day	NA	NA NA	NA.	3.34E-03	mg/kg-day	4.00E-02		
				Iron	8.20E+03	μg/L	1.22E-01	mg/kg-day	NA	NA.	NA NA	5.24E-01	mg/kg-day	7.00E-01	mg/kg-day	7.48E-01
				Manganese	4.12E+02	μg/L	6.13E-03	mg/kg-day	NA	NA	NA.	2.63E-02	mg/kg-day	1.40E-01	mg/kg-day	
				Vanadium	1.70E+01	μg/L	2.52E-04	mg/kg-day	NA	NA.	NA.	1.08E-03	mg/kg-day		mg/kg-day	
	<u> </u>		Exp. Route To		02.101	P9'-	1 2.022 0 .	grag day	101	10.	1.90E-04	1.002 00	g.n.g aay	1.002 00	mg/ng day	1.98E+01
Carriadoratas	C	Groundwater		Volatile Organic Compounds			<u> </u>			1	1.30L-04		1			1.30L+01
Groundwater	Groundwater	Groundwater	Dermal Contact	cis-1.2-Dichloroethene	5.45E+01	μg/L	NA	NA	NA	NA	NA	NA NA	NA	2.00E-03	mg/kg-day	NA
			Contact	Tetrachloroethene	9.92E-01		8.49E-06			(mg/kg-day) ⁻¹	1.78E-08	2.97E-05		6.00E-03	3 3 ,	4.95E-03
				trans-1,2-Dichloroethene	9.92E-01 2.28E+00	μg/L	8.49E-06 2.91E-06	mg/kg-day	2.10E-03 NA	(Hig/kg-day) NA	1.78E-08 NA	2.97E-05 1.02E-05	mg/kg-day	2.00E-03		4.95E-03 5.08E-04
						μg/L		mg/kg-day				II .	mg/kg-day	5.00E-02		
				Trichloroethene	5.64E-01	μg/L	4.04E-06 2.62E-06	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	8.94E-08 1.89E-06	4.90E-06 1.97E-06	mg/kg-day			9.80E-03
				Vinyl Chloride	7.30E-01	μg/L	2.02E-06	mg/kg-day	7.20E-01	(mg/kg-day)	1.89E-06	1.97E-06	mg/kg-day	3.00E-03	mg/kg-day	6.58E-04
				Inorganics Aluminum	2.04E+03	/1	1.63E-04		NA	NA	NIA.	5.71E-04		4.005.00		5.71E-04
						μg/L		mg/kg-day		(mg/kg-day) ⁻¹	NA 4 FOE OZ		mg/kg-day	1.00E+00		
				Arsenic	3.80E+00	μg/L	3.04E-07	mg/kg-day	1.50E+00		4.56E-07	1.06E-06	mg/kg-day	3.00E-04	0 0 ,	3.54E-03
				Barium	2.04E+02	μg/L	1.63E-05	mg/kg-day	NA	NA	NA	5.70E-05	mg/kg-day	1.40E-02		4.07E-03
				Chromium	8.35E+00	μg/L	6.69E-07	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	3.35E-07	2.34E-06	mg/kg-day	7.50E-05		3.12E-02
				Cobalt	1.07E+00	μg/L	3.44E-08	mg/kg-day	NA	NA	NA	1.20E-07	mg/kg-day	3.00E-04		4.01E-04
				Copper	5.22E+01	μg/L	4.19E-06	mg/kg-day	NA	NA	NA	1.46E-05	mg/kg-day	4.00E-02	0 0 ,	
				Iron	8.20E+03	μg/L	6.57E-04	mg/kg-day	NA	NA	NA	2.30E-03	mg/kg-day	7.00E-01	mg/kg-day	3.28E-03
				Manganese	4.12E+02	μg/L	3.30E-05	mg/kg-day	NA	NA	NA	1.15E-04	mg/kg-day	5.60E-03		2.06E-02
				Vanadium	1.70E+01	μg/L	1.36E-06	mg/kg-day	NA	NA	NA	4.75E-06	mg/kg-day	1.82E-06	mg/kg-day	
	-		Exp. Route To								2.79E-06					2.69E+00
Groundwater	Groundwater	Groundwater	Inhalation	Volatile Organic Compounds												
				cis-1,2-Dichloroethene	5.45E+01	μg/L	1.41E+01	µg/m³	NA	NA	NA	7.12E-02	mg/m³	NA	NA .	NA
				Tetrachloroethene	9.92E-01	μg/L	2.27E-01	μg/m ³	2.60E-07	(µg/m ³) ⁻¹	5.91E-08	1.15E-03	mg/m³	4.00E-02	mg/m ³	2.88E-02
				trans-1,2-Dichloroethene	2.28E+00	μg/L	5.86E-01	μg/m ³	NA	NA	NA	2.97E-03	mg/m ³	6.00E-02	mg/m ³	4.95E-02
				Trichloroethene	5.64E-01	μg/L	4.56E-01	μg/m³	4.10E-06	(µg/m³) ⁻¹	8.78E-10	6.89E-04	mg/m ³	2.00E-03		3.44E-01
				Vinyl Chloride	7.30E-01	μg/L	1.20E+00	μg/m [°]	4.40E-06	(µg/m [°]) ⁻ '	5.26E-06	9.94E-04	mg/m [°]	1.00E-01	mg/m ⁻	9.94E-03
	-		Exp. Route To	tal					•		5.32E-06					4.32E-01
	1	Exposure Point							1.98E-04	i				2.29E+01		
		Enpoduro i Ollit	· · · · · ·								1.000 04	11				2.20E :01

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-7.8 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Receptor Population: Future

Construction Worker

Receptor Age: Adult

	Exposure	Exposure	Exposure		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	lation	
Medium	Medium	Point	Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposul	re Concentration	Slope Fa	ctor/Unit Risk	Cancer	Intake/ Exposur	e Concentration	RfD	D/RfC	Hazard
	Wediam	1 Oil it	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface/	Surface/	Puerto Rico	Ingestion	Inorganics												
Subsurface	Subsurface	Beverage		Aluminum	1.64E+04	mg/kg	3.02E-04	mg/kg-day	NA	NA	NA	2.12E-02	mg/kg-day	1.00E+00	mg/kg-day	2.12E-02
Soil	Soil			Arsenic	7.20E-01	mg/kg	1.33E-08	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.99E-08	9.30E-07	mg/kg-day	3.00E-04	mg/kg-day	3.10E-03
				Chromium	5.81E+00	mg/kg	1.07E-07	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	5.36E-08	7.50E-06	mg/kg-day	3.00E-03	mg/kg-day	2.50E-03
				Cobalt	8.12E+00	mg/kg	1.50E-07	mg/kg-day	NA	NA	NA	1.05E-05	mg/kg-day	3.00E-04	mg/kg-day	3.50E-02
				Iron	2.80E+04	mg/kg	5.16E-04	mg/kg-day	NA	NA	NA	3.61E-02	mg/kg-day	7.00E-01	mg/kg-day	5.16E-02
				Manganese	3.27E+02	mg/kg	6.03E-06	mg/kg-day	NA	NA	NA	4.22E-04	mg/kg-day	1.40E-01	mg/kg-day	3.02E-03
				Vanadium	8.55E+01	mg/kg	1.58E-06	mg/kg-day	NA	NA	NA	1.10E-04	mg/kg-day	7.00E-05	mg/kg-day	1.58E+00
			Exp. Route To	tal							7.35E-08					1.69E+00
Surface/	Surface/	Puerto Rico	Dermal	Inorganics												
Subsurface	Subsurface	Beverage	Contact	Aluminum	1.64E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
Soil	Soil			Arsenic	7.20E-01	mg/kg	1.20E-09	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.79E-09	8.37E-08	mg/kg-day	3.00E-04	mg/kg-day	2.79E-04
				Chromium	5.81E+00	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	8.12E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	2.80E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	3.27E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	8.55E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal							1.79E-09					2.79E-04
Surface/	Surface/	Puerto Rico	Inhalation	Inorganics												
Subsurface	Subsurface	Beverage		Aluminum	1.64E+04	mg/kg	1.57E-05	μg/m³	NA	NA	NA	1.10E-06	mg/m ³	5.00E-03	mg/m ³	2.20E-04
Soil	Soil			Arsenic	7.20E-01	mg/kg	6.91E-10	μg/m ³	4.30E-03	(µg/m ³) ⁻¹	2.97E-12	4.83E-11	mg/m ³	1.50E-05	mg/m ³	3.22E-06
				Chromium	5.81E+00	mg/kg	5.57E-09	μg/m³	1.20E-02	(µg/m³) ⁻¹	6.68E-11	3.90E-10	mg/m ³	1.00E-04	mg/m ³	3.90E-06
				Cobalt	8.12E+00	mg/kg	7.79E-09	μg/m³	9.00E-03	(µg/m ³) ⁻¹	7.01E-11	5.45E-10	mg/m ³	6.00E-06	mg/m ³	9.09E-05
				Iron	2.80E+04	mg/kg	2.68E-05	μg/m ³	NA	NA	NA	1.88E-06	mg/m ³	NA	NA	NA
				Manganese	3.27E+02	mg/kg	3.14E-07	μg/m³	NA	NA	NA	2.20E-08	mg/m ³	5.00E-05	mg/m ³	4.39E-04
				Vanadium	8.55E+01	mg/kg	8.20E-08	μg/m³	8.30E-03	(µg/m³)-1	6.80E-10	5.74E-09	mg/m³	1.00E-04	mg/m³	5.74E-05
			Exp. Route To	tal	•						8.20E-10				•	8.14E-04
		Exposure Point	Total		-	•				•	7.61E-08		-		-	1.69E+00
NA - not app		_		PfD = reference dose			ma/ka – milliara					ua/m³ – microar				

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-7.9 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

| Scenario Timeframe: Current/Future | Receptor Population: Recreational Users | Receptor Age: Adolescent (7-12 yrs)

	Exposure	Evacouro	Evposuro		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	lation	
Medium	Medium	Exposure Point	Exposure Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposur	e Concentration	RfE)/RfC	Hazard
	Modium	1 Oil It	rtoute		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Sediment	Sediment	Maunabo River	Ingestion	Inorganics												
				Arsenic	2.70E+00	mg/kg	3.08E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	4.62E-07	3.60E-06	mg/kg-day	3.00E-04	mg/kg-day	1.20E-02
				Chromium	4.69E+00	mg/kg	5.36E-07	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	2.68E-07	6.25E-06	mg/kg-day	3.00E-03	mg/kg-day	2.08E-03
				Cobalt	5.29E+00	mg/kg	6.03E-07	mg/kg-day	NA	NA	NA	7.04E-06	mg/kg-day	3.00E-04	mg/kg-day	2.35E-02
				Iron	1.05E+04	mg/kg	1.20E-03	mg/kg-day	NA	NA	NA	1.40E-02	mg/kg-day	7.00E-01	mg/kg-day	2.00E-02
				Manganese	3.10E+02	mg/kg	3.54E-05	mg/kg-day	NA	NA	NA	4.13E-04	mg/kg-day	1.40E-01	mg/kg-day	2.95E-03
				Vanadium	5.41E+01	mg/kg	6.18E-06	mg/kg-day	NA	NA	NA	7.21E-05	mg/kg-day	7.00E-05	mg/kg-day	1.03E+00
			Exp. Route To	tal							7.30E-07					1.09E+00
Sediment	Sediment	Maunabo River	Dermal	Inorganics												
			Contact	Arsenic	2.70E+00	mg/kg	8.14E-08	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.22E-07	9.49E-07	mg/kg-day	3.00E-04	mg/kg-day	3.16E-03
				Chromium	4.69E+00	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	5.29E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	1.05E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	3.10E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	5.41E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal	•				•		1.22E-07		•		•	3.16E-03
		Exposure Point	Total			_					8.52E-07					1.09E+00

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram

mg/kg-day = milligram per kilogram per day



TABLE B-7.9 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Recreational Users
Receptor Age: Adolescent (7-12 yrs)

	F.,,,,,,,,,,,	F.,,,,,,,,,,,	F		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	lation	
Medium	Exposure Medium	Exposure Point	Exposure Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fa	ctor/Unit Risk	Cancer	Intake/ Exposur	e Concentration	RfD)/RfC	Hazard
	Woodani	1 OII I	rtouto		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface	Maunabo River	Ingestion	Volatile Organic Compounds												
Water	Water			Bromodichloromethane	1.00E+00	μg/L	5.71E-08	mg/kg-day	6.20E-02	(mg/kg-day) ⁻¹	3.54E-09	6.66E-07	mg/kg-day	2.00E-02	mg/kg-day	3.33E-05
				Dibromochloromethane	1.30E+00	μg/L	7.42E-08	mg/kg-day	8.40E-02	(mg/kg-day) ⁻¹	6.23E-09	8.66E-07	mg/kg-day	2.00E-02	mg/kg-day	4.33E-05
	Exp. Route Total										9.77E-09					7.66E-05
Surface	Surface	Maunabo River	Dermal	Volatile Organic Compounds												
Water	Water		Contact	Bromodichloromethane	1.00E+00	μg/L	1.50E-07	mg/kg-day	6.20E-02	(mg/kg-day) ⁻¹	9.29E-09	1.75E-06	mg/kg-day	2.00E-02	mg/kg-day	8.74E-05
				Dibromochloromethane	1.30E+00	μg/L	1.81E-07	mg/kg-day	8.40E-02	(mg/kg-day) ⁻¹	1.52E-08	2.11E-06	mg/kg-day	2.00E-02	mg/kg-day	1.06E-04
	Exp. Route Total							•			2.45E-08			•	•	1.93E-04
		Exposure Point	Total								3.43E-08					2.69E-04

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram

mg/kg-day = milligram per kilogram per day



TABLE B-7.10

CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site

aunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

	Evpouro	Exposure	Exposure		Exposure	Point		Cancer	Risk Calcula	ation			Non-Cancer H	azard Calci	ulation	
Medium	Exposure Medium	Point	Route	Chemical of Potential Concern	Concenti	ration	Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposur	re Concentration	RfD	D/RfC	Hazard
	Medium	Foint	Noute		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface	Tap Water	Ingestion	Volatile Organic Compounds												
Water	Water		-	Bromodichloromethane	1.00E+00	μg/L	1.49E-05	mg/kg-day		(mg/kg-day) ⁻¹	9.22E-07	6.39E-05	mg/kg-day	2.00E-02	mg/kg-day	3.20E-03
				Dibromochloromethane	1.30E+00	μg/L	1.93E-05	mg/kg-day	8.40E-02	(mg/kg-day)	1.62E-06	8.31E-05	mg/kg-day	2.00E-02	mg/kg-day	4.16E-03
	Exp. Route Total										2.55E-06					7.35E-03
Surface	Surface	Tap Water	Dermal	Volatile Organic Compounds												
Water	Water		Contact	Bromodichloromethane	1.00E+00	μg/L	NA	NA	6.20E-02	(mg/kg-day) ⁻¹	NA	NA	NA	2.00E-02	mg/kg-day	NA
				Dibromochloromethane	1.30E+00	μg/L	NA	NA	8.40E-02	(mg/kg-day)	NA	NA	NA	2.00E-02	mg/kg-day	NA
			Exp. Route To	otal												
Surface	Surface	Tap Water	Inhalation	Volatile Organic Compounds												
Water	Water			Bromodichloromethane	1.00E+00	μg/L	2.49E-01	μg/m³	3.70E-05	(µg/m³)-1	9.21E-06	1.26E-03	mg/m³	NA	NA	NA
				Dibromochloromethane	1.30E+00	μg/L	3.22E-01	μg/m ⁻	2.70E-05	(µg/m³)-	8.69E-06	1.63E-03	mg/m ^o	NA	NA	NA
			Exp. Route To	tal						1.79E-05						
	-	Exposure Point	Total	-		•		-		-	2.04E-05			·	-	7.35E-03

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE B-8 CALCULATION OF RADIATION CANCER RISKS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe:	NA
Receptor Population:	NA
Receptor Age:	NA

Medium	Exposure Medium	Exposure Point	Exposure Route	Radionuclide of Potential Concern	Exposu	e Point	Risk Calculation Approach		Can	cer Risk Ca	lculation	
					Concer	tration		Intake/	Activity	Cancer SI	ope Factor	
					Value	Unit		Value	Unit	Value	Unit	Cancer Risk
			NOT			·	TI IIC CITI					
				APPLICABI	_ ⊏ ∣	\cup						
					1							
			Exp. Route Total									
		Exposure Point Total			•						•	
Ĭ		•	•				•	Total of	Receptor F	Risks Across	s All Media	

There are no radionucleotides in this risk assessment. As a result, this table is blank



TABLE B-9.1

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs $\,$

REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

	Exposure	Exposure			Can	cer Risk		Nonc	ancer Haza	rd Quotient	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Former	Semi-volatile Organic Compounds									
Soil	Soil	Sugar Mill	Benzo(a)pyrene	2E-07	1E-07	4E-12	3E-07	NA	NA	NA	NA	NA
			Dibenzo(a,h)anthracene	5E-08	4E-08	1E-12	9E-08	NA	NA	NA	NA	NA
			Inorganics									
			Aluminum	NA	NA	NA	NA	Neurological	1E-02	NA	5E-04	1E-02
			Arsenic	2E-06	4E-07	9E-10	2E-06	Skin/Developmental/	1E-02	2E-03	4E-05	1E-02
								Cardiovascular				
								System/CNS/Lung				
			Chromium	3E-06	NA	1E-08	3E-06	Lung	5E-03	NA	3E-05	5E-03
			Cobalt	NA	NA	5E-09	5E-09	Thyroid/Respiratory	3E-02	NA	2E-04	3E-02
								System/Lung				
			Iron	NA	NA	NA	NA	GI Tract	5E-02	NA	NA	5E-02
			Manganese	NA	NA	NA	NA	CNS	3E-03	NA	2E-03	5E-03
			Vanadium	NA	NA	3E-08	3E-08	Kidney/Respiratory System	9E-01	NA	1E-04	9E-01
	l ,		Chemical Total	5E-06	6E-07	5E-08	5E-06	Chemical Total	1E+00	2E-03	3E-03	1E+00
J		Exposure Po	int Total		•		5E-06		•	•		1E+00
	Exposure Me	dium Total					5E-06					1E+00
Medium Total	I	•	·			5E-06		-	<u>-</u>		1E+00	



TABLE B-9.1

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs

REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

	Exposure	Exposure			Can	cer Risk		Nonc	ancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			cis-1,2-Dichloroethene	NA	NA	NA	NA	Kidney	3E-01	NA	NA	3E-01
			Tetrachloroethene	7E-09	9E-09	2E-08	4E-08	Liver	2E-03	2E-03	7E-03	1E-02
			trans-1,2-Dichloroethene	NA	NA	NA	NA	Blood/Lung/Liver	1E-03	2E-04	1E-02	1E-02
			Trichloroethene	9E-08	3E-08	2E-07	4E-07	Heart/ Immunogical/ Developmental/Kidney	1E-02	4E-03	8E-02	1E-01
			Vinyl Chloride	2E-06	2E-07	4E-07	2E-06	Liver	2E-03	3E-04	2E-03	5E-03
			Inorganics									
			Aluminum	NA	NA	NA	NA	Neurological	2E-02	2E-04	NA	2E-02
			Arsenic	2E-05	2E-07	NA	2E-05	Skin/Developmental/ Cardiovascular System/CNS/Lung	1E-01	1E-03	NA	1E-01
			Barium	NA	NA	NA	NA	Kidney/Fetus	1E-02	1E-03	NA	1E-02
			Chromium	1E-05	2E-07	NA	1E-05	Lung	3E-02	1E-02	NA	4E-02
			Cobalt	NA	NA	NA	NA	Thyroid/Respiratory System/Lung	4E-02	1E-04	NA	4E-02
			Copper	NA	NA	NA	NA	GI Tract	1E-02	1E-04	NA	1E-02
			Iron	NA	NA	NA	NA	GI Tract	1E-01	1E-03	NA	1E-01
			Manganese	NA	NA	NA	NA	CNS	3E-02	8E-03	NA	4E-02
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+00	1E+00	NA	3E+00
			Chemical Total	4E-05	6E-07	6E-07	4E-05	Chemical Total	3E+00	1E+00	1E-01	4E+00
		Exposure Po	int Total				4E-05					4E+00
	Exposure Me	dium Total					4E-05			·		4E+00
Medium Total							4E-05					4E+00
Receptor Total	al					4E-05					5E+00	

Total Excess Cancer Risk Across All Media 4E-05

Total Hazard Index Across All Media

5

Blood HI Across All Media = 0.01 Liver HI Across All Media = 0.03 Kidney HI Across All Media = CNS HI Across All Media = 0.2

Development HI Across All Media = 0.2 Respiratory System HI Across All Media = 4

0.3 Lung HI Across All Media = Cardiovascular System HI Across All Media = 0.1 Skin HI Across All Media =

Heart HI Across All Media = 0.1 0.2 GI Tract HI Across All Media = 0.01

Fetus HI Across All Media =

NA = not applicable CNS = central nervous system GI = gastrointestinal



Page 2 of 2 6/28/2012

TABLE B-9.2 SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future Receptor Population: Trespasser

Receptor Age: Adolescent (7-12 yrs)

Madhan	Exposure	Exposure	Observing of Batantial Oscillar		Can	cer Risk		Nonc	ancer Haza	rd Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Former	Semi-volatile Organic Compounds									
Soil	Soil	Sugar Mill	Benzo(a)pyrene	3E-08	1E-08	1E-13	4E-08	NA	NA	NA	NA	NA
			Dibenzo(a,h)anthracene	9E-09	3E-09	3E-14	1E-08	NA	NA	NA	NA	NA
			Inorganics									
			Aluminum	NA	NA	NA	NA	Neurological	1E-02	NA	2E-03	1E-02
			Arsenic	4E-07	3E-08	2E-11	4E-07	Skin/Developmental/	9E-03	7E-04	1E-05	1E-02
								Cardiovascular System/CNS				
			Chromium	5E-07	NA	3E-10	5E-07	None reported	4E-03	NA	1E-04	4E-03
			Cobalt	NA	NA	1E-10	1E-10	Thyroid	2E-02	NA	1E-03	2E-02
			Iron	NA	NA	NA	NA	GI Tract	4E-02	NA	NA	4E-02
			Manganese	NA	NA	NA	NA	CNS	3E-03	NA	2E-03	5E-03
			Vanadium	NA	NA	8E-10	8E-10	Kidney/Respiratory	7E-01	NA	2E-06	7E-01
								System/Eyes				
			Chemical Total	9E-07	4E-08	1E-09	9E-07	Chemical Total	8E-01	7E-04	5E-03	8E-01
]		Exposure Po	int Total				9E-07		-		-	8E-01
	Exposure Me	dium Total					9E-07					8E-01
Medium Total						9E-07					8E-01	
Receptor Tota	al						9E-07					8E-01

Total Excess Cancer Risk Across All Media

9E-07

Total Hazard Index Across All Media

8.0

0.7

0.01

<0.01

0.7 0.7

0.04

Kidney HI Across All Media =

CNS HI Across All Media =

Development HI Across All Media =

Respiratory System HI Across All Media =

Eyes HI Across All Media =

Cardiovascular System HI Across All Media =

<0.01 Skin HI Across All Media = <0.01

GI Tract HI Across All Media =

NA = not applicable CNS = central nervous system GI = gastrointestinal



TABLE B-9.3

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Resident
Receptor Age: Lifetime

	Exposure	Exposure			Can	cer Risk		None	cancer Haza	rd Quotient	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Former	Semi-volatile Organic Compounds									
Soil	Soil	Sugar Mill	Benzo(a)pyrene	3E-06	1E-06	6E-11	4E-06	NA	NA	NA	NA	NA
			Dibenzo(a,h)anthracene	9E-07	3E-07	2E-11	1E-06	NA	NA	NA	NA	NA
			Inorganics									
			Aluminum	NA	NA	NA	NA	Neurological	2E-01	NA	2E-03	2E-01
			Arsenic	9E-06	8E-07	5E-09	9E-06	Skin/Developmental/	2E-01	1E-02	2E-04	2E-01
								Cardiovascular				
								System/CNS/Lung				
			Chromium	1E-05	NA	5E-08	1E-05	Lung	6E-02	NA	1E-04	6E-02
			Cobalt	NA	NA	2E-08	2E-08	Thyroid/Respiratory	4E-01	NA	1E-03	4E-01
			l.					System/Lung	75.04			75.04
			Iron	NA	NA	NA	NA	GI Tract	7E-01	NA	NA	7E-01
			Manganese	NA	NA	NA	NA	CNS	4E-02	NA	7E-03	5E-02
			Vanadium	NA	NA	2E-07	2E-07	Kidney/Respiratory System		NA	4E-04	1E+01
	l .		Chemical Total	2E-05	2E-06	2E-07	3E-05	Chemical Total	1E+01	1E-02	1E-02	1E+01
		Exposure Po	int Total				3E-05					1E+01
	Exposure Me	dium Total	·				3E-05					1E+01
Medium Total							3E-05					1E+01



TABLE B-9.3

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs

REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Resident

Receptor Age: Lifetime

	Exposure	Exposure			Can	cer Risk		None	cancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			cis-1,2-Dichloroethene	NA	NA	NA	NA	Kidney	2E+00	NA	NA	2E+00
			Tetrachloroethene	3E-08	2E-08	6E-08	1E-07	Liver	1E-02	5E-03	3E-02	4E-02
			trans-1,2-Dichloroethene	NA	NA	NA	NA	Blood/Lung/Liver	7E-03	5E-04	5E-02	6E-02
			Trichloroethene	6E-07	9E-08	9E-10	6E-07	Heart/ Immunogical/ Developmental/Kidney	7E-02	1E-02	3E-01	4E-01
			Vinyl Chloride Inorganics	4E-05	2E-06	5E-06	5E-05	Liver	2E-02	7E-04	1E-02	3E-02
			Aluminum	NA	NA	NA	NA	Neurological	1E-01	6E-04	NA	1E-01
			Arsenic	8E-05	5E-07	NA	9E-05	Skin/Developmental/ Cardiovascular System/CNS/Lung	8E-01	4E-03	NA	8E-01
			Barium	NA	NA	NA	NA	Kidney/Fetus	7E-02	4E-03	NA	7E-02
			Chromium	6E-05	3E-07	NA	6E-05	Lung	2E-01	3E-02	NA	2E-01
			Cobalt	NA	NA	NA	NA	Thyroid/Respiratory System/Lung	2E-01	4E-04	NA	2E-01
			Copper	NA	NA	NA	NA	GI Tract	8E-02	4E-04	NA	8E-02
			Iron	NA	NA	NA	NA	GI Tract	7E-01	3E-03	NA	8E-01
			Manganese	NA	NA	NA	NA	CNS	2E-01	2E-02	NA	2E-01
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+01	3E+00	NA	2E+01
			Chemical Total	2E-04	3E-06	5E-06	2E-04	Chemical Total	2E+01	3E+00	4E-01	2E+01
<u> </u>		Exposure Po	int Total			2E-04					2E+01	
	Exposure Me	dium Total					2E-04					2E+01
Medium Total				•	•		2E-04		•	•	•	2E+01
Receptor Total	al						2E-04				•	4E+01

Total Excess Cancer Risk Across All Media 2E-04 Total Hazard Index Across All Media 36

Blood HI Across All Media = 0.06 Liver HI Across All Media = 0.1 Kidney HI Across All Media = 32 CNS HI Across All Media = 1 Development HI Across All Media = 30 Respiratory System HI Across All Media = Lung HI Across All Media = Cardiovascular System HI Across All Media = 1 Skin HI Across All Media : Heart HI Across All Media = 0.4 2 GI Tract HI Across All Media = Fetus HI Across All Media = 0.07

NA = not applicable CNS = central nervous system GI = gastrointestinal



Page 2 of 2 6/28/2012

TABLE B-9.4 SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future

Receptor Population: Construction Worker

Receptor Age: Adult

Madiana	Exposure	Exposure	Chemical of Potential Concern		Can	cer Risk		None	cancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface/	Surface/	Former	Semi-volatile Organic Compounds									
Subsurface	Subsurface	Sugar Mill	Benzo(a)pyrene	6E-09	2E-09	5E-14	9E-09	NA	NA	NA	NA	NA
Soil	Soil		Dibenzo(a,h)anthracene	2E-09	9E-10	2E-14	3E-09	NA	NA	NA	NA	NA
			Inorganics									
			Aluminum	NA	NA	NA	NA	Neurological	2E-02	NA	2E-04	2E-02
			Arsenic	5E-08	5E-09	8E-12	6E-08	Skin/Developmental/	8E-03	7E-04	9E-06	9E-03
								Cardiovascular				
								System/CNS/Lung				
			Chromium	9E-08	NA	1E-10	9E-08	Lung	4E-03	NA	7E-06	4E-03
			Cobalt	NA	NA	9E-11	9E-11	Thyroid/Respiratory	5E-02	NA	1E-04	5E-02
								System/Lung				
			Iron	NA	NA	NA	NA	GI Tract	5E-02	NA	NA	5E-02
			Manganese	NA	NA	NA	NA	CNS	4E-03	NA	6E-04	5E-03
			Thallium	NA	NA	NA	NA	Skin/Hair	3E-02	NA	NA	3E-02
			Vanadium	NA	NA	8E-10	8E-10	Kidney/Respiratory System	2E+00	NA	6E-05	2E+00
	ļ		Chemical Total	2E-07	8E-09	1E-09	2E-07	Chemical Total	2E+00	7E-04	1E-03	2E+00
		Exposure Po	int Total				2E-07					2E+00
	Exposure Med	dium Total					2E-07					2E+00
Medium Total							2E-07					2E+00
Receptor Tota	al						2E-07					2E+00

Total Excess Cancer Risk Across All Media

2E-07

Total Hazard Index Across All Media

2

0.01

<0.01

2

0.06

<0.01

0.04

0.05

Kidney HI Across All Media = CNS HI Across All Media =

Development HI Across All Media =

Respiratory System HI Across All Media =

Lung HI Across All Media =

Cardiovascular System HI Across All Media =

Skin HI Across All Media = GI Tract HI Across All Media =

Hair HI Across All Media =

NA = not applicable

CNS = central nervous system

GI = gastrointestinal



TABLE B-9.5

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

	Exposure	Exposure			Can	cer Risk		None	ancer Haza	rd Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Puerto Rico	Inorganics									
Soil	Soil	Beverage	Aluminum	NA	NA	NA	NA	Neurological	1E-02	NA	4E-04	1E-02
			Arsenic	2E-06	3E-07	7E-10	2E-06	Skin/Developmental/	9E-03	2E-03	3E-05	1E-02
								Cardiovascular				
								System/CNS/Lung				
			Chromium	4E-06	NA	2E-08	4E-06	Lung	8E-03	NA	4E-05	8E-03
			Cobalt	NA	NA	3E-09	3E-09	Thyroid/Respiratory	2E-02	NA	2E-04	2E-02
								System/Lung				
			Iron	NA	NA	NA	NA	GI Tract	4E-02	NA	NA	4E-02
			Manganese	NA	NA	NA	NA	CNS	2E-03	NA	1E-03	4E-03
			Vanadium	NA	NA	3E-08	3E-08	Kidney/Respiratory System		NA	9E-05	8E-01
			Chemical Total	6E-06	3E-07	5E-08	6E-06	Chemical Total	9E-01	2E-03	2E-03	9E-01
		Exposure Po	int Total				6E-06					9E-01
	Exposure Me	dium Total					6E-06		•	•		9E-01
Medium Total	I						6E-06					9E-01



TABLE B-9.5

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs

REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

	Exposure	Exposure			Can	cer Risk		Nonc	ancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			cis-1,2-Dichloroethene	NA	NA	NA	NA	Kidney	3E-01	NA	NA	3E-01
			Tetrachloroethene	7E-09	9E-09	2E-08	4E-08	Liver	2E-03	2E-03	7E-03	1E-02
			trans-1,2-Dichloroethene	NA	NA	NA	NA	Blood/Lung/Liver	1E-03	2E-04	1E-02	1E-02
			Trichloroethene	9E-08	3E-08	2E-07	4E-07	Heart/ Immunogical/ Developmental/Kidney	1E-02	4E-03	8E-02	1E-01
			Vinyl Chloride	2E-06	2E-07	4E-07	2E-06	Liver	2E-03	3E-04	2E-03	5E-03
			Inorganics									
			Aluminum	NA	NA	NA	NA	Neurological	2E-02	2E-04	NA	2E-02
			Arsenic	2E-05	2E-07	NA	2E-05	Skin/Developmental/ Cardiovascular System/CNS/Lung	1E-01	1E-03	NA	1E-01
			Barium	NA	NA	NA	NA	Kidney/Fetus	1E-02	1E-03	NA	1E-02
			Chromium	1E-05	2E-07	NA	1E-05	Lung	3E-02	1E-02	NA	4E-02
			Cobalt	NA	NA	NA	NA	Thyroid/Respiratory System/Lung	4E-02	1E-04	NA	4E-02
			Copper	NA	NA	NA	NA	GI Tract	1E-02	1E-04	NA	1E-02
			Iron	NA	NA	NA	NA	GI Tract	1E-01	1E-03	NA	1E-01
			Manganese	NA	NA	NA	NA	CNS	3E-02	8E-03	NA	4E-02
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+00	1E+00	NA	3E+00
			Chemical Total	4E-05	6E-07	6E-07	4E-05	Chemical Total	3E+00	1E+00	1E-01	4E+00
		Exposure Po	int Total				4E-05					4E+00
	Exposure Me	dium Total					4E-05			·		4E+00
Medium Total							4E-05					4E+00
Receptor Total	al					4E-05			·		5E+00	

Total Excess Cancer Risk Across All Media 4E-05

Total Hazard Index Across All Media

0.01

0.03

0.01

Blood HI Across All Media = Liver HI Across All Media =

Kidney HI Across All Media = 4

CNS HI Across All Media = 0.2

Development HI Across All Media = 0.2

Respiratory System HI Across All Media = 4

Lung HI Across All Media = 0.3

Cardiovascular System HI Across All Media = 0.1

Skin HI Across All Media =	0.1
Heart HI Across All Media =	0.1
GI Tract HI Across All Media =	0.2

Fetus HI Across All Media =

NA = not applicable CNS = central nervous system GI = gastrointestinal



Page 2 of 2 6/28/2012

TABLE B-9.6 SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Trespasser

Receptor Age: Adolescent (7-12 yrs)

Medium	Exposure Medium	Exposure Point	Chemical of Potential Concern	Cancer Risk				Noncancer Hazard Quotient				
				Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Puerto Rico	Inorganics									
Soil	Soil	Beverage	Aluminum	NA	NA	NA	NA	Neurological	1E-02	NA	2E-03	1E-02
			Arsenic	3E-07	2E-08	2E-11	3E-07	Skin/Developmental/	7E-03	6E-04	1E-05	8E-03
								Cardiovascular System/CNS				
			Chromium	8E-07	NA	4E-10	8E-07	None reported	6E-03	NA	2E-04	7E-03
			Cobalt	NA	NA	8E-11	8E-11	Thyroid	2E-02	NA	8E-04	2E-02
			Iron	NA	NA	NA	NA	GI Tract	3E-02	NA	NA	3E-02
			Manganese	NA	NA	NA	NA	CNS	2E-03	NA	2E-03	3E-03
			Vanadium	NA	NA	7E-10	7E-10	Kidney/Respiratory	6E-01	NA	1E-06	6E-01
								System/Eyes				
			Chemical Total	1E-06	2E-08	1E-09	1E-06	Chemical Total	7E-01	6E-04	4E-03	7E-01
Exposure Point Total						1E-06		•	·		7E-01	
Exposure Medium Total							1E-06		•			7E-01
Medium Total							1E-06					7E-01
Receptor Total							1E-06					7E-01

Total Excess Cancer Risk Across All Media 1E-06 Total Hazard Index Across All Media 0.7

Kidney HI Across All Media = 0.6

CNS HI Across All Media = 0.01

Development HI Across All Media = <0.01
Respiratory System HI Across All Media = 0.6

Eyes HI Across All Media = 0.6

Cardiovascular System HI Across All Media = <0.01

Skin HI Across All Media = <0.01
GI Tract HI Across All Media = 0.03

NA = not applicable CNS = central nervous system GI = gastrointestinal



TABLE B-9.7

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site

aunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

	Exposure	Exposure			Can	cer Risk		Nonc	ancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Puerto Rico	Inorganics									
Soil	Soil	Beverage	Aluminum	NA	NA	NA	NA	Neurological	2E-01	NA	2E-03	2E-01
			Arsenic	7E-06	6E-07	4E-09	7E-06	Skin/Developmental/	1E-01	1E-02	1E-04	1E-01
								Cardiovascular				
								System/CNS/Lung				
			Chromium	2E-05	NA	9E-08	2E-05	Lung	1E-01	NA	2E-04	1E-01
			Cobalt	NA	NA	2E-08	2E-08	Thyroid/Respiratory	3E-01	NA	7E-04	3E-01
								System/Lung				
			Iron	NA	NA	NA	NA	GI Tract	5E-01	NA	NA	5E-01
			Manganese	NA	NA	NA	NA	CNS	3E-02	NA	5E-03	4E-02
			Vanadium	NA	NA	1E-07	1E-07	Kidney/Respiratory System	1E+01	NA	4E-04	1E+01
			Chemical Total	3E-05	6E-07	3E-07	3E-05	Chemical Total	1E+01	1E-02	8E-03	1E+01
		Exposure Po	int Total				3E-05					1E+01
	Exposure Medium Total											1E+01
Medium Tota							3E-05					1E+01



TABLE B-9.7

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

	Exposure	Exposure			Can	cer Risk		None	ancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			cis-1,2-Dichloroethene	NA	NA	NA	NA	Kidney	2E+00	NA	NA	2E+00
			Tetrachloroethene	3E-08	2E-08	6E-08	1E-07	Liver	1E-02	5E-03	3E-02	4E-02
			trans-1,2-Dichloroethene	NA	NA	NA	NA	Blood/Lung/Liver	7E-03	5E-04	5E-02	6E-02
			Trichloroethene	6E-07	9E-08	9E-10	6E-07	Heart/ Immunogical/ Developmental/Kidney	7E-02	1E-02	3E-01	4E-01
			Vinyl Chloride Inorganics	4E-05	2E-06	5E-06	5E-05	Liver	2E-02	7E-04	1E-02	3E-02
			Aluminum	NA	NA	NA	NA	Neurological	1E-01	6E-04	NA	1E-01
			Arsenic	8E-05	5E-07	NA	9E-05	Skin/Developmental/ Cardiovascular System/CNS/Lung	8E-01	4E-03	NA	8E-01
			Barium	NA	NA	NA	NA	Kidney/Fetus	7E-02	4E-03	NA	7E-02
			Chromium	6E-05	3E-07	NA	6E-05	Lung	2E-01	3E-02	NA	2E-01
			Cobalt	NA	NA	NA	NA	Thyroid/Respiratory System/Lung	2E-01	4E-04	NA	2E-01
			Copper	NA	NA	NA	NA	GI Tract	8E-02	4E-04	NA	8E-02
			Iron	NA	NA	NA	NA	GI Tract	7E-01	3E-03	NA	8E-01
			Manganese	NA	NA	NA	NA	CNS	2E-01	2E-02	NA	2E-01
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+01	3E+00	NA	2E+01
			Chemical Total	2E-04	3E-06	5E-06	2E-04	Chemical Total	2E+01	3E+00	4E-01	2E+01
		Exposure Po	int Total				2E-04					2E+01
	Exposure Me	dium Total					2E-04					2E+01
Medium Total				•			2E-04		•	•		2E+01
Receptor Total	al				2E-04		•	•		3E+01		

Total Excess Cancer Risk Across All Media 2E-04 Total Hazard Index Across All Media 34

Blood HI Across All Media = 0.06 Liver HI Across All Media = 0.1 Kidney HI Across All Media = 31 CNS HI Across All Media = 1 Development HI Across All Media = 29 Respiratory System HI Across All Media = Lung HI Across All Media = Cardiovascular System HI Across All Media = 0.9 Skin HI Across All Media = Heart HI Across All Media = 0.4 GI Tract HI Across All Media = Fetus HI Across All Media = 0.07

NA = not applicable CNS = central nervous system GI = gastrointestinal



Page 2 of 2 6/28/2012

TABLE B-9.8 SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future

Receptor Population: Construction Worker

Receptor Age: Adult

	Exposure	Exposure			Can	cer Risk		None	ancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface/	Surface/	Puerto Rico	Inorganics									
Subsurface	Subsurface	Beverage	Aluminum	NA	NA	NA	NA	Neurological	2E-02	NA	2E-04	2E-02
Soil	Soil		Arsenic	2E-08	2E-09	3E-12	2E-08	Skin/Developmental/ Cardiovascular System/CNS/Lung	3E-03	3E-04	3E-06	3E-03
			Chromium	5E-08	NA	7E-11	5E-08	Lung	2E-03	NA	4E-06	3E-03
			Cobalt	NA	NA	7E-11	7E-11	Thyroid/Respiratory System/Lung	3E-02	NA	9E-05	4E-02
			Iron	NA	NA	NA	NA	GI Tract	5E-02	NA	NA	5E-02
			Manganese	NA	NA	NA	NA	CNS	3E-03	NA	4E-04	3E-03
			Vanadium	NA	NA	7E-10	7E-10	Kidney/Respiratory System	2E+00	NA	6E-05	2E+00
			Chemical Total	7E-08	2E-09	8E-10	8E-08	Chemical Total	2E+00	3E-04	8E-04	2E+00
		Exposure Poi	nt Total		•		8E-08		·	•		2E+00
	Exposure Medium Total									•		2E+00
Medium Total				•		8E-08			•		2E+00	
Receptor Total	al						8E-08					2E+00

Total Excess Cancer Risk Across All Media 8E-08

Total Hazard Index Across All Media

2

2

<0.01

0.05

Kidney HI Across All Media =

CNS HI Across All Media = <0.01

Development HI Across All Media = <0.01

Respiratory System HI Across All Media = 2

Lung HI Across All Media = 0.04
ystem HI Across All Media = <0.01

Cardiovascular System HI Across All Media =

Skin HI Across All Media = GI Tract HI Across All Media =

NA = not applicable CNS = central nervous system GI = gastrointestinal



Page 1 of 1 6/28/2012

TABLE B-9.9 SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future Receptor Population: Recreational Users Receptor Age: Adolescent (7-12 yrs)

	Exposure	Exposure			Can	cer Risk		Nonc	ancer Haza	ırd Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Sediment	Sediment	Maunabo	Inorganics									
		River	Arsenic	5E-07	1E-07	NA	6E-07	Skin	1E-02	3E-03	NA	2E-02
			Chromium	3E-07	NA	NA	3E-07	None reported	2E-03	NA	NA	2E-03
			Cobalt	NA	NA	NA	NA	Thyroid	2E-02	NA	NA	2E-02
			Iron	NA	NA	NA	NA	GI Tract	2E-02	NA	NA	2E-02
			Manganese	NA	NA	NA	NA	CNS	3E-03	NA	NA	3E-03
			Vanadium	NA	NA	NA	NA	Kidney	1E+00	NA	NA	1E+00
			Chemical Total	7E-07	1E-07		9E-07	Chemical Total	1E+00	3E-03		1E+00
		Exposure I	Point Total				9E-07					1E+00
	Exposure Me	dium Total					9E-07					1E+00
Medium To	otal						9E-07					1E+00
Surface	Surface	Maunabo	Volatile Organic Compounds									
Water	Water	River	Bromodichloromethane	4E-09	9E-09	NA	1E-08	Liver	3E-05	9E-05	NA	1E-04
			Dibromochloromethane	6E-09	2E-08	NA	2E-08	Liver	4E-05	1E-04	NA	1E-04
			Chemical Total	1E-08	2E-08		3E-08	Chemical Total	8E-05	2E-04		3E-04
		Exposure I	Point Total				3E-08					3E-04
	Exposure Me	dium Total			3E-08					3E-04		
Medium To	tal						3E-08					3E-04
Receptor T	otal		-				9E-07		•			1E+00

Total Excess Cancer Risk Across All Media

9E-07

Total Hazard Index Across All Media

Liver HI Across All Media = Kidney HI Across All Media =

<0.01 CNS HI Across All Media = <0.01 0.02

0.02

Skin HI Across All Media =

GI Tract HI Across All Media =

NA = not applicable CNS = central nervous system GI = gastrointestinal



Page 1 of 1 6/28/2012

TABLE B-9.10 SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCS REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

Marken	Exposure	Exposure	Observing to C. Partential Occurren		Can	cer Risk		None	cancer Haza	rd Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	•	Primary	Ingestion	Dermal	Inhalation	
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Tap Water	Volatile Organic Compounds									
Water	Water		Bromodichloromethane	9E-07	NA	9E-06	1E-05	Liver	3E-03	NA	NA	3E-03
			Dibromochloromethane	2E-06	NA	9E-06	1E-05	Liver	4E-03	NA	NA	4E-03
			Chemical Total	3E-06		2E-05	2E-05	Chemical Total	7E-03			7E-03
		Exposure Po	int Total	·			2E-05					7E-03
	Exposure Medium Total											7E-03
Medium Tota	um Total											7E-03
Receptor Tot	al						2E-05					7E-03

Total Excess Cancer Risk Across All Media

2E-05

Total Hazard Index Across All Media

0.007

Liver HI Across All Media =

<0.01

NA = not applicable

CNS = central nervous system

GI = gastrointestinal



TABLE B-10.1 RISK ASSESSMENT SUMMARY REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

NA - diam-	Exposure	Exposure	Observing of Datastics Occupan		Can	cer Risk		None	cancer Haza	ırd Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Former	Inorganics									
Soil	Soil	Sugar Mill	Arsenic	2E-06	4E-07	9E-10	2E-06	Skin/Developmental/ Cardiovascular System/CNS/Lung	1E-02	2E-03	4E-05	1E-02
			Chromium	3E-06	NA	1E-08	3E-06	Lung	5E-03	NA	3E-05	5E-03
			Chemical Total	5E-06	6E-07	5E-08	5E-06	Chemical Total	1E+00	2E-03	3E-03	1E+00
		Exposure Po	nt Total				5E-06					1E+00
	Exposure Medium Total						5E-06					1E+00
Medium Tota							5E-06					1E+00
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			Vinyl Chloride	2E-06	2E-07	4E-07	2E-06	Liver	2E-03	3E-04	2E-03	5E-03
			Inorganics									
			Arsenic	2E-05	2E-07	NA	2E-05	Skin/Developmental/ Cardiovascular System/CNS/Lung	1E-01	1E-03	NA	1E-01
			Chromium	1E-05	2E-07	NA	1E-05	Lung	3E-02	1E-02	NA	4E-02
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+00	1E+00	NA	3E+00
			Chemical Total	4E-05	6E-07	6E-07	4E-05	Chemical Total	3E+00	1E+00	1E-01	4E+00
	Exposure Point Total											4E+00
	Exposure Medium Total											4E+00
Medium Total	I				4E-05					4E+00		
Receptor Total	al			-			4E-05		-	-		5E+00

Total Excess Cancer Risk Across All Media

4E-05

Total Hazard Index Across All Media

5

Kidney HI Across All Media = Respiratory System HI Across All Media =

5 4

NA = not applicable

CNS = central nervous system

GI = gastrointestinal

Note:



TABLE B-10.2 RISK ASSESSMENT SUMMARY REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future Receptor Population: Trespasser

Receptor Age: Adolescent (7-12 yrs)

Madisus	Exposure	Exposure	Chamical of Detection Conserve		Can	cer Risk		None	cancer Haza	rd Quotient		
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
		rface Soil Former Chemical Total		Contact		Routes Total	Target Organ(s)		Contact		Routes Total	
Surface Soil	Surface Soil		Chemical Total	9E-07				Chemical Total	8E-01	7E-04	5E-03	8E-01
		Sugar Mill										
1		Exposure Po	int Total				9E-07					8E-01
	Exposure Medium Total											8E-01
Medium Tota	dium Total											8E-01
Receptor Total	al				•		9E-07			•	·	8E-01

Total Excess Cancer Risk Across All Media

9E-07

Total Hazard Index Across All Media

0.8

Note:



TABLE B-10.3 RISK ASSESSMENT SUMMARY REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Resident
Receptor Age: Lifetime

Medium	Exposure	Exposure	Chemical of Potential Concern		Can	cer Risk		None	cancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Former	Semi-volatile Organic Compounds									
Soil	Soil	Sugar Mill	Benzo(a)pyrene	3E-06	1E-06	6E-11	4E-06	NA	NA	NA	NA	NA
			Dibenzo(a,h)anthracene	9E-07	3E-07	2E-11	1E-06	NA	NA	NA	NA	NA
			Inorganics									
			Arsenic	9E-06	8E-07	5E-09	9E-06	Skin/Developmental/	2E-01	1E-02	2E-04	2E-01
								Cardiovascular				
				45.05			45.05	System/CNS/Lung	05.00		45.04	05.00
			Chromium	1E-05 NA	NA NA	5E-08	1E-05	Lung	6E-02	NA	1E-04 4E-04	6E-02
			Vanadium Chemical Total	2E-05	2E-06	2E-07 2E-07	2E-07 3E-05	Kidney/Respiratory System Chemical Total	1E+01 1E+01	NA 1E-02	4E-04 1E-02	1E+01 1E+01
	ı	Exposure Po		2E-05	2E-06	2E-07	3E-05	Chemical Total	1E+01	1E-02	TE-02	1E+01
ll r	E		int rotal									
	Exposure Me	dium i otai					3E-05					1E+01
Medium Total				1		<u> </u>	3E-05		1	r	1	1E+01
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds	NIA	NI A	N1.0		16.1	05.00		N10	05.00
			cis-1,2-Dichloroethene	NA 45.05	NA of oo	NA 55.00	NA 55.05	Kidney	2E+00	NA 75.04	NA 45.00	2E+00
			Vinyl Chloride	4E-05	2E-06	5E-06	5E-05	Liver	2E-02	7E-04	1E-02	3E-02
			Inorganics Arsenic	8E-05	5E-07	NA	9E-05	Skin/Developmental/	8E-01	4E-03	NA	8E-01
			Alsenic	0E-03	3E-07	INA	9⊑-03	Cardiovascular	0E-01	46-03	INA	0E-01
								System/CNS/Lung				
			Chromium	6E-05	3E-07	NA	6E-05	Lung	2E-01	3E-02	NA	2E-01
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+01	3E+00	NA	2E+01
			Chemical Total	2E-04	3E-06	5E-06	2E-04	Chemical Total	2E+01	3E+00	4E-01	2E+01
		Exposure Po	int Total				2E-04					2E+01
	Exposure Me	dium Total				2E-04					2E+01	
Medium Total						2E-04					2E+01	
Receptor Tota	al						2E-04					4E+01

Total Excess Cancer Risk Across All Media 2E-04 Total Hazard Index Across All Media

NA = not applicable CNS = central nervous system GI = gastrointestinal

Note:

Only chemicals above EPA's threshold values are listed in this table



36

TABLE B-10.4 RISK ASSESSMENT SUMMARY REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future

Receptor Population: Construction Worker

Receptor Age: Adult

No diame	Exposure	Exposure	Observing to 4 Particular Community		Can	cer Risk		None	cancer Haza	rd Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
	Surface/ Surface/ Former				Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface/	Surface/	Former	Inorganics									
Subsurface	Subsurface	Sugar Mill	Vanadium	NA	NA	8E-10	8E-10	Kidney/Respiratory System	2E+00	NA	6E-05	2E+00
Soil	Soil		Chemical Total	2E-07	8E-09	1E-09	2E-07	Chemical Total	2E+00	7E-04	1E-03	2E+00
		Exposure Po	int Total				2E-07					2E+00
	Exposure Medium Total											2E+00
Medium Total												2E+00
Receptor Total	al						2E-07					2E+00

Total Excess Cancer Risk Across All Media

Total Hazard Index Across All Media

Kidney HI Across All Media =

2 Respiratory System HI Across All Media =

NA = not applicable

CNS = central nervous system

GI = gastrointestinal

Note:



TABLE B-10.5 RISK ASSESSMENT SUMMARY REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

	Exposure	Exposure			Can	cer Risk		None	cancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Puerto Rico	Inorganics									
Soil	Soil		Arsenic	2E-06	3E-07	7E-10	2E-06	Skin/Developmental/ Cardiovascular System/CNS/Lung	9E-03	2E-03	3E-05	1E-02
			Chromium	4E-06	NA	2E-08	4E-06	Lung	8E-03	NA	4E-05	8E-03
			Chemical Total	6E-06	3E-07	5E-08	6E-06	Chemical Total	9E-01	2E-03	2E-03	9E-01
		Exposure Po		02 00	0L 01	02 00	6E-06	CHOIMICA TOTAL	02 01	22 00	EL 00	9E-01
	Exposure Me	<u> </u>					6E-06					9E-01
Medium Total		wedium i otal					6E-06					9E-01
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									<u>'</u>
			Vinyl Chloride	2E-06	2E-07	4E-07	2E-06	Liver	2E-03	3E-04	2E-03	5E-03
			Inorganics									
			Arsenic	2E-05	2E-07	NA	2E-05	Skin/Developmental/ Cardiovascular System/CNS/Lung	1E-01	1E-03	NA	1E-01
			Chromium	1E-05	2E-07	NA	1E-05	Lung	3E-02	1E-02	NA	4E-02
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+00	1E+00	NA	3E+00
	ı		Chemical Total	4E-05	6E-07	6E-07	4E-05	Chemical Total	3E+00	1E+00	1E-01	4E+00
	Exposure Point Total						4E-05					4E+00
	Exposure Medium Total											4E+00
Medium Total					4E-05					4E+00		
Receptor Tota	al		-				4E-05					5E+00

Total Excess Cancer Risk Across All Media

4E-05

Total Hazard Index Across All Media

5

Kidney HI Across All Media = Respiratory System HI Across All Media =

= 4

NA = not applicable

CNS = central nervous system

GI = gastrointestinal

Note:



TABLE B-10.6 RISK ASSESSMENT SUMMARY REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future Receptor Population: Trespasser

Receptor Age: Adolescent (7-12 yrs)

Madium	Exposure	Exposure	Chaminal of Datastial Canasan		Can	cer Risk		None	cancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
		ce Soil Puerto Rico Chemical Total			Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface Soil	Surface Soil	Puerto Rico	erto Rico Chemical Total 1E-06 2E-08 1E-				1E-06	Chemical Total	7E-01	6E-04	4E-03	7E-01
		Beverage										
		Exposure Poi	nt Total				1E-06					7E-01
	Exposure Medium Total											7E-01
Medium Tota	dium Total											7E-01
Receptor Total	al			•		1E-06				·	7E-01	

Total Excess Cancer Risk Across All Media

1E-06

Total Hazard Index Across All Media

0.7

Note:



TABLE B-10.7 RISK ASSESSMENT SUMMARY REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

Mandings	Exposure	Exposure	Chaminal of Datastial Consum		Can	cer Risk		None	cancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Puerto Rico	Inorganics									
Soil	Soil	Beverage	Arsenic	7E-06	6E-07	4E-09	7E-06	Skin/Developmental/	1E-01	1E-02	1E-04	1E-01
								Cardiovascular System/CNS/Lung				
			Chromium	2E-05	NA	9E-08	2E-05	Lung	1E-01	NA	2E-04	1E-01
			Vanadium	NA	NA	1E-07	1E-07	Kidney/Respiratory System	1E+01	NA	4E-04	1E+01
			Chemical Total	3E-05	6E-07	3E-07	3E-05	Chemical Total	1E+01	1E-02	8E-03	1E+01
		Exposure Poi	int Total				3E-05					1E+01
	Exposure Medium Total						3E-05					1E+01
Medium Total							3E-05					1E+01
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			cis-1,2-Dichloroethene	NA	NA	NA	NA	Kidney	2E+00	NA	NA	2E+00
			Vinyl Chloride	4E-05	2E-06	5E-06	5E-05	Liver	2E-02	7E-04	1E-02	3E-02
			Inorganics									
			Arsenic	8E-05	5E-07	NA	9E-05	Skin/Developmental/ Cardiovascular System/CNS/Lung	8E-01	4E-03	NA	8E-01
			Chromium	6E-05	3E-07	NA	6E-05	Lung	2E-01	3E-02	NA	2E-01
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+01	3E+00	NA	2E+01
			Chemical Total	2E-04	3E-06	5E-06	2E-04	Chemical Total	2E+01	3E+00	4E-01	2E+01
		Exposure Po	int Total				2E-04					2E+01
	Exposure Me	dium Total			2E-04					2E+01		
Medium Total							2E-04					2E+01
Receptor Total	al						2E-04					3E+01

Total Excess Cancer Risk Across All Media 2E-04 Total Hazard Index Across All Media

NA = not applicable CNS = central nervous system GI = gastrointestinal

Note:

Only chemicals above EPA's threshold values are listed in this table



34

TABLE B-10.8 RISK ASSESSMENT SUMMARY REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future

Receptor Population: Construction Worker

Receptor Age: Adult

Exposure		e Exposure	Observing to C. Partential Occurren	Cancer Risk				Noncancer Hazard Quotient				
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface/	Surface/	Puerto Rico	Inorganics									
Subsurface	Subsurface	Beverage	Vanadium	NA	NA	7E-10	7E-10	Kidney/Respiratory System	2E+00	NA	6E-05	2E+00
Soil	Soil		Chemical Total	7E-08	2E-09	8E-10	8E-08	Chemical Total	2E+00	3E-04	8E-04	2E+00
		Exposure Po	int Total				8E-08					2E+00
	Exposure Me	dium Total					8E-08					2E+00
Medium Total				8E-08					2E+00			
Receptor Total	al						8E-08			•	•	2E+00

Total Excess Cancer Risk Across All Media

8E-08

Total Hazard Index Across All Media

Kidney HI Across All Media =

2 Respiratory System HI Across All Media =

NA = not applicable

CNS = central nervous system

GI = gastrointestinal

Note:



TABLE B-10.9 RISK ASSESSMENT SUMMARY REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Recreational Users

Receptor Age: Adolescent (7-12 yrs)

	Exposure	Exposure		Cancer Risk			Noncancer Hazard Quotient					
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Sediment	Sediment	Maunabo	Inorganics									
		River	Vanadium	NA	NA	NA	NA	Kidney	1E+00	NA	NA	1E+00
			Chemical Total	7E-07	1E-07		9E-07	Chemical Total	1E+00	3E-03		1E+00
		Exposure f	Point Total				9E-07					1E+00
	Exposure Me	dium Total					9E-07					1E+00
Medium To	tal						9E-07					1E+00
Surface Water	Surface Water	Maunabo River	Chemical Total	1E-08	2E-08		3E-08	Chemical Total	8E-05	2E-04		3E-04
		Exposure I	Point Total				3E-08					3E-04
	Exposure Medium Total			3E-08					3E-04			
Medium Total			3E-08					3E-04				
Receptor T	otal						9E-07					1E+00

Total Excess Cancer Risk Across All Media

Total Hazard Index Across All Media

Kidney HI Across All Media = 1

NA = not applicable

CNS = central nervous system

GI = gastrointestinal

9E-07

Note:



TABLE B-10.10 RISK ASSESSMENT SUMMARY REASONABLE MAXIMUM EXPOSURE

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

Exposure Expo		Exposure	posure	Cancer Risk			Noncancer Hazard Quotient					
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Tap Water	Volatile Organic Compounds									
Water	Water		Bromodichloromethane	9E-07	NA	9E-06	1E-05	Liver	3E-03	NA	NA	3E-03
			Dibromochloromethane	2E-06	NA	9E-06	1E-05	Liver	4E-03	NA	NA	4E-03
			Chemical Total	3E-06		2E-05	2E-05	Chemical Total	7E-03			7E-03
		Exposure Po	int Total				2E-05					7E-03
	Exposure Medium Total				2E-05					7E-03		
Medium Total				2E-05					7E-03			
Receptor Total	al						2E-05					7E-03

Total Excess Cancer Risk Across All Media

2E-05

Total Hazard Index Across All Media

0.007

NA = not applicable

CNS = central nervous system

GI = gastrointestinal

Note:



Appendix C ProUCL Output for Chemicals of Potential Concern

Appendix C Contents Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

- C-1 ProUCL Output Surface Soil at Former Sugar Mill
- C-2 ProUCL Output Surface Soil at Puerto Rico Beverage
- C-3 ProUCL Output Surface/Subsurface Soil at Former Sugar Mill
- C-4 ProUCL Output Surface/Subsurface Soil at Puerto Rico Beverage
- C-5 ProUCL Output Groundwater
- C-6 ProUCL Output Surface Water
- C-7 ProUCL Output Sediment



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

General UCL Statistics for Data Sets with Non-Detects

User Selected Options

From File SS-FSM.wst

Full Precision OFF
Confidence Coefficient 95%
Number of Bootstrap Operations 2000

Benzo(a)pyrene

General Statistics

Paw Statistics		Log-transformed Statistics	
		Percent Non-Detects	33.33%
Number of Distinct Detected Data	4	Number of Non-Detect Data	2
Number of Valid Data	6	Number of Detected Data	4

Raw Statistics	Log-transformed Statistics						
Minimum Detected	7.9	Minimum Detected	2.067				
Maximum Detected	76	Maximum Detected	4.331				
Mean of Detected	33.33	Mean of Detected	3.082				
SD of Detected	32.07	SD of Detected	1.105				
Minimum Non-Detect	96	Minimum Non-Detect	4.564				
Maximum Non-Detect	96	Maximum Non-Detect	4.564				

Warning: There are only 4 Distinct Detected Values in this data

Note: It should be noted that even though bootstrap may be performed on this data set the resulting calculations may not be reliable enough to draw conclusions

It is recommended to have 10-15 or more distinct observations for accurate and meaningful results.

UCL Statistics

Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Only	,
Shapiro Wilk Test Statistic	0.874	Shapiro Wilk Test Statistic	0.882
5% Shapiro Wilk Critical Value	0.748	5% Shapiro Wilk Critical Value	0.748
Data appear Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	38.22	Mean	3.345
SD	25.97	SD	0.948
95% DL/2 (t) UCL	59.58	95% H-Stat (DL/2) UCL	235.8
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE method failed to converge properly		Mean in Log Scale	3.082
		SD in Log Scale	0.945
		Mean in Original Scale	30.99
		SD in Original Scale	26.78
		95% t UCL	53.02
		95% Percentile Bootstrap UCL	47.8
		95% BCA Bootstrap UCL	53.08
		95% H-UCL	179



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Only	Data Distribution Test with Detected Values Only		
k star (bias corrected)	0.497	Data appear Normal at 5% Significance Level	
Theta Star	67.11		
nu star	3.973		
A-D Test Statistic	0.392	Nonparametric Statistics	
5% A-D Critical Value	0.664	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.664	Mean	33.33
5% K-S Critical Value	0.401	SD	27.77
Data appear Gamma Distributed at 5% Significance Le	vel	SE of Mean	16.03
		95% KM (t) UCL	65.63
Assuming Gamma Distribution		95% KM (z) UCL	59.7
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	67.38
Minimum	7.9	95% KM (bootstrap t) UCL	80.54
Maximum	76	95% KM (BCA) UCL	58
Mean	32.41	95% KM (Percentile Bootstrap) UCL	58.98
Median	25.27	95% KM (Chebyshev) UCL	103.2
SD	27.92	97.5% KM (Chebyshev) UCL	133.4
k star	0.846	99% KM (Chebyshev) UCL	192.8
Theta star	38.31		
Nu star	10.15	Potential UCLs to Use	
AppChi2	4.036	95% KM (t) UCL	65.63
95% Gamma Approximate UCL	81.5	95% KM (Percentile Bootstrap) UCL	58.98
95% Adjusted Gamma UCL	N/A		

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006).

For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Dibenzo(a,h)anthracene

General Statistics	
6	Niveni

Number of Valid Data	6	Number of Detected Data	2
Number of Distinct Detected Data	2	Number of Non-Detect Data	4
		Percent Non-Detects	66.67%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	12	Minimum Detected	2.485
Maximum Detected	18	Maximum Detected	2.89
Mean of Detected	15	Mean of Detected	2.688
SD of Detected	4.243	SD of Detected	0.287

Note: Data have multiple DLs - Use of KM Method is recommended

Number treated as Non-Detect

Number treated as Non-Detect

Number treated as Detected

Number treated as Detected

Number treated as Detected

Number treated as Detected

100.00%

96

100

Minimum Non-Detect

Maximum Non-Detect

Warning: Data set has only 2 Distinct Detected Values.

This may not be adequate enough to compute meaningful and reliable test statistics and estimates.

The Project Team may decide to use alternative site specific values to estimate environmental parameters (e.g., EPC, BTV).

Unless Data Quality Objectives (DQOs) have been met, it is suggested to collect additional observations.

The number of detected data may not be adequate enough to perform GOF tests, bootstrap, and ROS methods.

Those methods will return a 'N/A' value on your output display!

It is necessary to have 4 or more Distinct Values for bootstrap methods.

However, results obtained using 4 to 9 distinct values may not be reliable.

It is recommended to have 10 to 15 or more observations for accurate and meaningful results and estimates.

UCL Statistics

Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Only				
Shapiro Wilk Test Statistic	N/A	Shapiro Wilk Test Statistic	N/A			
5% Shapiro Wilk Critical Value	N/A	5% Shapiro Wilk Critical Value	N/A			
Data not Normal at 5% Significance Level		Data not Lognormal at 5% Significance Level				
Assuming Normal Distribution		Assuming Lognormal Distribution				
DL/2 Substitution Method		DL/2 Substitution Method				
Mean	37.5	Mean	3.487			
SD	17.55	SD	0.632			
95% DL/2 (t) UCL	51.93	95% H-Stat (DL/2) UCL	92.74			
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method				
MLE method failed to converge properly		Mean in Log Scale	N/A			
		SD in Log Scale	N/A			
		Mean in Original Scale	N/A			
		SD in Original Scale	N/A			
		95% t UCL	N/A			
		95% Percentile Bootstrap UCL	N/A			
		95% BCA Bootstrap UCL	N/A			
		95% H-UCL	N/A			

Page 3 of 18



Minimum Non-Detect

Maximum Non-Detect

4.564

4.605

ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Only	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	N/A	Data do not follow a Discernable Distribution (0.05)	
Theta Star	N/A		
nu star	N/A		
A-D Test Statistic	N/A	Nonparametric Statistics	
5% A-D Critical Value	N/A	Kaplan-Meier (KM) Method	
K-S Test Statistic	N/A	Mean	15
5% K-S Critical Value	N/A	SD	3
Data not Gamma Distributed at 5% Significance Lev	el	SE of Mean	3
		95% KM (t) UCL	21.05
Assuming Gamma Distribution		95% KM (z) UCL	19.93
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	22.8
Minimum	N/A	95% KM (bootstrap t) UCL	N/A
Maximum	N/A	95% KM (BCA) UCL	18
Mean	N/A	95% KM (Percentile Bootstrap) UCL	18
Median	N/A	95% KM (Chebyshev) UCL	28.08
SD	N/A	97.5% KM (Chebyshev) UCL	33.73
k star	N/A	99% KM (Chebyshev) UCL	44.85
Theta star	N/A		
Nu star	N/A	Potential UCLs to Use	
AppChi2	N/A	95% KM (t) UCL	21.05
95% Gamma Approximate UCL	N/A	95% KM (% Bootstrap) UCL	18
95% Adjusted Gamma UCL	N/A		

Warning: Recommended UCL exceeds the maximum observation

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006).

For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Aluminum

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Log-transformed Statistics

Raw Statistics

Minimum 5140

Maximum 15800

Mean 10513

Median 10070

SD 3967

Minimum of Log Data 8.545

Maximum of Log Data 9.668

Mean of log Data 9.194

SD of log Data 0.412

Std. Error of Mean 1619 Coefficient of Variation 0.377 Skewness 0.0408

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.965 Shapiro Wilk Critical Value 0.788

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.949 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 13777

Assuming Lognormal Distribution

95% Chebyshev (MVUE) UCL 18276 97.5% Chebyshev (MVUE) UCL 21618 99% Chebyshev (MVUE) UCL 28183

95% H-UCL 16779

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 13206 95% Modified-t UCL (Johnson-1978) 13781



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo. Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected)	3.967	Data appear Normal at 5% Significance Level
Theta Star	2650	
MLE of Mean	10513	
MLE of Standard Deviation	5279	
nu star	47.6	
Approximate Chi Square Value (.05)	32.77	Nonparametric Statistics
Adjusted Level of Significance	0.0122	95% CLT UCL 13177

95% Jackknife UCL 13777 Adjusted Chi Square Value 28.39 95% Standard Bootstrap UCL 12951 95% Bootstrap-t UCL 13811 Anderson-Darling Test Statistic 0.242 Anderson-Darling 5% Critical Value 0.698 95% Hall's Bootstrap UCL 13379 Kolmogorov-Smirnov Test Statistic 0.179 95% Percentile Bootstrap UCL 12873 Kolmogorov-Smirnov 5% Critical Value 0.333 95% BCA Bootstrap UCL 12833

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 15273 95% Adjusted Gamma UCL 17625

95% Chebyshev(Mean, Sd) UCL 17573 97.5% Chebyshev(Mean, Sd) UCL 20627

99% Chebyshev(Mean, Sd) UCL 26627

Potential UCL to Use Use 95% Student's-t UCL 13777

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Arsenic

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics

Minimum 0.84 Maximum 4.6 Mean 2.557 Median 2.5 SD 1.311

Skewness 0.407

Median 2.5
SD 1.311
Std. Error of Mean 0.535
Coefficient of Variation 0.513

Log-transformed Statistics

Minimum of Log Data -0.174

Maximum of Log Data 1.526

Mean of log Data 0.809

SD of log Data 0.592

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.984 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.962 Shapiro Wilk Critical Value 0.788

95% H-UCL 5.724

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 3.635

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 3.532 95% Modified-t UCL (Johnson-1978) 3.65

Assuming Lognormal Distribution

95% Chebyshev (MVUE) UCL 5.314 97.5% Chebyshev (MVUE) UCL 6.493 99% Chebyshev (MVUE) UCL 8.807



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected)	2.113	Data appear Normal at 5% Significance Level
Theta Star	1.21	
MLE of Mean	2.557	
MLE of Standard Deviation	1.759	
nu star	25.36	
Approximate Chi Square Value (.05)	14.89	Nonparametric Statistics
Adjusted Level of Significance	0.0122	95% CLT UCL 3.437
Adjusted Chi Square Value	12.09	95% Jackknife UCL 3.635
		95% Standard Bootstrap UCL 3.361
Anderson-Darling Test Statistic	0.177	95% Bootstrap-t UCL 3.769
Anderson-Darling 5% Critical Value	0.7	95% Hall's Bootstrap UCL 3.661

Kolmogorov-Smirnov Test Statistic 0.164 Kolmogorov-Smirnov 5% Critical Value 0.334

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 4.355 95% Adjusted Gamma UCL 5.363

Potential UCL to Use

Use 95% Student's-t UCL 3.635

95% Percentile Bootstrap UCL 3.367

95% Chebyshev(Mean, Sd) UCL 4.89 97.5% Chebyshev(Mean, Sd) UCL 5.9

99% Chebyshev(Mean, Sd) UCL 7.883

95% BCA Bootstrap UCL 3.383

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chromium

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics

Log-transformed Statistics

Minimum 3 Maximum 17.1 Mean 9.8 Median 9.2 SD 6.352 Minimum of Log Data 1.099

Maximum of Log Data 2.839

Mean of log Data 2.065

SD of log Data 0.759

Std. Error of Mean 2.593 Coefficient of Variation 0.648

Skewness 0.134

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.86

Shapiro Wilk Critical Value 0.788

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.878 Shapiro Wilk Critical Value 0.788

95% H-UCL 32.75

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

Data appear Normal at 5% Significance Level

95% Student's-t UCL 15.03

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 14.22 95% Modified-t UCL (Johnson-1978) 15.05

Assuming Lognormal Distribution

95% Chebyshev (MVUE) UCL 23.28 97.5% Chebyshev (MVUE) UCL 29.05 99% Chebyshev (MVUE) UCL 40.39



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 1.336 Data appear Normal at 5% Significance Level

Theta Star 7.336

MLE of Mean 9.8

MLE of Standard Deviation 8.479

nu star 16.03

Approximate Chi Square Value (.05) 7.983

Adjusted Level of Significance 0.0122

Adjusted Chi Square Value 6.048

Anderson-Darling Test Statistic 0.449

Anderson-Darling 5% Critical Value 0.703

Kolmogorov-Smirnov Test Statistic 0.233

Kolmogorov-Smirnov 5% Critical Value 0.335

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 19.68

95% Adjusted Gamma UCL 25.97

Nonparametric Statistics

95% CLT UCL 14.07

95% Jackknife UCL 15.03

95% Standard Bootstrap UCL 13.68

95% Bootstrap-t UCL 16.67

95% Hall's Bootstrap UCL 12.81

95% Percentile Bootstrap UCL 13.77

95% BCA Bootstrap UCL 13.48

95% Chebyshev(Mean, Sd) UCL 21.1

97.5% Chebyshev(Mean, Sd) UCL 25.99

99% Chebyshev(Mean, Sd) UCL 35.6

Potential UCL to Use

Use 95% Student's-t UCL 15.03

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 10 of 18 6/29/2012

ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo. Puerto Rico

Cobalt

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics

Log-transformed Statistics

Minimum 3 Maximum 10.5 Mean 6.4

Median 5.6

SD 2.903 Std. Error of Mean 1.185

Coefficient of Variation 0.454

Skewness 0.549

Minimum of Log Data 1.099 Maximum of Log Data 2.351 Mean of log Data 1.768 SD of log Data 0.467

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods! If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.922

Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.958 Shapiro Wilk Critical Value 0.788

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution


95% Student's-t UCL 8.788

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 8.633 95% Modified-t UCL (Johnson-1978) 8.832 **Assuming Lognormal Distribution**

95% Chebyshev (MVUE) UCL 11.73 97.5% Chebyshev (MVUE) UCL 14.03

95% H-UCL 11.15





ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 3.012

Data appear Normal at 5% Significance Level

Theta Star 2.125

MLE of Mean 6.4

MLE of Standard Deviation 3.688

nu star 36.14

Approximate Chi Square Value (.05) 23.38

Adjusted Level of Significance 0.0122

Adjusted Chi Square Value 19.76

Anderson-Darling Test Statistic 0.267

Anderson-Darling 5% Critical Value 0.698

Kolmogorov-Smirnov Test Statistic 0.204

Kolmogorov-Smirnov 5% Critical Value 0.333

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 9.892 95% Adjusted Gamma UCL 11.7

Potential UCL to Use

Nonparametric Statistics

95% CLT UCL 8.349

95% Jackknife UCL 8.788

95% Standard Bootstrap UCL 8.182

95% Bootstrap-t UCL 11.12

95% Hall's Bootstrap UCL 28.69

95% Percentile Bootstrap UCL 8.267

95% BCA Bootstrap UCL 8.4

95% Chebyshev(Mean, Sd) UCL 11.57

97.5% Chebyshev(Mean, Sd) UCL 13.8

99% Chebyshev(Mean, Sd) UCL 18.19

Use 95% Student's-t UCL 8.788

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 12 of 18 6/29/2012

ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo. Puerto Rico

Iron

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics Log-transformed Statistics

Minimum 16600 Maximum 41800 Mean 28117 Median 27200 SD 11327

Minimum of Log Data 9.717 Maximum of Log Data 10.64 Mean of log Data 10.17 SD of log Data 0.42

95% H-UCL 45334

Std. Error of Mean 4624 Coefficient of Variation 0.403 Skewness 0.141

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods! If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.856 Shapiro Wilk Test Statistic 0.852 Shapiro Wilk Critical Value 0.788 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution Assuming Lognormal Distribution

95% Student's-t UCL 37435 95% Chebyshev (MVUE) UCL 49157 95% UCLs (Adjusted for Skewness) 95% Adjusted-CLT UCL (Chen-1995) 36007 97.5% Chebyshev (MVUE) UCL 58250

95% Modified-t UCL (Johnson-1978) 37479 99% Chebyshev (MVUE) UCL 76111



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

Data appear Normal at 5% Significance Level

k star (bias corrected) 3.675

Theta Star 7651

MLE of Mean 28117

MLE of Standard Deviation 14667

nu star 44.1

Approximate Chi Square Value (.05) 29.87

Adjusted Level of Significance 0.0122

Adjusted Chi Square Value 25.71

Anderson-Darling Test Statistic 0.514

Anderson-Darling 5% Critical Value 0.698

Kolmogorov-Smirnov Test Statistic 0.242

Kolmogorov-Smirnov 5% Critical Value 0.333

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 41512 95% Adjusted Gamma UCL 48218

Potential UCL to Use

Nonparametric Statistics

95% CLT UCL 35723

95% Jackknife UCL 37435

95% Standard Bootstrap UCL 35040

95% Bootstrap-t UCL 37099

95% Hall's Bootstrap UCL 33031

95% Percentile Bootstrap UCL 34933

95% BCA Bootstrap UCL 34983

95% Chebyshev(Mean, Sd) UCL 48274

97.5% Chebyshev(Mean, Sd) UCL 56996

99% Chebyshev(Mean, Sd) UCL 74129

Use 95% Student's-t UCL 37435

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 14 of 18 6/29/2012

R2-0002242

ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Manganese

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics

Minimum 221 Maximum 547

Mean 386.5 Median 364

SD 124

Std. Error of Mean 50.61 Coefficient of Variation 0.321

Skewness 0.191

Log-transformed Statistics

Minimum of Log Data 5.398

Maximum of Log Data 6.304

Mean of log Data 5.912

SD of log Data 0.335

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.935 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.943 Shapiro Wilk Critical Value 0.788

95% H-UCL 550.7

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 488.5

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 474 95% Modified-t UCL (Johnson-1978) 489.1

Assuming Lognormal Distribution

95% Chebyshev (MVUE) UCL 617.8 97.5% Chebyshev (MVUE) UCL 717.7 99% Chebyshev (MVUE) UCL 913.8



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 5.715	Data appear Normal at 5% Significance Level
Theta Star 67.63	
MLE of Mean 386.5	
MLE of Standard Deviation 161.7	

pproximate Chi Square Value (.05) 50.52	Nonparametric Statistics
Adjusted Level of Significance 0.0122	95%

nu star 68.58

Adjusted Chi Square Value 44.97 95% Jackknife UCL 488.5 95% Standard Bootstrap UCL 460.9 dderson-Darling Test Statistic 0.285 95% Bootstrap-t UCL 530.9

Anderson-Darling Test Statistic 0.285

Anderson-Darling 5% Critical Value 0.698

Anderson-Darling 5% Critical Value 0.698

Kolmogorov-Smirnov Test Statistic 0.199

Statistic 0.199

Forecattile Bootstrap UCL 462

Kolmogorov-Smirnov 5% Critical Value 0.332

Statistic 0.332

Pata appear Gamma Distributed at 5% Significance Level

95% Chebyshev(Mean, Sd) UCL 607.1

97.5% Chebyshev(Mean, Sd) UCL 702.6

Assuming Gamma Distribution

Potential UCL to Use

95% Approximate Gamma UCL 524.7 95% Adjusted Gamma UCL 589.4

Use 95% Student's-t UCL 488.5

99% Chebyshev(Mean, Sd) UCL 890.1

95% CLT UCL 469.7

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002)

and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 16 of 18 6/29/2012

ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Vanadium

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Log-transformed Statistics

Raw Statistics

Minimum 24.3 Maximum 69.3 Mean 48.77 Median 47.75 SD 18.16

Minimum of Log Data 3.19

Maximum of Log Data 4.238

Mean of log Data 3.822

SD of log Data 0.408

Std. Error of Mean 7.416

Coefficient of Variation 0.372

Skewness -0.0652

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set,

the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.931 Shapiro Wilk Critical Value 0.788

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.931 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Assuming Normal Distribution

mar at 0 /0 organicanos zover

95% Student's-t UCL 63.71

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 60.75 95% Modified-t UCL (Johnson-1978) 63.68

Assuming Lognormal Distribution

Data appear Lognormal at 5% Significance Level

95% H-UCL 77.39 95% Chebyshev (MVUE) UCL 84.46 97.5% Chebyshev (MVUE) UCL 99.82 99% Chebyshev (MVUE) UCL 130



ProUCL Output - Surface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 4.037 **Data appear Normal at 5% Significance Level**Theta Star 12.08

MLE of Standard Deviation 24.27 nu star 48.44

MLF of Mean 48 77

Approximate Chi Square Value (.05) 33.47
Adjusted Level of Significance 0.0122

Adjusted Chi Square Value 29.04

Anderson-Darling Test Statistic 0.27

Anderson-Darling 5% Critical Value 0.698

Kolmogorov-Smirnov Test Statistic 0.2

Kolmogorov-Smirnov 5% Critical Value 0.333

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 70.59 95% Adjusted Gamma UCL 81.35 **Nonparametric Statistics**

95% CLT UCL 60.96
95% Jackknife UCL 63.71
95% Standard Bootstrap UCL 59.81
95% Bootstrap-t UCL 65.64
95% Hall's Bootstrap UCL 61.53
95% Percentile Bootstrap UCL 59.8
95% BCA Bootstrap UCL 59
95% Chebyshev(Mean, Sd) UCL 81.09
97.5% Chebyshev(Mean, Sd) UCL 95.08

Potential UCL to Use

Use 95% Student's-t UCL 63.71

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.

Note: For highly negative-skewed data, confidence limits (e.g., Chen, Johnson, Lognormal, and Gamma) may not be reliable. Chen's and Johnson's methods provide adjustments for positvely skewed data sets.



ProUCL Output - Surface Soil at Puerto Rico Beverage

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

General UCL Statistics for Data Sets with Non-Detects

User Selected Options

From File SS-PRB.wst

Full Precision OFF

Confidence Coefficient 95%

Number of Bootstrap Operations 2000

Aluminum

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics

Minimum 7060 Maximum 15700 Mean 10240 Median 8825

SD 3403

Std. Error of Mean 1389 Coefficient of Variation 0.332

Skewness 1.02

Log-transformed Statistics

Minimum of Log Data 8.862 Maximum of Log Data 9.661 Mean of log Data 9.192 SD of log Data 0.312

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.868 Shapiro Wilk Critical Value 0.788 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

 95% Student's-t UCL 13040
 95% H-UCL 14104

 95% UCLs (Adjusted for Skewness)
 95% Chebyshev (MVUE) UCL 15896

95% Adjusted-CLT UCL (Chen-1995) 13144 97.5% Chebyshev (MVUE) UCL 18352 95% Modified-t UCL (Johnson-1978) 13136 99% Chebyshev (MVUE) UCL 23177



Page 1 of 15 6/29/2012

Assuming Lognormal Distribution

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 6.092 Data appear Normal at 5% Significance Level

Theta Star 1681

MLE of Mean 10240

MLE of Standard Deviation 4149

nu star 73.11

Approximate Chi Square Value (.05) 54.42

Adjusted Level of Significance 0.0122

Adjusted Chi Square Value 48.64

Anderson-Darling Test Statistic 0.425

Anderson-Darling 5% Critical Value 0.698

Kolmogorov-Smirnov Test Statistic 0.256

Kolmogorov-Smirnov 5% Critical Value 0.332

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 13757

95% Adjusted Gamma UCL 15391

Nonparametric Statistics

95% CLT UCL 12525 95% Jackknife UCL 13040

95% Standard Bootstrap UCL 12300

95% Bootstrap-t UCL 17711

95% Hall's Bootstrap UCL 30933

95% Percentile Bootstrap UCL 12387

95% BCA Bootstrap UCL 12703

95% Chebyshev(Mean, Sd) UCL 16296

97.5% Chebyshev(Mean, Sd) UCL 18917

99% Chebyshev(Mean, Sd) UCL 24065

Potential UCL to Use

Use 95% Student's-t UCL 13040

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



6/29/2012 Page 2 of 15

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Arsenic

General Statistics	
6	Number of Detect

Number of Valid Data 6 Number of Detected Data 2

Number of Distinct Detected Data 2

Number of Non-Detect Data 4

Percent Non-Detects 66.67%

Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.43	Minimum Detected	-0.844
Maximum Detected	2.9	Maximum Detected	1.065
Mean of Detected	1.665	Mean of Detected	0.11
SD of Detected	1.747	SD of Detected	1.35
Minimum Non-Detect	1.1	Minimum Non-Detect	0.0953
Maximum Non-Detect	1.1	Maximum Non-Detect	0.0953

Warning: Data set has only 2 Distinct Detected Values.

This may not be adequate enough to compute meaningful and reliable test statistics and estimates.

The Project Team may decide to use alternative site specific values to estimate environmental parameters (e.g., EPC, BTV).

Unless Data Quality Objectives (DQOs) have been met, it is suggested to collect additional observations.

The number of detected data may not be adequate enough to perform GOF tests, bootstrap, and ROS methods.

Those methods will return a 'N/A' value on your output display!

It is necessary to have 4 or more Distinct Values for bootstrap methods.

However, results obtained using 4 to 9 distinct values may not be reliable.

It is recommended to have 10 to 15 or more observations for accurate and meaningful results and estimates.

UCL Statistics

Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Only	/
Shapiro Wilk Test Statistic	N/A	Shapiro Wilk Test Statistic	N/A
5% Shapiro Wilk Critical Value	N/A	5% Shapiro Wilk Critical Value	N/A
Data not Normal at 5% Significance Level		Data not Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	0.922	Mean	-0.362
SD	0.97	SD	0.706
95% DL/2 (t) UCL	1.72	95% H-Stat (DL/2) UCL	2.444
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE method failed to converge properly		Mean in Log Scale	N/A
		SD in Log Scale	N/A
		Mean in Original Scale	N/A
		SD in Original Scale	N/A
		95% t UCL	N/A
		95% Percentile Bootstrap UCL	N/A
		95% BCA Bootstrap UCL	N/A
		95% H-UCL	N/A



Appendix C-2 ProUCL Output - Surface Soil at Puerto Rico Beverage Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico



Page 4 of 15 6/29/2012

Maunabo Groundwater Contamination Site

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Only	/	Data Distribution Test with Detected Values Only	
k star (bias corrected)	N/A	Data do not follow a Discernable Distribution (0.05)	
Theta Star	N/A		
nu star	N/A		
A-D Test Statistic	N/A	Nonparametric Statistics	
5% A-D Critical Value	N/A	Kaplan-Meier (KM) Method	
K-S Test Statistic	N/A	Mean	0.842
5% K-S Critical Value	N/A	SD	0.921
Data not Gamma Distributed at 5% Significance Leve	el	SE of Mean	0.531
		95% KM (t) UCL	1.913
Assuming Gamma Distribution		95% KM (z) UCL	1.716
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	N/A
Minimum	N/A	95% KM (bootstrap t) UCL	N/A
Maximum	N/A	95% KM (BCA) UCL	N/A
Mean	N/A	95% KM (Percentile Bootstrap) UCL	N/A
Median	N/A	95% KM (Chebyshev) UCL	3.158
SD	N/A	97.5% KM (Chebyshev) UCL	4.161
k star	N/A	99% KM (Chebyshev) UCL	6.13
Theta star	N/A		
Nu star	N/A	Potential UCLs to Use	
AppChi2	N/A	95% KM (BCA) UCL	N/A
95% Gamma Approximate UCL	N/A		
95% Adjusted Gamma UCL	N/A		

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006).

For additional insight, the user may want to consult a statistician.



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chromium

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics

Minimum 1.6 Maximum 27.5

Mean 6.967 Median 2.45 SD 10.17

Std. Error of Mean 4.152 Coefficient of Variation 1.46 Skewness 2.336

Log-transformed Statistics

Minimum of Log Data 0.47 Maximum of Log Data 3.314 Mean of log Data 1.337 SD of log Data 1.063

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.609 Shapiro Wilk Critical Value 0.788

Data not Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.809 Shapiro Wilk Critical Value 0.788

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 15.33

95% UCLs (Adjusted for Skewness) 95% Adjusted-CLT UCL (Chen-1995) 18.03

95% Modified-t UCL (Johnson-1978) 15.99

Assuming Lognormal Distribution

95% H-UCL 53.02 95% Chebyshev (MVUE) UCL 16.93 97.5% Chebyshev (MVUE) UCL 21.68 99% Chebyshev (MVUE) UCL 31.03



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 0.591 Data appear Lognormal at 5% Significance Level
Theta Star 11.78

MLE of Standard Deviation 9.06

nu star 7.096

11u Stat 7.090

MLE of Mean 6.967

Approximate Chi Square Value (.05) 2.223

Adjusted Level of Significance 0.0122

Adjusted Chi Square Value 1.371

Anderson-Darling Test Statistic 0.856

Anderson-Darling 5% Critical Value 0.716

Kolmogorov-Smirnov Test Statistic 0.347

Kolmogorov-Smirnov 5% Critical Value 0.341

Data not Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 22.23 95% Adjusted Gamma UCL 36.07

Nonparametric Statistics

95% CLT UCL 13.8
95% Jackknife UCL 15.33
95% Standard Bootstrap UCL 13.2
95% Bootstrap-t UCL 132.7
95% Hall's Bootstrap UCL 76.6
95% Percentile Bootstrap UCL 14.67
95% BCA Bootstrap UCL 19
95% Chebyshev(Mean, Sd) UCL 25.07

97.5% Chebyshev(Mean, Sd) UCL 32.9 99% Chebyshev(Mean, Sd) UCL 48.28

Potential UCL to Use

Use 95% Chebyshev (Mean, Sd) UCL 25.07

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 7 of 15 6/29/2012

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Cobalt

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics

Minimum 2.1 Maximum 7.5 Mean 4.783 Median 4.55

SD 1.913 Std. Error of Mean 0.781 Coefficient of Variation 0.4 Skewness 0.122

Log-transformed Statistics

Minimum of Log Data 0.742 Maximum of Log Data 2.015 Mean of log Data 1.489 SD of log Data 0.447

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.986 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.957 Shapiro Wilk Critical Value 0.788

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 6.357

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 6.109 95% Modified-t UCL (Johnson-1978) 6.363

Assuming Lognormal Distribution

95% H-UCL 8.095 95% Chebyshev (MVUE) UCL 8.634 97.5% Chebyshev (MVUE) UCL 10.29 99% Chebyshev (MVUE) UCL 13.54



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 3.468

Theta Star 1.379

MLE of Mean 4.783

MLE of Standard Deviation 2.568

Data appear Normal at 5% Significance Level

The appear Normal at 5% Significance Level

Approximate Chi Square Value (.05) 27.83 Non
Adjusted Level of Significance 0.0122

nu star 41.62

Adjusted Chi Square Value 23.84

Anderson-Darling Test Statistic 0.192
Anderson-Darling 5% Critical Value 0.698
Kolmogorov-Smirnov Test Statistic 0.142
Kolmogorov-Smirnov 5% Critical Value 0.333

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 7.153 95% Adjusted Gamma UCL 8.351 **Nonparametric Statistics**

95% CLT UCL 6.068
95% Jackknife UCL 6.357
95% Standard Bootstrap UCL 5.964
95% Bootstrap-t UCL 6.752
95% Hall's Bootstrap UCL 7.022
95% Percentile Bootstrap UCL 5.933
95% Chebyshev(Mean, Sd) UCL 8.187
97.5% Chebyshev(Mean, Sd) UCL 9.659
99% Chebyshev(Mean, Sd) UCL 12.55

Potential UCL to Use

Use 95% Student's-t UCL 6.357

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 9 of 15 6/29/2012

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Iron

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics Log-transformed Statistics

> Minimum 16400 Minimum of Log Data 9.705 Maximum 35900 Maximum of Log Data 10.49 Mean 23467 Mean of log Data 10.03 Median 22500 SD of log Data 0.294 SD 7258

Std. Error of Mean 2963 Coefficient of Variation 0.309 Skewness 1.035

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods! If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

> Shapiro Wilk Test Statistic 0.942 Shapiro Wilk Test Statistic 0.907 Shapiro Wilk Critical Value 0.788 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution Assuming Lognormal Distribution

95% Student's-t UCL 29438 95% H-UCL 31611 95% UCLs (Adjusted for Skewness) 95% Chebyshev (MVUE) UCL 35713 95% Adjusted-CLT UCL (Chen-1995) 29679 97.5% Chebyshev (MVUE) UCL 41025 95% Modified-t UCL (Johnson-1978) 29646 99% Chebyshev (MVUE) UCL 51459

Page 10 of 15 6/29/2012



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 6.907

Data appear Normal at 5% Significance Level

Theta Star 3397

MLE of Mean 23467

MLE of Standard Deviation 8929

nu star 82.89

Approximate Chi Square Value (.05) 62.91

Adjusted Level of Significance 0.0122

Adjusted Chi Square Value 56.66

Anderson-Darling Test Statistic 0.283

Anderson-Darling 5% Critical Value 0.698

Kolmogorov-Smirnov Test Statistic 0.179

Kolmogorov-Smirnov 5% Critical Value 0.332

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 30921 95% Adjusted Gamma UCL 34331 Nonparametric Statistics

95% CLT UCL 28341

95% Jackknife UCL 29438

95% Standard Bootstrap UCL 27796

95% Bootstrap-t UCL 32251

95% Hall's Bootstrap UCL 30768

95% Percentile Bootstrap UCL 28333

95% BCA Bootstrap UCL 29000

95% Chebyshev(Mean, Sd) UCL 36383

97.5% Chebyshev(Mean, Sd) UCL 41972

99% Chebyshev(Mean, Sd) UCL 52950

Potential UCL to Use

Use 95% Student's-t UCL 29438

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 11 of 15 6/29/2012

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Manganese

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics

Minimum 135 Maximum 365 Mean 269.3 Median 300 SD 96.46

Std. Error of Mean 39.38
Coefficient of Variation 0.358
Skewness -0.608

Log-transformed Statistics

Minimum of Log Data 4.905 Maximum of Log Data 5.9 Mean of log Data 5.531 SD of log Data 0.414

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.88 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.855 Shapiro Wilk Critical Value 0.788

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 348.7

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 323.7 95% Modified-t UCL (Johnson-1978) 347.1

Assuming Lognormal Distribution

95% H-UCL 432.1 95% Chebyshev (MVUE) UCL 470.2 97.5% Chebyshev (MVUE) UCL 556.4 99% Chebyshev (MVUE) UCL 725.8



Page 12 of 15 6/29/2012

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

Data appear Normal at 5% Significance Level	k star (bias corrected) 4.047	
	Theta Star 66.56	
	MLE of Mean 269.3	
	MLE of Standard Deviation 133.9	
	nu star 48.56	
Nonparametric Statistics	roximate Chi Square Value (.05) 33.56	Appro
95% CLT UCL 334	Adjusted Level of Significance 0.0122	

Adjusted Chi Square Value 29.13

95% Jackknife UCL 348.7

95% Standard Bootstrap UCL 327.9

Anderson-Darling Test Statistic 0.492

Anderson-Darling 5% Critical Value 0.698

Kolmogorov-Smirnov Test Statistic 0.266

Kolmogorov-Smirnov 5% Critical Value 0.333

95% BCA Bootstrap UCL 320

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 389.7 95% Adjusted Gamma UCL 448.9

Use 95% Student's-t UCL 348.7

95% Chebyshev(Mean, Sd) UCL 441

97.5% Chebyshev(Mean, Sd) UCL 515.3

99% Chebyshev(Mean, Sd) UCL 661.2

Potential UCL to Use

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.

Note: For highly negative-skewed data, confidence limits (e.g., Chen, Johnson, Lognormal, and Gamma) may not be reliable. Chen's and Johnson's methods provide adjustments for positvely skewed data sets.



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Vanadium

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics

Log-transformed Statistics
Minimum 31.9 Minimum c

Maximum 71.8

Mean 43.95 Median 37.5

SD 15.34

Std. Error of Mean 6.263 Coefficient of Variation 0.349

Skewness 1.527

Minimum of Log Data 3.463
Maximum of Log Data 4.274
Mean of log Data 3.739
SD of log Data 0.312

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.82 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.87 Shapiro Wilk Critical Value 0.788

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 56.57

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 58.42 95% Modified-t UCL (Johnson-1978) 57.22 **Assuming Lognormal Distribution**

95% Chebyshev (MVUE) UCL 68.15 97.5% Chebyshev (MVUE) UCL 78.69 99% Chebyshev (MVUE) UCL 99.38

95% H-UCL 60.47



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 5.902 Data appear Normal at 5% Significance Level

Theta Star 7.447

MLE of Mean 43.95

MLE of Standard Deviation 18.09

nu star 70.82

Approximate Chi Square Value (.05) 52.44

Adjusted Level of Significance 0.0122

Adjusted Chi Square Value 46.78

Anderson-Darling Test Statistic 0.496

Anderson-Darling 5% Critical Value 0.698

Kolmogorov-Smirnov Test Statistic 0.249

Kolmogorov-Smirnov 5% Critical Value 0.332

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 59.35 95% Adjusted Gamma UCL 66.53 **Nonparametric Statistics**

95% CLT UCL 54.25

95% Jackknife UCL 56.57

95% Standard Bootstrap UCL 53.15

95% Bootstrap-t UCL 80.02

95% Hall's Bootstrap UCL 104.5

95% Percentile Bootstrap UCL 53.82

95% BCA Bootstrap UCL 56.45

95% Chebyshev(Mean, Sd) UCL 71.25

97.5% Chebyshev(Mean, Sd) UCL 83.06

99% Chebyshev(Mean, Sd) UCL 106.3

Potential UCL to Use

Use 95% Student's-t UCL 56.57

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 15 of 15 6/29/2012

ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

General UCL Statistics for Data Sets with Non-Detects

User Selected Options

From File SB-FSM.wst
Full Precision OFF
Confidence Coefficient 95%
Number of Bootstrap Operations 2000

Benzo(a)pyrene

	General Sta	itistics	
Number of Valid Data	24	Number of Detected Data	7
Number of Distinct Detected Data	7	Number of Non-Detect Data	17
		Percent Non-Detects	70.83%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	7.9	Minimum Detected	2.067
Maximum Detected	76	Maximum Detected	4.331
Mean of Detected	29.21	Mean of Detected	3.008
SD of Detected	26.09	SD of Detected	0.937
Minimum Non-Detect	96	Minimum Non-Detect	4.564
Maximum Non-Detect	120	Maximum Non-Detect	4.787
Note: Data have multiple DLs - Use of KM Method is recommended	t	Number treated as Non-Detect	24
For all methods (except KM, DL/2, and ROS Methods),		Number treated as Detected	0
Observations < Largest ND are treated as NDs		Single DL Non-Detect Percentage	100.00%

Warning: There are only 7 Detected Values in this data

Note: It should be noted that even though bootstrap may be performed on this data set the resulting calculations may not be reliable enough to draw conclusions

It is recommended to have 10-15 or more distinct observations for accurate and meaningful results.

UCL Statistics Normal Distribution Test with Detected Values Only **Lognormal Distribution Test with Detected Values Only** Shapiro Wilk Test Statistic 0.838 Shapiro Wilk Test Statistic 0.872 5% Shapiro Wilk Critical Value 0.803 5% Shapiro Wilk Critical Value 0.803 Data appear Normal at 5% Significance Level Data appear Lognormal at 5% Significance Level **Assuming Normal Distribution Assuming Lognormal Distribution** DL/2 Substitution Method DL/2 Substitution Method Mean 46 21 Mean 3 69 17.72 SD SD 0.658 95% DL/2 (t) UCL 95% H-Stat (DL/2) UCL 66.68 52.41 Log ROS Method Maximum Likelihood Estimate(MLE) Method N/A MLE method failed to converge properly Mean in Log Scale 3.008 SD in Log Scale 0.742 Mean in Original Scale 26.23 SD in Original Scale 19.56 95% t UCL 33.08 95% Percentile Bootstrap UCL 33.19 95% BCA Bootstrap UCL 33.87 95% H-UCL 37.62



Appendix C-3
ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill
Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	y	Data Distribution Test with Detected Values Only	
k star (bias corrected)	0.957	Data appear Normal at 5% Significance Level	
Theta Star	30.53		
nu star	13.39		
A-D Test Statistic	0.503	Nonparametric Statistics	
5% A-D Critical Value		•	
	0.721	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.721	Mean	29.21
5% K-S Critical Value	0.317	SD	24.16
Data appear Gamma Distributed at 5% Significance Lo	evel	SE of Mean	9.862
		95% KM (t) UCL	46.12
Assuming Gamma Distribution		95% KM (z) UCL	45.44
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	47.09
Minimum	0.000001	95% KM (bootstrap t) UCL	60.31
Maximum	76	95% KM (BCA) UCL	46.4
Mean	29.23	95% KM (Percentile Bootstrap) UCL	44.88
Median	28.83	95% KM (Chebyshev) UCL	72.2
SD	20.74	97.5% KM (Chebyshev) UCL	90.8
k star	0.589	99% KM (Chebyshev) UCL	127.3
Theta star	49.65		
Nu star	28.26	Potential UCLs to Use	
AppChi2	17.13	95% KM (t) UCL	46.12
95% Gamma Approximate UCL	48.22	95% KM (Percentile Bootstrap) UCL	44.88
95% Adjusted Gamma UCL	50		

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006). For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Dibenzo(a,h)anthracene

	General Statis	stics	
Number of Valid Data	24	Number of Detected Data	3
Number of Distinct Detected Data	3	Number of Non-Detect Data	21
		Percent Non-Detects	87.50%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	8.6	Minimum Detected	2.152
Maximum Detected	18	Maximum Detected	2.89
Mean of Detected	12.87	Mean of Detected	2.509
SD of Detected	4.76	SD of Detected	0.37
Minimum Non-Detect	96	Minimum Non-Detect	4.564
Maximum Non-Detect	120	Maximum Non-Detect	4.787
Note: Data have multiple DLs - Use of KM Method is recommended		Number treated as Non-Detect	24
For all methods (except KM, DL/2, and ROS Methods),		Number treated as Detected	0
Observations < Largest ND are treated as NDs		Single DL Non-Detect Percentage	100.00%

Warning: There are only 3 Distinct Detected Values in this data set

The number of detected data may not be adequate enough to perform GOF tests, bootstrap, and ROS methods.

Those methods will return a 'N/A' value on your output display!

It is necessary to have 4 or more Distinct Values for bootstrap methods.

However, results obtained using 4 to 9 distinct values may not be reliable.

It is recommended to have 10 to 15 or more observations for accurate and meaningful results and estimates.

	UCL Statistic	es	
Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Only	/
Shapiro Wilk Test Statistic	0.975	Shapiro Wilk Test Statistic	0.997
5% Shapiro Wilk Critical Value	0.767	5% Shapiro Wilk Critical Value	0.767
Data appear Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	47.57	Mean	3.777
SD	13.99	SD	0.507
95% DL/2 (t) UCL	52.46	95% H-Stat (DL/2) UCL	61.28
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE method failed to converge properly		Mean in Log Scale	2.509
		SD in Log Scale	0.341
		Mean in Original Scale	12.99
		SD in Original Scale	4.415
		95% t UCL	14.53
		95% Percentile Bootstrap UCL	14.53
		95% BCA Bootstrap UCL	14.56
		95% H-UCL	14.86



Appendix C-3
ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill
Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Only		Data Distribution Test with Detected Values Only	
k star (bias corrected)	N/A	Data appear Normal at 5% Significance Level	
Theta Star	N/A		
nu star	N/A		
A-D Test Statistic	N/A	Nonparametric Statistics	
5% A-D Critical Value	N/A	Kaplan-Meier (KM) Method	
K-S Test Statistic	N/A	Mean	12.87
5% K-S Critical Value	N/A	SD	3.886
Data not Gamma Distributed at 5% Significance Leve	I	SE of Mean	2.748
		95% KM (t) UCL	17.58
Assuming Gamma Distribution		95% KM (z) UCL	17.39
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	18.51
Minimum	N/A	95% KM (bootstrap t) UCL	23.91
Maximum	N/A	95% KM (BCA) UCL	18
Mean	N/A	95% KM (Percentile Bootstrap) UCL	18
Median	N/A	95% KM (Chebyshev) UCL	24.84
SD	N/A	97.5% KM (Chebyshev) UCL	30.03
k star	N/A	99% KM (Chebyshev) UCL	40.21
Theta star	N/A		
Nu star	N/A	Potential UCLs to Use	
AppChi2	N/A	95% KM (t) UCL	17.58
95% Gamma Approximate UCL	N/A	95% KM (Percentile Bootstrap) UCL	18
95% Adjusted Gamma UCL	N/A		

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006). For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Aluminum

General Statistics

Number of Valid Observations 24 Number of Distinct Observations 24

Raw Statistics Log-transformed Statistics

> Minimum 5140 Minimum of Log Data 8.545 Maximum 28500 Maximum of Log Data 10.26 Mean 15516 Mean of log Data 9.593 Median 15750 SD of log Data 0.364 SD 4996

Std. Error of Mean 1020 Coefficient of Variation 0.322 Skewness 0.268

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

> Shapiro Wilk Test Statistic 0.973 Shapiro Wilk Test Statistic 0.93 Shapiro Wilk Critical Value 0.916 Shapiro Wilk Critical Value 0.916

Data appear Normal at 5% Significance Level Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

Assuming Lognormal Distribution 95% Student's-t UCL 17264 95% H-UCL 18047

95% UCLs (Adjusted for Skewness)

95% Chebyshev (MVUE) UCL 20780 95% Adjusted-CLT UCL (Chen-1995) 17253 97.5% Chebyshev (MVUE) UCL 23015 95% Modified-t UCL (Johnson-1978) 17273 99% Chebyshev (MVUE) UCL 27406

Gamma Distribution Test

Data Distribution Data appear Normal at 5% Significance Level k star (bias corrected) 7.85

Theta Star 1977

MLE of Mean 15516

MLE of Standard Deviation 5538

nu star 376.8

Approximate Chi Square Value (.05) 332.8 **Nonparametric Statistics**

Adjusted Level of Significance 0.0392 95% CLT UCL 17193 Adjusted Chi Square Value 329.9 95% Jackknife UCL 17264

Anderson-Darling Test Statistic 0.394 95% Bootstrap-t UCL 17286 Anderson-Darling 5% Critical Value 0.745 95% Hall's Bootstrap UCL 17504 Kolmogorov-Smirnov Test Statistic 0.112 95% Percentile Bootstrap UCL 17208

Kolmogorov-Smirnov 5% Critical Value 0.178 95% BCA Bootstrap UCL 17253 95% Chebyshev(Mean, Sd) UCL 19961

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 17567 95% Adjusted Gamma UCL 17721

Potential UCL to Use Use 95% Student's-t UCL 17264

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



6/29/2012 Page 5 of 14

95% Standard Bootstrap UCL 17155

97.5% Chebyshev(Mean, Sd) UCL 21885 99% Chebyshev(Mean, Sd) UCL 25664

Appendix C-3
ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill
Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Arsenic

	General Sta	tistics	
Number of Valid Data	24	Number of Detected Data	14
Number of Distinct Detected Data	14	Number of Non-Detect Data	10
		Percent Non-Detects	41.67%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.29	Minimum Detected	-1.238
Maximum Detected	4.6	Maximum Detected	1.526
Mean of Detected	2.089	Mean of Detected	0.463
SD of Detected	1.342	SD of Detected	0.859
Minimum Non-Detect	1.342	Minimum Non-Detect	0.039
Maximum Non-Detect	1.4	Maximum Non-Detect	0.102
Maximum Non-Detect	1.4	Maximum Non-Detect	0.330
Note: Data have multiple DLs - Use of KM Method is recommended	I	Number treated as Non-Detect	15
For all methods (except KM, DL/2, and ROS Methods),		Number treated as Detected	9
Observations < Largest ND are treated as NDs		Single DL Non-Detect Percentage	62.50%
Name of Biotellanday Test with Bots at ad Value of Only	UCL Statis		
Normal Distribution Test with Detected Values Only	0.050	Lognormal Distribution Test with Detected Values On	•
Shapiro Wilk Test Statistic	0.956	Shapiro Wilk Critical Value	0.918
5% Shapiro Wilk Critical Value	0.874	5% Shapiro Wilk Critical Value	0.874
Data appear Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	1.485	Mean	0.0835
SD	1.245	SD	0.792
95% DL/2 (t) UCL	1.921	95% H-Stat (DL/2) UCL	2.17
Mayirayan Libalib and Entirents/MLEV Mathod		Lag DOS Mathad	
Maximum Likelihood Estimate(MLE) Method	0.044	Log ROS Method	0.044
Mean	0.844	Mean in Log Scale	0.041
SD OFFICIAL F. (1) LIGH	1.951	SD in Log Scale	0.868
95% MLE (t) UCL	1.526	Mean in Original Scale	1.48
95% MLE (Tiku) UCL	1.844	SD in Original Scale	1.259
		95% t UCL	1.92
		95% Percentile Bootstrap UCL	1.891
		95% BCA Bootstrap UCL	1.984
		95% H UCL	2.333



Appendix C-3
ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill
Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	1.601	Data appear Normal at 5% Significance Level	
Theta Star	1.305		
nu star	44.81		
A-D Test Statistic	0.331	Nonparametric Statistics	
5% A-D Critical Value	0.746	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.746	Mean	1.465
5% K-S Critical Value	0.232	SD	1.244
Data appear Gamma Distributed at 5% Significance Lo	evel	SE of Mean	0.27
		95% KM (t) UCL	1.928
Assuming Gamma Distribution		95% KM (z) UCL	1.91
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	1.927
Minimum	0.000001	95% KM (bootstrap t) UCL	2.005
Maximum	4.6	95% KM (BCA) UCL	1.925
Mean	1.501	95% KM (Percentile Bootstrap) UCL	1.913
Median	1.184	95% KM (Chebyshev) UCL	2.642
SD	1.291	97.5% KM (Chebyshev) UCL	3.152
k star	0.336	99% KM (Chebyshev) UCL	4.152
Theta star	4.461		
Nu star	16.15	Potential UCLs to Use	
AppChi2	8.067	95% KM (t) UCL	1.928
95% Gamma Approximate UCL	3.004	95% KM (Percentile Bootstrap) UCL	1.913
95% Adjusted Gamma UCL	3.161		

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006). For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chromium

General Statistics

Number of Valid Observations 24

Number of Distinct Observations 20

Raw Statistics

Minimum 3 Maximum 20.8 Mean 8.283 Median 6.9 SD 4.453

Std. Error of Mean 0.909 Coefficient of Variation 0.538 Skewness 1.617

Log-transformed Statistics

Minimum of Log Data 1.099

Maximum of Log Data 3.035

Mean of log Data 2.004

SD of log Data 0.46

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.785 Shapiro Wilk Critical Value 0.916

Data not Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.915 Shapiro Wilk Critical Value 0.916

Data not Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 9.841

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 10.1 95% Modified-t UCL (Johnson-1978) 9.891

Assuming Lognormal Distribution

95% H-UCL 9.937 95% Chebyshev (MVUE) UCL 11.68 97.5% Chebyshev (MVUE) UCL 13.18 99% Chebyshev (MVUE) UCL 16.14

Gamma Distribution Test

k star (bias corrected) 4.127 Theta Star 2.007 MLE of Mean 8.283

MLE of Standard Deviation 4.077

Adjusted Chi Square Value 164.5

nu star 198.1

Approximate Chi Square Value (.05) 166.5 Adjusted Level of Significance 0.0392

Anderson-Darling Test Statistic 1.427 Anderson-Darling 5% Critical Value 0.747 Kolmogorov-Smirnov Test Statistic 0.249

Kolmogorov-Smirnov 5% Critical Value 0.178

Data not Gamma Distributed at 5% Significance Level

Data Distribution

Data do not follow a Discernable Distribution (0.05)

Assuming Gamma Distribution

95% Approximate Gamma UCL 9.853 95% Adjusted Gamma UCL 9.975

Nonparametric Statistics

95% CLT UCL 9.778
95% Jackknife UCL 9.841
95% Standard Bootstrap UCL 9.744
95% Bootstrap-t UCL 10.36
95% Hall's Bootstrap UCL 10.16
95% Percentile Bootstrap UCL 9.883
95% BCA Bootstrap UCL 10.04
95% Chebyshev(Mean, Sd) UCL 12.24
97.5% Chebyshev(Mean, Sd) UCL 13.96
99% Chebyshev(Mean, Sd) UCL 17.33

Potential UCL to Use

Use 95% Student's-t UCL 9.841 or 95% Modified-t UCL 9.891

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002)

and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Cobalt

General Statistics

Number of Valid Observations 24

Number of Distinct Observations 22

Raw Statistics

Minimum 3 Maximum 14.7 Mean 9.892 Median 10.4 SD 2.938

Std. Error of Mean 0.6 Coefficient of Variation 0.297 Skewness -0.77

Log-transformed Statistics

Minimum of Log Data 1.099

Maximum of Log Data 2.688

Mean of log Data 2.234

SD of log Data 0.38

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.945 Shapiro Wilk Critical Value 0.916

Data appear Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.838 Shapiro Wilk Critical Value 0.916

Data not Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 10.92

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 10.78 95% Modified-t UCL (Johnson-1978) 10.9

Assuming Lognormal Distribution

95% H-UCL 11.65 95% Chebyshev (MVUE) UCL 13.47 97.5% Chebyshev (MVUE) UCL 14.97 99% Chebyshev (MVUE) UCL 17.92

Gamma Distribution Test

k star (bias corrected) 7.734 Theta Star 1.279 MLE of Mean 9.892 MLE of Standard Deviation 3.557

nu star 371.2

Approximate Chi Square Value (.05) 327.6

Adjusted Level of Significance 0.0392

Adjusted Chi Square Value 324.7

Anderson-Darling Test Statistic 1.078 Anderson-Darling 5% Critical Value 0.745 Kolmogorov-Smirnov Test Statistic 0.194

Kolmogorov-Smirnov 5% Critical Value 0.178

Data not Gamma Distributed at 5% Significance Level

Data Distribution

Data appear Normal at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 11.21 95% Adjusted Gamma UCL 11.31

Nonparametric Statistics

95% CLT UCL 10.88
95% Jackknife UCL 10.92
95% Standard Bootstrap UCL 10.84
95% Bootstrap-t UCL 10.83
95% Hall's Bootstrap UCL 10.83
95% Percentile Bootstrap UCL 10.83
95% BCA Bootstrap UCL 10.75
95% Chebyshev(Mean, Sd) UCL 12.51
97.5% Chebyshev(Mean, Sd) UCL 13.64
99% Chebyshev(Mean, Sd) UCL 15.86

Potential UCL to Use

Use 95% Student's-t UCL 10.92

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002)

and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.

Note: For highly negative-skewed data, confidence limits (e.g., Chen, Johnson, Lognormal, and Gamma) may not be reliable. Chen's and Johnson's methods provide adjustments for positvely skewed data sets.



ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Iron

General Statistics

Number of Valid Observations 24

Number of Distinct Observations 24

Raw Statistics

Minimum 6780 Maximum 41800 Mean 26099 Median 25650 SD 8422

Std. Error of Mean 1719
Coefficient of Variation 0.323
Skewness -0.0624

Log-transformed Statistics

Minimum of Log Data 8.822 Maximum of Log Data 10.64 Mean of log Data 10.11 SD of log Data 0.39

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.979 Shapiro Wilk Critical Value 0.916

Data appear Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.887 Shapiro Wilk Critical Value 0.916

Data not Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 29045

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 28903 95% Modified-t UCL (Johnson-1978) 29042

Assuming Lognormal Distribution

95% H-UCL 30855 95% Chebyshev (MVUE) UCL 35748 97.5% Chebyshev (MVUE) UCL 39803 99% Chebyshev (MVUE) UCL 47769

Gamma Distribution Test

k star (bias corrected) 7.225 Theta Star 3612 MLE of Mean 26099 MLE of Standard Deviation 9709

MLE of Standard Deviation 9709 nu star 346.8

Approximate Chi Square Value (.05) 304.7

Adjusted Level of Significance 0.0392

Adjusted Chi Square Value 301.9

Anderson-Darling Test Statistic 0.369
Anderson-Darling 5% Critical Value 0.745
Kolmogorov-Smirnov Test Statistic 0.128
Kolmogorov-Smirnov 5% Critical Value 0.178

Data appear Gamma Distributed at 5% Significance Level

Data Distribution

Data appear Normal at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 29710 95% Adjusted Gamma UCL 29983

Nonparametric Statistics

95% CLT UCL 28927
95% Jackknife UCL 29045
95% Standard Bootstrap UCL 28844
95% Bootstrap-t UCL 29122
95% Hall's Bootstrap UCL 28907
95% Percentile Bootstrap UCL 28903
95% BCA Bootstrap UCL 28813
95% Chebyshev(Mean, Sd) UCL 33593
97.5% Chebyshev(Mean, Sd) UCL 36835
99% Chebyshev(Mean, Sd) UCL 43204

Potential UCL to Use

Use 95% Student's-t UCL 29045

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002)

and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.

Note: For highly negative-skewed data, confidence limits (e.g., Chen, Johnson, Lognormal, and Gamma) may not be reliable. Chen's and Johnson's methods provide adjustments for positvely skewed data sets.



ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Manganese

General Statistics

Number of Valid Observations 24 Number of Distinct Observations 24

Raw Statistics Log-transformed Statistics

> Minimum 191 Minimum of Log Data 5.252 Maximum 650 Maximum of Log Data 6.477 Mean 386.1 Mean of log Data 5.893 Median 360.5 SD of log Data 0.365 SD 141

Std. Error of Mean 28.78 Coefficient of Variation 0.365 Skewness 0.579

MLE of Standard Deviation 145.3

95% Approximate Gamma UCL 440.2 95% Adjusted Gamma UCL 444.3

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

> Shapiro Wilk Test Statistic 0.923 Shapiro Wilk Test Statistic 0.957 Shapiro Wilk Critical Value 0.916 Shapiro Wilk Critical Value 0.916

> > 95% H-UCL 446.6

Data appear Normal at 5% Significance Level Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution Assuming Lognormal Distribution

95% Student's-t UCL 435.4 95% UCLs (Adjusted for Skewness) 95% Chebyshev (MVUE) UCL 514.4

95% Adjusted-CLT UCL (Chen-1995) 437.1 97.5% Chebyshev (MVUE) UCL 569.9 95% Modified-t UCL (Johnson-1978) 436 99% Chebyshev (MVUE) UCL 678.9

Gamma Distribution Test Data Distribution

> Data appear Normal at 5% Significance Level k star (bias corrected) 7.065 Theta Star 54.65 MLE of Mean 386.1

nu star 339.1 Approximate Chi Square Value (.05) 297.4 **Nonparametric Statistics**

Adjusted Level of Significance 0.0392 95% CLT UCL 433.4 Adjusted Chi Square Value 294.7 95% Jackknife UCL 435.4 95% Standard Bootstrap UCL 432.8

Anderson-Darling Test Statistic 0.402 95% Bootstrap-t UCL 441.9 Anderson-Darling 5% Critical Value 0.745 95% Hall's Bootstrap UCL 439 Kolmogorov-Smirnov Test Statistic 0.138 95% Percentile Bootstrap UCL 433.2 Kolmogorov-Smirnov 5% Critical Value 0.178 95% BCA Bootstrap UCL 436.5 95% Chebyshev(Mean, Sd) UCL 511.6

Data appear Gamma Distributed at 5% Significance Level 97.5% Chebyshev(Mean, Sd) UCL 565.8

99% Chebyshev(Mean, Sd) UCL 672.5 **Assuming Gamma Distribution**

Potential UCL to Use Use 95% Student's-t UCL 435.4

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Appendix C-3
ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill
Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Thallium

	General Statis	stics	
Number of Valid Data	24	Number of Detected Data	23
Number of Distinct Detected Data	21	Number of Non-Detect Data	1
		Percent Non-Detects	4.17%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.0066	Minimum Detected	-5.021
Maximum Detected	0.8	Maximum Detected	-0.223
Mean of Detected	0.0605	Mean of Detected	-3.572
SD of Detected	0.162	SD of Detected	0.883
Minimum Non-Detect	1.2	Minimum Non-Detect	0.182
Maximum Non-Detect	1.2	Maximum Non-Detect	0.182
	UCL Statist	ics	
Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Onl	у
Shapiro Wilk Test Statistic	0.274	Shapiro Wilk Test Statistic	0.764
5% Shapiro Wilk Critical Value	0.914	5% Shapiro Wilk Critical Value	0.914
Data not Normal at 5% Significance Level		Data not Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	0.083	Mean	-3.444
SD	0.193	SD	1.066
95% DL/2 (t) UCL	0.15	95% H-Stat (DL/2) UCL	0.101
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE method failed to converge properly		Mean in Log Scale	-3.572
		SD in Log Scale	0.864
		Mean in Original Scale	0.0591
		SD in Original Scale	0.158
		95% t UCL	0.114
		95% Percentile Bootstrap UCL	0.123
		95% BCA Bootstrap UCL	0.157 0.0625
		95% H-UCL	



Appendix C-3 ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Only	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	0.705	Data do not follow a Discernable Distribution (0.05)	
Theta Star	0.0858		
nu star	32.43		
A-D Test Statistic	4.003	Nonparametric Statistics	
5% A-D Critical Value	0.781	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.781	Mean	0.0605
5% K-S Critical Value	0.188	SD	0.158
Data not Gamma Distributed at 5% Significance Leve	el	SE of Mean	0.0337
		95% KM (t) UCL	0.118
Assuming Gamma Distribution		95% KM (z) UCL	0.116
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	0.118
Minimum	0.0066	95% KM (bootstrap t) UCL	0.638
Maximum	0.8	95% KM (BCA) UCL	0.127
Mean	0.0601	95% KM (Percentile Bootstrap) UCL	0.127
Median	0.0275	95% KM (Chebyshev) UCL	0.207
SD	0.158	97.5% KM (Chebyshev) UCL	0.271
k star	0.734	99% KM (Chebyshev) UCL	0.396
Theta star	0.0819		
Nu star	35.22	Potential UCLs to Use	
AppChi2	22.64	95% KM (Chebyshev) UCL	0.207
95% Gamma Approximate UCL	0.0935		
95% Adjusted Gamma UCL	0.0965		

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006). For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface/Subsurface Soil at Former Sugar Mill

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Vanadium

General Statistics

Number of Valid Observations 24

Number of Distinct Observations 24

Raw Statistics

Minimum 24.3 Maximum 192 Mean 84.3

Median 80

SD 34.07 Std. Error of Mean 6.954 Coefficient of Variation 0.404 Skewness 1.11 Log-transformed Statistics

Minimum of Log Data 3.19

Maximum of Log Data 5.257

Mean of log Data 4.352

SD of log Data 0.434

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.917 Shapiro Wilk Critical Value 0.916 **Lognormal Distribution Test**

Shapiro Wilk Test Statistic 0.935 Shapiro Wilk Critical Value 0.916

Data appear Normal at 5% Significance Level

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 96.21

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 97.42 95% Modified-t UCL (Johnson-1978) 96.48 **Assuming Lognormal Distribution**

95% H-UCL 101.5 95% Chebyshev (MVUE) UCL 118.7 97.5% Chebyshev (MVUE) UCL 133.3 99% Chebyshev (MVUE) UCL 162

Gamma Distribution Test

k star (bias corrected) 5.49 Theta Star 15.35

MLE of Mean 84.3

MLE of Standard Deviation 35.97

nu star 263.5

Approximate Chi Square Value (.05) 227

Adjusted Level of Significance 0.0392 Adjusted Chi Square Value 224.6

Anderson-Darling Test Statistic 0.532

Anderson-Darling 5% Critical Value 0.746

Kolmogorov-Smirnov Test Statistic 0.145

Kolmogorov-Smirnov 5% Critical Value 0.178

Data appear Gamma Distributed at 5% Significance Level

Data Distribution

Data appear Normal at 5% Significance Level

Nonparametric Statistics

95% CLT UCL 95.73
95% Jackknife UCL 96.21
95% Standard Bootstrap UCL 95.39
95% Bootstrap-t UCL 98.79
95% Hall's Bootstrap UCL 102
95% Percentile Bootstrap UCL 95.25
95% BCA Bootstrap UCL 97.01
95% Chebyshev(Mean, Sd) UCL 114.6
97.5% Chebyshev(Mean, Sd) UCL 127.7
99% Chebyshev(Mean, Sd) UCL 153.5

Assuming Gamma Distribution

95% Approximate Gamma UCL 97.89 95% Adjusted Gamma UCL 98.93

Potential UCL to Use

Use 95% Student's-t UCL 96.21

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 14 of 14 6/29/2012

ProUCL Output - Surface/Subsurface Soil at Puerto Rico Beverage

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

General UCL Statistics for Data Sets with Non-Detects

User Selected Options

From File SB-PRB.wst Full Precision OFF

Confidence Coefficient 95%

Number of Bootstrap Operations 2000

Aluminum

General Statistics

Number of Valid Observations 20 Number of Distinct Observations 20

Raw Statistics Log-transformed Statistics

 Minimum 7060
 Minimum of Log Data 8.862

 Maximum 37800
 Maximum of Log Data 10.54

 Mean 13551
 Mean of log Data 9.409

 Median 11150
 SD of log Data 0.446

Std. Error of Mean 1648
Coefficient of Variation 0.544
Skewness 2.078

95% Student's-t UCL 16400

k star (bias corrected) 4.191

SD 7369

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.78
Shapiro Wilk Critical Value 0.905
Shapiro Wilk Critical Value 0.905

Data not Normal at 5% Significance Level

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution Assuming Lognormal Distribution

 95% UCLs (Adjusted for Skewness)
 95% Chebyshev (MVUE) UCL 19384

 95% Adjusted-CLT UCL (Chen-1995) 17080
 97.5% Chebyshev (MVUE) UCL 21977

95% Modified-t UCL (Johnson-1978) 16528 99% Chebyshev (MVUE) UCL 27069

Gamma Distribution Test Data Distribution

Theta Star 3233

Data appear Gamma Distributed at 5% Significance Level

MLE of Mean 13551 MLE of Standard Deviation 6619 nu star 167.6

Approximate Chi Square Value (.05) 138.7 Nonparametric Statistics

Adjusted Level of Significance 0.038 95% CLT UCL 16261

Adjusted Chi Square Value 136.6 95% Jackknife UCL 16400

95% Standard Bootstrap UCL 16171

Anderson-Darling Test Statistic 0.703 95% Bootstrap-t UCL 17855
Anderson-Darling 5% Critical Value 0.745 95% Hall's Bootstrap UCL 20221
Kolmogorov-Smirnov Test Statistic 0.158 95% Percentile Bootstrap UCL 16368
Kolmogorov-Smirnov 5% Critical Value 0.194 95% BCA Bootstrap UCL 16929

Data appear Gamma Distributed at 5% Significance Level 95% Chebyshev(Mean, Sd) UCL 20734

97.5% Chebyshev(Mean, Sd) UCL 23842

Assuming Gamma Distribution 99% Chebyshev(Mean, Sd) UCL 29946

95% Approximate Gamma UCL 16378 95% Adjusted Gamma UCL 16627

Potential UCL to Use Use 95% Approximate Gamma UCL 16378

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and Iaci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



95% H-UCL 16469

ProUCL Output - Surface/Subsurface Soil at Puerto Rico Beverage Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Arsenic

	General St	atistics	
Number of Valid Data	20	Number of Detected Data	4
Number of Distinct Detected Data	4	Number of Non-Detect Data	16
		Percent Non-Detects	80.00%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.27	Minimum Detected	-1.309
Maximum Detected	2.9	Maximum Detected	1.065
Mean of Detected	0.973	Mean of Detected	-0.582
SD of Detected	1.287	SD of Detected	1.116
Minimum Non-Detect	1.1	Minimum Non-Detect	0.0953
Maximum Non-Detect	1.5	Maximum Non-Detect	0.405
Note: Data have multiple DLs - Use of KM Method is recommended	d	Number treated as Non-Detect	19
For all methods (except KM, DL/2, and ROS Methods),		Number treated as Detected	1
Observations < Largest ND are treated as NDs		Single DL Non-Detect Percentage	95.00%

Warning: There are only 4 Distinct Detected Values in this data

Note: It should be noted that even though bootstrap may be performed on this data set the resulting calculations may not be reliable enough to draw conclusions

It is recommended to have 10-15 or more distinct observations for accurate and meaningful results.

UCL Statistics

Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Only		
Shapiro Wilk Test Statistic	0.675	Shapiro Wilk Test Statistic	0.771	
5% Shapiro Wilk Critical Value	0.748	5% Shapiro Wilk Critical Value	0.748	
Data not Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level		
Assuming Normal Distribution		Assuming Lognormal Distribution		
DL/2 Substitution Method		DL/2 Substitution Method		
Mean	0.68	Mean	-0.522	
SD	0.537	SD	0.456	
95% DL/2 (t) UCL	0.887	95% H-Stat (DL/2) UCL	0.81	
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method		
MLE method failed to converge properly		Mean in Log Scale	-0.963	
		SD in Log Scale	0.701	
		Mean in Original Scale	0.516	
		SD in Original Scale	0.597	
		95% t UCL	0.747	
		95% Percentile Bootstrap UCL	0.774	
		95% BCA Bootstrap UCL	0.924	
		95% H-UCL	0.699	



Appendix C-4 ProUCL Output - Surface/Subsurface Soil at Puerto Rico Beverage Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Only		Data Distribution Test with Detected Values Only		
k star (bias corrected)	0.426	Data Follow Appr. Gamma Distribution at 5% Significance	Level	
Theta Star	2.282			
nu star	3.409			
A-D Test Statistic	0.708	Nonparametric Statistics		
5% A-D Critical Value	0.666	Kaplan-Meier (KM) Method		
K-S Test Statistic	0.666	Mean	0.459	
5% K-S Critical Value	0.402	SD	0.564	
Data follow Appr. Gamma Distribution at 5% Significance Level		SE of Mean	0.151	
		95% KM (t) UCL	0.72	
Assuming Gamma Distribution		95% KM (z) UCL	0.708	
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	0.702	
Minimum	0.000001	95% KM (bootstrap t) UCL	1.2	
Maximum	2.9	95% KM (BCA) UCL	0.839	
Mean	0.589	95% KM (Percentile Bootstrap) UCL	0.804	
Median	0.301	95% KM (Chebyshev) UCL	1.119	
SD	0.735	97.5% KM (Chebyshev) UCL	1.405	
k star	0.217	99% KM (Chebyshev) UCL	1.966	
Theta star	2.717			
Nu star	8.673	Potential UCLs to Use		
AppChi2	3.131	95% KM (t) UCL	0.72	
95% Gamma Approximate UCL	1.632			
95% Adjusted Gamma UCL	N/A			

Note: DL/2 is not a recommended method.

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Maichle, and Lee (2006). For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface/Subsurface Soil at Puerto Rico Beverage

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chromium

General Statistics

Number of Valid Observations 20 Number of Distinct Observations 18

Raw Statistics Log-transformed Statistics

 Minimum 0.9
 Minimum of Log Data -0.105

 Maximum 27.5
 Maximum of Log Data 3.314

 Mean 4.065
 Mean of log Data 1.029

 Median 2.45
 SD of log Data 0.749

Std. Error of Mean 1.275 Coefficient of Variation 1.403 Skewness 4.014

SD 5.703

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.46 Shapiro Wilk Test Statistic 0.907
Shapiro Wilk Critical Value 0.905 Shapiro Wilk Critical Value 0.905

Data not Normal at 5% Significance Level

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution Assuming Lognormal Distribution

95% Student's-t UCL 6.27 95% H-UCL 5.499

95% UCLs (Adjusted for Skewness) 95% Chebyshev (MVUE) UCL 6.502

95% Adjusted-CLT UCL (Chen-1995) 7.386 97.5% Chebyshev (MVUE) UCL 7.74
95% Modified-t UCL (Johnson-1978) 6.461 99% Chebyshev (MVUE) UCL 10.17

Gamma Distribution Test Data Distribution

k star (bias corrected) 1.296 Data Follow Appr. Gamma Distribution at 5% Significance Level

Nonparametric Statistics

Theta Star 3.138 MLE of Mean 4.065

MLE of Standard Deviation 3.571 nu star 51.82

Adjusted Level of Significance 0.038 95% CLT UCL 6.163
Adjusted Chi Square Value 35.26 95% Jackknife UCL 6.27

Anderson-Darling Test Statistic 1.393

Anderson-Darling Test Statistic 1.393

Anderson-Darling 5% Critical Value 0.758

Anderson-Darling 5% Critical Value 0.758

Kolmogorov-Smirnov Test Statistic 0.188

Somma Distribution at 5% Significance Level

95% Chebyshev(Mean, Sd) UCL 9.624

Data follow Appr. Gamma Distribution at 5% Significance Level 95% Chebyshev(Mean, Sd) UCL 9.624 97.5% Chebyshev(Mean, Sd) UCL 12.03

Assuming Gamma Distribution

95% Approximate Gamma UCL 5.805 95% Adjusted Gamma UCL 5.974

Approximate Chi Square Value (.05) 36.29

Potential UCL to Use Use 95% Approximate Gamma UCL 5.805

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



99% Chebyshev(Mean, Sd) UCL 16.75

ProUCL Output - Surface/Subsurface Soil at Puerto Rico Beverage

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Cobalt

General Statistics

Number of Valid Observations 20 Number of Distinct Observations 18

Raw Statistics Log-transformed Statistics

 Minimum 2.1
 Minimum of Log Data 0.742

 Maximum 16.1
 Maximum of Log Data 2.779

 Mean 6.62
 Mean of log Data 1.768

 Median 6.05
 SD of log Data 0.505

SD 3.535 Std. Error of Mean 0.79

Coefficient of Variation 0.534 Skewness 1.32

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.881 Shapiro Wilk Critical Value 0.905 Shapiro Wilk Critical Value 0.905

Data not Normal at 5% Significance Level

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution Assuming Lognormal Distribution

95% Student's-t UCL 7.987 95% H-UCL 8.41 **95% UCLs (Adjusted for Skewness)** 95% Chebyshev (MVUE) UCL 9.978

95% Adjusted-CLT UCL (Chen-1995) 8.169 97.5% Chebyshev (MVUE) UCL 11.44 95% Modified-t UCL (Johnson-1978) 8.026 99% Chebyshev (MVUE) UCL 14.3

Gamma Distribution Test Data Distribution

k star (bias corrected) 3.645 Data appear Gamma Distributed at 5% Significance Level

Nonparametric Statistics

Theta Star 1.816
MLE of Mean 6.62

nu star 145.8

Adjusted Level of Significance 0.038 95% CLT UCL 7.92
Adjusted Chi Square Value 117 95% Jackknife UCL 7.987

Anderson-Darling Test Statistic 0.349

Anderson-Darling Test Statistic 0.349

Anderson-Darling 5% Critical Value 0.745

Kolmogorov-Smirnov Test Statistic 0.136

Kolmogorov-Smirnov 5% Critical Value 0.195

Mall's Bootstrap UCL 8.427

Forma Distributed at 5% Significance Level

95% Chebyshev(Mean, Sd) UCL 10.07

Data appear Gamma Distributed at 5% Significance Level 95% Chebyshev(Mean, Sd) UCL 10.07 97.5% Chebyshev(Mean, Sd) UCL 11.56

Assuming Gamma Distribution

95% Approximate Gamma UCL 8.118 95% Adjusted Gamma UCL 8.251

MLE of Standard Deviation 3.467

Approximate Chi Square Value (.05) 118.9

Potential UCL to Use Use 95% Approximate Gamma UCL 8.118

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and Iaci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



99% Chebyshev(Mean, Sd) UCL 14.48

ProUCL Output - Surface/Subsurface Soil at Puerto Rico Beverage

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Iron

General Statistics

Number of Valid Observations 20 Number of Distinct Observations 18

Raw Statistics Log-transformed Statistics

 Minimum 13200
 Minimum of Log Data 9.488

 Maximum 44700
 Maximum of Log Data 10.71

 Mean 24125
 Mean of log Data 10.03

 Median 20100
 SD of log Data 0.364

Std. Error of Mean 2093
Coefficient of Variation 0.388
Skewness 0.917

SD 9362

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.877 Shapiro Wilk Test Statistic 0.93
Shapiro Wilk Critical Value 0.905 Shapiro Wilk Critical Value 0.905

Data appear Lognormal at 5% Significance Level

95% CLT UCL 27568

97.5% Chebyshev(Mean, Sd) UCL 37198

99% Chebyshev(Mean, Sd) UCL 44953

Data not Normal at 5% Significance Level

Assuming Normal Distribution Assuming Lognormal Distribution

95% Student's-t UCL 27745 95% H-UCL 28285

95% UCLs (Adjusted for Skewness) 95% Chebyshev (MVUE) UCL 32754

95% Adjusted-CLT UCL (Chen-1995) 28027 97.5% Chebyshev (MVUE) UCL 36517 95% Modified-t UCL (Johnson-1978) 27816 99% Chebyshev (MVUE) UCL 43909

Gamma Distribution Test Data Distribution

k star (bias corrected) 6.672 Data Follow Appr. Gamma Distribution at 5% Significance Level

MLE of Mean 24125

Theta Star 3616

MLE of Standard Deviation 9340

Adjusted Level of Significance 0.038

nu star 266.9

Approximate Chi Square Value (.05) 230 Nonparametric Statistics

Adjusted Chi Square Value 227.3 95% Jackknife UCL 27745 95% Standard Bootstrap UCL 27382

Anderson-Darling Test Statistic 0.737 95% Bootstrap-t UCL 28554

Anderson-Darling 5% Critical Value 0.743 95% Hall's Bootstrap UCL 27949

Kolmogorov-Smirnov Test Statistic 0.196 95% Percentile Bootstrap UCL 27455

Kolmogorov-Smirnov 5% Critical Value 0.194 95% BCA Bootstrap UCL 28240

Samma Distribution at 5% Significance Level 95% Chebyshev(Mean, Sd) UCL 33249

Data follow Appr. Gamma Distribution at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 27988 95% Adjusted Gamma UCL 28320

Potential UCL to Use Use 95% Approximate Gamma UCL 27988

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and Iaci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



ProUCL Output - Surface/Subsurface Soil at Puerto Rico Beverage

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Manganese

General Statistics

Number of Valid Observations 20 Number of Distinct Observations 19

Raw Statistics Log-transformed Statistics

> Maximum 474 Maximum of Log Data 6.161 Mean 285 1 Mean of log Data 5.569

Median 287.5 SD of log Data 0.447

SD 108.3 Std. Error of Mean 24.23 Coefficient of Variation 0.38

Minimum 89.6

Skewness -0.107

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

> Shapiro Wilk Test Statistic 0.97 Shapiro Wilk Critical Value 0.905

Data appear Normal at 5% Significance Level Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 327

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 324.3 95% Modified-t UCL (Johnson-1978) 326.9

Gamma Distribution Test

k star (bias corrected) 5.235

Theta Star 54.45

MLE of Mean 285.1

MLE of Standard Deviation 124.6

nu star 209.4

Approximate Chi Square Value (.05) 176.9 Adjusted Level of Significance 0.038

Adjusted Chi Square Value 174.6

Anderson-Darling Test Statistic 0.445 Anderson-Darling 5% Critical Value 0.744

Kolmogorov-Smirnov Test Statistic 0.149

Kolmogorov-Smirnov 5% Critical Value 0.194 Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

Potential UCL to Use

95% Approximate Gamma UCL 337.4 95% Adjusted Gamma UCL 342

Shapiro Wilk Test Statistic 0.926

Shapiro Wilk Critical Value 0.905

Minimum of Log Data 4.495

Assuming Lognormal Distribution

95% H-UCL 354.4

95% Chebyshev (MVUE) UCL 417.2 97.5% Chebyshev (MVUE) UCL 473.1

99% Chebyshev (MVUE) UCL 582.9

Data Distribution

Data appear Normal at 5% Significance Level

Nonparametric Statistics

95% CLT UCL 324.9

95% Jackknife UCL 327

95% Standard Bootstrap UCL 324

95% Bootstrap-t UCL 326.2

95% Hall's Bootstrap UCL 323.8

95% Percentile Bootstrap UCL 322.5 95% BCA Bootstrap UCL 322.3

95% Chebyshev(Mean, Sd) UCL 390.7

97.5% Chebyshev(Mean, Sd) UCL 436.4

99% Chebyshev(Mean, Sd) UCL 526.1

Use 95% Student's-t UCL 327

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.

> Note: For highly negative-skewed data, confidence limits (e.g., Chen, Johnson, Lognormal, and Gamma) may not be reliable. Chen's and Johnson's methods provide adjustments for positvely skewed data sets.



ProUCL Output - Surface/Subsurface Soil at Puerto Rico Beverage

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Vanadium

General Statistics

Number of Valid Observations 20 Number of Distinct Observations 20

Raw Statistics Log-transformed Statistics

 Minimum 31.9
 Minimum of Log Data 3.463

 Maximum 162
 Maximum of Log Data 5.088

 Mean 69.29
 Mean of log Data 4.109

 Median 54.35
 SD of log Data 0.513

Std. Error of Mean 8.435
Coefficient of Variation 0.544
Skewness 1.047

95% Student's-t UCL 83.88

MLE of Mean 69.29

nu star 138.4

SD 37.72

Relevant UCL Statistics

Normal Distribution Test Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.868 Shapiro Wilk Test Statistic 0.926
Shapiro Wilk Critical Value 0.905 Shapiro Wilk Critical Value 0.905

Data not Normal at 5% Significance Level

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution Assuming Lognormal Distribution

95% UCLs (Adjusted for Skewness) 95% Chebyshev (MVUE) UCL 104.8

95% Adjusted-CLT UCL (Chen-1995) 85.27 97.5% Chebyshev (MVUE) UCL 120.2 95% Modified-t UCL (Johnson-1978) 84.2 99% Chebyshev (MVUE) UCL 150.7

Gamma Distribution Test Data Distribution

k star (bias corrected) 3.46 Data appear Gamma Distributed at 5% Significance Level
Theta Star 20.03

Nonparametric Statistics

99% Chebyshev(Mean, Sd) UCL 153.2

MLE of Standard Deviation 37.25

Adjusted Level of Significance 0.038 95% CLT UCL 83.16
Adjusted Chi Square Value 110.4 95% Jackknife UCL 83.88

95% Standard Bootstrap UCL 82.63
Anderson-Darling Test Statistic 0.629
95% Bootstrap-t UCL 86.56
Anderson-Darling 5% Critical Value 0.746
95% Hall's Bootstrap UCL 85.78
Kolmogorov-Smirnov Test Statistic 0.162
95% Percentile Bootstrap UCL 83.6
Kolmogorov-Smirnov 5% Critical Value 0.195
95% BCA Bootstrap UCL 85.15

Data appear Gamma Distributed at 5% Significance Level 95% Chebyshev(Mean, Sd) UCL 106.1 97.5% Chebyshev(Mean, Sd) UCL 122

Assuming Gamma Distribution

Approximate Chi Square Value (.05) 112.2

95% Approximate Gamma UCL 85.46 95% Adjusted Gamma UCL 86.9

Potential UCL to Use Use 95% Approximate Gamma UCL 85.46

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.

Page 8 of 8



95% H-UCL 88.22

General UCL Statistics for Data Sets with Non-Detects

User Selected Options

From File GW_a.wst Full Precision OFF

Confidence Coefficient 95% Number of Bootstrap Operations 2000

cis-1,2-Dichloroethene

	General Sta		
Number of Valid Data	35	Number of Detected Data	16
Number of Distinct Detected Data	15	Number of Non-Detect Data	19
		Percent Non-Detects	54.29%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.38	Minimum Detected	-0.968
Maximum Detected	300	Maximum Detected	5.704
Mean of Detected	66.63	Mean of Detected	2.181
SD of Detected	112.3	SD of Detected	2.331
Minimum Non-Detect	0.5	Minimum Non-Detect	-0.693
Maximum Non-Detect	0.5	Maximum Non-Detect	-0.693
	UCL Statis	stics	
Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values On	ıly
Shapiro Wilk Test Statistic	0.623	Shapiro Wilk Test Statistic	0.913
5% Shapiro Wilk Critical Value	0.887	5% Shapiro Wilk Critical Value	0.887
Data not Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	30.6	Mean	0.244
SD	81.77	SD	2.376
95% DL/2 (t) UCL	53.97	95% H-Stat (DL/2) UCL	133.8
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE yields a negative mean		Mean in Log Scale	-0.69
		SD in Log Scale	3.438
		Mean in Original Scale	30.55
		SD in Original Scale	81.79
		95% t UCL	53.92
		95% Percentile Bootstrap UCL	55.83
		95% BCA Bootstrap UCL	63.96
		95% H-UCL	7352



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Only		
k star (bias corrected) 0.314		Level
212.1		
10.05		
1.014	Nonparametric Statistics	
0.83	Kaplan-Meier (KM) Method	
0.83	Mean	30.67
0.232	SD	80.56
Level	SE of Mean	14.06
	95% KM (t) UCL	54.45
	95% KM (z) UCL	53.8
	95% KM (jackknife) UCL	53.94
0.000001	95% KM (bootstrap t) UCL	67.94
300	95% KM (BCA) UCL	55.8
30.46	95% KM (Percentile Bootstrap) UCL	56.25
0.000001	95% KM (Chebyshev) UCL	91.97
81.82	97.5% KM (Chebyshev) UCL	118.5
0.0955	99% KM (Chebyshev) UCL	170.6
318.8		
6.688	Potential UCLs to Use	
2.001	95% KM (t) UCL	54.45
101.8		
	0.314 212.1 10.05 1.014 0.83 0.83 0.232 Level 0.000001 300 30.46 0.000001 81.82 0.0955 318.8 6.688	0.314 Data Follow Appr. Gamma Distribution at 5% Significance 212.1 10.05 1.014 Nonparametric Statistics 0.83 Kaplan-Meier (KM) Method 0.83 SD Level SE of Mean 95% KM (t) UCL 95% KM (z) UCL 95% KM (jackknife) UCL 0.000001 95% KM (bootstrap t) UCL 300 95% KM (Percentile Bootstrap) UCL 0.000001 95% KM (Chebyshev) UCL 81.82 97.5% KM (Chebyshev) UCL 0.0955 99% KM (Chebyshev) UCL 318.8 6.688 Potential UCLs to Use

Note: DL/2 is not a recommended method.



Appendix C-5

ProUCL Output - Groundwater

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Tetrachloroethene

General S	tatistics
-----------	-----------

Number of Valid Data	35	Number of Detected Data	9
Number of Distinct Detected Data	8	Number of Non-Detect Data	26
		Percent Non-Detects	74.29%
Raw Statistics		Log-transformed Statistics	
		9	
Minimum Detected	0.1	Minimum Detected	-2.303
Minimum Detected Maximum Detected	0.1 8.5	ŭ	-2.303 2.14

SD of Detected

Minimum Non-Detect

Maximum Non-Detect

1.524

-1.609

-1.609

Warning: There are only 9 Detected Values in this data

2.722

0.2

0.2

SD of Detected

Minimum Non-Detect

Maximum Non-Detect

Note: It should be noted that even though bootstrap may be performed on this data set the resulting calculations may not be reliable enough to draw conclusions

It is recommended to have 10-15 or more distinct observations for accurate and meaningful results.

UCL Statistics

Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Onl	iy
Shapiro Wilk Test Statistic	0.666	Shapiro Wilk Test Statistic	0.931
5% Shapiro Wilk Critical Value	0.829	5% Shapiro Wilk Critical Value	0.829
Data not Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	0.521	Mean	-1.829
SD	1.506	SD	1.102
95% DL/2 (t) UCL	0.951	95% H-Stat (DL/2) UCL	0.48
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE yields a negative mean		Mean in Log Scale	-2.063
		SD in Log Scale	1.565
		Mean in Original Scale	0.538
		SD in Original Scale	1.505
		95% t UCL	0.968
		95% Percentile Bootstrap UCL	0.978
		95% BCA Bootstrap UCL	1.278
		95% H-UCL	1.027



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	0.481	Data appear Gamma Distributed at 5% Significance Lev	el
Theta Star	3.61		
nu star	8.654		
A-D Test Statistic	0.517	Nonparametric Statistics	
5% A-D Critical Value	0.762	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.762	Mean	0.543
5% K-S Critical Value	0.292	SD	1.479
Data appear Gamma Distributed at 5% Significance Lo	evel	SE of Mean	0.266
		95% KM (t) UCL	0.992
Assuming Gamma Distribution		95% KM (z) UCL	0.98
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	0.975
Minimum	0.000001	95% KM (bootstrap t) UCL	1.914
Maximum	8.5	95% KM (BCA) UCL	1.114
Mean	0.585	95% KM (Percentile Bootstrap) UCL	1.049
Median	0.000001	95% KM (Chebyshev) UCL	1.701
SD	1.524	97.5% KM (Chebyshev) UCL	2.202
k star	0.121	99% KM (Chebyshev) UCL	3.186
Theta star	4.845		
Nu star	8.449	Potential UCLs to Use	
AppChi2	2.998	95% KM (t) UCL	0.992
95% Gamma Approximate UCL	1.648		
95% Adjusted Gamma UCL	1.737		

Note: DL/2 is not a recommended method.



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

trans-1,2-Dichloroethene

General S	Statistics
-----------	------------

Number of Valid Data	35	Number of Detected Data	4
Number of Distinct Detected Data	4	Number of Non-Detect Data	31
		Percent Non-Detects	88.57%
Raw Statistics		Log-transformed Statistics	
Raw Statistics Minimum Detected	0.99	Log-transformed Statistics Minimum Detected	-0.0101
	0.99 13	· ·	-0.0101 2.565

SD of Detected

Minimum Non-Detect

Maximum Non-Detect

1.262

-0.693

-0.693

Warning: There are only 4 Distinct Detected Values in this data

5.714

0.5

0.5

SD of Detected

Minimum Non-Detect

Maximum Non-Detect

Note: It should be noted that even though bootstrap may be performed on this data set the resulting calculations may not be reliable enough to draw conclusions

It is recommended to have 10-15 or more distinct observations for accurate and meaningful results.

UCL Statistics

Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Onl	y
Shapiro Wilk Test Statistic	0.885	Shapiro Wilk Test Statistic	0.885
5% Shapiro Wilk Critical Value	0.748	5% Shapiro Wilk Critical Value	0.748
Data appear Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	0.881	Mean	-1.087
SD	2.461	SD	0.925
95% DL/2 (t) UCL	1.585	95% H-Stat (DL/2) UCL	0.753
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE yields a negative mean		Mean in Log Scale	-5.528
		SD in Log Scale	3.943
		Mean in Original Scale	0.688
		SD in Original Scale	2.514
		95% t UCL	1.407
		95% Percentile Bootstrap UCL	1.438
		95% BCA Bootstrap UCL	1.793
		95% H-UCL	1141



Appendix C-5

ProUCL Output - Groundwater

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	0.441	Data appear Normal at 5% Significance Level	
Theta Star	13.08		
nu star	3.53		
A D 7 O			
A-D Test Statistic	0.395	Nonparametric Statistics	
5% A-D Critical Value	0.666	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.666	Mean	1.537
5% K-S Critical Value	0.402	SD	2.261
Data appear Gamma Distributed at 5% Significance Lo	evel	SE of Mean	0.441
		95% KM (t) UCL	2.283
Assuming Gamma Distribution		95% KM (z) UCL	2.263
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	2.09
Minimum	0.000001	95% KM (bootstrap t) UCL	2.235
Maximum	13	95% KM (BCA) UCL	13
Mean	0.66	95% KM (Percentile Bootstrap) UCL	8.003
Median	0.000001	95% KM (Chebyshev) UCL	3.46
SD	2.52	97.5% KM (Chebyshev) UCL	4.293
k star	0.0851	99% KM (Chebyshev) UCL	5.928
Theta star	7.753		
Nu star	5.957	Potential UCLs to Use	
AppChi2	1.618	95% KM (t) UCL	2.283
95% Gamma Approximate UCL	2.429	95% KM (Percentile Bootstrap) UCL	8.003
95% Adjusted Gamma UCL	N/A		

Note: DL/2 is not a recommended method.



Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

General Statistics

Trichloroethene

Number of Valid Data	35	Number of Detected Data	7
Number of Distinct Detected Data	7	Number of Non-Detect Data	28
		Percent Non-Detects	80.00%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.29	Minimum Detected	-1.238
Maximum Detected	1 0	Maximum Detected	0.642

Minimum Detected	0.29	Minimum Detected	-1.238
Maximum Detected	1.9	Maximum Detected	0.642
Mean of Detected	0.783	Mean of Detected	-0.515
SD of Detected	0.67	SD of Detected	0.753
Minimum Non-Detect	0.5	Minimum Non-Detect	-0.693
Maximum Non-Detect	2.5	Maximum Non-Detect	0.916

Note: Data have multiple DLs - Use of KM Method is recommended Number treated as Non-Detect For all methods (except KM, DL/2, and ROS Methods), 0 Number treated as Detected Single DL Non-Detect Percentage Observations < Largest ND are treated as NDs 100.00%

Warning: There are only 7 Detected Values in this data

Note: It should be noted that even though bootstrap may be performed on this data set the resulting calculations may not be reliable enough to draw conclusions

It is recommended to have 10-15 or more distinct observations for accurate and meaningful results.

UCL Statistics

	UCL Statist	ics	
Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Only	у
Shapiro Wilk Test Statistic	0.723	Shapiro Wilk Test Statistic	0.809
5% Shapiro Wilk Critical Value	0.803	5% Shapiro Wilk Critical Value	0.803
Data not Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	0.385	Mean	-1.166
SD	0.385	SD	0.532
95% DL/2 (t) UCL	0.495	95% H-Stat (DL/2) UCL	0.429
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE method failed to converge properly		Mean in Log Scale	-0.902
		SD in Log Scale	0.553
		Mean in Original Scale	0.481
		SD in Original Scale	0.357
		95% t UCL	0.583
		95% Percentile Bootstrap UCL	0.584
		95% BCA Bootstrap UCL	0.631
		95% H-UCL	0.571



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	1.239	Data appear Lognormal at 5% Significance Level	
Theta Star	0.632		
nu star	17.34		
A-D Test Statistic	0.879	Nonparametric Statistics	
5% A-D Critical Value	0.715	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.715	Mean	0.453
5% K-S Critical Value	0.315	SD	0.331
Data not Gamma Distributed at 5% Significance Lev	rel	SE of Mean	0.0654
		95% KM (t) UCL	0.564
Assuming Gamma Distribution		95% KM (z) UCL	0.561
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	0.562
Minimum	0.000001	95% KM (bootstrap t) UCL	0.704
Maximum	1.9	95% KM (BCA) UCL	0.567
Mean	0.547	95% KM (Percentile Bootstrap) UCL	0.572
Median	0.483	95% KM (Chebyshev) UCL	0.738
SD	0.446	97.5% KM (Chebyshev) UCL	0.861
k star	0.335	99% KM (Chebyshev) UCL	1.103
Theta star	1.632		
Nu star	23.45	Potential UCLs to Use	
AppChi2	13.43	95% KM (t) UCL	0.564
95% Gamma Approximate UCL	0.955	95% KM (% Bootstrap) UCL	0.572
95% Adjusted Gamma UCL	0.981		

Note: DL/2 is not a recommended method.



Appendix C-5

ProUCL Output - Groundwater

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

General Statistics

Vinyl Chloride

35	Number of Detected Data	3
3	Number of Non-Detect Data	32
	Percent Non-Detects	91.43%
		3 Number of Non-Detect Data

Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.22	Minimum Detected	-1.514
Maximum Detected	0.73	Maximum Detected	-0.315
Mean of Detected	0.53	Mean of Detected	-0.758
SD of Detected	0.272	SD of Detected	0.658
Minimum Non-Detect	0.2	Minimum Non-Detect	-1.609
Maximum Non-Detect	0.2	Maximum Non-Detect	-1 609

Warning: There are only 3 Distinct Detected Values in this data set

The number of detected data may not be adequate enough to perform GOF tests, bootstrap, and ROS methods.

Those methods will return a 'N/A' value on your output display!

It is necessary to have 4 or more Distinct Values for bootstrap methods.

However, results obtained using 4 to 9 distinct values may not be reliable.

It is recommended to have 10 to 15 or more observations for accurate and meaningful results and estimates.

UCL Statistics

	002 014110110	•	
Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Only	у
Shapiro Wilk Test Statistic	0.878	Shapiro Wilk Test Statistic	0.831
5% Shapiro Wilk Critical Value	0.767	5% Shapiro Wilk Critical Value	0.767
Data appear Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	0.137	Mean	-2.17
SD	0.139	SD	0.467
95% DL/2 (t) UCL	0.177	95% H-Stat (DL/2) UCL	0.148
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE yields a negative mean		Mean in Log Scale	-4.616
		SD in Log Scale	2.086
		Mean in Original Scale	0.0658
		SD in Original Scale	0.162
		95% t UCL	0.112
		95% Percentile Bootstrap UCL	0.114
		95% BCA Bootstrap UCL	0.135
		95% H-UCL	0.368



Maunabo Groundwater Contamination Site

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Only		Data Distribution Test with Detected Values Only	
k star (bias corrected)	N/A	Data appear Normal at 5% Significance Level	
Theta Star	N/A		
nu star	N/A		
A-D Test Statistic	N/A	Nonparametric Statistics	
5% A-D Critical Value	N/A	Kaplan-Meier (KM) Method	
K-S Test Statistic	N/A	Mean	0.247
5% K-S Critical Value	N/A	SD	0.108
Data not Gamma Distributed at 5% Significance Leve	I	SE of Mean	0.0225
		95% KM (t) UCL	0.285
Assuming Gamma Distribution		95% KM (z) UCL	0.284
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	0.514
Minimum	N/A	95% KM (bootstrap t) UCL	0.263
Maximum	N/A	95% KM (BCA) UCL	0.73
Mean	N/A	95% KM (Percentile Bootstrap) UCL	0.73
Median	N/A	95% KM (Chebyshev) UCL	0.344
SD	N/A	97.5% KM (Chebyshev) UCL	0.387
k star	N/A	99% KM (Chebyshev) UCL	0.47
Theta star	N/A		
Nu star	N/A	Potential UCLs to Use	
AppChi2	N/A	95% KM (t) UCL	0.285
95% Gamma Approximate UCL	N/A	95% KM (Percentile Bootstrap) UCL	0.73
95% Adjusted Gamma UCL	N/A		

Note: DL/2 is not a recommended method.



Aluminum

	General Sta	tistics	
Number of Valid Data	31	Number of Detected Data	22
Number of Distinct Detected Data	20	Number of Non-Detect Data	9
Number of Missing Values	4	Percent Non-Detects	29.03%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	48.2	Minimum Detected	3.875
Maximum Detected	8190	Maximum Detected	9.011
Mean of Detected	540.8	Mean of Detected	5.127
SD of Detected	1714	SD of Detected	1.087
Minimum Non-Detect	20	Minimum Non-Detect	2.996
Maximum Non-Detect	20	Maximum Non-Detect	2.996
	UCL Statis	stics	
Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values On	ly
Shapiro Wilk Test Statistic	0.277	Shapiro Wilk Test Statistic	0.774
5% Shapiro Wilk Critical Value	0.911	5% Shapiro Wilk Critical Value	0.911
Data not Normal at 5% Significance Level		Data not Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	386.7	Mean	4.307
SD	1455	SD	1.589
95% DL/2 (t) UCL	830.2	95% H-Stat (DL/2) UCL	664.3
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE yields a negative mean		Mean in Log Scale	4.432
,		SD in Log Scale	1.466
		Mean in Original Scale	389
		SD in Original Scale	1454
		95% t UCL	832.3
		95% Percentile Bootstrap UCL	913.1
		95% BCA Bootstrap UCL	1184
		95% H-UCL	554.2



Appendix C-5

ProUCL Output - Groundwater

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	y	Data Distribution Test with Detected Values Only	
k star (bias corrected)	0.495	Data do not follow a Discernable Distribution (0.05)	
Theta Star	1092		
nu star	21.79		
A-D Test Statistic	3.989	Nonparametric Statistics	
5% A-D Critical Value	0.801	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.801	Mean	397.8
5% K-S Critical Value	0.195	SD	1429
Data not Gamma Distributed at 5% Significance Lev	rel	SE of Mean	262.6
•		95% KM (t) UCL	843.5
Assuming Gamma Distribution		95% KM (z) UCL	829.7
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	839.6
Minimum	0.000001	95% KM (bootstrap t) UCL	4965
Maximum	8190	95% KM (BCA) UCL	929.6
Mean	383.8	95% KM (Percentile Bootstrap) UCL	914.6
Median	122	95% KM (Chebyshev) UCL	1542
SD	1456	97.5% KM (Chebyshev) UCL	2038
k star	0.134	99% KM (Chebyshev) UCL	3011
Theta star	2860		
Nu star	8.32	Potential UCLs to Use	
AppChi2	2.922	97.5% KM (Chebyshev) UCL	2038
95% Gamma Approximate UCL	1093		
95% Adjusted Gamma UCL	1163		

Note: DL/2 is not a recommended method.



Arsenic

	General Stati	stics	
Number of Valid Data	31	Number of Detected Data	16
Number of Distinct Detected Data	13	Number of Non-Detect Data	15
Number of Missing Values	4	Percent Non-Detects	48.39%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.41	Minimum Detected	-0.892
Maximum Detected	7.2	Maximum Detected	1.974
Mean of Detected	5.202	Mean of Detected	1.432
SD of Detected	2.177	SD of Detected	0.89
Minimum Non-Detect	1	Minimum Non-Detect	0
Maximum Non-Detect	1	Maximum Non-Detect	0
	UCL Ctation		
Normal Distribution Test with Detected Values Only	UCL Statist	Lognormal Distribution Test with Detected Values On	lv.
Shapiro Wilk Test Statistic	0.801	Shapiro Wilk Test Statistic	ر. 0.608
5% Shapiro Wilk Critical Value	0.887	5% Shapiro Wilk Critical Value	0.887
Data not Normal at 5% Significance Level	0.007	Data not Lognormal at 5% Significance Level	0.007
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	2.927	Mean	0.404
SD	2.842	SD	1.25
95% DL/2 (t) UCL	3.793	95% H-Stat (DL/2) UCL	6.103
Maximum Likelihood Estimate(MLE) Method		Log ROS Method	
Mean	5.879	Mean in Log Scale	0.725
SD	1.19	SD in Log Scale	1.055
95% MLE (t) UCL	6.241	Mean in Original Scale	3.229
95% MLE (Tiku) UCL	6.418	SD in Original Scale	2.61
		95% t UCL	4.024
		95% Percentile Bootstrap UCL	4.065
		95% BCA Bootstrap UCL	4.071
		95% H UCL	5.812



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	y	Data Distribution Test with Detected Values Only	
k star (bias corrected)	2.037	Data do not follow a Discernable Distribution (0.05)	
Theta Star	2.554		
nu star	65.18		
A-D Test Statistic	2.266	Nonparametric Statistics	
5% A-D Critical Value	0.748	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.748	Mean	2.91
5% K-S Critical Value	0.217	SD	2.811
Data not Gamma Distributed at 5% Significance Lev	el	SE of Mean	0.522
		95% KM (t) UCL	3.795
Assuming Gamma Distribution		95% KM (z) UCL	3.768
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	3.783
Minimum	0.000001	95% KM (bootstrap t) UCL	3.76
Maximum	7.2	95% KM (BCA) UCL	4.958
Mean	3.252	95% KM (Percentile Bootstrap) UCL	4.861
Median	3.139	95% KM (Chebyshev) UCL	5.184
SD	2.71	97.5% KM (Chebyshev) UCL	6.168
k star	0.238	99% KM (Chebyshev) UCL	8.101
Theta star	13.68		
Nu star	14.74	Potential UCLs to Use	
AppChi2	7.083	95% KM (t) UCL	3.795
95% Gamma Approximate UCL	6.769	95% KM (% Bootstrap) UCL	4.861
95% Adjusted Gamma UCL	7.062		

Note: DL/2 is not a recommended method.



Maunabo Groundwater Contamination Site Maunabo. Puerto Rico

Barium

General Statistics

Number of Valid Observations 31 Number of Missing Values 4 Number of Distinct Observations 28

Minimum of Log Data 3.325

Raw Statistics

Minimum 27.8

Maximum 346

Mean 175.7

Median 154

SD 91.41

Std. Error of Mean 16.42

Skewness 0.259

Maximum of Log Data 5.846 Mean of log Data 4.991 SD of log Data 0.678

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.939 Shapiro Wilk Critical Value 0.929

Coefficient of Variation 0.52

Lognormal Distribution Test

Log-transformed Statistics

Shapiro Wilk Test Statistic 0.878 Shapiro Wilk Critical Value 0.929

Data appear Normal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 203.6

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 203.595% Modified-t UCL (Johnson-1978) 203.7

Assuming Lognormal Distribution

Data not Lognormal at 5% Significance Level

95% H-UCL 239.5 95% Chebyshev (MVUE) UCL 288.4 97.5% Chebyshev (MVUE) UCL 333.8 99% Chebyshev (MVUE) UCL 422.9

Gamma Distribution Test

Theta Star 64.89

MLE of Mean 175.7

MLE of Standard Deviation 106.8

nu star 167.9

k star (bias corrected) 2.708

Approximate Chi Square Value (.05) 138.9

Adjusted Level of Significance 0.0413

Adjusted Chi Square Value 137.5

Anderson-Darling Test Statistic 0.668
Anderson-Darling 5% Critical Value 0.753
Kolmogorov-Smirnov Test Statistic 0.126
Kolmogorov-Smirnov 5% Critical Value 0.159

Data appear Gamma Distributed at 5% Significance Level

Data Distribution

Data appear Normal at 5% Significance Level

 Nonparametric Statistics

 95% CLT UCL
 202.7

 95% Jackknife UCL
 203.6

 95% Standard Bootstrap UCL
 202.4

 95% Bootstrap-t UCL
 205.4

 95% Hall's Bootstrap UCL
 203.7

 95% Percentile Bootstrap UCL
 201.8

 95% BCA Bootstrap UCL
 205

 95% Chebyshev(Mean, Sd) UCL
 247.3

 97.5% Chebyshev(Mean, Sd) UCL
 278.3

 99% Chebyshev(Mean, Sd) UCL
 339.1

Assuming Gamma Distribution

95% Approximate Gamma UCL 212.4 95% Adjusted Gamma UCL 214.6

Potential UCL to Use

Use 95% Student's-t UCL 203.6



Chromium

	General Statistics	5	
Number of Valid Data	17	Number of Detected Data	6
Number of Distinct Detected Data	6	Number of Non-Detect Data	11
Number of Missing Values	18	Percent Non-Detects	64.71%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	2.2	Minimum Detected	0.788
Maximum Detected	33.4	Maximum Detected	3.509
Mean of Detected	9.767	Mean of Detected	1.767
SD of Detected	12.11	SD of Detected	1.041
Minimum Non-Detect	2	Minimum Non-Detect	0.693
Maximum Non-Detect	2	Maximum Non-Detect	0.693

Warning: There are only 6 Detected Values in this data

Note: It should be noted that even though bootstrap may be performed on this data set the resulting calculations may not be reliable enough to draw conclusions

It is recommended to have 10-15 or more distinct observations for accurate and meaningful results.

UCL Statistics

	Lognormal Distribution Test with Detected Values Only	1
0.705	Shapiro Wilk Test Statistic	0.89
0.788	5% Shapiro Wilk Critical Value	0.788
	Data appear Lognormal at 5% Significance Level	
	Assuming Lognormal Distribution	
	DL/2 Substitution Method	
4.094	Mean	0.624
8.029	SD	1.047
7.494	95% H-Stat (DL/2) UCL	6.614
N/A	Log ROS Method	
	Mean in Log Scale	-0.674
	SD in Log Scale	2.251
	Mean in Original Scale	3.623
	SD in Original Scale	8.231
	95% t UCL	7.108
	95% Percentile Bootstrap UCL	7.127
	95% BCA Bootstrap UCL	8.975
	95% H-UCL	98.63
	0.788 4.094 8.029 7.494	0.705 Shapiro Wilk Test Statistic 0.788 5% Shapiro Wilk Critical Value Data appear Lognormal at 5% Significance Level Assuming Lognormal Distribution DL/2 Substitution Method 4.094 Mean 8.029 SD 7.494 95% H-Stat (DL/2) UCL N/A Log ROS Method Mean in Log Scale SD in Log Scale SD in Log Scale SD in Original Scale SD in Original Scale 95% t UCL 95% Percentile Bootstrap UCL



Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	0.668	Data appear Gamma Distributed at 5% Significance Leve	el
Theta Star	14.61		
nu star	8.021		
A-D Test Statistic	0.557	Nonparametric Statistics	
5% A-D Critical Value	0.713	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.713	Mean	4.871
5% K-S Critical Value	0.34	SD	7.496
Data appear Gamma Distributed at 5% Significance Lo	evel	SE of Mean	1.992
		95% KM (t) UCL	8.348
Assuming Gamma Distribution		95% KM (z) UCL	8.147
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	7.996
Minimum	0.000001	95% KM (bootstrap t) UCL	27.38
Maximum	33.4	95% KM (BCA) UCL	9.959
Mean	3.447	95% KM (Percentile Bootstrap) UCL	8.676
Median	0.000001	95% KM (Chebyshev) UCL	13.55
SD	8.304	97.5% KM (Chebyshev) UCL	17.31
k star	0.11	99% KM (Chebyshev) UCL	24.69
Theta star	31.2		
Nu star	3.756	Potential UCLs to Use	
AppChi2	0.628	95% KM (t) UCL	8.348
95% Gamma Approximate UCL	20.62		
95% Adjusted Gamma UCL	25.29		

Note: DL/2 is not a recommended method.



Cobalt

	General Sta	atistics	
Number of Valid Data	31	Number of Detected Data	13
Number of Distinct Detected Data	13	Number of Non-Detect Data	18
Number of Missing Values	4	Percent Non-Detects	58.06%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.12	Minimum Detected	-2.12
Maximum Detected	6.5	Maximum Detected	1.872
Mean of Detected	1.164	Mean of Detected	-0.489
SD of Detected	1.695	SD of Detected	1.144
Minimum Non-Detect	1	Minimum Non-Detect	0
Maximum Non-Detect	1	Maximum Non-Detect	0
	UCL Stati	stics	
Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values On	ly
Shapiro Wilk Test Statistic	0.601	Shapiro Wilk Test Statistic	0.962
5% Shapiro Wilk Critical Value	0.866	5% Shapiro Wilk Critical Value	0.866
Data not Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	0.778	Mean	-0.608
SD	1.123	SD	0.731
95% DL/2 (t) UCL	1.121	95% H-Stat (DL/2) UCL	0.946
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE yields a negative mean		Mean in Log Scale	-0.915
		SD in Log Scale	1.003
		Mean in Original Scale	0.709
		SD in Original Scale	1.159
		95% t UCL	1.063
		95% Percentile Bootstrap UCL	1.077
		95% BCA Bootstrap UCL	1.38
		95% H-UCL	1.034



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	0.752	Data appear Gamma Distributed at 5% Significance Lev	el
Theta Star	1.547		
nu star	19.56		
A-D Test Statistic	0.49	Nonparametric Statistics	
5% A-D Critical Value	0.762	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.762	Mean	0.701
5% K-S Critical Value	0.244	SD	1.137
Data appear Gamma Distributed at 5% Significance L	evel	SE of Mean	0.22
		95% KM (t) UCL	1.074
Assuming Gamma Distribution		95% KM (z) UCL	1.062
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	1.068
Minimum	0.000001	95% KM (bootstrap t) UCL	1.504
Maximum	6.5	95% KM (BCA) UCL	1.116
Mean	0.827	95% KM (Percentile Bootstrap) UCL	1.098
Median	0.473	95% KM (Chebyshev) UCL	1.658
SD	1.205	97.5% KM (Chebyshev) UCL	2.073
k star	0.246	99% KM (Chebyshev) UCL	2.887
Theta star	3.366		
Nu star	15.24	Potential UCLs to Use	
AppChi2	7.426	95% KM (t) UCL	1.074
95% Gamma Approximate UCL	1.697		
95% Adjusted Gamma UCL	1.769		

Note: DL/2 is not a recommended method.



Copper

	General Stat	tistics	
Number of Valid Data	31	Number of Detected Data	23
Number of Distinct Detected Data	21	Number of Non-Detect Data	8
Number of Missing Values	4	Percent Non-Detects	25.81%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.45	Minimum Detected	-0.799
Maximum Detected	211	Maximum Detected	5.352
Mean of Detected	12.42	Mean of Detected	0.726
SD of Detected	43.87	SD of Detected	1.389
Minimum Non-Detect	2	Minimum Non-Detect	0.693
Maximum Non-Detect	2	Maximum Non-Detect	0.693
	UCL Statis	stics	
Normal Distribution Test with Detected Values Only	•	Lognormal Distribution Test with Detected Values On	ly
Shapiro Wilk Test Statistic	0.286	Shapiro Wilk Test Statistic	0.79
5% Shapiro Wilk Critical Value	0.914	5% Shapiro Wilk Critical Value	0.914
Data not Normal at 5% Significance Level		Data not Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	9.476	Mean	0.539
SD	37.91	SD	1.233
95% DL/2 (t) UCL	21.03	95% H-Stat (DL/2) UCL	6.751
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE yields a negative mean		Mean in Log Scale	0.511
		SD in Log Scale	1.293
		Mean in Original Scale	9.501
		SD in Original Scale	37.9
		95% t UCL	21.06
		95% Percentile Bootstrap UCL	22.81
		95% BCA Bootstrap UCL	29.92
		95% H-UCL	7.441



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	0.352	Data do not follow a Discernable Distribution (0.05)	
Theta Star	35.31		
nu star	16.19		
A-D Test Statistic	4.268	Nonparametric Statistics	
5% A-D Critical Value	0.833	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.833	Mean	9.465
5% K-S Critical Value	0.195	SD	37.29
Data not Gamma Distributed at 5% Significance Lev	rel	SE of Mean	6.849
		95% KM (t) UCL	21.09
Assuming Gamma Distribution		95% KM (z) UCL	20.73
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	21.02
Minimum	0.000001	95% KM (bootstrap t) UCL	240.1
Maximum	211	95% KM (BCA) UCL	22.61
Mean	9.467	95% KM (Percentile Bootstrap) UCL	22.81
Median	1.115	95% KM (Chebyshev) UCL	39.32
SD	37.93	97.5% KM (Chebyshev) UCL	52.24
k star	0.179	99% KM (Chebyshev) UCL	77.61
Theta star	52.96		
Nu star	11.08	Potential UCLs to Use	
AppChi2	4.629	97.5% KM (Chebyshev) UCL	52.24
95% Gamma Approximate UCL	22.66		
95% Adjusted Gamma UCL	23.85		

Note: DL/2 is not a recommended method.



Iron

	General St	atistics	
Number of Valid Data	31	Number of Detected Data	28
Number of Distinct Detected Data	28	Number of Non-Detect Data	3
Number of Missing Values	4	Percent Non-Detects	9.68%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	28	Minimum Detected	3.332
Maximum Detected	16600	Maximum Detected	9.717
Mean of Detected	1750	Mean of Detected	5.733
SD of Detected	3854	SD of Detected	1.843
Minimum Non-Detect	200	Minimum Non-Detect	5.298
Maximum Non-Detect	200	Maximum Non-Detect	5.298
	1101.00	est.	
Name of Biotoliustics Test with Betested Values Only	UCL Star		-1
Normal Distribution Test with Detected Values Only	0.507	Lognormal Distribution Test with Detected Values Or Shapiro Wilk Test Statistic	0.907
Shapiro Wilk Test Statistic 5% Shapiro Wilk Critical Value	0.507	5% Shapiro Wilk Critical Value	0.907
· ·	0.924	· ·	0.924
Data not Normal at 5% Significance Level		Data not Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	1590	Mean	5.623
SD	3690	SD	1.781
95% DL/2 (t) UCL	2715	95% H-Stat (DL/2) UCL	4193
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE yields a negative mean		Mean in Log Scale	5.591
		SD in Log Scale	1.814
		Mean in Original Scale	1589
		SD in Original Scale	3691
		95% t UCL	2714
		95% Percentile Bootstrap UCL	2736
		95% BCA Bootstrap UCL	3194
		95% H-UCL	4480



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	0.365	Data do not follow a Discernable Distribution (0.05)	
Theta Star	4795		
nu star	20.44		
A-D Test Statistic	2.173	Nonparametric Statistics	
5% A-D Critical Value	0.836	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.836	Mean	1587
5% K-S Critical Value	0.178	SD	3631
Data not Gamma Distributed at 5% Significance Lev	rel	SE of Mean	664.2
		95% KM (t) UCL	2714
Assuming Gamma Distribution		95% KM (z) UCL	2680
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	2712
Minimum	0.000001	95% KM (bootstrap t) UCL	3992
Maximum	16600	95% KM (BCA) UCL	2826
Mean	1581	95% KM (Percentile Bootstrap) UCL	2790
Median	120	95% KM (Chebyshev) UCL	4482
SD	3694	97.5% KM (Chebyshev) UCL	5735
k star	0.209	99% KM (Chebyshev) UCL	8196
Theta star	7563		
Nu star	12.96	Potential UCLs to Use	
AppChi2	5.864	99% KM (Chebyshev) UCL	8196
95% Gamma Approximate UCL	3493		
95% Adjusted Gamma UCL	3658		

Note: DL/2 is not a recommended method.



Maunabo Groundwater Contamination Site Maunabo. Puerto Rico

Manganese

General Statistics

Number of Valid Observations 31 Number of Missing Values 4 Number of Distinct Observations 31

Raw Statistics

Minimum 0.62 Maximum 2340 Mean 228.5 Median 59.2 SD 483.7 **Log-transformed Statistics**Minimum of Log Data -0.478

Maximum of Log Data 7.758 Mean of log Data 3.759 SD of log Data 2.207

Std. Error of Mean 86.87 Coefficient of Variation 2.117 Skewness 3.562

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.499 Shapiro Wilk Critical Value 0.929

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.955 Shapiro Wilk Critical Value 0.929

Data not Normal at 5% Significance Level

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 375.9

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 430.7 95% Modified-t UCL (Johnson-1978) 385.2

Assuming Lognormal Distribution

95% H-UCL 2583 95% Chebyshev (MVUE) UCL 1316 97.5% Chebyshev (MVUE) UCL 1717 99% Chebyshev (MVUE) UCL 2504

Gamma Distribution Test

k star (bias corrected) 0.378

Theta Star 604.9

MLE of Mean 228.5

MLE of Standard Deviation 371.7

nu star 23.42

Approximate Chi Square Value (.05) 13.41

Adjusted Level of Significance 0.0413

Adjusted Chi Square Value 12.98

Anderson-Darling Test Statistic 0.553
Anderson-Darling 5% Critical Value 0.833
Kolmogorov-Smirnov Test Statistic 0.126

Kolmogorov-Smirnov 5% Critical Value 0.169

Data appear Gamma Distributed at 5% Significance Level

Data Distribution

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 399.1 95% Adjusted Gamma UCL 412

Nonparametric Statistics

95% CLT UCL 371.4
95% Jackknife UCL 375.9
95% Standard Bootstrap UCL 365.8
95% Bootstrap-t UCL 685.5
95% Hall's Bootstrap UCL 1012
95% Percentile Bootstrap UCL 386.7
95% BCA Bootstrap UCL 434.4
95% Chebyshev(Mean, Sd) UCL 607.1
97.5% Chebyshev(Mean, Sd) UCL 771
99% Chebyshev(Mean, Sd) UCL 1093

Potential UCL to Use

Use 95% Adjusted Gamma UCL 412

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 24 of 26 6/29/2012

Vanadium

	General Sta	ntistics	
Number of Valid Data	31	Number of Detected Data	26
Number of Distinct Detected Data	25	Number of Non-Detect Data	5
Number of Missing Values	4	Percent Non-Detects	16.13%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.72	Minimum Detected	-0.329
Maximum Detected	68.2	Maximum Detected	4.222
Mean of Detected	14.44	Mean of Detected	2.316
SD of Detected	13.2	SD of Detected	0.946
Minimum Non-Detect	5	Minimum Non-Detect	1.609
Maximum Non-Detect	5	Maximum Non-Detect	1.609
	UCL Stati	stics	
Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values On	ly
Shapiro Wilk Test Statistic	0.734	Shapiro Wilk Test Statistic	0.941
5% Shapiro Wilk Critical Value	0.92	5% Shapiro Wilk Critical Value	0.92
Data not Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	12.51	Mean	2.09
SD	12.85	SD	1.01
95% DL/2 (t) UCL	16.43	95% H-Stat (DL/2) UCL	21.09
Maximum Likelihood Estimate(MLE) Method		Log ROS Method	
Mean	10.17	Mean in Log Scale	2.08
SD	15.53	SD in Log Scale	1.033
95% MLE (t) UCL	14.91	Mean in Original Scale	12.51
95% MLE (Tiku) UCL	15.11	SD in Original Scale	12.85
		95% t UCL	16.43
		95% Percentile Bootstrap UCL	16.57
		95% BCA Bootstrap UCL	17.69
		95% H UCL	21.73



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Onl	у	Data Distribution Test with Detected Values Only	
k star (bias corrected)	1.406	Data appear Gamma Distributed at 5% Significance Lev	/el
Theta Star	10.27		
nu star	73.12		
A-D Test Statistic	0.334	Nonparametric Statistics	
5% A-D Critical Value	0.761	Kaplan-Meier (KM) Method	
K-S Test Statistic	0.761	Mean	12.46
5% K-S Critical Value	0.174	SD	12.69
Data appear Gamma Distributed at 5% Significance Lo	evel	SE of Mean	2.327
		95% KM (t) UCL	16.41
Assuming Gamma Distribution		95% KM (z) UCL	16.29
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	16.4
Minimum	0.000001	95% KM (bootstrap t) UCL	18.72
Maximum	68.2	95% KM (BCA) UCL	16.96
Mean	12.18	95% KM (Percentile Bootstrap) UCL	16.42
Median	10.2	95% KM (Chebyshev) UCL	22.61
SD	13.14	97.5% KM (Chebyshev) UCL	27
k star	0.333	99% KM (Chebyshev) UCL	35.62
Theta star	36.63		
Nu star	20.62	Potential UCLs to Use	
AppChi2	11.31	95% KM (BCA) UCL	16.96
95% Gamma Approximate UCL	22.21		
95% Adjusted Gamma UCL	22.99		

Note: DL/2 is not a recommended method.



Appendix C-6 ProUCL Output - Surface Water

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

General UCL Statistics for Data Sets with Non-Detects

User Selected Options

From File SW.wst
Full Precision OFF
Confidence Coefficient 95%
Number of Bootstrap Operations 2000

Bromodichloromethane

	General	Statis	stics
--	---------	--------	-------

Number of Valid Data	6	Number of Detected Data	3
Number of Distinct Detected Data	3	Number of Non-Detect Data	3
		Percent Non-Detects	50.00%

Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.38	Minimum Detected	-0.968
Maximum Detected	1	Maximum Detected	0
Mean of Detected	0.7	Mean of Detected	-0.432
SD of Detected	0.31	SD of Detected	0.492
Minimum Non-Detect	0.5	Minimum Non-Detect	-0.693
Maximum Non-Detect	0.5	Maximum Non-Detect	-0.693

Warning: There are only 3 Distinct Detected Values in this data set

The number of detected data may not be adequate enough to perform GOF tests, bootstrap, and ROS methods.

Those methods will return a 'N/A' value on your output display!

It is necessary to have 4 or more Distinct Values for bootstrap methods.

However, results obtained using 4 to 9 distinct values may not be reliable.

It is recommended to have 10 to 15 or more observations for accurate and meaningful results and estimates.

UCL Statistics

Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Only	y
Shapiro Wilk Test Statistic	0.997	Shapiro Wilk Test Statistic	0.967
5% Shapiro Wilk Critical Value	0.767	5% Shapiro Wilk Critical Value	0.767
Data appear Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	0.475	Mean	-0.909
SD	0.315	SD	0.608
95% DL/2 (t) UCL	0.734	95% H-Stat (DL/2) UCL	1.071
Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE method failed to converge properly		Mean in Log Scale	-0.715
		SD in Log Scale	0.474
		Mean in Original Scale	0.539
		SD in Original Scale	0.272
		95% t UCL	0.763
		95% Percentile Bootstrap UCL	0.716
		95% BCA Bootstrap UCL	0.747
		95% H-UCL	0.944

Page 1 of 4



Appendix C-6 ProUCL Output - Surface Water

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Only	/	Data Distribution Test with Detected Values Only	
k star (bias corrected)	N/A	Data appear Normal at 5% Significance Level	
Theta Star	N/A		
nu star	N/A		
A-D Test Statistic	N/A	Nonparametric Statistics	
5% A-D Critical Value	N/A	Kaplan-Meier (KM) Method	
K-S Test Statistic	N/A	Mean	0.54
5% K-S Critical Value	N/A	SD	0.24
Data not Gamma Distributed at 5% Significance Leve	el	SE of Mean	0.12
		95% KM (t) UCL	0.782
Assuming Gamma Distribution		95% KM (z) UCL	0.738
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	0.827
Minimum	N/A	95% KM (bootstrap t) UCL	0.617
Maximum	N/A	95% KM (BCA) UCL	1
Mean	N/A	95% KM (Percentile Bootstrap) UCL	1
Median	N/A	95% KM (Chebyshev) UCL	1.064
SD	N/A	97.5% KM (Chebyshev) UCL	1.29
k star	N/A	99% KM (Chebyshev) UCL	1.735
Theta star	N/A		
Nu star	N/A	Potential UCLs to Use	
AppChi2	N/A	95% KM (t) UCL	0.782
95% Gamma Approximate UCL	N/A	95% KM (Percentile Bootstrap) UCL	1
95% Adjusted Gamma UCL	N/A		

Note: DL/2 is not a recommended method.



Appendix C-6

ProUCL Output - Surface Water

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Dibromochloromethane

Ganara	Statistics	

Number of Valid Data	6	Number of Detected Data	3
Number of Distinct Detected Data	3	Number of Non-Detect Data	3
		Percent Non-Detects	50.00%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.57	Minimum Detected	-0.562

-0.562	Minimum Detected	0.57	Minimum Detected
0.262	Maximum Detected	1.3	Maximum Detected
-0.121	Mean of Detected	0.937	Mean of Detected
0.415	SD of Detected	0.365	SD of Detected
-0.693	Minimum Non-Detect	0.5	Minimum Non-Detect
-0.693	Maximum Non-Detect	0.5	Maximum Non-Detect

Warning: There are only 3 Distinct Detected Values in this data set

The number of detected data may not be adequate enough to perform GOF tests, bootstrap, and ROS methods.

Those methods will return a 'N/A' value on your output display!

It is necessary to have 4 or more Distinct Values for bootstrap methods.

However, results obtained using 4 to 9 distinct values may not be reliable.

It is recommended to have 10 to 15 or more observations for accurate and meaningful results and estimates.

UCL Statistics

	OOL Olalisi	100	
Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Onl	у
Shapiro Wilk Test Statistic	1	Shapiro Wilk Test Statistic	0.985
5% Shapiro Wilk Critical Value	0.767	5% Shapiro Wilk Critical Value	0.767
Data appear Normal at 5% Significance Level		Data appear Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
DL/2 Substitution Method		DL/2 Substitution Method	
Mean	0.593	Mean	-0.753
SD	0.441	SD	0.741
95% DL/2 (t) UCL	0.956	95% H-Stat (DL/2) UCL	1.848
Maximum Likelihood Estimate(MLE) Method		Log ROS Method	
Mean	0.511	Mean in Log Scale	-0.817
SD	0.524	SD in Log Scale	0.847
95% MLE (t) UCL	0.942	Mean in Original Scale	0.585
95% MLE (Tiku) UCL	1.042	SD in Original Scale	0.453
		95% t UCL	0.957
		95% Percentile Bootstrap UCL	0.866
		95% BCA Bootstrap UCL	0.896
		95% H UCL	2.485



Appendix C-6 ProUCL Output - Surface Water

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test with Detected Values Only	/	Data Distribution Test with Detected Values Only	
k star (bias corrected)	N/A	Data appear Normal at 5% Significance Level	
Theta Star	N/A		
nu star	N/A		
A-D Test Statistic	NI/A	Noncomparis Southern	
	N/A	Nonparametric Statistics	
5% A-D Critical Value	N/A	Kaplan-Meier (KM) Method	
K-S Test Statistic	N/A	Mean	0.753
5% K-S Critical Value	N/A	SD	0.279
Data not Gamma Distributed at 5% Significance Leve	el	SE of Mean	0.14
		95% KM (t) UCL	1.035
Assuming Gamma Distribution		95% KM (z) UCL	0.983
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	1.076
Minimum	N/A	95% KM (bootstrap t) UCL	0.859
Maximum	N/A	95% KM (BCA) UCL	1.3
Mean	N/A	95% KM (Percentile Bootstrap) UCL	1.3
Median	N/A	95% KM (Chebyshev) UCL	1.362
SD	N/A	97.5% KM (Chebyshev) UCL	1.626
k star	N/A	99% KM (Chebyshev) UCL	2.143
Theta star	N/A		
Nu star	N/A	Potential UCLs to Use	
AppChi2	N/A	95% KM (t) UCL	1.035
95% Gamma Approximate UCL	N/A	95% KM (Percentile Bootstrap) UCL	1.3
95% Adjusted Gamma UCL	N/A		

Note: DL/2 is not a recommended method.



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

General UCL Statistics for Data Sets with Non-Detects

User Selected Options

From File SD.wst
Full Precision OFF
Confidence Coefficient 95%
Number of Bootstrap Operations 2000

Arsenic

	General Statistics		
Number of Valid Data	6	Number of Detected Data	2
Number of Distinct Detected Data	2	Number of Non-Detect Data	4
		Percent Non-Detects	66.67%
Raw Statistics		Log-transformed Statistics	
Minimum Detected	0.65	Minimum Detected	-0.431
Maximum Detected	2.7	Maximum Detected	0.993
Mean of Detected	1.675	Mean of Detected	0.281
SD of Detected	1.45	SD of Detected	1.007
Minimum Non-Detect	0.5	Minimum Non-Detect	-0.693
Maximum Non-Detect	0.62	Maximum Non-Detect	-0.478
Note: Data have multiple DLs - Use of KM Method is recommended	d	Number treated as Non-Detect	4
For all methods (except KM, DL/2, and ROS Methods),		Number treated as Detected	2
Observations < Largest ND are treated as NDs		Single DL Non-Detect Percentage	66 67%

Warning: Data set has only 2 Distinct Detected Values.

This may not be adequate enough to compute meaningful and reliable test statistics and estimates.

The Project Team may decide to use alternative site specific values to estimate environmental parameters (e.g., EPC, BTV).

Unless Data Quality Objectives (DQOs) have been met, it is suggested to collect additional observations.

The number of detected data may not be adequate enough to perform GOF tests, bootstrap, and ROS methods.

Those methods will return a 'N/A' value on your output display!

It is necessary to have 4 or more Distinct Values for bootstrap methods.

However, results obtained using 4 to 9 distinct values may not be reliable.

It is recommended to have 10 to 15 or more observations for accurate and meaningful results and estimates.

UCL Statistics

Normal Distribution Test with Detected Values Only		Lognormal Distribution Test with Detected Values Only	,
Shapiro Wilk Test Statistic	N/A	Shapiro Wilk Test Statistic	N/A
5% Shapiro Wilk Critical Value	N/A	5% Shapiro Wilk Critical Value	N/A
Data not Normal at 5% Significance Level		Data not Lognormal at 5% Significance Level	
Assuming Normal Distribution		Assuming Lognormal Distribution	
Assuming Normal Distribution DL/2 Substitution Method		Assuming Lognormal Distribution DL/2 Substitution Method	
· ·	0.746	u u	-0.754
DL/2 Substitution Method	0.746 0.969	DL/2 Substitution Method	-0.754 0.922



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Maximum Likelihood Estimate(MLE) Method	N/A	Log ROS Method	
MLE method failed to converge properly		Mean in Log Scale	N/A
		SD in Log Scale	N/A
		Mean in Original Scale	N/A
		SD in Original Scale	N/A
		95% t UCL	N/A
		95% Percentile Bootstrap UCL	N/A
		95% BCA Bootstrap UCL	N/A
		95% H-UCL	N/A
Gamma Distribution Test with Detected Values Only		Data Distribution Test with Detected Values Only	
k star (bias corrected)	N/A	Data do not follow a Discernable Distribution (0.05)	
Theta Star	N/A		
nu star	N/A		
A-D Test Statistic	N/A	Nonparametric Statistics	
5% A-D Critical Value	N/A	Kaplan-Meier (KM) Method	
K-S Test Statistic	N/A	Mean	0.992
5% K-S Critical Value	N/A	SD	0.764
Data not Gamma Distributed at 5% Significance Leve	I	SE of Mean	0.441
		95% KM (t) UCL	1.88
Assuming Gamma Distribution		95% KM (z) UCL	1.717
Gamma ROS Statistics using Extrapolated Data		95% KM (jackknife) UCL	2.594
Minimum	N/A	95% KM (bootstrap t) UCL	N/A
Maximum	N/A	95% KM (BCA) UCL	N/A
Mean	N/A	95% KM (Percentile Bootstrap) UCL	2.7
Median	N/A	95% KM (Chebyshev) UCL	2.914
SD	N/A	97.5% KM (Chebyshev) UCL	3.746
k star	N/A	99% KM (Chebyshev) UCL	5.38
Theta star	N/A		
Nu star	N/A	Potential UCLs to Use	
AppChi2	N/A	95% KM (BCA) UCL	N/A
95% Gamma Approximate UCL	N/A		
95% Adjusted Gamma UCL	N/A		

Note: DL/2 is not a recommended method.



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Chromium

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Log-transformed Statistics

Raw Statistics

Minimum 2.1 Maximum 6 Mean 3.6 Median 3.25 SD 1.328

Maximum of Log Data 1.792 Mean of log Data 1.229 SD of log Data 0.348

Minimum of Log Data 0.742

Std. Error of Mean 0.542 Coefficient of Variation 0.369

Skewness 1.301

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.898 Shapiro Wilk Critical Value 0.788 Lognormal Distribution Test
Shapiro Wilk Test Statistic 0.964

Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% UCLs (Adjusted for Skewness)

95% Student's-t UCL 4.693

Assuming Lognormal Distribution

95% H-UCL 5.203 95% Chebyshev (MVUE) UCL 5.817

95% Adjusted-CLT UCL (Chen-1995) 4.8 95% Modified-t UCL (Johnson-1978) 4.741 97.5% Chebyshev (MVUE) UCL 6.779 99% Chebyshev (MVUE) UCL 8.67



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected)	5.003	Data appear Normal at 5% Significance Level
Theta Star	0.72	
MLE of Mean	3.6	
MLE of Standard Deviation	1.609	
nu star	60.04	
Approximate Chi Square Value (.05)	43.22	Nonparametric Statistics
Adjusted Level of Significance	0.0122	95% CLT UCL 4.492
Adjusted Chi Square Value	38.13	95% Jackknife UCL 4.693
		95% Standard Bootstrap UCL 4.415
Anderson-Darling Test Statistic	0.293	95% Bootstrap-t UCL 5.555

Anderson-Darling 5% Critical Value 0.698 Kolmogorov-Smirnov Test Statistic 0.194 Kolmogorov-Smirnov 5% Critical Value 0.332 Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 5.001 95% Adjusted Gamma UCL 5.669

Use 95% Student's-t UCL 4.693

95% Hall's Bootstrap UCL 9.904

95% BCA Bootstrap UCL 4.65

95% Percentile Bootstrap UCL 4.467

95% Chebyshev(Mean, Sd) UCL 5.963 97.5% Chebyshev(Mean, Sd) UCL 6.986

99% Chebyshev(Mean, Sd) UCL 8.995

Potential UCL to Use

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 4 of 12 6/29/2012

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Cobalt

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Log-transformed Statistics

Raw Statistics

Minimum 2.5 Maximum 7.1 Mean 3.933 Median 3.55 SD 1.643

Minimum of Log Data 0.916 Maximum of Log Data 1.96 Mean of log Data 1.31 SD of log Data 0.361

Std. Error of Mean 0.671 Coefficient of Variation 0.418 Skewness 1.864

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.804 Shapiro Wilk Critical Value 0.788

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.908 Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 5.285

Assuming Lognormal Distribution 95% H-UCL 5.767

95% Chebyshev (MVUE) UCL 6.421 97.5% Chebyshev (MVUE) UCL 7.507 99% Chebyshev (MVUE) UCL 9.641

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 5.582 95% Modified-t UCL (Johnson-1978) 5.37



Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 4.389 Data appear Normal at 5% Significance Level
Theta Star 0.896
MI F of Mean 3.933

MLE of Standard Deviation 1.877 nu star 52.67

Approximate Chi Square Value (.05) 37

Adjusted Level of Significance 0.0122

Adjusted Chi Square Value 32.32

Anderson-Darling Test Statistic 0.445
Anderson-Darling 5% Critical Value 0.698
Kolmogorov-Smirnov Test Statistic 0.268
Kolmogorov-Smirnov 5% Critical Value 0.333

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 5.599 95% Adjusted Gamma UCL 6.41 Nonparametric Statistics

95% CLT UCL 5.036
95% Jackknife UCL 5.285
95% Standard Bootstrap UCL 4.915
95% Bootstrap-t UCL 6.678
95% Hall's Bootstrap UCL 10.14
95% Percentile Bootstrap UCL 5.067
95% BCA Bootstrap UCL 5.35
95% Chebyshev(Mean, Sd) UCL 6.857
97.5% Chebyshev(Mean, Sd) UCL 8.122
99% Chebyshev(Mean, Sd) UCL 10.61

Potential UCL to Use

Use 95% Student's-t UCL 5.285



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Iron

General Statistics

Number of Valid Observations 6 Number of Distinct Observations 6

 Minimum
 5220
 Minimum of Log Data
 8.56

 Maximum
 13500
 Maximum of Log Data
 9.51

 Mean
 8155
 Mean of log Data
 8.961

 Median
 7435
 SD of log Data
 0.32

 SD
 2871
 2871

Std. Error of Mean 1172 Coefficient of Variation 0.352 Skewness 1.556

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.868
Shapiro Wilk Critical Value 0.788

Data appear Normal at 5% Significance Level

Lognormal Distribution Test
Shapiro Wilk Test Statistic 0.95
Shapiro Wilk Critical Value 0.788

Data appear Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Modified-t UCL (Johnson-1978) 10641

95% Student's-t UCL 10517
95% UCLs (Adjusted for Skewness)
95% Adjusted-CLT UCL (Chen-1995) 10878

95% H-UCL 11338 95% Chebyshev (MVUE) UCL 12762 97.5% Chebyshev (MVUE) UCL 14765 99% Chebyshev (MVUE) UCL 18699

Assuming Lognormal Distribution



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected)	5.723	Data appear Normal at 5% Significance Level
Theta Star	1425	
MLE of Mean	8155	
MLE of Standard Deviation	3409	
nu star	68.67	
Approximate Chi Square Value (.05)	50.6	Nonparametric Statistics
Adjusted Level of Significance	0.0122	95% CLT UCL 10083
Adjusted Chi Square Value	45.04	95% Jackknife UCL 10517
		95% Standard Bootstrap UCL 9881
Anderson-Darling Test Statistic	0.331	95% Bootstrap-t UCL 12751
Anderson-Darling 5% Critical Value	0.698	95% Hall's Bootstrap UCL 20905

Kolmogorov-Smirnov 5% Critical Value 0.332

Kolmogorov-Smirnov Test Statistic 0.209

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 11068 95% Adjusted Gamma UCL 12433

Use 95% Student's-t UCL 10517

95% Percentile Bootstrap UCL 10098

95% Chebyshev(Mean, Sd) UCL 13264 97.5% Chebyshev(Mean, Sd) UCL 15475

99% Chebyshev(Mean, Sd) UCL 19817

95% BCA Bootstrap UCL 10358

Potential UCL to Use

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Manganese

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Minimum of Log Data 5.468

Raw Statistics

Minimum 237

Maximum 333

Mean 284.3

Median 284.5

SD 31.68

Maximum of Log Data 5.808 Mean of log Data 5.645 SD of log Data 0.112

Log-transformed Statistics

Std. Error of Mean 12.93 Coefficient of Variation 0.111 Skewness 0.0814

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.967 Shapiro Wilk Critical Value 0.788

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.965 Shapiro Wilk Critical Value 0.788

95% H-UCL 314

Data appear Normal at 5% Significance Level

95% UCLs (Adjusted for Skewness)

Assuming Normal Distribution

95% Student's-t UCL 310.4

95% Adjusted-CLT UCL (Chen-1995) 306.1 95% Modified-t UCL (Johnson-1978) 310.5

Assuming Lognormal Distribution

Data appear Lognormal at 5% Significance Level

95% Chebyshev (MVUE) UCL 341.2 97.5% Chebyshev (MVUE) UCL 365.8 99% Chebyshev (MVUE) UCL 414.1



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected)	48.07	Data appear Normal at 5% Significance Level
Theta Star	5.915	
MLE of Mean	284.3	
MLE of Standard Deviation	41.01	
nu star	576.9	
Approximate Chi Square Value (.05)	522.2	Nonparametric Statistics
Adjusted Level of Significance	0.0122	95% CLT UCL 305.6
Adjusted Chi Square Value	503.2	95% Jackknife UCL 310.4
		95% Standard Bootstrap UCL 303.8
Anderson-Darling Test Statistic	0.253	95% Bootstrap-t UCL 310.3
Anderson-Darling 5% Critical Value	0.696	95% Hall's Bootstrap UCL 313.9

Kolmogorov-Smirnov Test Statistic 0.179 Kolmogorov-Smirnov 5% Critical Value 0.332

Data appear Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 314.1 95% Adjusted Gamma UCL 326

Potential UCL to Use

Use 95% Student's-t UCL 310.4

95% Percentile Bootstrap UCL 304.2

95% Chebyshev(Mean, Sd) UCL 340.7 97.5% Chebyshev(Mean, Sd) UCL 365.1

99% Chebyshev(Mean, Sd) UCL 413

95% BCA Bootstrap UCL 303.5

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL. These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 10 of 12 6/29/2012

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Vanadium

General Statistics

Number of Valid Observations 6

Number of Distinct Observations 6

Raw Statistics

Minimum 33.5 Maximum 70.6 Mean 41.27 Median 35.55

SD 14.44 Std. Error of Mean 5.895

Coefficient of Variation 0.35
Skewness 2.398

Log-transformed Statistics

Minimum of Log Data 3.512

Maximum of Log Data 4.257

Mean of log Data 3.681

SD of log Data 0.285

Warning: A sample size of 'n' = 6 may not adequate enough to compute meaningful and reliable test statistics and estimates!

It is suggested to collect at least 8 to 10 observations using these statistical methods!

If possible compute and collect Data Quality Objectives (DQO) based sample size and analytical results.

Warning: There are only 6 Values in this data

Note: It should be noted that even though bootstrap methods may be performed on this data set, the resulting calculations may not be reliable enough to draw conclusions

The literature suggests to use bootstrap methods on data sets having more than 10-15 observations.

Relevant UCL Statistics

Normal Distribution Test

Shapiro Wilk Test Statistic 0.589 Shapiro Wilk Critical Value 0.788

Data not Normal at 5% Significance Level

Lognormal Distribution Test

Shapiro Wilk Test Statistic 0.628 Shapiro Wilk Critical Value 0.788

Data not Lognormal at 5% Significance Level

Assuming Normal Distribution

95% Student's-t UCL 53.14

95% UCLs (Adjusted for Skewness)

95% Adjusted-CLT UCL (Chen-1995) 57.13 95% Modified-t UCL (Johnson-1978) 54.11

Assuming Lognormal Distribution

95% H-UCL 54.71 95% Chebyshev (MVUE) UCL 61.86 97.5% Chebyshev (MVUE) UCL 70.86 99% Chebyshev (MVUE) UCL 88.54



Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Gamma Distribution Test

Data Distribution

k star (bias corrected) 6.614 Data do not follow a Discernable Distribution (0.05)

Theta Star 6.24

MLE of Mean 41.27

MLE of Standard Deviation 16.05

nu star 79.36

Approximate Chi Square Value (.05) 59.84

Adjusted Level of Significance 0.0122

Adjusted Chi Square Value 53.76

Anderson-Darling Test Statistic 1.254

Anderson-Darling 5% Critical Value 0.698

Kolmogorov-Smirnov Test Statistic 0.423

Kolmogorov-Smirnov 5% Critical Value 0.332

Data not Gamma Distributed at 5% Significance Level

Assuming Gamma Distribution

95% Approximate Gamma UCL 54.73

95% Adjusted Gamma UCL 60.93

Potential UCL to Use

Nonparametric Statistics

95% CLT UCL 50.96

95% Jackknife UCL 53.14

95% Standard Bootstrap UCL 50.28

95% Bootstrap-t UCL 137.4

95% Hall's Bootstrap UCL 115.4

95% Percentile Bootstrap UCL 52.67

95% BCA Bootstrap UCL 53.87

95% Chebyshev(Mean, Sd) UCL 66.96

97.5% Chebyshev(Mean, Sd) UCL 78.08

99% Chebyshev(Mean, Sd) UCL 99.92

Use 95% Student's-t UCL 53.14

or 95% Modified-t UCL 54.11

Note: Suggestions regarding the selection of a 95% UCL are provided to help the user to select the most appropriate 95% UCL.

These recommendations are based upon the results of the simulation studies summarized in Singh, Singh, and laci (2002) and Singh and Singh (2003). For additional insight, the user may want to consult a statistician.



Page 12 of 12 6/29/2012

R2-0002325

Appendix D

Shower Model

Input Assumptions and Estimated Air Concentrations

Appendix D Contents Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

- D-1 Values Used for Shower Model Adult
- D-2 Values Used for Shower Model Child (0-6 years)
- D-3 Medium-Specific Exposure Point Concentration Summary Groundwater (Adult)
- D-4 Medium-Specific Exposure Point Concentration Summary Groundwater (Child [0-6 years])
- D-5 Medium-Specific Exposure Point Concentration Summary Surface Water (Adult)
- D-6 Medium-Specific Exposure Point Concentration Summary Surface Water (Child [0-6 years])



TABLE D-1 VALUES USED FOR SHOWER MODEL

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Medium: Groundwater or Surface Water

Exposure Medium: Air

Receptor Population: Resident or Commercial/Industrial Worker

Receptor Age: Adult

Exposure	Parameter	Parameter Definition	Unit	Reasonable Ma	ximum Exposure	Central Tende	ency Exposure	Intake Equation/ Model Name
Route	Code	Parameter Delimition	Offic	Value	Reference	Value	Reference	intake Equation/ Model Name
Inhalation	CW	Chemical Concentration in Water	μg/L	Table B-3.3	Table B-3.3	Table B-3.3		Maximum air concentration in bathroom
	f	Fraction volatilized		chem-specific	Schaum et al. (1)	chem-specific	Schaum et al. (1)	$(C_{aMax}) (\mu g/m^3) =$
	F_w	Flow Rate	L/hr	1000	Schaum et al.	500		CW x f x Fw x t ₁ x 1/Va
	t ₁	Time of shower	hr	0.25	EPA 2004	0.10	EPA 2004	
	V_a	Bathroom volume	2		Schaum et al.	16	Schaum et al.	EPC (μ g/m ³) =
	t_2	Time after shower in bathroom	hr	0.33	EPA 2004	0.15	EPA 2004	$(((C_{aMax}/2) \times t_1) + (C_{aMax} \times t_2)) / (t_1 + t_2)$

EPC = Exposure Point Concentration, the average air concentration in the bathroom during and after shower

 $\mu g = microgram$

L = liter

hr = hour

m = meter

Note:

Sources:

EPA 2004. Risk Assessment Guidance for Superfund, Volume I: Human Health Evaluation Manual, Part E, Supplemental Guidance for Dermal Risk Assessment. EPA/540/R/99/005. Schaum *et al.* 1994. *Estimating Dermal and Inhalation Exposure to Volatile Chemicals in Domestic Water.* Water Contamination and Health, edited by Rhoda G.M. Wang. New York: Marcel Dekker, Inc.



Page 1 of 1 6/28/2012

⁽¹⁾ applies only to volatile chemicals

TABLE D-2 VALUES USED FOR SHOWER MODEL

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Medium: Groundwater or Surface Water

Exposure Medium: Air
Receptor Population: Resident

Receptor Age: Child (0-6 years)

Exposure	Parameter	Parameter Definition	Unit	Reasonable Ma	ximum Exposure	Central Tende	ency Exposure	Intake Equation/ Model Name
Route	Code	Parameter Delimition	Offic	Value	Reference	Value	Reference	intake Equation/ Model Name
Inhalation	CW	Chemical Concentration in Water	μg/L	Table B-3.3	Table B-3.3	Table B-3.3		Maximum air concentration in bathroom
	f	Fraction volatilized		chem-specific	Schaum et al. (1)	chem-specific	Schaum et al. (1)	$(C_{aMax}) (\mu g/m^3) =$
	$F_{\rm w}$	Flow Rate	L/hr	1000	Schaum et al.	500	Schaum et al.	CW x f x Fw x t ₁ x 1/Va
	t ₁	Time of shower	hr	0.45	EPA 2004	0.14	EPA 2004	
	V_a	Bathroom volume	m^3	6	Schaum et al.	16	Schaum et al.	EPC (μ g/m ³) =
	t_2	Time after shower in bathroom	hr	0.55	EPA 2004	0.19	EPA 2004	$(((C_{aMax}/2) \times t_1) + (C_{aMax} \times t_2)) / (t_1 + t_2)$

EPC = Exposure Point Concentration, the average air concentration in the bathroom during and after shower

 $\mu g = microgram$

L = liter

hr = hour

m = meter

Note:

Sources:

EPA 2004. Risk Assessment Guidance for Superfund, Volume I: Human Health Evaluation Manual, Part E, Supplemental Guidance for Dermal Risk Assessment. EPA/540/R/99/005. Schaum *et al.* 1994. *Estimating Dermal and Inhalation Exposure to Volatile Chemicals in Domestic Water*. Water Contamination and Health, edited by Rhoda G.M. Wang. New York: Marcel Dekker, Inc.



⁽¹⁾ applies only to volatile chemicals

TABLE D-3 MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future Medium: Groundwater

Exposure Medium: Air

Receptor Population: Resident or Commercial/Industrial Worker

Receptor Age: Adult

Evocaura Daint	CAS No.	Chemical of Potential Concern	Groundwater Exposure Point Concentration	Fraction		e Maximum osure	Central Tendency Exposure	
Exposure Point Water Vapor at	CAS NO.	Chemical of Potential Concern	(EPC) (µg/L)	Volatilized	C _{aMax} (µg/m³)	Air EPC (µg/m³)	C _{aMax} (µg/m³)	Air EPC (µg/m³)
Water Vapor at		Volatile Organic Compounds						
Showerhead	156-59-2	cis-1,2-Dichloroethene	5.4E+01	5.6E-01	1.3E+03	1.0E+03	9.6E+01	7.7E+01
	127-18-4	Tetrachloroethene	9.9E-01	5.0E-01	2.1E+01	1.6E+01	1.5E+00	1.2E+00
	156-60-5	trans-1,2-Dichloroethene	2.3E+00	5.6E-01	5.3E+01	4.2E+01	4.0E+00	3.2E+00
	79-01-6	Trichloroethene	5.6E-01	5.3E-01	1.2E+01	9.7E+00	9.3E-01	7.4E-01
	75-01-4	Vinyl Chloride	7.3E-01	5.9E-01	1.8E+01	1.4E+01	1.3E+00	1.1E+00



TABLE D-4 MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future Medium: Groundwater

Exposure Medium: Air Receptor Population: Resident

Receptor Age: Child (0-6 years)

Exposure Point	CAS No.	Chemical of Potential Concern	Groundwater Exposure Point	Fraction		e Maximum osure		endency sure
Exposure Point	CAS No.	Chemical of Potential Concern	Concentration (EPC) (µg/L)	Volatilized	C _{aMax} (µg/m³)	Air EPC (µg/m³)	C _{aMax} (µg/m³)	Air EPC (µg/m³)
Water Vapor at		Volatile Organic Compounds						
Showerhead	156-59-2	cis-1,2-Dichloroethene	5.4E+01	5.6E-01	2.3E+03	1.8E+03	1.3E+02	1.1E+02
	127-18-4	Tetrachloroethene	9.9E-01	5.0E-01	3.7E+01	2.9E+01	2.2E+00	1.7E+00
	156-60-5	trans-1,2-Dichloroethene	2.3E+00	5.6E-01	9.6E+01	7.4E+01	5.6E+00	4.4E+00
	79-01-6	Trichloroethene	5.6E-01	5.3E-01	2.2E+01	1.7E+01	1.3E+00	1.0E+00
	75-01-4	Vinyl Chloride	7.3E-01	5.9E-01	3.2E+01	2.5E+01	1.9E+00	1.5E+00



TABLE D-5 MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future

Medium: Surface Water

Exposure Medium: Air Receptor Population: Resident Receptor Age: Adult

Exposure Point	CAS No	Chamical of Potential Concern	Groundwater Exposure Point Concentration	Fraction	Reasonable Expo	e Maximum osure		endency sure
Exposure Point	por at head 75-27-4 Bromodichloromethane	(EPC) (µg/L)	Volatilized	C _{aMax} (µg/m³)	Air EPC (μg/m³)	C _{aMax} (µg/m³)	Air EPC (µg/m³)	
Water Vapor at		Volatile Organic Compounds	(p-3p = /					
Showerhead	75-27-4	Bromodichloromethane	1.0E+00	5.4E-01	2.3E+01	1.8E+01	1.7E+00	1.4E+00
	124-48-1	Dibromochloromethane	1.3E+00	5.4E-01	2.9E+01	2.3E+01	2.2E+00	1.8E+00



TABLE D-6 MEDIUM-SPECIFIC EXPOSURE POINT CONCENTRATION SUMMARY

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future

Medium: Surface Water

Exposure Medium: Air Receptor Population: Resident

Receptor Age: Child (0-6 years)

Exposure Point	CAS No	Chemical of Potential Concern	Groundwater Exposure Point Concentration	Fraction	Reasonable Expo	e Maximum osure	_	endency sure
Exposure i dint	CAS No. Chemical of Potential Conc Volatile Organic Compounds Bromodichloromethane Dibromochloromethane	Chemical of Fotential Concern	(EPC) (µg/L)	Volatilized	C _{aMax} (µg/m³)	Air EPC (µg/m³)	C _{aMax} (µg/m³)	Air EPC (µg/m³)
Water Vapor at		Volatile Organic Compounds						
Showerhead	75-27-4	Bromodichloromethane	1.0E+00	5.4E-01	4.1E+01	3.2E+01	2.4E+00	1.9E+00
	124-48-1	124-48-1 Dibromochloromethane		5.4E-01	5.3E+01	4.1E+01	3.1E+00	2.4E+00



Appendix E Vapor Intrusion Screening

Appendix E Contents Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Vapor Evaluation of Site Groundwater
Table E-1 Comparison of Maximum Detected Concentrations to Vapor Intrusion Screening Levels



Appendix E

Vapor Evaluation of Site Groundwater

CDM Smith performed a screening evaluation of the vapor intrusion pathway at the Maunabo Groundwater Contamination Site (Table E-1). The following contaminants were identified as contaminants of potential concern (COPCs) for the vapor intrusion pathway when the maximum detected concentrations in groundwater were compared to their respective screening levels (Table 2c of EPA 2002): bromoform, cis-1,2-dichloroethene (cis-1,2-DCE), tetrachloroethene (PCE), trichloroethene (TCE), and vinyl chloride.

CDM Smith has evaluated the distribution of these COPCs in groundwater based on the groundwater screening survey and monitoring well data from the Maunabo Remedial Investigation (RI) report (Figures 4-6 and 4-7, respectively, in the RI report), to determine if vapor intrusion is potentially a complete exposure pathway. The RI report identified three distinct plumes at the site (Figure 4-9 in the RI report). Each plume area was evaluated for the potential for vapor intrusion, as summarized below.

Groundwater Plume North of Maunabo #1 Supply Well

- The groundwater plume is in an area that is largely rural, with no buildings or structures. The only building in the area is the Puerto Rico Beverage (PRB) building.
- The concentration of at least one of the five COPCs for the vapor intrusion pathway exceeded the screening levels at MW-AD, MW-B, and MW-I. MW-AD and MW-I are located more than 100 feet from the PRB building. MW-B is located within 100 feet of the PRB building; however, the COPCs were not detected above the screening levels at T1-C, which is the groundwater screening survey for MW-B, (Figure 4-6 in the RI report) at the top of the groundwater table (6 to 10 feet below ground surface). Other screening locations (T1-N, GS-B, and T1-L) which are closer to the PRB building and located between T1-C/MW-B and the PRB building also had no detections of COPCs above screening levels at the top of the groundwater table.

Groundwater Plume South of Maunabo #1 Supply Well

- The groundwater plume south of the Rio Maunabo and the Maunabo #1 supply well is underneath several residences.
- The concentration of at least one of the five COPCs (PCE and TCE) for the vapor intrusion pathway exceeded the screening levels at MW-C, MW-FS, and MW-FD. MW-C is located more than 100 feet from the nearby residence. MW-FS and MW-FD are located within 100 feet of the nearby residence. The groundwater screening survey results at T4-C, which is the groundwater screening survey for MW-FS/FD, indicated that there is an uncontaminated layer of groundwater above the contaminated groundwater.

Groundwater Plume North of Maunabo #4 Supply Well

- This groundwater plume is in an area that is largely rural, with few buildings or structures.
- The concentration of one of the COPCs (bromoform) for the vapor intrusion pathway exceeded the screening levels at MW-M and MW-N. Both wells are located more than 100 feet from nearby buildings.



Conclusions and Recommendations

- The three groundwater plumes identified at the site are primarily in undeveloped areas with minimal structures.
- The concentration of the five COPCs for the vapor intrusion pathways exceeded the screening levels at three locations near buildings or structures in the area north and south of the Maunabo #1.
- COPCs were not detected in the top 15 to 20 feet of groundwater in the majority of groundwater screening samples.
- Based on the available data, vapor intrusion sampling (i.e., subslab and indoor air) is not warranted at this time because the existing structures are not near the COPC concentrations which exceed the screening levels and no detections of COPCs were above the screening levels at the top of the water table. In addition, the majority of the site area has uncontaminated groundwater in the top 15 to 20 feet (and more in some locations) of the water table.

TABLE E-1 COMPARISON OF MAXIMUM DETECTED CONCENTRATIONS TO VAPOR INTRUSION SCREENING LEVELS

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Exposure Point	CAS No.	Chemical	Minimum Concentration (Qualifier)	Maximum Concentration (Qualifier)	Unit	Location of Maximum Concentration	Detection Frequency	Range of Reporting Limit	Concentration Used for Screening (1)	Toxicity Value	COPC Flag (Yes/No)
Groundwater	Volatile Organ	nic Compounds									
	76-13-1	1,1,2-Trichloro-1,2,2-Trifluoroethane	3.2	23	μg/L	MW-AD	5 / 35	0.5 - 0.5	23	1500 n	No
	75-34-3	1,1-Dichloroethane	0.27 J	0.75	μg/L	MW-I	6 / 35	0.5 - 0.5	0.75	2200 n	No
	75-35-4	1,1-Dichloroethene	0.22 J	25 J	μg/L	MW-L	12 / 35	0.5 - 0.5	25	190 n	No
	107-06-2	1,2-Dichloroethane	0.2	0.2	μg/L	MW-AD	1 / 35	0.2 - 0.2	0.2	2.3 c	No
	78-87-5	1,2-Dichloropropane	0.52	0.52	μg/L	MW-N	1 / 35	0.2 - 0.2	0.52	35 n	No
	67-64-1	Acetone	1.6 J	15	μg/L	MW-N	2 / 35	5 - 5	15	220000 n	No
	75-25-2	Bromoform	1.6	5	μg/L	MW-M	3 / 35	0.5 - 0.5	5	0.083 c	Yes
	75-15-0	Carbon Disulfide	1.4	1.4	μg/L	MW-AS	1 / 35	0.5 - 0.5	1.4	560 n	No
	75-00-3	Chloroethane	0.27 J	0.27 J	μg/L	MW-I	1 / 35	0.5 - 0.5	0.27	28000 n	No
	156-59-2	cis-1,2-Dichloroethene	0.38 J	300	μg/L	MW-B	16 / 35	0.5 - 0.5	300	210 n	Yes
	124-48-1	Dibromochloromethane	0.54	0.54	μg/L	MW-M	1 / 35	0.5 - 0.5	0.54	3.2 c	No
	1634-04-4	Methyl Tert-Butyl Ether	0.27 J	2	μg/L	MW-K	8 / 35	0.5 - 0.5	2	120000 n	No
	75-09-2	Methylene Chloride	1.3	1.7	μg/L	MW-FD	4 / 35	0.5 - 0.5	1.7	58 c	No
	127-18-4	Tetrachloroethene	0.1 J	8.5 J	μg/L	MW-FD	9 / 35	0.2 - 0.2	8.5	1.1 c	Yes
	156-60-5	trans-1,2-Dichloroethene	0.99	13	μg/L	MW-B	4 / 35	0.5 - 0.5	13	180 n	No
	10061-02-6	trans-1,3-Dichloropropene	0.2 J	0.2 J	μg/L	MW-N	1 / 35	0.2 - 0.2	0.2	0.84 n ⁽³⁾	No
	79-01-6	Trichloroethene	0.29 J	1.9	μg/L	MW-FD	7 / 35	0.5 - 0.5	1.9	0.053 с	Yes
	75-69-4	Trichlorofluoromethane	0.36 J	8	μg/L	MW-L	6 / 35	0.5 - 0.5	8	180 n	No
	75-01-4	Vinyl Chloride	0.22	0.73	μg/L	MW-B	3 / 35	0.2 - 0.2	0.73	0.25 с	Yes

⁽¹⁾ Maximum detected concentration used for screening

NA = not available

n = screening toxicity value based on noncancer effects

c = screening toxicity value based on cancer effects

COPC = chemical of potential concern

J = qualifier for estimated value

μg/L = micrograms per liter



Page 1 of 1 6/29/2012

R2-0002338

⁽²⁾ Screened against Draft Guidance for Evaluating the Vapor Intrusion to Indoor Air Pathway from Groundwater Table 2c: Generic Screening Levels and Summary Sheet, Risk =1x10⁻⁶ and for value based on MCL, refers to Table 2a (risk = 1 x 10⁻⁴) and adjusted the value to a 10⁻⁶ value http://www.epa.gov/osw/hazard/correctiveaction/eis/vapor/complete.pdf

⁽³⁾ screening value for 1,3-dichloropropene

Appendix F RAGS D Tables – CTE Scenario

F-10.1

F-10.2 F-10.3

F-10.4

F-7 Calculation of Chemical Cancer Risks and Noncancer Hazards - Central Tendency Exposure Current/Future Commercial/Industrial Worker - Former Sugar Mill F-7.2 Current/Future Resident - Former Sugar Mill F-7.3 Current/Future Commercial/Industrial Worker - Puerto Rico Beverage F-7.4 Future Resident - Puerto Rico Beverage F-8 Calculation of Radiation Cancer Risks - NOT USED F-9 Summary of Receptor Risks and Hazards for Chemical of Potential Concerns - Central Tendency Exposure Current/Future Commercial/Industrial Worker - Former Sugar Mill F-9.2 Current/Future Resident - Former Sugar Mill F-9.3 Current/Future Commercial/Industrial Worker - Puerto Rico Beverage F-9.4 Future Resident - Puerto Rico Beverage F-10 Risk Assessment Summary - Central Tendency Exposure

Current/Future Commercial/Industrial Worker - Former Sugar Mill

Current/Future Commercial/Industrial Worker - Puerto Rico Beverage

Current/Future Resident - Former Sugar Mill

Future Resident - Puerto Rico Beverage



TABLE F-7.1 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Commercial/Industrial Worker
Receptor Age: Adult

	F	F	F		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	lation	
Medium	Exposure Medium	Exposure Point	Exposure Route	Chemical of Potential Concern	Concent		Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposur	re Concentration	RfD)/RfC	Hazard
	Mediaiii	Foint	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface Soil	Former Sugar	Ingestion	Semi-volatile Organic Compounds												
Soil		Mill		Benzo(a)pyrene	6.56E-02	mg/kg	3.62E-09	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	2.64E-08	2.81E-08	mg/kg-day	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	9.92E-10	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	7.24E-09	7.71E-09	mg/kg-day	NA	NA	NA
				Inorganics												
				Aluminum	1.38E+04	mg/kg	7.59E-04	mg/kg-day	NA	NA	NA	5.90E-03	mg/kg-day	1.00E+00	mg/kg-day	5.90E-03
				Arsenic	3.64E+00	mg/kg	2.00E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	3.00E-07	1.56E-06	mg/kg-day	3.00E-04	mg/kg-day	5.19E-03
				Chromium	1.50E+01	mg/kg	8.28E-07	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	4.14E-07	6.44E-06	mg/kg-day	3.00E-03	mg/kg-day	2.15E-03
				Cobalt	8.79E+00	mg/kg	4.84E-07	mg/kg-day	NA	NA	NA	3.77E-06	mg/kg-day	3.00E-04	mg/kg-day	1.26E-02
				Iron	3.74E+04	mg/kg	2.06E-03	mg/kg-day	NA	NA	NA	1.60E-02	mg/kg-day	7.00E-01	mg/kg-day	2.29E-02
				Manganese	4.89E+02	mg/kg	2.69E-05	mg/kg-day	NA	NA	NA	2.09E-04	mg/kg-day	1.40E-01	mg/kg-day	1.50E-03
				Vanadium	6.37E+01	mg/kg	3.51E-06	mg/kg-day	NA	NA	NA	2.73E-05	mg/kg-day	7.00E-05	mg/kg-day	3.90E-01
			Exp. Route To	tal							7.48E-07					4.40E-01
Surface	Surface Soil	Former Sugar	Dermal	Semi-volatile Organic Compounds												
Soil		Mill	Contact	Benzo(a)pyrene	6.56E-02	mg/kg	6.21E-10	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	4.53E-09	4.83E-09	mg/kg-day	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	1.70E-10	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	1.24E-09	1.32E-09	mg/kg-day	NA	NA	NA
				Inorganics												
				Aluminum	1.38E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
				Arsenic	3.64E+00	mg/kg	7.93E-09	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.19E-08	6.17E-08	mg/kg-day	3.00E-04	mg/kg-day	2.06E-04
				Chromium	1.50E+01	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	8.79E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	3.74E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	4.89E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	6.37E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal							1.77E-08					2.06E-04
Surface	Surface Soil	Former Sugar	Inhalation	Semi-volatile Organic Compounds												
Soil		Mill		Benzo(a)pyrene	6.56E-02	mg/kg	6.20E-10	μg/m³	1.10E-03	(µg/m ³) ⁻¹	6.82E-13	4.83E-12	mg/m ³	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	1.70E-10	μg/m³	1.20E-03	(µg/m ³) ⁻¹	2.04E-13	1.32E-12	mg/m ³	NA	NA	NA
				Inorganics												
				Aluminum	1.38E+04	mg/kg	1.30E-04	μg/m³	NA	NA	NA	1.01E-06	mg/m ³	5.00E-03	mg/m ³	2.03E-04
				Arsenic	3.64E+00	mg/kg	3.44E-08	μg/m³	4.30E-03	$(\mu g/m^3)^{-1}$	1.48E-10	2.67E-10	mg/m ³	1.50E-05	mg/m ³	1.78E-05
				Chromium	1.50E+01	mg/kg	1.42E-07	μg/m³	1.20E-02	(µg/m ³) ⁻¹	1.71E-09	1.11E-09	mg/m ³	1.00E-04	mg/m ³	1.11E-05
				Cobalt	8.79E+00	mg/kg	8.31E-08	μg/m³	9.00E-03	$(\mu g/m^3)^{-1}$	7.48E-10	6.46E-10	mg/m ³	6.00E-06	mg/m ³	1.08E-04
				Iron	3.74E+04	mg/kg	3.54E-04	μg/m³	NA	NA	NA	2.75E-06	mg/m ³	NA	NA	NA
				Manganese	4.89E+02	mg/kg	4.62E-06	μg/m³	NA	NA	NA	3.59E-08	mg/m ³	5.00E-05	mg/m ³	7.18E-04
				Vanadium	6.37E+01	mg/kg	6.02E-07	μg/m³	8.30E-03	(µg/m³) ⁻¹	5.00E-09	4.68E-09	mg/m³	1.00E-04	mg/m³	4.68E-05
			Exp. Route To	tal							7.60E-09					1.10E-03
	·	Exposure Point	Total				·	·			7.73E-07					4.42E-01

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE F-7.1 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Commercial/Industrial Worker
Receptor Age: Adult

	Exposure	Exposure	Exposure		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	lation	
Medium	Medium	Point	Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposu	re Concentration	RfE)/RfC	Hazard
	Wediam	1 Ollit	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Groundwater	Groundwater	Groundwater	Ingestion	Volatile Organic Compounds												
				cis-1,2-Dichloroethene	5.45E+01	μg/L	6.00E-05	mg/kg-day	NA	NA	NA	4.67E-04	mg/kg-day	2.00E-03	mg/kg-day	2.33E-01
				Tetrachloroethene	9.92E-01	μg/L	1.09E-06	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	2.30E-09	8.50E-06	mg/kg-day	6.00E-03	mg/kg-day	1.42E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	2.52E-06	mg/kg-day	NA	NA	NA	1.96E-05	mg/kg-day	2.00E-02	mg/kg-day	9.78E-04
				Trichloroethene	5.64E-01	μg/L	6.22E-07	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	2.86E-08	4.83E-06	mg/kg-day	5.00E-04	mg/kg-day	9.67E-03
				Vinyl Chloride	7.30E-01	μg/L	8.04E-07	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	5.79E-07	6.26E-06	mg/kg-day	3.00E-03	mg/kg-day	2.09E-03
				Inorganics												
				Aluminum	2.04E+03	μg/L	2.25E-03	mg/kg-day	NA	NA	NA	1.75E-02	mg/kg-day	1.00E+00		
				Arsenic	3.80E+00	μg/L	4.18E-06	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	6.27E-06	3.25E-05	mg/kg-day		mg/kg-day	
				Barium	2.04E+02	μg/L	2.24E-04	mg/kg-day	NA	NA	NA	1.75E-03	mg/kg-day	2.00E-01	mg/kg-day	
				Chromium	8.35E+00	μg/L	9.20E-06	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	4.60E-06	7.16E-05	mg/kg-day	3.00E-03	mg/kg-day	1
				Cobalt	1.07E+00	μg/L	1.18E-06	mg/kg-day	NA	NA	NA	9.21E-06	mg/kg-day	3.00E-04	mg/kg-day	1 1
				Copper	5.22E+01	μg/L	5.76E-05	mg/kg-day	NA	NA	NA	4.48E-04	mg/kg-day	4.00E-02	mg/kg-day	1.12E-02
				Iron	8.20E+03	μg/L	9.03E-03	mg/kg-day	NA	NA	NA	7.03E-02	mg/kg-day	7.00E-01	mg/kg-day	1.00E-01
				Manganese	4.12E+02	μg/L	4.54E-04	mg/kg-day	NA	NA	NA	3.53E-03	mg/kg-day	1.40E-01	mg/kg-day	2.52E-02
				Vanadium	1.70E+01	μg/L	1.87E-05	mg/kg-day	NA	NA	NA	1.45E-04	mg/kg-day	7.00E-05	mg/kg-day	
			Exp. Route To								1.15E-05					2.65E+00
Groundwater	Groundwater	Groundwater	Dermal	Volatile Organic Compounds		_										
			Contact	cis-1,2-Dichloroethene	5.45E+01	μg/L	NA	NA	NA	NA	NA	NA	NA	2.00E-03		NA
				Tetrachloroethene	9.92E-01	μg/L	8.56E-07	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	1.80E-09	6.66E-06	mg/kg-day	6.00E-03		
				trans-1,2-Dichloroethene	2.28E+00	μg/L	2.93E-07	mg/kg-day	NA	NA	NA	2.28E-06	mg/kg-day	2.00E-02	mg/kg-day	
				Trichloroethene	5.64E-01	μg/L	1.41E-07	mg/kg-day	4.60E-02	(mg/kg-day)	6.50E-09	1.10E-06	mg/kg-day	5.00E-04		
				Vinyl Chloride	7.30E-01	μg/L	5.49E-08	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	3.95E-08	4.27E-07	mg/kg-day	3.00E-03	mg/kg-day	1.42E-04
				Inorganics	0.045.00		4 045 05					7.005.05		4.005.00		7.005.05
				Aluminum	2.04E+03	μg/L	1.01E-05	mg/kg-day	NA 4 FOE - OO	NA (mg/kg-day) ⁻¹	NA 0.00E.00	7.86E-05	mg/kg-day		mg/kg-day	1
				Arsenic Barium	3.80E+00 2.04E+02	μg/L μg/L	1.88E-08 1.01E-06	mg/kg-day mg/kg-day	1.50E+00 NA	(Hig/kg-day) NA	2.82E-08 NA	1.46E-07 7.85E-06	mg/kg-day	3.00E-04 1.40E-02	mg/kg-day mg/kg-day	4.88E-04 5.61E-04
				Chromium	8.35E+00		4.14E-08		5.00E-01	(mg/kg-day) ⁻¹	2.07E-08	7.85E-06 3.22E-07	mg/kg-day		0 0 ,	
				Cobalt	1.07E+00	μg/L μg/L	4.14E-08 2.13E-09	mg/kg-day	5.00E-01 NA	(Hig/kg-day)	2.07E-08 NA	3.22E-07 1.66E-08	mg/kg-day	7.50E-05 3.00E-04	mg/kg-day mg/kg-day	4.29E-03 5.52E-05
				Copper	5.22E+01	μg/L μg/L	2.13E-09 2.59E-07	mg/kg-day mg/kg-day	NA NA	NA NA	NA NA	2.01E-06	mg/kg-day mg/kg-day	4.00E-04	mg/kg-day	5.04E-05
				Iron	8.20E+01	μg/L μg/L	4.06E-05	mg/kg-day	NA NA	NA NA	NA NA	3.16E-04	mg/kg-day	7.00E-02	mg/kg-day	4.52E-04
				Manganese	4.12E+02	μg/L	2.04E-06	mg/kg-day	NA NA	NA NA	NA NA	1.59E-05	mg/kg-day		mg/kg-day	
				Vanadium	1.70E+01	μg/L	8.41E-08	mg/kg-day	NA NA	NA NA	NA NA	6.54E-07	mg/kg-day		mg/kg-day	
			Exp. Route To		1.702+01	µg/L	0.41L-00	mg/kg-uay	INA	INA	9.68E-08	0.546-07	mg/kg-day	1.02L-00	mg/kg-uay	3.72E-01
Groundwater	Groundwater	Groundwater	Inhalation	Volatile Organic Compounds			<u> </u>			1	3.00L-00		ı			J./ZL-U1
Groundwater	Groundwater	Groundwater	innaiation	cis-1,2-Dichloroethene	1.00E+03	μg/m³	8.05E-01	μg/m³	NA	NA	NA	6.26E-03	mg/m³	NA	NA	NA
				Tetrachloroethene	1.62E+01	μg/m ³		μg/m ³	2.60E-07	NA (μg/m ³) ⁻¹	3.39E-09	1.01E-04	mg/m ³	4.00E-02	mg/m ³	2.53E-03
				trans-1,2-Dichloroethene	4.18E+01	μg/m ³	3.36E-02	μg/m ³	2.60E-07 NA	(μg/III) NA	3.39E-09 NA	2.61E-04	mg/m ³	6.00E-02	mg/m ³	4.35E-03
				Trichloroethene	9.69E+00	μg/m ³	7.79E-03	μg/m ³	4.10E-06	NA (μg/m ³) ⁻¹	3.19E-08	6.06E-05	mg/m ³	2.00E-02	mg/m ³	4.35E-03 3.03E-02
				Vinyl Chloride	9.69E+00 1.40E+01	μg/m	1.12E-02	μg/m [~]	4.10E-06 4.40E-06	(μg/m) · '	3.19E-08 4.95E-08	8.74E-05	mg/m	1.00E-03	mg/m	8.74E-04
			Exp. Route To		1.706701	1-5	1.12L-02	F-5	7.70L-00	(F3····/	8.48E-08	0.742-03		1.00L-01		3.80E-02
		F		ntai								<u> </u>				
	Exposure Point Total										1.17E-05	ll				3.06E+00

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE F-7.2 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Resident
Receptor Age: Lifetime

					Exposure	Point		Cancer	Risk Calcula	ation			Noncancer H	azard Calcu	ılation	
Medium	Exposure	Exposure	Exposure	Chemical of Potential Concern	Concent		Intake/ Exposur	e Concentration		ctor/Unit Risk	Cancer	Intake/ Exposu	re Concentration	Rff	D/RfC	Hazard
	Medium	Point	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface Soil	Former Sugar	Ingestion	Semi-volatile Organic Compounds	Value	OTIN	74.40	0	raido	0	rtioit	74.40	0	raido	0	Quotion
Soil		Mill		Benzo(a)pyrene	6.56E-02	mg/kg	2.09E-07	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	1.53E-06	4.20E-07	mg/kg-day	NA	NA	NA
00				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	5.74E-08	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	4.19E-07	1.15E-07	mg/kg-day	NA	NA	NA
				Inorganics		g/g	0 12 00	gritg day	7.002700	(99 ==.,,			g, ng day			
				Aluminum	1.38E+04	mg/kg	8.76E-03	mg/kg-day	NA	NA	NA	8.81E-02	mg/kg-day	1.00E+00	mg/kg-day	8.81E-02
				Arsenic	3.64E+00	mg/kg	2.31E-06	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	3.47E-06	2.32E-05	mg/kg-day	3.00E-04	mg/kg-day	
				Chromium	1.50E+01	mg/kg	9.56E-06	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	4.78E-06	9.61E-05	mg/kg-day	3.00E-03	mg/kg-day	
				Cobalt	8.79E+00	mg/kg	5.59E-06	mg/kg-day	NA	NA NA	NA	5.62E-05	mg/kg-day	3.00E-04	mg/kg-day	1
				Iron	3.74E+04	mg/kg	2.38E-02	mg/kg-day	NA	NA	NA	2.39E-01	mg/kg-day	7.00E-01	mg/kg-day	3.42E-01
				Manganese	4.89E+02	mg/kg	3.11E-04	mg/kg-day	NA	NA	NA	3.12E-03	mg/kg-day	1.40E-01	mg/kg-day	2.23E-02
					6.37E+01	mg/kg	4.05E-05	mg/kg-day	NA	NA	NA	4.07E-04	mg/kg-day	7.00E-05		5.82E+00
·	ı.		Exp. Route To	tal							1.02E-05					6.57E+00
Surface	Surface Soil	Former Sugar	Dermal	Semi-volatile Organic Compounds												
Soil		Mill	Contact	Benzo(a)pyrene	6.56E-02	mg/kg	3.05E-08	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	2.23E-07	6.11E-08	mg/kg-day	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	8.36E-09	mg/kg-day	7.30E+00	(mg/kg-day) ⁻¹	6.11E-08	1.68E-08	mg/kg-day	NA	NA	NA
				Inorganics		0 0							,			
				Aluminum	1.38E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
				Arsenic	3.64E+00	mg/kg	7.79E-08	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.17E-07	7.81E-07	mg/kg-day	3.00E-04	mg/kg-day	2.60E-03
				Chromium	1.50E+01	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	8.79E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	3.74E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	4.89E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	6.37E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal							4.00E-07					2.60E-03
Surface	Surface Soil	Former Sugar	Inhalation	Semi-volatile Organic Compounds												
Soil	l	Mill		Benzo(a)pyrene	6.56E-02	mg/kg	5.02E-08	μg/m³	1.10E-03	(µg/m³) ⁻¹	5.53E-11	4.63E-11	mg/m ³	NA	NA	NA
				Dibenzo(a,h)anthracene	1.80E-02	mg/kg	1.38E-08	μg/m³	1.20E-03	$(\mu g/m^3)^{-1}$	1.65E-11	1.27E-11	mg/m ³	NA	NA	NA
	l			Inorganics												
	l			Aluminum	1.38E+04	mg/kg	2.08E-03	μg/m ³	NA	NA	NA	9.71E-06	mg/m ³	5.00E-03	mg/m ³	1.94E-03
	l			Arsenic	3.64E+00	mg/kg	5.49E-07	μg/m ³	4.30E-03	(µg/m ³) ⁻¹	2.36E-09	2.56E-09	mg/m ³	1.50E-05	mg/m ³	1.71E-04
				Chromium	1.50E+01	mg/kg	2.27E-06	μg/m ³	1.20E-02	(µg/m³)-1	2.73E-08	1.06E-08	mg/m ³	1.00E-04	mg/m ³	1.06E-04
	l			Cobalt	8.79E+00	mg/kg	1.33E-06	μg/m ³	9.00E-03	$(\mu g/m^3)^{-1}$	1.19E-08	6.20E-09	mg/m ³	6.00E-06	mg/m ³	1.03E-03
				Iron	3.74E+04	mg/kg	5.66E-03	μg/m³	NA	NA	NA	2.64E-05	mg/m ³	NA	NA	NA
	l			Manganese	4.89E+02	mg/kg	7.38E-05	μg/m³	NA	NA	NA	3.44E-07	mg/m ³	5.00E-05	mg/m ³	6.89E-03
				Vanadium	6.37E+01	mg/kg	9.63E-06	μg/m³	8.30E-03	(µg/m³) ⁻¹	7.99E-08	4.49E-08	mg/m³	1.00E-04	mg/m³	4.49E-04
			Exp. Route To	tal				-		·	1.22E-07					1.06E-02
Exposure Point Total											1.07E-05					6.58E+00

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE F-7.2 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Resident
Receptor Age: Lifetime

					Exposure	Point		Cancer	Risk Calcula	ation			Noncancer H	azard Calcu	lation	
Medium	Exposure	Exposure	Exposure	Chemical of Potential Concern	Concent		Intake/ Exposur	e Concentration		ctor/Unit Risk	Cancer	Intake/ Exposu	re Concentration		D/RfC	Hazard
	Medium	Point	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Groundwater	Groundwater	Groundwater	Ingestion	Volatile Organic Compounds			Ì					ĺ				
				cis-1,2-Dichloroethene	5.45E+01	μg/L	2.54E-04	mg/kg-day	NA	NA	NA	1.39E-03	mg/kg-day	2.00E-03	mg/kg-day	6.96E-01
				Tetrachloroethene	9.92E-01	μg/L	4.62E-06	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	9.70E-09	2.54E-05	mg/kg-day	6.00E-03	mg/kg-day	4.23E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	1.06E-05	mg/kg-day	NA	NA	NA	5.84E-05	mg/kg-day	2.00E-02	mg/kg-day	2.92E-03
				Trichloroethene	5.64E-01	μg/L	1.08E-05	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	1.97E-07	1.44E-05	mg/kg-day	5.00E-04	mg/kg-day	2.88E-02
				Vinyl Chloride	7.30E-01	μg/L	2.29E-05	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	1.65E-05	1.87E-05	mg/kg-day	3.00E-03	mg/kg-day	6.22E-03
				Inorganics												
				Aluminum	2.04E+03	μg/L	9.49E-03	mg/kg-day	NA	NA	NA	5.21E-02	mg/kg-day	1.00E+00	mg/kg-day	5.21E-02
				Arsenic	3.80E+00	μg/L	1.77E-05	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	2.65E-05	9.70E-05	mg/kg-day	3.00E-04	mg/kg-day	3.23E-01
				Barium	2.04E+02	μg/L	9.48E-04	mg/kg-day	NA	NA	NA	5.21E-03	mg/kg-day	2.00E-01	mg/kg-day	2.60E-02
				Chromium	8.35E+00	μg/L	3.89E-05	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	1.94E-05	2.13E-04	mg/kg-day	3.00E-03	mg/kg-day	7.12E-02
				Cobalt	1.07E+00	μg/L	5.00E-06	mg/kg-day	NA	NA	NA	2.75E-05	mg/kg-day	3.00E-04	mg/kg-day	9.15E-02
				Copper	5.22E+01	μg/L	2.43E-04	mg/kg-day	NA	NA	NA	1.34E-03	mg/kg-day	4.00E-02	mg/kg-day	3.34E-02
				Iron	8.20E+03	μg/L	3.82E-02	mg/kg-day	NA	NA	NA	2.10E-01	mg/kg-day	7.00E-01	mg/kg-day	2.99E-01
				Manganese	4.12E+02	μg/L	1.92E-03	mg/kg-day	NA	NA	NA	1.05E-02	mg/kg-day	1.40E-01	mg/kg-day	7.53E-02
				Vanadium	1.70E+01	μg/L	7.90E-05	mg/kg-day	NA	NA	NA	4.34E-04	mg/kg-day	7.00E-05	mg/kg-day	6.20E+00
			Exp. Route To	tal			Ì				6.26E-05	i				7.91E+00
Groundwater	Groundwater	Groundwater	Dermal	Volatile Organic Compounds			Ì					i				
Or our rawator	Or our amaio.	O. Cananata	Contact	cis-1.2-Dichloroethene	5.45E+01	μq/L	NA	NA	NA	NA	NA	NA	NA	2.00E-03	mg/kg-day	/ NA
				Tetrachloroethene	9.92E-01	μg/L	3.11E-06	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	6.53E-09	1.93E-05	mg/kg-day	6.00E-03	3 3	
				trans-1.2-Dichloroethene	2.28E+00	μg/L	1.07E-06	mg/kg-day	NA	NA	NA	6.62E-06	mg/kg-day	2.00E-02		
				Trichloroethene	5.64E-01	μg/L	2.18E-06	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	3.93E-08	3.19E-06	mg/kg-day	5.00E-04	0 0 ,	
				Vinyl Chloride	7.30E-01	μg/L	6.98E-15	mg/kg-day	7.20E-01	(mg/kg-day)	5.03E-15	1.24E-06	mg/kg-day		mg/kg-day	
				Inorganics		F-5-		99,		(3 3 , ,						
				Aluminum	2.04E+03	μq/L	3.90E-05	mg/kg-day	NA	NA	NA	2.42E-04	mg/kg-day	1.00E+00	mg/kg-day	2.42E-04
				Arsenic	3.80E+00	μg/L	7.26E-08	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.09E-07	4.52E-07	mg/kg-day	3.00E-04		
				Barium	2.04E+02	μg/L	3.90E-06	mg/kg-day	NA	NA NA	NA	2.42E-05	mg/kg-day	1.40E-02	3 3	
				Chromium	8.35E+00	μg/L	1.60E-07	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	7.99E-08	9.93E-07	mg/kg-day	7.50E-05	mg/kg-day	
				Cobalt	1.07E+00	μg/L	8.22E-09	mg/kg-day	NA	NA	NA	5.11E-08	mg/kg-day	3.00E-04		
				Copper	5.22E+01	μg/L	1.00E-06	mg/kg-day	NA.	NA.	NA.	6.22E-06	mg/kg-day	4.00E-02	0 0 ,	
				Iron	8.20E+03	μg/L	1.57E-04	mg/kg-day	NA.	NA NA	NA NA	9.75E-04	mg/kg-day	7.00E-02	mg/kg-day	
				Manganese	4.12E+02	μg/L	7.89E-06	mg/kg-day	NA.	NA NA	NA NA	4.90E-05	mg/kg-day		mg/kg-day	
				Vanadium	1.70E+01	μg/L	3.25E-07	mg/kg-day	NA.	NA NA	NA NA	2.02E-06	mg/kg-day		mg/kg-day	
	<u> </u>		Exp. Route To		1.70L+01	µg/L	3.23L-07	mg/kg-day	INA	INA	2.35E-07	Z.02L-00	mg/kg-day	1.02L-00	mg/kg-day	1.15E+00
Groundwater	Groundwater	Groundwater	Inhalation	Volatile Organic Compounds	1		<u> </u>	I		I	2.00L-01		1			1.132+00
Giouriuwater	Giouriuwater	Giouridwater	innaiauon	cis-1,2-Dichloroethene	5.45E+01	/1	3.30E+00	μg/m³	NA	NA	NA	2.35E-02	mg/m³	NA	NA	NA
	l			Tetrachloroethene	9.92E-01	μg/L	5.34E-02	μg/m ³	NA 2.60E-07	NA (μg/m ⁻³) ⁻¹	1.39E-08	2.35E-02 3.80E-04	mg/m³	4.00E-02	mg/m ³	9.50E-03
	l					μg/L		μg/m μg/m³				3.80E-04 9.79E-04	mg/m ³		mg/m ³	
	l			trans-1,2-Dichloroethene	2.28E+00	μg/L	1.38E-01		NA 4.40E.00	NA (μg/m ³) ⁻¹	NA 4 FFF 44			6.00E-02		1.63E-02
	l			Trichloroethene	5.64E-01	μg/L	1.41E-01	μg/m ³	4.10E-06	(μg/m ⁻)	1.55E-11	2.27E-04	mg/m³ mg/m°	2.00E-03	mg/m³ mg/m°	1.14E-01
				Vinyl Chloride	7.30E-01	μg/L	1.00E+00	μg/m [°]	4.40E-06	(µg/111)	4.41E-06	3.28E-04	mg/m	1.00E-01	mg/m	3.28E-03
			Exp. Route To	tal							4.43E-06					1.43E-01
·		Exposure Point	Total								6.73E-05					9.20E+00

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE F-7.3 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Commercial/Industrial Worker
Receptor Age: Adult

	Exposure	Exposure	Exposure		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	lation	
Medium	Medium	Point	Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fa	ctor/Unit Risk	Cancer	Intake/ Exposur	re Concentration	RfD)/RfC	Hazard
	Modium	1 Ollik	rtouto		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface Soil	Puerto Rico	Ingestion	Inorganics												
Soil		Beverage		Aluminum	1.30E+04	mg/kg	7.19E-04	mg/kg-day	NA	NA	NA	5.59E-03	mg/kg-day	1.00E+00	mg/kg-day	5.59E-03
				Arsenic	2.90E+00	mg/kg	1.60E-07	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	2.40E-07	1.24E-06	mg/kg-day	3.00E-04	mg/kg-day	4.14E-03
				Chromium	2.51E+01	mg/kg	1.38E-06	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	6.91E-07	1.07E-05	mg/kg-day	3.00E-03	mg/kg-day	3.58E-03
				Cobalt	6.36E+00	mg/kg	3.50E-07	mg/kg-day	NA	NA	NA	2.72E-06	mg/kg-day	3.00E-04	mg/kg-day	9.08E-03
				Iron	2.94E+04	mg/kg	1.62E-03	mg/kg-day	NA	NA	NA	1.26E-02	mg/kg-day	7.00E-01	mg/kg-day	1.80E-02
				Manganese	3.49E+02	mg/kg	1.92E-05	mg/kg-day	NA	NA	NA	1.49E-04	mg/kg-day	1.40E-01	mg/kg-day	1.07E-03
				Vanadium	5.66E+01	mg/kg	3.12E-06	mg/kg-day	NA	NA	NA	2.42E-05	mg/kg-day	7.00E-05	mg/kg-day	3.46E-01
			Exp. Route To	tal							9.30E-07					3.88E-01
Surface	Surface Soil	Puerto Rico	Dermal	Inorganics												
Soil		Beverage	Contact	Aluminum	1.30E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
				Arsenic	2.90E+00	mg/kg	6.33E-09	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	9.49E-09	4.92E-08	mg/kg-day	3.00E-04	mg/kg-day	1.64E-04
				Chromium	2.51E+01	mg/kg	NA	NA	5.00E-01	(mg/kg-day)-1	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	6.36E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	2.94E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	3.49E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	5.66E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA	1.82E-06	mg/kg-day	NA
			Exp. Route To	tal							9.49E-09					1.64E-04
Surface	Surface Soil	Puerto Rico	Inhalation	Inorganics												
Soil		Beverage		Aluminum	1.30E+04	mg/kg	1.23E-04	μg/m ³	NA	NA	NA	9.59E-07	mg/m ³	5.00E-03	mg/m ³	1.92E-04
				Arsenic	2.90E+00	mg/kg	2.74E-08	μg/m ³	4.30E-03	(µg/m ³) ⁻¹	1.18E-10	2.13E-10	mg/m ³	1.50E-05	mg/m ³	1.42E-05
				Chromium	2.51E+01	mg/kg	2.37E-07	μg/m³	1.20E-02	$(\mu g/m^3)^{-1}$	2.84E-09	1.84E-09	mg/m ³	1.00E-04	mg/m ³	1.84E-05
				Cobalt	6.36E+00	mg/kg	6.01E-08	μg/m ³	9.00E-03	$(\mu g/m^3)^{-1}$	5.41E-10	4.67E-10	mg/m ³	6.00E-06	mg/m ³	7.79E-05
				Iron	2.94E+04	mg/kg	2.78E-04	μg/m ³	NA	NA	NA	2.16E-06	mg/m ³	NA	NA	NA
				Manganese	3.49E+02	mg/kg	3.30E-06	μg/m³	NA	NA	NA	2.56E-08	mg/m ³	5.00E-05	mg/m ³	5.13E-04
				Vanadium	5.66E+01	mg/kg	5.35E-07	μg/m³	8.30E-03	(µg/m³) ⁻¹	4.44E-09	4.16E-09	mg/m³	1.00E-04	mg/m³	4.16E-05
			Exp. Route To	tal							7.94E-09					8.57E-04
		Exposure Point	Total								9.48E-07					3.89E-01

NA = not applicable RfD = reference dose mg/kg = milligram per kilogram $\mu g/m^3 = mg/kg$ -day = milligram per kilogram per day $mg/m^3 = mg/kg$ -day = milligram per kilogram per day



TABLE F-7.3 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Commercial/Industrial Worker
Receptor Age: Adult

	_	_	_		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	zard Calcu	lation	
Medium	Exposure Medium	Exposure Point	Exposure Route	Chemical of Potential Concern	Concent		Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposu	re Concentration	RfE)/RfC	Hazard
	iviedium	Point	Route		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Groundwater	Groundwater	Groundwater	Ingestion	Volatile Organic Compounds			ĺ									
			-	cis-1,2-Dichloroethene	5.45E+01	μg/L	6.00E-05	mg/kg-day	NA	NA	NA	4.67E-04	mg/kg-day	2.00E-03	mg/kg-day	2.33E-01
				Tetrachloroethene	9.92E-01	μg/L	1.09E-06	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	2.30E-09	8.50E-06	mg/kg-day	6.00E-03	mg/kg-day	1.42E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	2.52E-06	mg/kg-day	NA	NA	NA	1.96E-05	mg/kg-day	2.00E-02	mg/kg-day	9.78E-04
				Trichloroethene	5.64E-01	μg/L	6.22E-07	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	2.86E-08	4.83E-06	mg/kg-day	5.00E-04	mg/kg-day	9.67E-03
				Vinyl Chloride	7.30E-01	μg/L	8.04E-07	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	5.79E-07	6.26E-06	mg/kg-day	3.00E-03	mg/kg-day	2.09E-03
				Inorganics												
				Aluminum	2.04E+03	μg/L	2.25E-03	mg/kg-day	NA	NA	NA	1.75E-02	mg/kg-day	1.00E+00	mg/kg-day	1.75E-02
				Arsenic	3.80E+00	μg/L	4.18E-06	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	6.27E-06	3.25E-05	mg/kg-day	3.00E-04	mg/kg-day	1.08E-01
				Barium	2.04E+02	μg/L	2.24E-04	mg/kg-day	NA	NA	NA	1.75E-03	mg/kg-day	2.00E-01	mg/kg-day	8.73E-03
				Chromium	8.35E+00	μg/L	9.20E-06	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	4.60E-06	7.16E-05	mg/kg-day	3.00E-03	mg/kg-day	2.39E-02
				Cobalt	1.07E+00	μg/L	1.18E-06	mg/kg-day	NA	NA	NA	9.21E-06	mg/kg-day	3.00E-04	mg/kg-day	3.07E-02
				Copper	5.22E+01	μg/L	5.76E-05	mg/kg-day	NA	NA	NA	4.48E-04	mg/kg-day	4.00E-02	mg/kg-day	1.12E-02
				Iron	8.20E+03	μg/L	9.03E-03	mg/kg-day	NA	NA	NA	7.03E-02	mg/kg-day	7.00E-01	mg/kg-day	1.00E-01
				Manganese	4.12E+02	μg/L	4.54E-04	mg/kg-day	NA	NA	NA	3.53E-03	mg/kg-day	1.40E-01	mg/kg-day	2.52E-02
				Vanadium	1.70E+01	μg/L	1.87E-05	mg/kg-day	NA	NA	NA	1.45E-04	mg/kg-day	7.00E-05	mg/kg-day	2.08E+00
			Exp. Route To	tal							1.15E-05					2.65E+00
Groundwater	Groundwater	Groundwater	Dermal	Volatile Organic Compounds												
			Contact	cis-1,2-Dichloroethene	5.45E+01	μg/L	NA	NA	NA	NA	NA	NA	NA	2.00E-03	mg/kg-day	NA
				Tetrachloroethene	9.92E-01	μg/L	8.56E-07	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	1.80E-09	6.66E-06	mg/kg-day	6.00E-03	mg/kg-day	1.11E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	2.93E-07	mg/kg-day	NA	NA	NA	2.28E-06	mg/kg-day	2.00E-02	mg/kg-day	1.14E-04
				Trichloroethene	5.64E-01	μg/L	1.41E-07	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	6.50E-09	1.10E-06	mg/kg-day	5.00E-04	mg/kg-day	2.20E-03
				Vinyl Chloride	7.30E-01	μg/L	5.49E-08	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	3.95E-08	4.27E-07	mg/kg-day	3.00E-03	mg/kg-day	1.42E-04
				Inorganics												
				Aluminum	2.04E+03	μg/L	1.01E-05	mg/kg-day	NA	NA	NA	7.86E-05	mg/kg-day	1.00E+00	mg/kg-day	7.86E-05
				Arsenic	3.80E+00	μg/L	1.88E-08	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	2.82E-08	1.46E-07	mg/kg-day	3.00E-04	mg/kg-day	4.88E-04
				Barium	2.04E+02	μg/L	1.01E-06	mg/kg-day	NA	NA	NA	7.85E-06	mg/kg-day	1.40E-02	mg/kg-day	5.61E-04
				Chromium	8.35E+00	μg/L	4.14E-08	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	2.07E-08	3.22E-07	mg/kg-day	7.50E-05	mg/kg-day	4.29E-03
				Cobalt	1.07E+00	μg/L	2.13E-09	mg/kg-day	NA	NA	NA	1.66E-08	mg/kg-day	3.00E-04	mg/kg-day	5.52E-05
				Copper	5.22E+01	μg/L	2.59E-07	mg/kg-day	NA	NA	NA	2.01E-06	mg/kg-day		mg/kg-day	5.04E-05
				Iron	8.20E+03	μg/L	4.06E-05	mg/kg-day	NA	NA	NA	3.16E-04	mg/kg-day		mg/kg-day	4.52E-04
				Manganese	4.12E+02	μg/L	2.04E-06	mg/kg-day	NA	NA	NA	1.59E-05	mg/kg-day		mg/kg-day	2.84E-03
				Vanadium	1.70E+01	μg/L	8.41E-08	mg/kg-day	NA	NA	NA	6.54E-07	mg/kg-day	1.82E-06	mg/kg-day	3.59E-01
			Exp. Route To								9.68E-08					3.72E-01
Groundwater	Groundwater	Groundwater	Inhalation	Volatile Organic Compounds									. 4			
				cis-1,2-Dichloroethene	1.00E+03	µg/m ³	8.05E-01	μg/m³	NA	NA	NA	6.26E-03	mg/m³	NA	NA .	NA
				Tetrachloroethene	1.62E+01	μg/m ³	1.30E-02	µg/m³	2.60E-07	(µg/m ³) ⁻¹	3.39E-09	1.01E-04	mg/m ³	4.00E-02	mg/m ³	2.53E-03
				trans-1,2-Dichloroethene	4.18E+01	µg/m ³	3.36E-02	μg/m³	NA	NA	NA	2.61E-04	mg/m³	6.00E-02	mg/m ³	4.35E-03
				Trichloroethene	9.69E+00	µg/m³	7.79E-03	μg/m³	4.10E-06	(µg/m³)-1	3.19E-08	6.06E-05	mg/m³	2.00E-03	mg/m ³	3.03E-02
				Vinyl Chloride	1.40E+01	μg/m ³	1.12E-02	µg/m²	4.40E-06	(µg/m³)-	4.95E-08	8.74E-05	mg/m ̈	1.00E-01	mg/m ³	8.74E-04
			Exp. Route To	tal							8.48E-08					3.80E-02
		Exposure Point	Total								1.17E-05					3.06E+00

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE F-7.4 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

	Exposure	Exposure	Exposure		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	lation	
Medium	Medium	Point	Route	Chemical of Potential Concern	Concent	ration	Intake/ Exposur	e Concentration	Slope Fa	ctor/Unit Risk	Cancer	Intake/ Exposul	re Concentration	RfD)/RfC	Hazard
	Wediam	1 Ollit	Noute		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Surface	Surface Soil	Puerto Rico	Ingestion	Inorganics												
Soil		Beverage		Aluminum	1.30E+04	mg/kg	8.29E-03	mg/kg-day	NA	NA	NA	8.34E-02	mg/kg-day	1.00E+00	mg/kg-day	8.34E-02
				Arsenic	2.90E+00	mg/kg	1.84E-06	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	2.77E-06	1.85E-05	mg/kg-day	3.00E-04	mg/kg-day	6.18E-02
				Chromium	2.51E+01	mg/kg	1.59E-05	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	7.97E-06	1.60E-04	mg/kg-day	3.00E-03	mg/kg-day	5.34E-02
				Cobalt	6.36E+00	mg/kg	4.04E-06	mg/kg-day	NA	NA	NA	4.06E-05	mg/kg-day	3.00E-04	mg/kg-day	1.35E-01
				Iron	2.94E+04	mg/kg	1.87E-02	mg/kg-day	NA	NA	NA	1.88E-01	mg/kg-day	7.00E-01	mg/kg-day	2.69E-01
				Manganese	3.49E+02	mg/kg	2.22E-04	mg/kg-day	NA	NA	NA	2.23E-03	mg/kg-day	1.40E-01	mg/kg-day	1.59E-02
				Vanadium	5.66E+01	mg/kg	3.60E-05	mg/kg-day	NA	NA	NA	3.62E-04	mg/kg-day	7.00E-05	mg/kg-day	5.17E+00
			Exp. Route To	tal							1.07E-05					5.79E+00
Surface	Surface Soil	Puerto Rico	Dermal	Inorganics												
Soil	il Beverage Contact Aluminum 1.30E+0						NA	NA	NA	NA	NA	NA	NA	1.00E+00	mg/kg-day	NA
	Beverage Contact Aluminum 1.30E+1 Arsenic 2.90E+1						6.21E-08	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	9.32E-08	6.23E-07	mg/kg-day	3.00E-04	mg/kg-day	2.08E-03
				Chromium	2.51E+01	mg/kg	NA	NA	5.00E-01	(mg/kg-day) ⁻¹	NA	NA	NA	7.50E-05	mg/kg-day	NA
				Cobalt	6.36E+00	mg/kg	NA	NA	NA	NA	NA	NA	NA	3.00E-04	mg/kg-day	NA
				Iron	2.94E+04	mg/kg	NA	NA	NA	NA	NA	NA	NA	7.00E-01	mg/kg-day	NA
				Manganese	3.49E+02	mg/kg	NA	NA	NA	NA	NA	NA	NA	5.60E-03	mg/kg-day	NA
				Vanadium	5.66E+01	mg/kg	NA	NA	NA	NA	NA	NA	NA		mg/kg-day	NA
			Exp. Route To	tal							9.32E-08					2.08E-03
Surface	Surface Soil	Puerto Rico	Inhalation	Inorganics												
Soil		Beverage		Aluminum	1.30E+04	mg/kg	1.97E-03	μg/m³	NA	NA	NA	9.19E-06	mg/m ³	5.00E-03	mg/m ³	1.84E-03
		-		Arsenic	2.90E+00	mg/kg	4.38E-07	μg/m ³	4.30E-03	$(\mu g/m^3)^{-1}$	1.88E-09	2.04E-09	mg/m ³	1.50E-05	mg/m ³	1.36E-04
				Chromium	2.51E+01	mg/kg	3.79E-06	μg/m³	1.20E-02	(µg/m ³) ⁻¹	4.55E-08	1.77E-08	mg/m ³	1.00E-04	mg/m ³	1.77E-04
				Cobalt	6.36E+00	mg/kg	9.60E-07	μg/m ³	9.00E-03	$(\mu g/m^3)^{-1}$	8.64E-09	4.48E-09	mg/m ³	6.00E-06	mg/m ³	7.47E-04
				Iron	2.94E+04	mg/kg	4.45E-03	μg/m ³	NA	NA	NA	2.08E-05	mg/m ³	NA	NA	NA
				Manganese	3.49E+02	mg/kg	5.27E-05	μg/m ³	NA	NA	NA	2.46E-07	mg/m ³	5.00E-05	mg/m ³	4.92E-03
				Vanadium	5.66E+01	mg/kg	8.55E-06	μg/m³	8.30E-03	(µg/m³)-1	7.09E-08	3.99E-08	mg/m³	1.00E-04	mg/m³	3.99E-04
			Exp. Route To	tal							1.27E-07					8.22E-03
		Exposure Point	Total								1.10E-05					5.80E+00
		<u> </u>		D(D(<u> </u>				

NA = not applicable RfD = reference dose mg/kg = milligram per kilogram $\mu g/m^3 = microgram$ mg/kg-day = milligram per kilogram per day $mg/m^3 = milligram$






TABLE F-7.4 CALCULATION OF CHEMICAL CANCER RISKS AND NONCANCER HAZARDS CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

	_	_	_		Exposure	Point		Cancer	Risk Calcula	ation			Noncancer Ha	azard Calcu	ulation	
Medium	Exposure Medium	Exposure Point	Exposure Route	Chemical of Potential Concern	Concent		Intake/ Exposur	e Concentration	Slope Fac	ctor/Unit Risk	Cancer	Intake/ Exposu	re Concentration	RfI	D/RfC	Hazard
	Mediaiii	Foint	Koule		Value	Unit	Value	Unit	Value	Unit	Risk	Value	Unit	Value	Unit	Quotient
Groundwater	Groundwater	Groundwater	Ingestion	Volatile Organic Compounds												
				cis-1,2-Dichloroethene	5.45E+01	μg/L	2.54E-04	mg/kg-day	NA	NA	NA	1.39E-03	mg/kg-day	2.00E-03	mg/kg-day	6.96E-01
				Tetrachloroethene	9.92E-01	μg/L	4.62E-06	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	9.70E-09	2.54E-05	mg/kg-day	6.00E-03		4.23E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	1.06E-05	mg/kg-day	NA	NA	NA	5.84E-05	mg/kg-day	2.00E-02	mg/kg-day	2.92E-03
				Trichloroethene	5.64E-01	μg/L	1.08E-05	mg/kg-day	4.60E-02	(mg/kg-day) ⁻¹	1.97E-07	1.44E-05	mg/kg-day	5.00E-04		2.88E-02
				Vinyl Chloride	7.30E-01	μg/L	2.29E-05	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	1.65E-05	1.87E-05	mg/kg-day	3.00E-03	mg/kg-day	6.22E-03
				Inorganics												
				Aluminum	2.04E+03	μg/L	9.49E-03	mg/kg-day	NA	NA	NA	5.21E-02	mg/kg-day	1.00E+00		5.21E-02
				Arsenic	3.80E+00	μg/L	1.77E-05	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	2.65E-05	9.70E-05	mg/kg-day	3.00E-04	mg/kg-day	
				Barium	2.04E+02	μg/L	9.48E-04	mg/kg-day	NA	NA	NA	5.21E-03	mg/kg-day	2.00E-01	mg/kg-day	
				Chromium	8.35E+00	μg/L	3.89E-05	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	1.94E-05	2.13E-04	mg/kg-day	3.00E-03		7.12E-02
				Cobalt	1.07E+00	μg/L	5.00E-06	mg/kg-day	NA	NA	NA	2.75E-05	mg/kg-day	3.00E-04		9.15E-02
				Copper	5.22E+01	μg/L	2.43E-04	mg/kg-day	NA	NA	NA	1.34E-03	mg/kg-day	4.00E-02		3.34E-02
				Iron	8.20E+03	μg/L	3.82E-02	mg/kg-day	NA	NA	NA	2.10E-01	mg/kg-day	7.00E-01	mg/kg-day	2.99E-01
				Manganese	4.12E+02	μg/L	1.92E-03	mg/kg-day	NA	NA	NA	1.05E-02	mg/kg-day	1.40E-01	mg/kg-day	
				Vanadium	1.70E+01	μg/L	7.90E-05	mg/kg-day	NA	NA	NA	4.34E-04	mg/kg-day	7.00E-05	mg/kg-day	6.20E+00
			Exp. Route To								6.26E-05					7.91E+00
Groundwater	Groundwater	Groundwater	Dermal	Volatile Organic Compounds												
			Contact	cis-1,2-Dichloroethene	5.45E+01	μg/L	NA	NA	NA	NA .	NA	NA	NA	2.00E-03		NA
				Tetrachloroethene	9.92E-01	μg/L	3.11E-06	mg/kg-day	2.10E-03	(mg/kg-day) ⁻¹	6.53E-09	1.93E-05	mg/kg-day	6.00E-03		3.22E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	1.07E-06	mg/kg-day	NA	NA	NA	6.62E-06	mg/kg-day	2.00E-02		3.31E-04
				Trichloroethene	5.64E-01	μg/L	2.18E-06	mg/kg-day	4.60E-02	(mg/kg-day)	3.93E-08	3.19E-06	mg/kg-day	5.00E-04	0 0 ,	6.38E-03
				Vinyl Chloride	7.30E-01	μg/L	6.98E-15	mg/kg-day	7.20E-01	(mg/kg-day) ⁻¹	5.03E-15	1.24E-06	mg/kg-day	3.00E-03	mg/kg-day	4.13E-04
				Inorganics												
				Aluminum	2.04E+03	μg/L	3.90E-05	mg/kg-day	NA	NA	NA	2.42E-04	mg/kg-day	1.00E+00		
				Arsenic	3.80E+00	μg/L	7.26E-08	mg/kg-day	1.50E+00	(mg/kg-day) ⁻¹	1.09E-07	4.52E-07	mg/kg-day	3.00E-04		1.51E-03
				Barium	2.04E+02	μg/L	3.90E-06	mg/kg-day	NA	NA	NA	2.42E-05	mg/kg-day	1.40E-02	0 0 ,	1.73E-03
				Chromium	8.35E+00	μg/L	1.60E-07	mg/kg-day	5.00E-01	(mg/kg-day) ⁻¹	7.99E-08	9.93E-07	mg/kg-day	7.50E-05		
				Cobalt	1.07E+00	μg/L	8.22E-09	mg/kg-day	NA	NA	NA	5.11E-08	mg/kg-day	3.00E-04	0 0 ,	
	l			Copper	5.22E+01	μg/L	1.00E-06	mg/kg-day	NA	NA	NA	6.22E-06	mg/kg-day	4.00E-02		
	l			Iron	8.20E+03	μg/L	1.57E-04	mg/kg-day	NA	NA	NA	9.75E-04	mg/kg-day	7.00E-01	mg/kg-day	1.39E-03
				Manganese	4.12E+02	μg/L	7.89E-06	mg/kg-day	NA	NA	NA	4.90E-05	mg/kg-day	5.60E-03		8.75E-03
				Vanadium	1.70E+01	μg/L	3.25E-07	mg/kg-day	NA	NA	NA	2.02E-06	mg/kg-day	1.82E-06	mg/kg-day	1.11E+00
			Exp. Route To								2.35E-07			•		1.15E+00
Groundwater	Groundwater	Groundwater	Inhalation	Volatile Organic Compounds				/3		l			3	l	l	l
	l			cis-1,2-Dichloroethene	5.45E+01	μg/L	3.30E+00	μg/m ³	NA	NA (µg/m³) ⁻¹	NA 4 00 E 00	2.35E-02	mg/m ³	NA 4 00E 00	NA	NA
				Tetrachloroethene	9.92E-01	μg/L	5.34E-02	μg/m³ μg/m³	2.60E-07	" " ,	1.39E-08	3.80E-04	mg/m ³	4.00E-02	mg/m ³	9.50E-03
				trans-1,2-Dichloroethene	2.28E+00	μg/L	1.38E-01		NA 4.40E.00	NA (u.g/m ³ \-1	NA 4.555.44	9.79E-04	mg/m ³	6.00E-02		1.63E-02
	l			Trichloroethene	5.64E-01	μg/L	1.41E-01	μg/m³ μg/m~	4.10E-06	(µg/m³) ⁻¹ (µg/mˇ)	1.55E-11	2.27E-04	mg/m³ mg/m~	2.00E-03	mg/m³ mg/m³	1.14E-01
<u> </u>				Vinyl Chloride	7.30E-01	μg/L	1.00E+00	µу/пт	4.40E-06	(μg/111)	4.41E-06	3.28E-04	mg/m	1.00E-01	IIIg/III	3.28E-03
	-		Exp. Route To	tal							4.43E-06					1.43E-01
		Exposure Point	Total								6.73E-05					9.20E+00

NA = not applicable

RfD = reference dose

mg/kg = milligram per kilogram mg/kg-day = milligram per kilogram per day



TABLE F-9.1 SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCS CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

	Exposure	Exposure			Can	cer Risk		None	cancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Former	Semi-volatile Organic Compounds									
Soil	Soil	Sugar Mill	Benzo(a)pyrene	3E-08	5E-09	7E-13	3E-08	NA	NA	NA	NA	NA
			Dibenzo(a,h)anthracene	7E-09	1E-09	2E-13	8E-09	NA	NA	NA	NA	NA
			Inorganics									
			Aluminum	NA	NA	NA	NA	Neurological	6E-03	NA	2E-04	6E-03
			Arsenic	3E-07	1E-08	1E-10	3E-07	Skin/Developmental/	5E-03	2E-04	2E-05	5E-03
								Cardiovascular System/CNS/Lung				
			Chromium	4E-07	NA	2E-09	4E-07	Lung	2E-03	NA	1E-05	2E-03
			Cobalt	NA	NA	7E-10	7E-10	Thyroid/Respiratory System/Lung	1E-02	NA	1E-04	1E-02
			Iron	NA	NA	NA	NA	GI Tract	2E-02	NA	NA	2E-02
			Manganese	NA	NA	NA	NA	CNS	1E-03	NA	7E-04	2E-03
			Vanadium	NA	NA	5E-09	5E-09	Kidney/Respiratory System	4E-01	NA	5E-05	4E-01
			Chemical Total	7E-07	2E-08	8E-09	8E-07	Chemical Total	4E-01	2E-04	1E-03	4E-01
		Exposure Poi	int Total		•		8E-07			•		4E-01
	Exposure Me	dium Total			•		8E-07			•		4E-01
Medium Total					•		8E-07			•		4E-01



Page 1 of 2 6/29/2012

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs

CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

	Exposure	Exposure			Can	er Risk		Nonc	cancer Haza	ard Quotient	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			cis-1,2-Dichloroethene	NA	NA	NA	NA	Kidney	2E-01	NA	NA	2E-01
			Tetrachloroethene	2E-09	2E-09	3E-09	7E-09	Liver	1E-03	1E-03	3E-03	5E-03
			trans-1,2-Dichloroethene	NA	NA	NA	NA	Blood/Lung/Liver	1E-03	1E-04	4E-03	5E-03
			Trichloroethene	3E-08	6E-09	3E-08	7E-08	Heart/ Immunogical/ Developmental/Kidney	1E-02	2E-03	3E-02	4E-02
			Vinyl Chloride Inorganics	6E-07	4E-08	5E-08	7E-07	Liver	2E-03	1E-04	9E-04	3E-03
			Aluminum	NA	NA	NA	NA	Neurological	2E-02	8E-05	NA	2E-02
			Arsenic	6E-06	3E-08	NA	6E-06	Skin/Developmental/ Cardiovascular System/CNS/Lung	1E-01	5E-04	NA	1E-01
			Barium	NA	NA	NA	NA	Kidney/Fetus	9E-03	6E-04	NA	9E-03
			Chromium	5E-06	2E-08	NA	5E-06	Lung	2E-02	4E-03	NA	3E-02
			Cobalt	NA	NA	NA	NA	Thyroid/Respiratory System/Lung	3E-02	6E-05	NA	3E-02
			Copper	NA	NA	NA	NA	GI Tract	1E-02	5E-05	NA	1E-02
			Iron	NA	NA	NA	NA	GI Tract	1E-01	5E-04	NA	1E-01
			Manganese	NA	NA	NA	NA	CNS	3E-02	3E-03	NA	3E-02
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+00	4E-01	NA	2E+00
			Chemical Total	1E-05	1E-07	8E-08	1E-05	Chemical Total	3E+00	4E-01	4E-02	3E+00
		Exposure Po	int Total				1E-05					3E+00
	Exposure Me	dium Total					1E-05					3E+00
Medium Total			.				1E-05					3E+00
Receptor Total	al		·		•		1E-05					4E+00

Total Excess Cancer Risk Across All Media

1E-05

Total Hazard Index Across All Media

<0.01

<0.01

Blood HI Across All Media = Liver HI Across All Media =

Liver HI Across All Media = 0.01

Kidney HI Across All Media = 3

CNS HI Across All Media = 0.1

Development HI Across All Media = 0.2

Respiratory System HI Across All Media = 3

 Lung HI Across All Media =
 0.2

 Cardiovascular System HI Across All Media =
 0.1

 Skin HI Across All Media =
 0.1

Heart HI Across All Media = 0.04

GI Tract HI Across All Media = 0.1

Fetus HI Across All Media =

NA = not applicable

CNS = central nervous system

GI = gastrointestinal



Page 2 of 2 6/29/2012

TABLE F-9.2 SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCS CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Resident
Receptor Age: Lifetime

Madison	Exposure	Exposure	Chemical of Potential Concern		Can	cer Risk		None	cancer Haza	rd Quotient	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Former	Semi-volatile Organic Compounds									
Soil	Soil	Sugar Mill	Benzo(a)pyrene	2E-06	2E-07	6E-11	2E-06	NA	NA	NA	NA	NA
			Dibenzo(a,h)anthracene	4E-07	6E-08	2E-11	5E-07	NA	NA	NA	NA	NA
			Inorganics									1
			Aluminum	NA	NA	NA	NA	Neurological	9E-02	NA	2E-03	9E-02
			Arsenic	3E-06	1E-07	2E-09	4E-06	Skin/Developmental/	8E-02	3E-03	2E-04	8E-02
								Cardiovascular				1
								System/CNS/Lung				1
			Chromium	5E-06	NA	3E-08	5E-06	Lung	3E-02	NA	1E-04	3E-02
			Cobalt	NA	NA	1E-08	1E-08	Thyroid/Respiratory System/Lung	2E-01	NA	1E-03	2E-01
			Iron	NA	NA	NA	NA	GI Tract	3E-01	NA	NA	3E-01
			Lead					NA				1
			Manganese	NA	NA	NA	NA	CNS	2E-02	NA	7E-03	3E-02
			Vanadium	NA	NA	8E-08	8E-08	Kidney/Respiratory System	6E+00	NA	4E-04	6E+00
			Chemical Total	1E-05	4E-07	1E-07	1E-05	Chemical Total	7E+00	3E-03	1E-02	7E+00
		Exposure Po	int Total				1E-05		•	•		7E+00
	Exposure Me	dium Total					1E-05		· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·		7E+00
Medium Total				•	•	•	1E-05		•	•		7E+00



SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs

CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future
Receptor Population: Resident
Receptor Age: Lifetime

	Exposure	Exposure			Can	cer Risk		None	ancer Haza	rd Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			cis-1,2-Dichloroethene	NA	NA	NA	NA	Kidney	7E-01	NA	NA	7E-01
			Tetrachloroethene	1E-08	7E-09	1E-08	3E-08	Liver	4E-03	3E-03	9E-03	2E-02
			trans-1,2-Dichloroethene	NA	NA	NA	NA	Blood/Lung/Liver	3E-03	3E-04	2E-02	2E-02
			Trichloroethene	2E-07	4E-08	2E-11	2E-07	Heart/ Immunogical/ Developmental/Kidney	3E-02	6E-03	1E-01	1E-01
			Vinyl Chloride Inorganics	2E-05	5E-15	4E-06	2E-05	Liver	6E-03	4E-04	3E-03	1E-02
			Aluminum	NA	NA	NA	NA	Neurological	5E-02	2E-04	NA	5E-02
			Arsenic	3E-05	1E-07	NA	3E-05	Skin/Developmental/	3E-01	2E-03	NA	3E-01
								Cardiovascular System/CNS/Lung				
			Barium	NA	NA	NA	NA	Kidney/Fetus	3E-02	2E-03	NA	3E-02
			Chromium	2E-05	8E-08	NA	2E-05	Lung	7E-02	1E-02	NA	8E-02
			Cobalt	NA	NA	NA	NA	Thyroid/Respiratory System/Lung	9E-02	2E-04	NA	9E-02
			Copper	NA	NA	NA	NA	GI Tract	3E-02	2E-04	NA	3E-02
			Iron	NA	NA	NA	NA	GI Tract	3E-01	1E-03	NA	3E-01
			Manganese	NA	NA	NA	NA	CNS	8E-02	9E-03	NA	8E-02
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	6E+00	1E+00	NA	7E+00
			Chemical Total	6E-05	2E-07	4E-06	7E-05	Chemical Total	8E+00	1E+00	1E-01	9E+00
]		Exposure Po	int Total				7E-05					9E+00
	Exposure Me	dium Total					7E-05					9E+00
Medium Total				•	•	•	7E-05		•	•		9E+00
Receptor Total	al						8E-05					2E+01

Total Excess Cancer Risk Across All Media 8E-05 Total Hazard Index Across All Media 16

Blood HI Across All Media = 0.02 Liver HI Across All Media = 0.05 Kidney HI Across All Media = 14 CNS HI Across All Media = 0.5 Development HI Across All Media = 0.6 Respiratory System HI Across All Media = 13 0.8 Lung HI Across All Media = Cardiovascular System HI Across All Media = 0.4 Skin HI Across All Media = 0.4 Heart HI Across All Media = 0.1 GI Tract HI Across All Media = 0.7 Fetus HI Across All Media = 0.03

NA = not applicable CNS = central nervous system GI = gastrointestinal



Page 2 of 2 6/29/2012

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs

CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adul

	Exposure	Exposure			Can	cer Risk		Nonc	ancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Puerto Rico	Inorganics									
Soil	Soil	Beverage	Aluminum	NA	NA	NA	NA	Neurological	6E-03	NA	2E-04	6E-03
			Arsenic	2E-07	9E-09	1E-10	2E-07	Skin/Developmental/	4E-03	2E-04	1E-05	4E-03
								Cardiovascular				
								System/CNS/Lung				
			Chromium	7E-07	NA	3E-09	7E-07	Lung	4E-03	NA	2E-05	4E-03
			Cobalt	NA	NA	5E-10	5E-10	Thyroid/Respiratory	9E-03	NA	8E-05	9E-03
								System/Lung				
			Iron	NA	NA	NA	NA	GI Tract	2E-02	NA	NA	2E-02
			Manganese	NA	NA	NA	NA	CNS	1E-03	NA	5E-04	2E-03
			Vanadium	NA	NA	4E-09	4E-09	Kidney/Respiratory System	3E-01	NA	4E-05	3E-01
			Chemical Total	9E-07	9E-09	8E-09	9E-07	Chemical Total	4E-01	2E-04	9E-04	4E-01
		Exposure Po	int Total				9E-07					4E-01
	Exposure Me	dium Total					9E-07					4E-01
Medium Tota							9E-07					4E-01



SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs

CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

	Exposure	Exposure			Can	cer Risk		None	cancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			cis-1,2-Dichloroethene	NA	NA	NA	NA	Kidney	2E-01	NA	NA	2E-01
			Tetrachloroethene	2E-09	2E-09	3E-09	7E-09	Liver	1E-03	1E-03	3E-03	5E-03
			trans-1,2-Dichloroethene	NA	NA	NA	NA	Blood/Lung/Liver	1E-03	1E-04	4E-03	5E-03
			Trichloroethene	3E-08	6E-09	3E-08	7E-08	Heart/ Immunogical/ Developmental/Kidney	1E-02	2E-03	3E-02	4E-02
			Vinyl Chloride	6E-07	4E-08	5E-08	7E-07	Liver	2E-03	1E-04	9E-04	3E-03
			Inorganics									
			Aluminum	NA	NA	NA	NA	Neurological	2E-02	8E-05	NA	2E-02
			Arsenic	6E-06	3E-08	NA	6E-06	Skin/Developmental/ Cardiovascular System/CNS/Lung	1E-01	5E-04	NA	1E-01
			Barium	NA	NA	NA	NA	Kidney/Fetus	9E-03	6E-04	NA	9E-03
			Chromium	5E-06	2E-08	NA	5E-06	Lung	2E-02	4E-03	NA	3E-02
			Cobalt	NA	NA	NA	NA	Thyroid/Respiratory System/Lung	3E-02	6E-05	NA	3E-02
			Copper	NA	NA	NA	NA	GI Tract	1E-02	5E-05	NA	1E-02
			Iron	NA	NA	NA	NA	GI Tract	1E-01	5E-04	NA	1E-01
			Manganese	NA	NA	NA	NA	CNS	3E-02	3E-03	NA	3E-02
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+00	4E-01	NA	2E+00
			Chemical Total	1E-05	1E-07	8E-08	1E-05	Chemical Total	3E+00	4E-01	4E-02	3E+00
		Exposure Po	int Total				1E-05					3E+00
	Exposure Me	dium Total					1E-05			·	·	3E+00
Medium Total							1E-05					3E+00
Receptor Total	al						1E-05					3E+00

Total Excess Cancer Risk Across All Media 1E-05 Total Hazard Index Across All Media

Blood HI Across All Media =

Liver HI Across All Media =

Kidney HI Across All Media =

CNS HI Across All Media = 0.1

Development HI Across All Media = 0.2

3

<0.01

0.01

Respiratory System HI Across All Media = 3

Lung HI Across All Media = 0.2

Cardiovascular System HI Across All Media = 0.1

 Skin HI Across All Media =
 0.1

 Heart HI Across All Media =
 0.04

 GI Tract HI Across All Media =
 0.1

 Fetus HI Across All Media =
 <0.01</td>

NA = not applicable CNS = central nervous system GI = gastrointestinal



Page 2 of 2 6/29/2012

SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs

CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site
Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

	Exposure	Exposure			Can	cer Risk		Nonc	ancer Haza	ard Quotien	t	
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Puerto Rico	Inorganics									
Soil	Soil	Beverage	Aluminum	NA	NA	NA	NA	Neurological	8E-02	NA	2E-03	9E-02
			Arsenic	3E-06	9E-08	2E-09	3E-06	Skin/Developmental/	6E-02	2E-03	1E-04	6E-02
								Cardiovascular				
								System/CNS/Lung				
			Chromium	8E-06	NA	5E-08	8E-06	Lung	5E-02	NA	2E-04	5E-02
			Cobalt	NA	NA	9E-09	9E-09	Thyroid/Respiratory	1E-01	NA	7E-04	1E-01
								System/Lung				
			Iron	NA	NA	NA	NA	GI Tract	3E-01	NA	NA	3E-01
			Manganese	NA	NA	NA	NA	CNS	2E-02	NA	5E-03	2E-02
			Vanadium	NA	NA	7E-08	7E-08	Kidney/Respiratory System	5E+00	NA	4E-04	5E+00
			Chemical Total	1E-05	9E-08	1E-07	1E-05	Chemical Total	6E+00	2E-03	8E-03	6E+00
		Exposure Po	int Total				1E-05					6E+00
	Exposure Me	dium Total					1E-05					6E+00
Medium Tota							1E-05					6E+00



SUMMARY OF RECEPTOR RISKS AND HAZARDS FOR COPCs

CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Future
Receptor Population: Resident
Receptor Age: Lifetime

	Exposure	Exposure	Observing of Patential Os	Cancer Risk				Noncancer Hazard Quotient				
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			cis-1,2-Dichloroethene	NA	NA	NA	NA	Kidney	7E-01	NA	NA	7E-01
			Tetrachloroethene	1E-08	7E-09	1E-08	3E-08	Liver	4E-03	3E-03	9E-03	2E-02
			trans-1,2-Dichloroethene	NA	NA	NA	NA	Blood/Lung/Liver	3E-03	3E-04	2E-02	2E-02
			Trichloroethene	2E-07	4E-08	2E-11	2E-07	Heart/ Immunogical/ Developmental/Kidney	3E-02	6E-03	1E-01	1E-01
			Vinyl Chloride	2E-05	5E-15	4E-06	2E-05	Liver	6E-03	4E-04	3E-03	1E-02
			Inorganics									
			Aluminum	NA	NA	NA	NA	Neurological	5E-02	2E-04	NA	5E-02
			Arsenic	3E-05	1E-07	NA	3E-05	Skin/Developmental/ Cardiovascular System/CNS/Lung	3E-01	2E-03	NA	3E-01
			Barium	NA	NA	NA	NA	Kidney/Fetus	3E-02	2E-03	NA	3E-02
			Chromium	2E-05	8E-08	NA	2E-05	Lung	7E-02	1E-02	NA	8E-02
			Cobalt	NA	NA	NA	NA	Thyroid/Respiratory System/Lung	9E-02	2E-04	NA	9E-02
			Copper	NA	NA	NA	NA	GI Tract	3E-02	2E-04	NA	3E-02
			Iron	NA	NA	NA	NA	GI Tract	3E-01	1E-03	NA	3E-01
			Manganese	NA	NA	NA	NA	CNS	8E-02	9E-03	NA	8E-02
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	6E+00	1E+00	NA	7E+00
			Chemical Total	6E-05	2E-07	4E-06	7E-05	Chemical Total	8E+00	1E+00	1E-01	9E+00
]		Exposure Po	int Total	•			7E-05			•	•	9E+00
	Exposure Me	dium Total					7E-05					9E+00
Medium Total							7E-05					9E+00
Receptor Total	al				· ·		8E-05				·	1E+01

Total Excess Cancer Risk Across All Media 8E-05 Total Hazard Index Across All Media 15

Blood HI Across All Media = 0.02 Liver HI Across All Media = 0.05 Kidney HI Across All Media = 13 CNS HI Across All Media = 0.5 Development HI Across All Media = 0.5 Respiratory System HI Across All Media = 13 0.8 Lung HI Across All Media = Cardiovascular System HI Across All Media = 0.4 Skin HI Across All Media = 0.4 Heart HI Across All Media = 0.1 GI Tract HI Across All Media = 0.6 Fetus HI Across All Media = 0.03

NA = not applicable CNS = central nervous system GI = gastrointestinal



Page 2 of 2 6/29/2012

TABLE F-10.1 RISK ASSESSMENT SUMMARY CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

	Exposure	Exposure		Cancer Risk				Noncancer Hazard Quotient						
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure		
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total		
Surface Soil	Surface Soil	Former	Chemical Total	7E-07	2E-08	8E-09	8E-07	Chemical Total	4E-01	2E-04	1E-03	4E-01		
		Sugar Mill												
		Exposure Po	int Total				8E-07					4E-01		
	Exposure Me	dium Total					8E-07					4E-01		
Medium Total							8E-07					4E-01		
Groundwater	Groundwater	Groundwater	Inorganics											
			Arsenic	6E-06	3E-08	NA	6E-06	Skin/Developmental/	1E-01	5E-04	NA	1E-01		
								Cardiovascular						
								System/CNS/Lung						
			Chromium	5E-06	2E-08	NA	5E-06	Lung	_			3E-02		
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System				2E+00		
			Chemical Total	1E-05	1E-07	8E-08	1E-05	Chemical Total	3E+00	4E-01	4E-02	3E+00		
		Exposure Po	int Total				1E-05					3E+00		
	Exposure Me	dium Total					1E-05					3E+00		
Medium Total		-					1E-05			E-01 5E-04 NA 1E- E-02 4E-03 NA 3E- E+00 4E-01 NA 2E- E+00 4E-01 4E-02 3E- 3E- 3E- 3E- 3E- 3E-				
Receptor Total	al						1E-05		stem 2E+00 4E-01 NA 2E+ 3E+00 4E-01 4E-02 3E+ 3E+ 3E+ 3E+					

Total Excess Cancer Risk Across All Media

1E-05

Total Hazard Index Across All Media

4

Kidney HI Across All Media = Respiratory System HI Across All Media =

edia = 3 edia = 3

NA = not applicable

CNS = central nervous system

GI = gastrointestinal

Note:

Only chemicals above EPA's threshold values are listed in this table



TABLE F-10.2 RISK ASSESSMENT SUMMARY CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Resident
Receptor Age: Lifetime

Markey	Exposure	Exposure	Observing of Batantial Occurre	Cancer Risk				Noncancer Hazard Quotient				
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Former	Semi-volatile Organic Compounds									
Soil	Soil	Sugar Mill	Benzo(a)pyrene	2E-06	2E-07	6E-11	2E-06	NA	NA	NA	NA	NA
			Inorganics									
			Arsenic	3E-06	1E-07	2E-09	4E-06	Skin/Developmental/ Cardiovascular System/CNS/Lung	8E-02	3E-03	2E-04	8E-02
			Chromium	5E-06	NA	3E-08	5E-06	Lung	3E-02	NA	1E-04	3E-02
			Vanadium	NA	NA	8E-08	8E-08	Kidney/Respiratory System	6E+00	NA	4E-04	6E+00
			Chemical Total	1E-05	4E-07	1E-07	1E-05	Chemical Total	7E+00	3E-03	1E-02	7E+00
		Exposure Po	int Total				1E-05					7E+00
	Exposure Me	dium Total					1E-05					7E+00
Medium Total							1E-05					7E+00
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			Vinyl Chloride	2E-05	5E-15	4E-06	2E-05	Liver	6E-03	4E-04	3E-03	1E-02
			Inorganics	3E-05	1E-07	NA	3E-05	01: /5	3E-01	2E-03	NA	3E-01
			Arsenic	3E-05	1E-07	NA	3E-05	Skin/Developmental/ Cardiovascular System/CNS/Lung	3E-01	2E-03	NA	3E-01
			Chromium	2E-05	8E-08	NA	2E-05	Lung	7E-02	1E-02	NA	8E-02
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	6E+00	1E+00	NA	7E+00
	_		Chemical Total	6E-05	2E-07	4E-06	7E-05	Chemical Total	8E+00	1E+00	1E-01	9E+00
		Exposure Po	int Total				7E-05					9E+00
	Exposure Me	dium Total					7E-05					9E+00
Medium Total	Vanadium NA NA Chemical Total 6E-05 2E-07 4 Exposure Point Total Exposure Medium Total dium Total											9E+00
Receptor Tota	al						8E-05					2E+01

Total Excess Cancer Risk Across All Media

8E-05

Total Hazard Index Across All Media

16

Kidney HI Across All Media = Respiratory System HI Across All Media =

dia = 14 dia = 13

NA = not applicable

CNS = central nervous system

GI = gastrointestinal

Note:

Only chemicals above EPA's threshold values are listed in this table



Page 1 of 1 6/29/2012

TABLE F-10.3 RISK ASSESSMENT SUMMARY CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site Maunabo, Puerto Rico

Scenario Timeframe: Current/Future

Receptor Population: Commercial/Industrial Worker

Receptor Age: Adult

	Exposure	Exposure		Cancer Risk				Noncancer Hazard Quotient						
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure		
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total		
Surface Soil	Surface Soil	Puerto Rico	Chemical Total	9E-07	9E-09	8E-09	9E-07	Chemical Total	4E-01	2E-04	9E-04	4E-01		
		Beverage												
		Exposure Poi	nt Total				9E-07					4E-01		
	Exposure Me	dium Total					9E-07					4E-01		
Medium Tota	ĺ						9E-07			Dermal Inhalation Exp Contact Pe-04 4				
Groundwater	Groundwater	Groundwater	Inorganics											
			Arsenic	6E-06	3E-08	NA	6E-06	Skin/Developmental/	1E-01	5E-04	NA	1E-01		
								Cardiovascular System/CNS/Lung						
			Chromium	5E-06	2E-08	NA	5E-06	Lung	2E-02	4E-03	NA	3E-02		
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	2E+00	4E-01	NA	2E+00		
			Chemical Total	1E-05	1E-07	8E-08	1E-05	Chemical Total	3E+00	4E-01	4E-02	3E+00		
		Exposure Poi	nt Total				1E-05					3E+00		
	Exposure Me	dium Total			•		1E-05			•	•	3E+00		
Medium Tota	I						1E-05					3E+00		
Receptor Total	Exposure Point Total Exposure Medium Total edium Total						1E-05		•	•	•	3E+00		

Total Excess Cancer Risk Across All Media

1E-05

Total Hazard Index Across All Media

3

Kidney HI Across All Media = Respiratory System HI Across All Media =

NA = not applicable

CNS = central nervous system

GI = gastrointestinal

Only chemicals above EPA's threshold values are listed in this table



TABLE F-10.4 RISK ASSESSMENT SUMMARY CENTRAL TENDENCY EXPOSURE

Maunabo Groundwater Contamination Site

Maunabo, Puerto Rico

Scenario Timeframe:	Future
Receptor Population:	Resident
Receptor Age:	Lifetime

NA - Wome	Exposure	Exposure	Observing of Patential Oscillar	Cancer Risk				Noncancer Hazard Quotient				
Medium	Medium	Point	Chemical of Potential Concern	Ingestion	Dermal	Inhalation	Exposure	Primary	Ingestion	Dermal	Inhalation	Exposure
					Contact		Routes Total	Target Organ(s)		Contact		Routes Total
Surface	Surface	Puerto Rico	Inorganics									
Soil	Soil	Beverage	Arsenic	3E-06	9E-08	2E-09	3E-06	Skin/Developmental/ Cardiovascular System/CNS/Lung	6E-02	2E-03	1E-04	6E-02
			Chromium	8E-06	NA	5E-08	8E-06	Lung	5E-02	NA	2E-04	5E-02
			Vanadium	NA	NA	7E-08	7E-08	Kidney/Respiratory System	5E+00	NA	4E-04	5E+00
			Chemical Total	1E-05	9E-08	1E-07	1E-05	Chemical Total	6E+00	2E-03	8E-03	6E+00
		Exposure Poi	nt Total				1E-05					6E+00
	Exposure Me	dium Total					1E-05					6E+00
Medium Tota							1E-05					6E+00
Groundwater	Groundwater	Groundwater	Volatile Organic Compounds									
			Vinyl Chloride	2E-05	5E-15	4E-06	2E-05	Liver	6E-03	4E-04	3E-03	1E-02
			Inorganics									
			Arsenic	3E-05	1E-07	NA	3E-05	Skin/Developmental/	3E-01	2E-03	NA	3E-01
								Cardiovascular System/CNS/Lung				
			Chromium	2E-05	8E-08	NA	2E-05	Lung	7E-02	1E-02	NA	8E-02
			Vanadium	NA	NA	NA	NA	Kidney/Respiratory System	6E+00	1E+00	NA	7E+00
			Chemical Total	6E-05	2E-07	4E-06	7E-05	Chemical Total	8E+00	1E+00	1E-01	9E+00
		Exposure Poi	nt Total				7E-05					9E+00
	Exposure Medium Total											9E+00
Medium Total			-				7E-05					9E+00
Receptor Total	al						8E-05					1E+01

Total Excess Cancer Risk Across All Media 8E-05 Total Hazard Index Across All Media 15

Kidney HI Across All Media = 13

Respiratory System HI Across All Media = 13

NA = not applicable CNS = central nervous system GI = gastrointestinal

Note:

Only chemicals above EPA's threshold values are listed in this table

